



Search products:


1. According to the product code, search in the code index (in the end of this catalogue)
2. According to the product functions, search following index.



Please scan QR code to watch the basic operation video of the products.


P1-3

**OUTPUT INTERFACE
WIRELESS DATA TRANSFER SYSTEM**




P4-49

**DIGITAL CALIPER
VERNIER CALIPER
DIAL CALIPER**






P50-67

**DEPTH CALIPER
DEPTH MICROMETER
DEPTH INDICATOR**





P68-77

HEIGHT GAGE



P78-125


**OUTSIDE MICROMETER
MICROMETER HEAD
MICROMETER STAND**



INDEX


P126-152

INSIDE MICROMETER
BORE GAUGE
RADIUS GAUGE
CIRCUMFERENCE TAPE




P153-198

LINEAR GAUGE
DIAL INDICATOR
DIGITAL INDICATOR
DIAL TEST INDICATOR
STYLI
MAGNETIC STAND
INDICATOR STAND
CONCENTRICITY GAUGE



P199-220

DIAL CALIPER GAUGE
DIGITAL CALIPER GAUGE
THICKNESS GAUGE
SNAP GAUGE
CRANKSHAFT TESTER




P221-251

GAUGE BLOCK
PIN GAUGE
STEEL BALL
MASTER SETTING DISC
RING GAUGE
PLUG GAUGE




P251-278

PROTRACTOR
SQUARE
STRAIGHT EDGE
LEVEL




P279-284

CHAMFER GAUGE
DIGITAL KEYWAY GAUGE
DIGITAL STEP GAUGE




P285-325

FEELER
PITCH GAUGE
ANGLE GAUGE
RADIUS GAUGE
TELESCOPING GAUGE
TAPER GAUGE
WELDING GAUGE
CHAMFER GAUGE
KEY GAUGE
INSIDE/OUTSIDE CALIPER
DIVIDER
STEEL RULE
MEASURING TAPE
MARKING GAUGE
DIGITAL SCALE
STEP GAUGE




P326-346

GRANITE SURFACE PLATE
V-BLOCK
PARALLEL SET
ANGLE PLATE SET
PRECISION VISE
CENTERING INDICATOR
EDGE FINDER
ZERO SET



P346-351



MEASURING TOOLS SET



INDEX


P352-384

ENDOSCOPE
DIGITAL MICROSCOPE
STEREO MICROSCOPE
VIDEO MICROSCOPE
CAMERA
PROFILE PROJECTOR
VISION MACHINE
TOOL PRESETTER




P385-409

HARDNESS TESTER






P409-417

ROUGHNESS SPECIMEN
ROUGHNESS TESTER
ROUNDNESS TESTER




P418-442


ULTRASONIC THICKNESS GAUGE
COATING THICKNESS GAUGE
TEMPERATURE METER
INFRARED THERMOMETER
DIGITAL MULTIMETER
LASER TACHOMETER
LASER DISTANCE METER
LASER LEVEL
GLOSS METER
COLOR METER



P443-463


FORCE GAUGE
TORQUE WRENCH
TORQUE SCREWDRIVER
TORQUE METER
WEIGHING SCALE
WEIGHT











VIDEO

800-11

800-02

- ◆ Max. transmission distance: 15m
- ◆ For single channel receiver (code: 800-01), it can be only connected to one receiver(gages). There is no software, the data can be transferred into Excel, Word directly.
- ◆ For multi- channel receiver(code: 800-02) , it can be connected to Max. 10 receivers(gages). It includes a software, the data can be transferred into the software.
- ◆ Wireless zigbee protocol, conforming to IEEE802, 2.4GHz band


CABLE

Code	Name	Plug to product	Products
800-01	single channel receiver		for follow measuring tools
800-02	multi- channel receiver		for follow measuring tools
800-10	transmitter		for digital calipers with following electronics *
800-10L	transmitter		for digital height gage with following electronics *
800-11	transmitter		for digital calipers with following electronics

Code	Name	Plug to product	Products
800-15	transmitter		for digital calipers and height gage with following electronics
800-21	transmitter		for digital indicators with following electronics
800-20	transmitter		for digital indicators with following electronics
800-30	transmitter		for digital micrometers with data output with following electronics

* Confirm the electronics output port type when placing orders




VIDEO





100-11

- ◆ The cable without software, push the black button or footswitch, the data can be transferred into Excel, Word directly.
- ◆ The cable with software, the data can be transferred into the software at a set interval time automatically.

Connect foot switch to transfer the data (code: 400-01)



Software



Code	Software	Plug to product	Products
100-03	Without		for digital calipers with following electronics
100-04	With		*
100-03L	Without		for digital height gage with following electronics
100-04L	With	8mm	*
100-11	Without		for digital calipers with following electronics
100-12	With		
100-15	Without		for digital calipers and height gage with following electronics
100-17	Without		for digital calipers with following electronics

Code	Software	Plug to product	Products
200-03	Without		for digital indicators with following electronics
200-04	With		*
200-01	Without		for digital indicators with following electronics
200-02	With		
200-05	Without		for digital indicators with following electronics
200-06	With		for digital indicators with following electronics (output radius)
300-03	Without		for digital micrometers with data output with following electronics
300-04	With		

Code	Name
400-01	foot switch

* Confirm the electronics output port type when placing orders

SERIES 200

USB OUTPUT INTERFACE

- ◆ Connecting series 208 (software is included)
- ◆ Connecting 206 (software is included)

For following series 208
(counter for linear gauge)



208-004-01



208-008-01

For following 206




206-010-01



200-92


Work with series 208 (counter for linear gauge)



code	Plug to product	Products
200-91		for digital indicators with following electronics
200-92		for digital indicators with following electronics

809

MOVABLE WORKBENCH



unit:mm

Application



Code	Description	LxWxH(mm)
809-040-11	movable workbench	1000x600x1250


SERIES 111

WIRELESS DIGITAL CALIPER



ATTENTION:
THE WORKING LIFE OF ONE
BATTERY IS ABOUT 3-5 MONTHS


NEW



data transmission signal light



111-006-18

unit: mm



- ◆ Non waterproof
- ◆ Built-in wireless data transmission module, Zigbee signal
- ◆ Transmission distance is 10 meter (under the condition of no obstruction and no electromagnetic interference)
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Made of stainless steel
- ◆ Optional accessory: receiver (code 800-01 or 800-02)

Application



Receiver (optional)



Code	Range	Accuracy	a	b	c	h	L
111-006-18	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-18	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-18	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400
111-006-18W	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-18W	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-18W	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate



SERIES 111

DIGITAL CALIPER



111-006-11N

- ◆ High accuracy due to using the glass scale
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, ABS
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Automatic power on/off
- ◆ Meet DIN862
- ◆ Made of stainless steel



Code	Range	Accuracy	a	b	c	h	L
111-006-11N	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-11N	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-11N	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate



SERIES 111

DIGITAL CALIPER



111-006-10

- ◆ High accuracy due to using the glass scale
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Automatic power on/off
- ◆ Meet DIN862
- ◆ Made of stainless steel




Code	Range	Accuracy	a	b	c	h	L
111-006-10	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-10	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-10	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400
111-006-10W	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-10W	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-10W	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate


SERIES 111

DIGITAL CALIPER



111-006-12


- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Data output(cable code:100-11 or 100-12)
- ◆ Automatic power on/off
- ◆ Meet DIN862
- ◆ Made of stainless steel



without thumb roller (W)


Code	Range	Accuracy	a	b	c	h	L
111-006-12	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-12	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-12	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400
111-006-12W	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-12W	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-12W	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate




SERIES 111

DIGITAL CALIPER WITH ROUND DEPTH BAR




111-006-12R

- ◆ With round depth bar, for small hole depth measurement
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Data output(cable code:100-11 or 100-12)
- ◆ Automatic power on/off
- ◆ Meet DIN862
- ◆ Made of stainless steel




without thumb roller (W)



Code	Range	Accuracy	Thumb roller	a	b	c	h	L
111-006-12R	0-150mm/0-6"	±0.03mm	with	21	16	16	40	236
111-006-12RW	0-150mm/0-6"	±0.03mm	without	21	16	16	40	236

With manufacturer inspection certificate




SERIES 111

DIGITAL CALIPER WITH METAL COVER



111-006-16


unit: mm



- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Made of stainless steel


Code	Range	Accuracy	a	b	c	h	L
111-006-16	0-150mm/0-6"	±0.03mm	21	16	16	40	236
111-008-16	0-200mm/0-8"	±0.03mm	24	19	16	50	286
111-012-16	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate




SERIES 111

DIGITAL CALIPER



111-006-17


unit: mm



- ◆ High accuracy
- ◆ Absolute system
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, ABS/ZERO, inch/mm, ORIGIN
- ◆ Data output(cable code: 100-17)
- ◆ Meet DIN862
- ◆ Made of stainless steel


Code	Range	Accuracy	a	b	c	h	L
111-006-17	0-150mm/0-6"	±0.02mm	21	16.5	16	40	236
111-008-17	0-200mm/0-8"	±0.02mm	24	19	16	50	286
111-012-17	0-300mm/0-12"	±0.03mm	26	20.5	16	60	400

With manufacturer inspection certificate




SERIES 112

IP67 DIGITAL CALIPER




112-006-11H

- ◆ IP67 protection level
- ◆ Absolute measuring system
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power off
- ◆ Buttons: zero, mm/inch, data preset
- ◆ Made of stainless steel



Code	Range	Accuracy	a	b	c	h	L
112-006-11H	0-150mm/0-6"	±0.02mm	21	16.5	16	40	236
112-008-11H	0-200mm/0-8"	±0.02mm	24	19	16	50	286
112-012-11H	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate




SERIES 112

WATERPROOF DIGITAL CALIPER WITH ROUND DEPTH BAR




112-006-11HR

- ◆ IP67 protection level
- ◆ Absolute measuring system
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power off
- ◆ Buttons: zero, mm/inch, data preset
- ◆ Made of stainless steel




Code	Range	Accuracy
112-006-11HR	0-150mm/0-6"	±0.02mm

With manufacturer inspection certificate




SERIES 112

IP67 DIGITAL CALIPER




112-006-12

- ◆ IP67 protection level
- ◆ Absolute measuring system
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power off
- ◆ Buttons: on/off, zero, mm/inch



Code	Range	Accuracy	a	b	c	h	L
112-006-12	0-150mm/0-6"	±0.03mm	21	16.5	16	40	236
112-008-12	0-200mm/0-8"	±0.03mm	24	20	16	50	286
112-012-12	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate




SERIES 106

DIGITAL CALIPER WITH LARGE SCREEN




106-006-11

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Data output(cable code:100-03)
- ◆ Made of stainless steel
- ◆ Power: rechargeable battery, for 3 months continuous working(full charge)



Code	Range	Accuracy	a	b	c	h	L
106-006-11	0-150mm/0-6"	±0.03mm	21	16	16	40	236
106-008-11	0-200mm/0-8"	±0.03mm	24	19	16	50	286
106-012-11	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate




SERIES 106

DIGITAL CALIPER WITH LARGE SCREEN




106-006-21

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Automatic power on/off
- ◆ Meet DIN862
- ◆ Made of stainless steel




Code	Range	Accuracy	a	b	c	h	L
106-006-21	0-150mm/0-6"	±0.03mm	21	16	16	40	236
106-008-21	0-200mm/0-8"	±0.03mm	24	19	16	50	286
106-012-21	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate




SERIES 113

FRACTIONAL DIGITAL CALIPER




113-006-11

- ◆ With fraction reading
- ◆ Resolution: 0.01mm, 0.0005", 1/128"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Made of stainless steel




Code	Range	Accuracy	a	b	c	h	L
113-006-11	0-150mm/0-6"	±0.03mm	21	16	16	40	236
113-008-11	0-200mm/0-8"	±0.03mm	24	19	16	50	286
113-012-11	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate






- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Meet DIN862
- ◆ Made of stainless steel





Code	Range	Accuracy
114-004-11	0-100mm/0-4"	±0.02mm

With manufacturer inspection certificate



115-006-11


- ◆ Ceramic tipped jaws for outside measurements, good wear- resistance, non-magnetic, non-conductive
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Automatic power on/off
- ◆ Made of stainless steel



Ceramic tipped jaws

Code	Range	Accuracy	a	b	c	h	L
115-006-11	0-150mm/0-6"	±0.03mm	21	16.5	16	40	236
115-008-11	0-200mm/0-8"	±0.03mm	24	19	16	50	286
115-012-11	0-300mm/0-12"	±0.03mm	26	20.5	16	60	400

With manufacturer inspection certificate



SERIES 116



DIGITAL CALIPER WITH CARBIDE TIPPED JAWS




116-006-11

unit: mm


- ◆ Carbide tipped jaws for inside and outside measurements, good wear-resistance
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Automatic power on/off
- ◆ Made of stainless steel



Carbide tipped jaws



Carbide tipped jaws




Code	Range	Accuracy	a	b	c	h	L
116-006-11	0-150mm/0-6"	±0.03mm	21	16	16	40	236
116-008-11	0-200mm/0-8"	±0.03mm	24	19	16	50	286
116-012-11	0-300mm/0-12"	±0.03mm	25	20.5	16	60	400

With manufacturer inspection certificate



117

PLASTIC DIGITAL CALIPER



unit: mm


- ◆ Made of hard plastic
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch



Code	Range	Accuracy	a	b	c	h	L
117-006-11	0-150mm/0-6"	±0.2mm	21	16	16	40	243

SERIES 101

DIAL CALIPER



101-006-21

- ◆ Shockproof dial indicator
- ◆ Made of stainless steel


Graduation 0.01mm

Code	Range	Accuracy	a	b	c	h	s	D	L
101-006-11	0-150mm	±0.03mm	21	16.5	16	40	6.5	Ø39	235
101-008-11	0-200mm	±0.03mm	24	19	16	48	6.5	Ø39	288
101-012-11	0-300mm	±0.03mm	28	22	20	62	7.5	Ø44.5	410

Graduation 0.02mm


Code	Range	Accuracy	a	b	c	h	s	D	L
101-006-21	0-150mm	±0.03mm	21	16.5	16	40	6.5	Ø39	235
101-008-21	0-200mm	±0.03mm	24	19	16	48	6.5	Ø39	288
101-012-21	0-300mm	±0.03mm	28	22	20	62	7.5	Ø44.5	410

With manufacturer inspection certificate





SERIES 101

INCH DIAL CALIPER



101-006-21I


- ◆ Shockproof dial indicator
- ◆ Made of stainless steel




Code	Range	Graduation	Accuracy	a	b	c	h	D	L
101-006-21I	0-6"	0.001in	±0.0015in	21	16.5	16	40	Ø39	233
101-008-21I	0-8"	0.001in	±0.0020in	24	19	16	50	Ø39	288
101-012-21I	0-12"	0.001in	±0.0020in	30	25	20	64	Ø44	390

SERIES 103

DIAL CALIPER



103-006-21



- ◆ Shockproof dial indicator
- ◆ Made of stainless steel


Graduation 0.01mm

Code	Range	Accuracy	a	b	c	h	D	L
103-006-11	0-150mm	±0.03mm	21	16.5	16	40	Ø39	233
103-008-11	0-200mm	±0.03mm	24	19	16	50	Ø39	288
103-012-11	0-300mm	±0.03mm	30	25	20	64	Ø44	390

Graduation 0.02mm


Code	Range	Accuracy	a	b	c	h	D	L
103-006-21	0-150mm	±0.03mm	21	16.5	16	40	Ø39	233
103-008-21	0-200mm	±0.03mm	24	19	16	50	Ø39	288
103-012-21	0-300mm	±0.03mm	30	25	20	64	Ø44	390

With manufacturer inspection certificate




SERIES 120

VERNIER CALIPER



120-006-12




- ◆ Meet DIN862
- ◆ Satin chrome plated reading surface
- ◆ Made of stainless steel

Graduation 0.02mm/0.001"

Code	Range	Accuracy	a	b	c	h	L
120-006-12	0-150mm/0-6"	±0.03mm	20.5	15.5	16	40	235
120-008-12	0-200mm/0-8"	±0.03mm	23.5	19	16	50	290
120-012-12	0-300mm/0-12"	±0.03mm	29.5	24	20	62	414


Graduation 0.05mm/1/128"

Code	Range	Accuracy	a	b	c	h	L
120-006-14	0-150mm/0-6"	±0.05mm	20.5	15.5	16	40	235
120-008-14	0-200mm/0-8"	±0.05mm	23.5	19	16	50	290
120-012-14	0-300mm/0-12"	±0.05mm	29.5	24	20	62	414



SERIES 120


VERNIER CALIPER



120-006-12S

unit: mm

- ◆ Meet DIN862
- ◆ Satin chrome plated reading surface
- ◆ Made of stainless steel




Graduation 0.02mm/0.001"

Code	Range	Accuracy	a	b	c	h	L
120-006-12S	0-150mm/0-6"	±0.03mm	20.5	15.5	16	40	235
120-008-12S	0-200mm/0-8"	±0.03mm	23.5	19	16	50	290
120-012-12S	0-300mm/0-12"	±0.03mm	27.5	22	20	64	414

Graduation 0.05mm/1/128"


Code	Range	Accuracy	a	b	c	h	L
120-006-14S	0-150mm/0-6"	±0.05mm	20.5	15.5	16	40	235
120-008-14S	0-200mm/0-8"	±0.05mm	23.5	19	16	50	290
120-012-14S	0-300mm/0-12"	±0.05mm	27.5	22	20	64	414



CALIPER

SERIES 124


VERNIER CALIPER



124-006-14

unit: mm

- ◆ With auto thumb clamp
- ◆ Meet DIN862
- ◆ Satin chrome plated reading surface
- ◆ Made of stainless steel




Graduation 0.02mm/0.001"

Code	Range	Accuracy	a	b	c	h	L
124-006-12	0-150mm/0-6"	±0.03mm	20.5	15.5	16	40	235
124-008-12	0-200mm/0-8"	±0.03mm	23.5	19	16	50	290

Graduation 0.05mm/1/128"


Code	Range	Accuracy	a	b	c	h	L
124-006-14	0-150mm/0-6"	±0.05mm	20.5	15.5	16	40	235
124-008-14	0-200mm/0-8"	±0.05mm	23.5	19	16	50	290






SERIES 125

VERNIER CALIPER




125-005-11




- ◆ With fine adjustment
- ◆ Graduation: 0.02mm/0.001"
- ◆ Meet DIN862
- ◆ Satin chrome plated reading surface
- ◆ Made of stainless steel

Code	Range	Accuracy	a	b	c	h	L
125-005-11	0-130mm/0-5"	±0.03mm	20.5	16.5	16	40	230
125-007-11	0-180mm/0-7"	±0.03mm	23.5	19	16	50	295
125-011-11	0-280mm/0-11"	±0.03mm	27.5	22	20	60	410




SERIES 121

MINI VERNIER CALIPER





121-003-11



- ◆ Meet DIN862
- ◆ Satin chrome plated reading surface
- ◆ Made of stainless steel


Code	Range	Graduation	Accuracy	a	b	h	L	C
121-003-11	0-70mm	0.05mm	±0.05mm	10	8	19	113	8
121-004-11	0-100mm	0.05mm	±0.05mm	17	13	30	160	12






- ◆ Meet DIN862
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface

Code	Range	Graduation	Accuracy	L
121-004-11B	0-100mm	0.05mm	±0.05mm	160



SERIES 140

VERNIER CALIPER WITH CARBIDE TIPPED JAWS




140-006-11

- ◆ Carbide tipped jaws
- ◆ Meet DIN862
- ◆ Satin chrome reading surface
- ◆ Made of stainless steel



Carbide tipped jaws




Carbide tipped jaws

Graduation 0.02mm

Code	Range	Accuracy	a	b	c	h	L
140-006-11	0-150mm	±0.03mm	21	16.5	16	40	235
140-008-11	0-200mm	±0.03mm	24	19	16	50	295
140-012-11	0-300mm	±0.03mm	25	20	17	60	410

Graduation 0.05mm

Code	Range	Accuracy	a	b	c	h	L
140-006-13	0-150mm	±0.05mm	21	16.5	16	40	235
140-008-13	0-200mm	±0.05mm	24	19	16	50	295
140-012-13	0-300mm	±0.05mm	25	20	17	60	410



SERIES 123


VERNIER CALIPER (ANTI MAGNETIC)

ATTENTION:
Not hardened



123-006-11

- ◆ Suitable for magnetic parts
- ◆ Made of pure copper




Graduation 0.02mm

Code	Range	Accuracy
123-006-11	0-150mm	±0.05mm


Graduation 0.05mm

Code	Range	Accuracy
123-006-13	0-150mm	±0.05mm




SERIES 150

DIGITAL CALIPER




150-018-11

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Button function: on/off, zero, mm/inch, ABS, data preset
- ◆ Data output(cable code:100-15)
- ◆ Made of stainless steel




Code	Range	Accuracy	a	c	h	L
150-018-11	0-450mm/0-18"	±0.05mm	45	24	100	610
150-024-11	0-600mm/0-24"	±0.05mm	45	24	100	770
150-040-11	0-1000mm/0-40"	±0.08mm	60	31	150	1220




SERIES 118

DIGITAL CALIPER




118-012-14


- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Preset: 10mm, don't need to add the width of the jaws on the reading
- ◆ Automatic power on/off
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Made of stainless steel



Preset buttons




Code	Range	Accuracy	a	c	h	L
118-008-11	0-200mm/0-8"	±0.03mm	12	17	60	320
118-012-14	0-300mm/0-12"	±0.04mm	12	17	60	420
118-012-15	0-300mm/0-12"	±0.06mm	12	17	90	420





SERIES 118

DIGITAL CALIPER



118-020-11



Code	Range	Accuracy	a	c	h
118-012-11	0-300mm/0-12"	±0.04mm	18	24	100
118-012-12	0-300mm/0-12"	±0.05mm	18	24	150
118-012-13	0-300mm/0-12"	±0.05mm	18	24	200
118-020-11	0-500mm/0-20"	±0.05mm	18	24	100
118-020-12	0-500mm/0-20"	±0.06mm	18	24	150
118-020-13	0-500mm/0-20"	±0.06mm	24	32	200
118-020-14	0-500mm/0-20"	±0.08mm	24	42	300
118-024-11	0-600mm/0-24"	±0.05mm	18	24	100
118-024-12	0-600mm/0-24"	±0.06mm	18	24	150
118-024-13	0-600mm/0-24"	±0.06mm	24	32	200
118-024-15	0-600mm/0-24"	±0.08mm	24	42	300
118-032-11	0-800mm/0-32"	±0.07mm	24	32	150
118-040-11	0-1000mm/0-40"	±0.08mm	24	32	150
118-040-12	0-1000mm/0-40"	±0.08mm	24	32	200
118-040-13	0-1000mm/0-40"	±0.10mm	24	42	300
118-060-11	0-1500mm/0-60"	±0.11mm	24	42	150
118-080-11	0-2000mm/0-80"	±0.14mm	24	42	150



- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch, ABS, data preset
- ◆ Preset: 20mm, don't need to add the width of the jaws on the reading
- ◆ Data output(cable code:100-15)
- ◆ Made of stainless steel

119

DIGITAL CALIPER




- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Automatic power on/off
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Made of stainless steel


Preset buttons




Low jaws




Preset: 10mm,result=reading



External measurement



Internal measurement(1)
(size>10mm)




Internal measurement(2)

Code	Range	Accuracy
119-012-11	0-300mm/0-12"	±0.04mm


SERIES 119

DIGITAL CALIPER




119-020-11

Low jaws




Preset: 20mm,result=reading




unit: mm


Code	Range	Accuracy	a	b	c	h
119-012-12	0-300mm/0-12"	±0.05mm	18	45	24	100
119-018-11	0-450mm/0-18"	±0.05mm	18	45	24	100
119-020-11	0-500mm/0-20"	±0.05mm	18	45	24	100
119-020-12	0-500mm/0-20"	±0.06mm	18	45	24	150
119-020-13	0-500mm/0-20"	±0.06mm	24	60	32	200
119-024-11	0-600mm/0-24"	±0.05mm	18	45	24	100
119-024-12	0-600mm/0-24"	±0.06mm	18	45	24	150
119-024-14	0-600mm/0-24"	±0.06mm	24	60	32	200
119-040-11	0-1000mm/0-40"	±0.08mm	24	60	32	150
119-040-12	0-1000mm/0-40"	±0.08mm	24	60	32	200
119-060-11	0-1500mm/0-60"	±0.11mm	24	60	42	150
119-060-12	0-1500mm/0-60"	±0.12mm	24	60	42	200



External measurement



Internal measurement(1)
(size>20mm)




Internal measurement(2)

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch, ABS, data preset
- ◆ Data output(cable code:100-15)
- ◆ Made of stainless steel

SERIES 130


DIGITAL CALIPER



130-012-11

L

unit: mm




- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel

Preset buttons




Low jaws




Preset: 10mm,result=reading


Code	Range	Accuracy	a	b	c	h	L
130-008-11	0-200mm/0-8"	±0.03mm	12	38	17	60	320
130-012-11	0-300mm/0-12"	±0.04mm	12	38	17	60	420
130-012-12	0-300mm/0-12"	±0.04mm	12	38	17	90	420



External measurement




External measurement



Internal measurement (size>10mm)

SERIES 131


DIGITAL CALIPER



131-020-11


L

unit: mm




- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch, ABS, data preset
- ◆ Data output(cable code:100-15)
- ◆ Made of stainless steel

Low jaws




Preset: 20mm,result=reading

Code	Range	Accuracy	a	b	c	h	L
131-012-11	0-300mm/0-12"	±0.05mm	18	56	24	100	420
131-020-11	0-500mm/0-20"	±0.05mm	18	56	24	100	675
131-020-12	0-500mm/0-20"	±0.06mm	18	56	24	150	675
131-024-11	0-600mm/0-24"	±0.05mm	18	56	24	100	770
131-028-11	0-800mm/0-32"	±0.07mm	24	67	31	150	1025
131-040-11	0-1000mm/0-40"	±0.08mm	24	67	31	150	1220






External measurement

External measurement



Internal measurement (size>20mm)





- ◆ With fine adjustment
- ◆ Made of stainless steel
- ◆ Satin chrome reading surface

Graduation 0.02mm/0.001"



Code	Range	Accuracy	a	c	h	w	L
126-012-11	0-300mm/0-12"	±0.05mm	12	17	90	10	410
126-012-12	0-300mm/0-12"	±0.05mm	18	24	150	20	470
126-020-11	0-500mm/0-20"	±0.06mm	18	24	150	20	670
126-020-12	0-500mm/0-20"	±0.06mm	18	24	200	20	670
126-024-11	0-600mm/0-24"	±0.06mm	18	24	150	20	770
126-024-12	0-600mm/0-24"	±0.08mm	24	32	250	20	820
126-040-11	0-1000mm/0-40"	±0.08mm	24	32	200	20	1220
126-040-12	0-1000mm/0-40"	±0.11mm	24	32	300	20	1330
126-120-12	0-3000mm/0-120"	±0.26mm	24	50	300	20	3360

Graduation 0.05mm/1/128"

Code	Range	Accuracy	a	c	h	w	L
126-012-51	0-300mm/0-12"	±0.07mm	12	17	90	10	410
126-012-52	0-300mm/0-12"	±0.07mm	18	24	150	20	470
126-020-51	0-500mm/0-20"	±0.08mm	18	24	150	20	670
126-020-52	0-500mm/0-20"	±0.08mm	18	24	200	20	670
126-024-51	0-600mm/0-24"	±0.08mm	18	24	150	20	770
126-024-52	0-600mm/0-24"	±0.08mm	24	32	250	20	820
126-040-51	0-1000mm/0-40"	±0.12mm	24	32	200	20	1220
126-040-52	0-1000mm/0-40"	±0.12mm	24	32	300	20	1330
126-120-52	0-3000mm/0-120"	±0.31mm	24	50	300	20	3360


127-020-11





- ◆ With fine adjustment
- ◆ Made of stainless steel
- ◆ Satin chrome reading surface


Graduation 0.02mm/0.001"

Code	Range	Accuracy	a	c	h	w	L
127-012-11	0-300mm/0-12"	±0.05mm	10	20	75	10	410
127-020-11	0-500mm/0-20"	±0.05mm	18	24	100	20	670
127-024-11	0-600mm/0-24"	±0.05mm	18	24	100	20	770
127-032-11	0-800mm/0-32"	±0.08mm	24	32	150	20	1020
127-040-11	0-1000mm/0-40"	±0.08mm	24	32	140	20	1216
127-060-11	0-1500mm/0-60"	±0.11mm	24	42	180	20	1830
127-080-11	0-2000mm/0-80"	±0.14mm	24	42	200	20	2320

Graduation 0.05mm/1/128"

Code	Range	Accuracy	a	c	h	w	L
127-012-51	0-300mm/0-12"	±0.05mm	10	20	75	10	410
127-020-51	0-500mm/0-20"	±0.08mm	18	24	100	20	670
127-024-51	0-600mm/0-24"	±0.08mm	18	24	100	20	770
127-040-51	0-1000mm/0-40"	±0.10mm	24	32	140	20	1216
127-060-51	0-1500mm/0-60"	±0.15mm	24	42	180	20	1830
127-080-51	0-2000mm/0-80"	±0.20mm	24	42	200	20	2320



- ◆ Made of stainless steel
- ◆ With fine adjustment
- ◆ Satin chrome plated reading surface

Graduation 0.02mm/0.001"

Code	Range	Accuracy	a	c	h	w	L
128-008-21	0-200mm/0-8"	±0.05mm	12	20	100	10	330
128-012-21	0-300mm/0-12"	±0.05mm	18	24	90	20	410
128-012-22	0-300mm/0-12"	±0.07mm	18	24	150	20	410
128-020-21	0-500mm/0-20"	±0.05mm	18	24	100	20	670
128-020-22	0-500mm/0-20"	±0.06mm	18	24	150	20	670
128-024-21	0-600mm/0-24"	±0.06mm	18	24	100	20	770
128-024-22	0-600mm/0-24"	±0.08mm	18	24	150	20	770
128-040-21	0-1000mm/0-40"	±0.08mm	24	32	150	20	1230
128-060-21	0-1500mm/0-60"	±0.11mm	24	42	150	20	1820
128-080-21	0-2000mm/0-80"	±0.14mm	24	42	150	20	2230


Graduation 0.05mm/1/128"

Code	Range	Accuracy	a	c	h	w	L
128-008-51	0-200mm/0-8"	±0.06mm	12	20	100	20	330
128-012-51	0-300mm/0-12"	±0.07mm	18	24	90	20	410
128-012-52	0-300mm/0-12"	±0.07mm	18	24	150	20	410
128-020-51	0-500mm/0-20"	±0.08mm	18	24	100	20	670
128-020-52	0-500mm/0-20"	±0.08mm	18	24	150	20	670
128-024-51	0-600mm/0-24"	±0.08mm	18	24	100	20	770
128-024-52	0-600mm/0-24"	±0.09mm	18	24	150	20	770
128-032-51	0-800mm/0-32"	±0.09mm	24	31	150	20	1030
128-040-51	0-1000mm/0-40"	±0.12mm	24	32	150	20	1230
128-060-51	0-1500mm/0-60"	±0.16mm	24	42	150	20	1820
128-080-51	0-2000mm/0-80"	±0.20mm	24	42	150	20	2230

SERIES 129

VERNIER CALIPER


- ◆ Made of stainless steel
- ◆ With fine adjustment
- ◆ Satin chrome plated reading surface



129-020-12


Graduation 0.02mm/0.001"

Code	Range	Accuracy	a	b	c	h	w	L
129-020-11	0-500mm/0-20"	±0.05mm	18	45	24	100	20	670
129-020-12	0-500mm/0-20"	±0.06mm	18	45	24	150	20	670
129-024-11	0-600mm/0-24"	±0.06mm	18	45	24	100	20	770
129-040-11	0-1000mm/0-40"	±0.08mm	24	60	31	150	20	1230




Graduation 0.05mm/1/128"

Code	Range	Accuracy	a	b	c	h	w	L
129-020-51	0-500mm/0-20"	±0.07mm	18	45	24	100	20	670
129-020-52	0-500mm/0-20"	±0.08mm	18	45	24	150	20	670
129-024-51	0-600mm/0-24"	±0.08mm	18	45	24	100	20	770
129-040-51	0-1000mm/0-40"	±0.12mm	24	60	31	150	20	1230



SERIES 120

VERNIER CALIPER (SOLID TYPE)



120-024-51


- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface


Graduation 0.02mm/0.001"

code	Range	Accuracy
120-024-11	0-600mm/0-24"	±0.06mm


Graduation 0.05mm/1/128"

code	Range	Accuracy
120-024-51	0-600mm/0-24"	±0.08mm








- ◆ With fine adjustment
- ◆ Made of stainless steel
- ◆ Satin chrome reading surface




Result=reading+10mm



Code	Range	Graduation	Accuracy
122-012-11	0-300mm	0.02mm	±0.03mm



122-020-21




- ◆ With fine adjustment
- ◆ Made of stainless steel
- ◆ Satin chrome reading surface

Graduation: 0.02mm/0.001"


Code	Range	Accuracy	h	a	b	c	w	L
122-012-21	0-300mm/0-12"	±0.05mm	90	12	40	20	10	410
122-020-21	0-500mm/0-20"	±0.05mm	100	18	56	24	20	670
122-020-22	0-500mm/0-20"	±0.06mm	150	18	56	24	20	670
122-032-21	0-800mm/0-32"	±0.07mm	150	24	67	31	20	1020
122-040-21	0-1000mm/0-40"	±0.08mm	150	24	67	31	20	1220

Graduation: 0.05mm/1/128"

Code	Range	Accuracy	h	a	b	c	w	L
122-012-51	0-300mm/0-12"	±0.07mm	90	12	40	20	10	410
122-020-51	0-500mm/0-20"	±0.07mm	100	18	56	24	20	670
122-020-52	0-500mm/0-20"	±0.08mm	150	18	56	24	20	670
122-032-51	0-800mm/0-32"	±0.09mm	150	24	67	31	20	1020
122-040-51	0-1000mm/0-40"	±0.12mm	150	24	67	31	20	1220




Result=reading+W




SERIES 138

DIGITAL POINT CALIPER



138-006-11

- ◆ Measure small holes or grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Made of stainless steel




Code	Range	Accuracy	a	b	h	L
138-006-11	0-150mm/0-6"	±0.03mm	21	16	40	236
138-008-11	0-200mm/0-8"	±0.03mm	24	19	50	286
138-012-11	0-300mm/0-12"	±0.03mm	25	21	60	400


(mm)	
a	b
1	2.5
2	5
3	7.5
4	10
5	12.5
6	15

168

DIGITAL SMALL POINT CALIPER



- ◆ Small point jaws fits into small grooves and recesses
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy
168-006-11	0-150mm/0-6"	±0.03mm

SERIES 133

DIGITAL OUTSIDE NECK CALIPER




VIDEO





133-006-11

- ◆ Measure wall thickness and recesses
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output
- ◆ Made of stainless steel




133-012-12



Code	Range	Accuracy	a	c	e	f	h	L
133-006-11	0-150mm/0-6"	±0.04mm	5	16	1	4	40	250
133-008-11	0-200mm/0-8"	±0.05mm	9	16	1.5	4	80	310
133-012-11	0-300mm/0-12"	±0.05mm	10	16	1.5	4	60	410
133-012-12	0-300mm/0-12"	±0.06mm	12	24	2	5	150	490


SERIES 143

OUTSIDE NECK VERNIER CALIPER



143-006-11

- ◆ Measure wall thickness and recesses
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface





Graduation 0.02mm

Code	Range	Accuracy
143-006-11	0-150mm	±0.04mm

Graduation 0.05mm

Code	Range	Accuracy
143-006-13	0-150mm	±0.05mm



SERIES 134


DIGITAL OUTSIDE POINT CALIPER



ACCUD




VIDEO





134-006-11

- ◆ Measure wall thickness of inside bores and recesses
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output
- ◆ Made of stainless steel




For range 300mm



Code	Range	Accuracy	a	b	c	Ød	e	h	L
134-006-11	0-150mm/0-6"	±0.04mm	5	10	16	2	2	40	250
134-008-11	0-200mm/0-8"	±0.05mm	9	14	16	3	3	80	310
134-012-12	0-300mm/0-12"	±0.06mm	12	20	24	3	3	150	490


SERIES 144

OUTSIDE POINT VERNIER CALIPER



144-006-11

- ◆ Measure wall thickness of inside bores and recesses
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface





Graduation 0.02mm

Code	Range	Accuracy
144-006-11	0-150mm	±0.04mm

Graduation 0.05mm

Code	Range	Accuracy
144-006-13	0-150mm	±0.05mm



SERIES 135

DIGITAL INSIDE NECK CALIPER



VIDEO




Data output




CR2032

- ◆ Measure the grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Preset: 2b, don't need to add the width of the jaws on the reading
- ◆ Data output
- ◆ Made of stainless steel



135-006-11

unit: mm




For range 500mm




Preset buttons




Code	Range	Accuracy	a	b	c	e	h	L
135-006-11	22-150mm	±0.04mm	5	11	16	1	30	250
135-008-11	25-200mm	±0.04mm	5	12.5	16	1	40	310
135-012-11	30-300mm	±0.05mm	5	15	17	1.5	50	410
135-020-11	80-500mm	±0.07mm	16	40	24	4	90	680
135-006-12	35-150mm	±0.06mm	6	17.5	16	1.5	60	250
135-008-12	40-200mm	±0.06mm	7	20	16	1.5	70	310
135-012-12	50-300mm	±0.07mm	8	25	16	1.5	80	410
135-020-12	80-500mm	±0.08mm	16	40	24	5	150	680




size < h



size > e




size < 5mm




SERIES 145

INSIDE NECK VERNIER CALIPER



145-006-11

unit: mm




- ◆ Measure the grooves
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface

Graduation 0.02mm


Code	Range	Accuracy
145-006-11	22-150mm	±0.04mm

Graduation 0.05mm


Code	Range	Accuracy
145-006-13	22-150mm	±0.05mm




Result = reading + 22




size < h



size > 1mm



size < 5mm



SERIES 136

DIGITAL INSIDE POINT CALIPER



- ◆ Measure the grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Preset: 2b, don't need to add the width of the jaws on the reading
- ◆ Data output
- ◆ Made of stainless steel



136-006-11






For range 500mm



Preset buttons




Code	Range	Accuracy	a	b	c	d	h	L
136-006-11	24-150mm	±0.04mm	5	12	16	Ø2	30	250
136-008-11	25-200mm	±0.04mm	5	12.5	16	Ø2	40	310
136-012-11	50-300mm	±0.07mm	8	25	17	Ø3	80	410
136-020-11	80-500mm	±0.07mm	16	40	24	Ø3	90	680
136-006-12	35-150mm	±0.05mm	6	17.5	16	Ø2	60	250
136-008-12	40-200mm	±0.05mm	7	20	16	Ø2	70	310
136-012-12	30-300mm	±0.05mm	5	15	16	Ø3	50	410
136-020-12	80-500mm	±0.08mm	16	40	24	Ø3	150	680



SERIES 146

INSIDE POINT VERNIER CALIPER



146-006-11







- ◆ Measure the grooves
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface

Graduation 0.02mm

Code	Range	Accuracy	a	b	c	d	h	L
146-006-11	24-150mm	±0.04mm	5	12	16	Ø2	30	250
146-012-11	50-300mm	±0.06mm	8	25	17	Ø3	80	410

Graduation 0.05mm

Code	Range	Accuracy	a	b	c	d	h	L
146-006-13	24-150mm	±0.05mm	5	12	16	Ø2	30	250
146-012-13	50-300mm	±0.08mm	8	25	17	Ø3	80	410







136

DIGITAL INSIDE POINT CALIPER




VIDEO



unit: mm

- ◆ Measure the grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Preset: 50mm, don't need to add the width of the jaws on the reading
- ◆ Data output (cable code: 100-03 or 100-04)
- ◆ Made of stainless steel


Preset buttons



Code	Range	Accuracy
136-012-13S	50-300mm	±0.06mm



132

DIGITAL INSIDE GROOVE CALIPER








unit: mm

- ◆ Measure diameter of grooves inside small bores
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel




Code	Range	Accuracy
132-006-21	10-150mm/0.39-6"	±0.04mm


 $h > 2\text{mm}$

 $w < 10\text{mm}$


- ◆ Measure diameter of grooves inside bores
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output (cable code: 100-03 or 100-04)
- ◆ Made of stainless steel

Application



Code	Range	Accuracy
132-012-11	25-300mm	±0.05mm



D	L
Ø25	<50mm
Ø26	<60mm
Ø27~300	<110mm

137

DIGITAL TUBE THICKNESS CALIPER



- ◆ Measure the wall thickness
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy
137-006-11	0-150mm/0-6"	±0.05mm




SERIES 139

DIGITAL INSIDE KNIFE-EDGE CALIPER



139-006-11

- ◆ Measure the diameter of deep holes or grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy	L	h	a	b
139-006-11	15-150mm	±0.05mm	250	60	12	3
139-008-11	20-200mm	±0.05mm	310	90	15	4
139-012-11	20-300mm	±0.06mm	410	90	16	4

SERIES 159


DIGITAL INSIDE GROOVE CALIPER




ACCUD



- ◆ Measure diameter of grooves inside bores
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel




Code	Range of upper jaw	Range of lower jaw	Accuracy	L
159-006-11	9-150mm	15-150mm	±0.04mm	260
159-008-11	9-200mm	15-200mm	±0.06mm	310




SERIES 109

INSIDE GROOVE CALIPER





- ◆ Measure diameter of grooves inside bores
- ◆ Graduation: 0.02mm
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface

109-006-11



Code	Range of upper jaw	Range of lower jaw	Accuracy	L
109-006-11	9-150mm	16-150mm	±0.04mm	260
109-008-11	9-200mm	16-200mm	±0.06mm	310
109-012-11	9-300mm	16-300mm	±0.06mm	415






- ◆ Supplied with 3 pairs of points and one zero setting block for external measurement
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Automatic power on/off
- ◆ Data output (cable code: 100-03 or 100-04)
- ◆ Made of stainless steel


Preset buttons




Install points




Short spherical points (included)



Long spherical/flat points (included)




Short spherical blade points (included)





Zero setting block for external measurement (included)



Measure internal and external grooves



Code	Point	Range	Accuracy	Application
149-008-11	short spherical points	12-212mm/0.5-8.5"(internal)	±0.03mm	for grooves/inside small hole
	long spherical/flat points	24-224mm/1-8.8"(internal) 0-187mm/0-7.5"(external)	±0.03mm	spherical points for grooves/inside hole, flat points for external grooves
	spherical blade points	24-224mm/1-8.8"(internal) 0-187mm/0-7.5"(external)	±0.03mm	for narrow grooves/inside hole




- ◆ Supplied with 4 pairs of points and one zero setting block for external measurement
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+, P-)
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel


Preset buttons




Install points




Short spherical/flat points




Short spherical blade points




Long spherical/flat points




Long spherical blade points

Zero setting block for external
measurement (included)

Measure internal and external grooves




Code	Point	Range	Accuracy	Application
149-012-11	short spherical/flat points	24-324mm/1-12.7"(internal) 0-288mm/0-11.3"(external)	±0.04mm	spherical points for grooves/inside hole, (small hole) flat points for external grooves
	long spherical/flat points	40-340mm/1.5-13.3"(internal) 0-272mm/0-10.7"(external)	±0.04mm	spherical points for grooves/inside hole, (large hole) flat points for external grooves
	short spherical blade points	24-324mm/1-12.7"(internal) 0-288mm/0-11.3"(external)	±0.04mm	for narrow grooves (small hole)
	long spherical blade points	40-340mm/1.5-13.3"(internal) 0-272mm/0-10.7"(external)	±0.04mm	for narrow grooves (large hole)




unit: mm

- ◆ Supplied with 4 pairs of points
(Cylindrical needle point: 270-006-16 2pc,
Cylindrical needle point: 270-006-04 2pc,
Conical needle point: 270-006-21 2pc,
Conical needle point: 270-006-23 2pc)
- ◆ Zero setting block for external measurement
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Automatic power on/off
- ◆ Data output (cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



4 pairs of points (included)



Preset buttons








Points (optional)



Zero setting block for external measurement (included)



Measure internal and external grooves



Code	Range	Accuracy
149-012-21	0-300mm/0-12"	±0.04mm

SERIES 151


DIGITAL OFFSET CENTERLINE CALIPER



ACCUD




VIDEO



151-006-11

- ◆ Measure the hole center-to-center distance in same plane, or between offset planes
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: mm/in, SET, preset(P+, P-)
- ◆ Data output
- ◆ Made of stainless steel




Preset buttons

For range 500mm or above




Code	Range	Accuracy	c	ØD	L1	L2	L
151-006-11	10-150mm/0.4-6"	±0.05mm	16	10	32	65	236
151-008-11	10-200mm/0.4-8"	±0.07mm	16	10	32	65	306
151-012-11	10-300mm/0.4-12"	±0.09mm	16	10	32	65	396
151-020-11	20-500mm/0.8-20"	±0.09mm	24	20	48	88	686
151-040-11	30-1000mm/1.2-40"	±0.12mm	31	30	42	88	1242



SERIES 161

OFFSET CENTERLINE VERNIER CALIPER



161-006-11



Graduation 0.02mm

Code	Range	Accuracy	L
161-006-11	10-150mm	±0.05mm	236
161-008-11	10-200mm	±0.07mm	306
161-012-11	10-300mm	±0.09mm	396

Graduation 0.05mm

Code	Range	Accuracy	L
161-006-13	10-150mm	±0.05mm	236
161-008-13	10-200mm	±0.07mm	306
161-012-13	10-300mm	±0.09mm	396

- ◆ Measure the hole center-to-center distance in same plane, or between offset planes
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface



CALIPER

SERIES 141

DIGITAL BACK-JAW CENTERLINE CALIPER




VIDEO



141-008-11

- ◆ Measure hole center distance in the same or offset planes
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Data output
- ◆ Automatic power on/off
- ◆ Made of stainless steel





Preset buttons



For range 500mm or above



Code	Range	Accuracy	ØD	c	L1	L2	L
141-008-11	10-200mm/0.4-8"	±0.1mm	10	16	18	45	310
141-012-11	10-300mm/0.4-12"	±0.1mm	10	16	18	45	410
141-020-11	20-500mm/0.8-20"	±0.1mm	20	24	26	70	692
141-040-11	30-1000mm/1.2-40"	±0.12mm	30	31	39	70	1242
141-060-11	30-1500mm/1.2-60"	±0.15mm	30	31	39	70	1745



SERIES 147

BACK-JAW DIGITAL EDGE TO CENTER CALIPER




VIDEO



147-008-11



- ◆ Measure edge to hole center distance
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Automatic power on/off
- ◆ Made of stainless steel





Preset buttons



Measure edge to hole center distance



Code	Range	Accuracy	L
147-008-11	5-200mm/0.2-8"	±0.1mm	310
147-012-11	5-300mm/0.2-12"	±0.1mm	410




- ◆ Measure hole center distance or edge to hole center distance
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Automatic power on/off
- ◆ Made of stainless steel


Preset buttons



Measure edge to hole center distance



Measure hole center distance




Code	Range of upper jaw (center to center)	Range of lower jaw (edge to center)	Accuracy
148-012-11	10-300mm/0.4-12"	5-300mm/0.2-12"	±0.08mm

SERIES 153


DIGITAL BLADE CALIPER




153-006-11



- ◆ Measure small grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy	a	b	c	h	e	L
153-006-11	0-150mm/0-6"	±0.03mm	21	16	16	40	0.75	235
153-008-11	0-200mm/0-8"	±0.03mm	24	19	16	50	0.75	297
153-012-11	0-300mm/0-12"	±0.04mm	26	20.5	16	60	1.00	390




SERIES 152

DIGITAL OFFSET CALIPER




152-006-11

- ◆ Adjust the beam-mounted jaw to facilitate measurement of stepped sections and hard-to reach workpiece
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel




Code	Range	Accuracy	a	b	c	h	L
152-006-11	0-150mm/0-6"	±0.04mm	40	16.5	16	110	239
152-008-11	0-200mm/0-8"	±0.04mm	50	19.5	16	120	289
152-012-11	0-300mm/0-12"	±0.05mm	60	20.5	17	130	389




SERIES 162

OFFSET VERNIER CALIPER

- ◆ Adjust the beam-mounted jaw to facilitate measurement of stepped sections and hard-to reach workpiece
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface



162-006-14




Graduation 0.02mm/0.001"

Code	Range	Accuracy	a	b	c	h	L
162-006-12	0-150mm/0-6"	±0.04mm	40	16.5	16	110	239
162-008-12	0-200mm/0-8"	±0.04mm	50	19.5	16	120	289
162-012-12	0-300mm/0-12"	±0.05mm	60	20.5	17	130	389

Graduation 0.05mm/1/128"

Code	Range	Accuracy	a	b	c	h	L
162-006-14	0-150mm/0-6"	±0.04mm	40	16.5	16	110	239
162-008-14	0-200mm/0-8"	±0.04mm	50	19.5	16	120	289
162-012-14	0-300mm/0-12"	±0.05mm	60	20.5	17	130	389




SERIES 154

DIGITAL HOOK CALIPER





154-005-11

- ◆ Measure width of groove inside bores
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy	a	L
154-005-11	3-125mm	±0.04mm	24	250
154-008-11	3-200mm	±0.04mm	34	310
154-012-11	3-300mm	±0.05mm	86	460




SERIES 169



DIGITAL ARC RADIUS CALIPER



- ◆ Measure the radius of arc less than half round
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel




Code	Range(R)	Accuracy	c	d	L
169-006-11	5-150mm/0.2-6"	±0.05mm	16	65	263
169-008-11	5-200mm/0.2-8"	±0.07mm	16	85	313






142-012-11


Preset buttons



142-012-11



142-024-11




For range 600mm




- ◆ Measure ring grooves of flange
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Preset: 25mm, don't need to add the width of the jaws on the reading
- ◆ Data output
- ◆ Made of stainless steel

Measure outside diameter of RTJ ring groove



Measure inside diameter of RTJ ring groove





Code	Range (inside diameter of RTJ ring groove)	Range (outside diameter of RTJ ring groove)	Angle of RTJ ring groove	Accuracy
142-012-11	10-300mm/0.4-12"	25-300mm/1-12"	23°	±0.06mm
142-024-11	10-600mm/0.4-24"	25-600mm/1-24"	23°	±0.07mm



unit: mm


- ◆ Measure diameter of wire ropes, and thickness of soft materials like rubber, etc.
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Measure thickness of rubber



Measure diameter of wire ropes



Code	Range	Accuracy
167-008-11	0-200mm/0-8"	±0.07mm

SERIES 107

DIGITAL CALIPER WITH LONG UPPER JAWS





- ◆ Non waterproof
- ◆ Long upper jaws for measuring diameter of deep holes
- ◆ Resolution: 0.01 mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power off, move the digital unit to turn on power
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



107-008-11


unit: mm



Code	Range	Accuracy	L
107-006-11	0-150mm/0-6"	±0.04mm	236
107-008-11	0-200mm/0-8"	±0.04mm	286

SERIES 156


DIGITAL GEAR TOOTH CALIPER



- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Made of stainless steel


156-001-11

Code	Range	Accuracy	L1	L2	a	c	h
156-001-11	M1-25mm	±0.04mm	170	165.5	21	16	30.5
156-002-11	M5-50mm	±0.04mm	220	190	50.5	16	55




166

VERNIER GEAR TOOTH CALIPER



- ◆ Graduation: 0.02mm
- ◆ Made of stainless steel


Code	Range	Accuracy
166-001-11	M1-26mm	±0.04mm






- ◆ Measure thickness of disk brakes
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel

Code	Range	Accuracy
157-005-11	0-125mm/0-5"	±0.05mm



- ◆ Measure thickness of disk brakes and pad wear
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel

Code	Range	Accuracy
165-006-11	0-150mm/0-6"	±0.07mm




158

DIGITAL DRUM BRAKE CALIPER



- ◆ Measure internal and external diameter of drum brakes
- ◆ Resolution 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy
158-012-11	0-300mm/0-12"	±0.07mm

880

CALIPER END GRINDING MACHINE

- ◆ Used for grinding the depth measuring surface of the end of calipers



Application




Code	Power supply	Dimension (LxWxH)	Weight
880-000-11	220V, 50/60Hz	370x200x 160mm	15kg

881


CALIPER/MICROMETER LAPPING MACHINE

- ◆ For lapping measuring surfaces of caliper lower jaws and outside micrometer
- ◆ Suitable for 0-300mm range calipers and 0-100mm range outside micrometers




Micrometer lapping block (optional)

Caliper lapping block (included)



Lapping measuring surfaces of outside micrometer



lapping measuring surfaces of caliper lower jaws



Code	Power supply	Dimension (L x W x H)	Weight
881-002-11	220V, 50/60Hz	430x400x210mm	28kg

SERIES 179

ACCESSORY FOR CALIPER




179-000-00



179-000-01

- ◆ For caliper to increase the stability of depth measurement
- ◆ For all calipers which range is 150mm and 200mm and beam width is 16mm
- ◆ Made of stainless steel



Application



Code	h	L
179-000-00	30	75
179-000-01	32	100

SERIES 197



IP67 WATERPROOF DIGITAL DEPTH CALIPER



197-008-11

unit: mm

- ◆ IP67 protection level
- ◆ Absolute measuring system
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power off
- ◆ Buttons: zero, mm/inch, data preset
- ◆ Made of stainless steel



Code	Range	Accuracy	a	c	h	L
197-006-11	0-150mm/0-6"	±0.02mm	5	14.5	100	232
197-008-11	0-200mm/0-8"	±0.02mm	5	14.5	100	285
197-012-11	0-300mm/0-12"	±0.03mm	5	14.5	150	390

SERIES 197


IP67 WATERPROOF DIGITAL DEPTH CALIPER WITH HOLES




197-006-21

unit: mm

- ◆ IP67 protection level
- ◆ Absolute measuring system
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power off
- ◆ Buttons: zero, mm/inch, data preset
- ◆ Made of stainless steel
- ◆ Optional accessory: series 170 extension base



Accessories




Code	Range	Accuracy	L
197-006-21	0-150mm/0-6"	±0.02mm	237
197-008-21	0-200mm/0-8"	±0.02mm	287
197-012-21	0-300mm/0-12"	±0.03mm	403

SERIES 171


DIGITAL DEPTH CALIPER



- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy	a	c	h	L
171-006-11	0-150mm/0-6"	±0.03mm	6	14.5	100	230
171-008-11	0-200mm/0-8"	±0.03mm	6	14.5	100	280
171-012-11	0-300mm/0-12"	±0.04mm	6	14.5	150	380
171-020-11	0-500mm/0-20"	±0.05mm	7	15	150	585




SERIES 171

DIGITAL DEPTH CALIPER





171-006-61P

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy	a	c	h	L
171-006-61P	0-150mm/0-6"	±0.03mm	6	14.5	100	230
171-008-61P	0-200mm/0-8"	±0.03mm	6	14.5	100	280
171-012-61P	0-300mm/0-12"	±0.04mm	6	14.5	150	380
171-020-61P	0-500mm/0-20"	±0.05mm	7	16	150	585
171-024-61P	0-600mm/0-24"	±0.05mm	7	16	150	685




SERIES 172

DIGITAL PIN DEPTH CALIPER




172-008-11

- ◆ Measure the depth of small holes or grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



unit: mm



Code	Range	Accuracy	H	L	C
172-008-11	0-200mm/0-8"	±0.03mm	100	291	14.5
172-012-11	0-300mm/0-12"	±0.04mm	150	395	15

SERIES 173

DIGITAL HOOK DEPTH CALIPER




VIDEO

- ◆ Measure the depth of grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: mm/in, SET, preset(P+,P-)
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel



173-006-11

unit: mm



Code	Range	Accuracy	a	b	h	L
173-006-11	0-150mm/0-6"	±0.04mm	2	5	100	235
173-008-11	0-200mm/0-8"	±0.04mm	2	5	100	285
173-012-11	0-300mm/0-12"	±0.05mm	2	5	150	390
173-020-11	0-500mm/0-20"	±0.05mm	3	8	150	585
173-006-21	0-150mm/0-6"	±0.04mm	1	4	100	235
173-008-21	0-200mm/0-8"	±0.04mm	1	4	100	285
173-012-21	0-300mm/0-12"	±0.05mm	1	4	150	390
173-020-21	0-500mm/0-20"	±0.05mm	3	8	200	585

SERIES 174

DIGITAL DOUBLE HOOK DEPTH CALIPER



ACCUD




VIDEO






174-006-11

- ◆ Measure the depth of grooves
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy	h	L
174-006-11	0-150mm/0-6"	±0.03mm	100	233
174-008-11	0-200mm/0-8"	±0.03mm	100	283
174-012-11	0-300mm/0-12"	±0.04mm	150	383



SERIES 191

DIGITAL DEPTH CALIPER WITH HOLES




DEPTH




191-006-11

- ◆ With hole, for mounting the extension base
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Made of stainless steel
- ◆ Optional accessory: series 170 extension base



Code	Range	Accuracy	L
191-006-11	0-150mm/0-6"	±0.03mm	237
191-008-11	0-200mm/0-8"	±0.03mm	287
191-012-11	0-300mm/0-12"	±0.04mm	403



Accessories



SERIES 193


DIGITAL DEPTH CALIPER WITH ROUND DEPTH BAR




193-004-11

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Supplied with three interchangeable points (flat, spherical, disk)
- ◆ Buttons: on/off, set, mm/inch
- ◆ Automatic power off
- ◆ Data output (cable code: 100-11 or 100-12)
- ◆ Made of stainless steel


Accessory application



170 series (optional)





unit: mm



193-006-11, 193-008-11 and 193-012-11

points (include)




Code	Range	Accuracy	L
193-004-11	0-100mm/0-4"	±0.02mm	200
193-006-11	0-150mm/0-6"	±0.03mm	300
193-008-11	0-200mm/0-8"	±0.03mm	300
193-012-11	0-300mm/0-12"	±0.04mm	400


OPTIONAL ACCESSORIES

Code	Description	Remark
193-T04	0.5mm disk point	for grooves inside blind hole
193-T05	0.5mm disk point	for narrow grooves

193-T04 (optional)



193-T05 (optional)




SERIES 194


DIGITAL DEPTH CALIPER WITH ROUND DEPTH BAR



- ◆ Measure depth of small groove and hole
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, set, mm/inch
- ◆ Automatic power off
- ◆ Data output (cable code: 100-11 or 100-12)
- ◆ Made of stainless steel




194-002-11



Code	Range	Accuracy	L	W
194-001-11	0-25mm/0-1"	±0.02mm	110	85
194-002-11	0-50mm/0-2"	±0.02mm	135	85
194-006-11	0-150mm/0-6"	±0.03mm	235	100



SERIES 179

DIAL DEPTH CALIPER



179-006-21

- ◆ Shockproof dial indicator
- ◆ Graduation: 0.02mm
- ◆ Made of stainless steel




Code	Range	Accuracy	D	L
179-006-21	0-150mm	±0.03mm	Ø39	235
179-008-21	0-200mm	±0.03mm	Ø39	285
179-012-21	0-300mm	±0.04mm	Ø39	308





SERIES 177

VERNIER DEPTH CALIPER



177-008-11


- ◆ Graduation: 0.02mm
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface



Code	Range	Accuracy	h	L
177-006-11	0-150mm	±0.03mm	100	245
177-008-11	0-200mm	±0.03mm	100	282
177-012-11	0-300mm	±0.04mm	100	382
177-020-11	0-500mm	±0.05mm	150	585

SERIES 175

VERNIER DEPTH CALIPER



175-006-11



- ◆ Made of stainless steel
- ◆ Satin chrome plating finish on reading surface
- ◆ Optional accessory: series 170 extension base

Graduation 0.02mm

Code	Range	Accuracy	c	h	L
175-006-11	0-150mm	±0.03mm	16	100	240
175-008-11	0-200mm	±0.03mm	16	100	290
175-012-11	0-300mm	±0.04mm	16	100	390
175-024-11	0-600mm	±0.05mm	16	150	704
175-040-11	0-1000mm	±0.07mm	18	200	1124

Graduation 0.05mm

Code	Range	Accuracy	c	h	L
175-006-13	0-150mm	±0.05mm	16	100	240
175-008-13	0-200mm	±0.05mm	16	100	290
175-012-13	0-300mm	±0.08mm	16	100	390
175-024-13	0-600mm	±0.10mm	16	150	704
175-040-13	0-1000mm	±0.15mm	18	200	1124




Accessories



SERIES 178

VERNIER DEPTH CALIPER



178-006-11


- ◆ With fine adjustment
- ◆ Made of stainless steel
- ◆ Satin chrome plating finish on reading surface
- ◆ Optional accessory: series 170 extension base

Graduation 0.02mm

Code	Range	Accuracy	c	h	L
178-006-11	0-150mm	±0.03mm	16	100	256
178-008-11	0-200mm	±0.03mm	16	100	306
178-012-11	0-300mm	±0.04mm	16	100	406
178-024-11	0-600mm	±0.05mm	16	150	720
178-040-11	0-1000mm	±0.07mm	18	200	1140


Graduation 0.05mm

Code	Range	Accuracy	c	h	L
178-006-13	0-150mm	±0.05mm	16	100	256
178-008-13	0-200mm	±0.05mm	16	100	306
178-012-13	0-300mm	±0.08mm	16	100	406
178-024-13	0-600mm	±0.10mm	16	150	720
178-040-13	0-1000mm	±0.15mm	18	200	1140




Accessories

series 170 (optional)




SERIES 192

VERNIER HOOK DEPTH CALIPER




192-006-11

- ◆ Graduation: 0.02mm
- ◆ Made of stainless steel
- ◆ Satin chrome plating finish on reading surface
- ◆ Optional accessory: series 170 extension base



Accessories

series 170 (optional)



Code	Range	Accuracy	L
192-006-11	0-150mm	±0.03mm	245
192-008-11	0-200mm	±0.03mm	295
192-012-11	0-300mm	±0.04mm	395

SERIES 170

EXTENSION BASE FOR DEPTH CALIPER




VIDEO




170-260-01


unit: mm



170-180-01






170-260-01



170-320-01

- ◆ Add extension base to measure large hole or gap
- ◆ For depth caliper 175, 178, 191, 192, 197-xxx-21 series and 193(range 150, 200, 300mm) series

Code	Length
170-180-01	180mm
170-260-01	260mm
170-320-01	320mm




Application

DEPTH

176

DIGITAL DEPTH CALIPER



- ◆ Measure the depth of grooves, small holes and tire thread
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel


Set zero




Measure tire thread



Zero setting block (included)



unit: mm





Code	Range	Accuracy
176-001-11	0-25mm/0-1"	±0.03mm



- ◆ Measure depth of small groove and hole
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power off
- ◆ Data output (cable code: 100-03 or 100-04)
- ◆ Made of stainless steel

Set zero




Zero setting block (included)





Code	Range	Accuracy
176-001-21	0-30mm/0-1.2"	±0.03mm

- ◆ Measure the depth of grooves, small holes and tire thread
- ◆ Graduation: 0.1mm
- ◆ Made of stainless steel

Set zero



Measure



Code	Range	Accuracy
176-030-12	0-30mm	±0.10mm






VIDEO




395-002-01


- ◆ Resolution: 0.001mm/0.00005"
- ◆ Micrometer head accuracy: $\pm 3\mu\text{m}$
Rod accuracy: $\pm(2+L/75)\mu\text{m}$, L is the measuring range in mm
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ IP65 protection level
- ◆ Data output
- ◆ Automatic power off
- ◆ Rods with flat end
- ◆ Ratchet stop




Application



Install rod



Rod (included)



Code	Range	Base(HxW)	Rod
395-001-01	0-25mm/0-1"	101x17mm	1pc
395-002-01	0-50mm/0-2"	101x17mm	2pcs
395-004-01	0-100mm/0-4"	101x17mm	4pcs
395-006-01	0-150mm/0-6"	101x17mm	6pcs
395-008-01	0-200mm/0-8"	101x17mm	8pcs
395-012-01	0-300mm/0-12"	101x17mm	12pcs
395-001-02	0-25mm/0-1"	63x17mm	1pc
395-002-02	0-50mm/0-2"	63x17mm	2pcs
395-004-02	0-100mm/0-4"	63x17mm	4pcs
395-006-02	0-150mm/0-6"	63x17mm	6pcs
395-008-02	0-200mm/0-8"	63x17mm	8pcs
395-012-02	0-300mm/0-12"	63x17mm	12pcs

SERIES 391


DEPTH MICROMETER

- ◆ Micrometer head accuracy: $\pm 3\mu\text{m}$
- ◆ Rod accuracy: $\pm(2+L/75)\mu\text{m}$,
L is the measuring range in mm
- ◆ Supplied with rods
- ◆ Ratchet stop




Code	Range	Base (HxW)	Rod
391-001-01	0-25mm	101.5x17mm	1pc
391-002-01	0-50mm	101.5x17mm	2pcs
391-003-01	0-75mm	101.5x17mm	3pcs
391-004-01	0-100mm	101.5x17mm	4pcs
391-006-01	0-150mm	101.5x17mm	6pcs
391-008-01	0-200mm	101.5x17mm	8pcs
391-012-01	0-300mm	101.5x17mm	12pcs
391-001-02	0-25mm	63x17mm	1pc
391-002-02	0-50mm	63x17mm	2pcs
391-003-02	0-75mm	63x17mm	3pcs
391-004-02	0-100mm	63x17mm	4pcs
391-006-02	0-150mm	63x17mm	6pcs
391-008-02	0-200mm	63x17mm	8pcs
391-012-02	0-300mm	63x17mm	12pcs



391-001-01



Rod (included)



Install rod



SERIES 392


DEPTH MICROMETER

- ◆ Micrometer head accuracy: $\pm 3\mu\text{m}$
- ◆ Rod accuracy: $\pm(2+L/75)\mu\text{m}$,
L is the measuring range in mm
- ◆ Supplied with rods
- ◆ Ratchet stop




Code	Range	Base (HxW)	Rod
392-001-01	0-25mm	101.5x17mm	1pc
392-002-01	0-50mm	101.5x17mm	2pcs
392-003-01	0-75mm	101.5x17mm	3pcs
392-004-01	0-100mm	101.5x17mm	4pcs
392-006-01	0-150mm	101.5x17mm	6pcs
392-008-01	0-200mm	101.5x17mm	8pcs
392-012-01	0-300mm	101.5x17mm	12pcs
392-001-02	0-25mm	63x17mm	1pc
392-002-02	0-50mm	63x17mm	2pcs
392-003-02	0-75mm	63x17mm	3pcs
392-004-02	0-100mm	63x17mm	4pcs
392-006-02	0-150mm	63x17mm	6pcs
392-008-02	0-200mm	63x17mm	8pcs
392-012-02	0-300mm	63x17mm	12pcs



392-001-01



Rod (included)



Install rod

Use





VIDEO

- ◆ Button: tolerance set, data preset, inch/mm conversion, measuring direction set, max./min./range measurement, absolute/incremental measurement
- ◆ Data output (cable code: 200-03 or 200-04)
- ◆ Automatic power off
- ◆ Stainless steel base
- ◆ Supplied with pointed tip and ball tip





Styli (included)





293-010-12

unit: mm



293-010-01 and 293-010-11



293-010-02 and 293-010-12

Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Digital indicator stroke	Base
293-010-01	0-10mm/0-0.4"	±5μm	12.7mm/0.5"	63x17mm
293-010-02	0-10mm/0-0.4"	±5μm	12.7mm/0.5"	101.5x17mm

Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Digital indicator stroke	Base
293-010-11	0-10mm/0-0.4"	±0.03mm	12.7mm/0.5"	63x17mm
293-010-12	0-10mm/0-0.4"	±0.03mm	12.7mm/0.5"	101.5x17mm







VIDEO

- ◆ Button: tolerance set, data preset, inch/mm conversion, measuring direction set, max./min./range measurement, absolute/incremental measurement
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Automatic power off
- ◆ Stainless steel base
- ◆ Supplied with pointed tip and ball tip





293-025-12

Styli (included)



293-025-01 and 293-025-11



293-025-02 and 293-025-12

Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Digital indicator stroke	Base
293-025-01	0-25mm/0-1"	±5µm	25.4mm/1"	63x17mm
293-025-02	0-25mm/0-1"	±5µm	25.4mm/1"	101.5x17mm


Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Digital indicator stroke	Base
293-025-11	0-25mm/0-1"	±0.03mm	25.4mm/1"	63x17mm
293-025-12	0-25mm/0-1"	±0.03mm	25.4mm/1"	101.5x17mm




VIDEO


- ◆ Button: tolerance set, data preset, inch/mm conversion, measuring direction set, max./min./range measurement, absolute/incremental measurement
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Automatic power off
- ◆ Stainless steel base
- ◆ Supplied with pointed tip and ball tip



Extension rods (included)





Styli (included)





293-300-12

unit: mm



293-300-11 and 293-300-01



293-300-12 and 293-300-02



Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Digital indicator stroke	Base
293-300-01	0-300mm/0-12"	±5µm	25.4mm/1"	63x17mm
293-300-02	0-300mm/0-12"	±5µm	25.4mm/1"	101.5x17mm

Resolution 0.01mm/0.0005"



Code	Range	Accuracy	Digital indicator stroke	Base
293-300-11	0-300mm/0-12"	±0.03mm	25.4mm/1"	63x17mm
293-300-12	0-300mm/0-12"	±0.03mm	25.4mm/1"	101.5x17mm

- ◆ Graduation: 0.01mm
- ◆ Indicator travel: 30mm
- ◆ Accuracy: $\pm 0.03\text{mm}$
- ◆ Stainless steel base
- ◆ With needle and ball styli
- ◆ Extension rod: 25mm (1pc), 50mm (1pc), 75mm (1pc), 100mm (2pcs)



292-300-12

292-300-11

292-300-12

unit: mm

Extension rods



Styli (included)



Code	Range	Base
292-300-11	0-300mm	63x17mm
292-300-12	0-300mm	101.5x17mm




SERIES 291

DIAL DEPTH INDICATOR


- ◆ Graduation: 0.01mm
- ◆ Indicator travel: 10mm
- ◆ Accuracy: $\pm 0.03\text{mm}$
- ◆ Stainless steel base
- ◆ With needle and ball styli



291-010-12





291-010-11




291-010-12

Styli (included)



needle styli



ball styli

Code	Range	Base
291-010-11	0-10mm	63x17mm
291-010-12	0-10mm	101.5x17mm

SERIES 295

DIAL DEPTH INDICATOR


- ◆ Stainless steel base
- ◆ Pointed tip




295-010-12




295-010-11



295-010-11



295-010-12



Code	Range	Accuracy	Dial indicator stroke	Dial indicator graduation	Base
295-010-11	0-10mm	17 μm	10mm	0.01mm	Ø16mm
295-010-12	0-10mm	17 μm	10mm	0.01mm	Ø25mm


SERIES 299

DIGITAL DEPTH INDICATOR




- ◆ Button: on/off, zero, mm/inch, ABS, data preset, change measuring direction
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Automatic power off
- ◆ Stainless steel base
- ◆ Pointed tip

299-010-02



Type B



Type A

unit: mm

Resolution 0.01mm/0.0005"


Code	Range	Accuracy	Digital indicator stroke	Base	Type
299-010-11	0-12.7mm/0-0.5"	±20μm	12.7mm/0.5"	Ø16mm	A
299-010-12	0-12.7mm/0-0.5"	±20μm	12.7mm/0.5"	Ø25mm	B

Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Digital indicator stroke	Base	Type
299-010-01	0-12.7mm/0-0.5"	±5μm	12.7mm/0.5"	Ø16mm	A
299-010-02	0-12.7mm/0-0.5"	±5μm	12.7mm/0.5"	Ø25mm	B



299-010-11



SERIES 399

DEPTH MICROMETER CHECKERS



- ◆ To check depth micrometers and set zero
- ◆ Constructed with steel gage blocks
- ◆ Supplied with anvil block


Application




anvil block
(included)



399-012-01



399-012-01



399-006-01

unit: mm

DEPTH

Code	Size	Range	Accuracy
399-006-01	0-150mm	25, 50, 75, 100, 125, 150mm	±2μm
399-012-01	0-300mm	25, 50, 75, 100, 125, 150, 175, 200, 225, 250, 275, 300mm	±3μm

With manufacturer inspection certificate

- ◆ The instrument is suitable for One-Dimensional as well as Two-Dimensional measurements
- ◆ Programming, for batch quantities measurements
- ◆ Color LCD screen
- ◆ The probe moves up and down automatically
- ◆ Low and high limits with judgement
- ◆ Built-in air compressor provides smooth movement on granite surface plate.
- ◆ With re-chargeable battery, for 10 hours working
- ◆ With manufacturer inspection certificate




VIDEO


Optional Accessories

unit: mm


Ø1mm concentric ruby ball probe(code:R1HC)




Ø2mm eccentric ruby ball probe(code:R2H)




Ø3mm eccentric ruby ball probe(code:R3H100)




Ø10mm disc probe (code:DS10H)




Ø2mm depth probe(code:DP2H)



Ø10 carbide ball probe(code:SR10H)



Depth hole probe(code:DP80H)















AccuGage700

Ø4mm carbide ball probe

Squareness probe
(Optional, Code:SQ10)



Basic Measurement

-  1 Contacting a plane from above
-  2 Contacting a shaft from above/bore below
-  3 Measuring a shaft diameter and center
-  4 Measuring groove width and center
-  5 Measuring MIN-MAX-DELTA
-  6 Measuring job squareness
-  7 Contacting a plane from below
-  8 Contacting a shaft from below/ bore above
-  9 Measuring bore diameter and center
-  0 Measuring ledge width and center
-  +/- Difference key
-  +/- Set references


SPECIFICATION

Code	AccuGage700	AccuGage1000
Range	0-700mm	0-1000mm
Expandable range	1015mm	1315mm
Squareness	6μm	10μm
Resolutions	0.5μm, 1μm	
Accuracy	2+L/330μm, L is measuring length in mm (working temperature is 20±1°C)	
Repeatability (with standard probe)	0.001 mm on plane and 0.002 mm on bore	
Measuring force	1±0.2N	
Output	USB or RS232	
Power supply	Rechargeable battery	
Working temperature	10°C - 40°C	
Weight	25kg	

INCLUDED ACCESSORIES

Main unit	1pc
Ø4x48mm ruby ball probe	1pc
Calibration block	1pc
Software and USB cable	1pc each
Allen key	1set
AC/DC Adapter	1pc



2D Measurement

-  ♦ Measure pitch circle diameter(PCD)
- ♦ Measure distance between two points
- ♦ Measure angles
- ♦ Preset coordinates


Programming and replay, for batch quantities measurements



Calculation

-  Calculate height difference
-  Calculate height center

Application Demo



- ◆ The instrument is only suitable for One-Dimensional measurement
- ◆ The probe moves up and down automatically
- ◆ Low and high limits with judgement
- ◆ Built-in air compressor provides smooth movement on granite surface plate.
- ◆ With re-chargeable battery, for 10 hours working
- ◆ With manufacturer inspection certificate




VIDEO


Optional Accessories

unit: mm


Ø1mm concentric ruby ball probe(code:R1HC)




Ø2mm eccentric ruby ball probe(code:R2H)




Ø3mm eccentric ruby ball probe(code:R3H100)




Ø10mm disc probe (code:DS10H)



Ø2mm depth probe(code:DP2H)




Ø10 carbide ball probe(code:SR10H)



Ø4mm carbide ball probe

Depth hole probe(code:DP80H)















Squareness probe
(Optional, Code:SQ10)



AccuHite700

Basic Measurement

-  1 Contacting a plane from above
-  2 Contacting a shaft from above/bore below
-  3 Measuring a shaft diameter and center
-  4 Measuring groove width and center
-  5 Contacting a plane from below
-  6 Contacting a shaft from below/ bore above
-  7 Measuring bore diameter and center
-  8 Measuring ledge width and center
-  9 Measuring MIN-MAX-DELTA
-  0 Difference key
-  + Measuring job squareness
-  +/- Set references


SPECIFICATION

Code	AccuHite700	AccuHite1000
Range	0-700mm	0-1000mm
Expandable range	1015mm	1315mm
Squareness	10μm	12μm
Resolutions	0.5μm, 1μm, 10μm	
Accuracy	3+L/250μm, L is measuring length in mm (working temperature is 20±1°C)	
Repeatability (with standard probe)	0.0015 mm on plane and 0.003 mm on bore	
Measuring force	1±0.2N	
Output	USB or RS232	
Power supply	Rechargeable battery	
Working temperature	10°C - 40°C	
Weight	21kg	

INCLUDED ACCESSORIES

Main unit	1pc
Ø4x48mm carbide ball probe	1pc
Calibration block	1pc
Software and USB cable	1pc each
Allen key	1set
AC/DC Adapter	1pc

Demo Application




SERIES HG

DIGITAL HEIGHT GAGE WITH STAND




- ◆ Working table is made of ceramic
- ◆ Response speed: max.5000mm/sec
- ◆ Easy convert between metric and inch 8 bits
- ◆ Highlight green LED
- ◆ Power off automatically
- ◆ Data output (USB port)
- ◆ Optional accessories series 270


Needle contact point




Ball contact point



HG100E



unit:mm



SPECIFICATION

Code	HG50E	HG100E	HG50S	HG100S
Measuring range	0-50mm	0-100mm	0-50mm	0-100mm
Accuracy	2 μ m*	3 μ m*	3 μ m*	4 μ m*
Resolution	0.5 μ m/1 μ m (adjustable)		1 μ m	
Repeatability	0.5 μ m	1 μ m	1 μ m	2 μ m
Tip force	≤ 1.2 N	≤ 1.6 N	≤ 1.2 N	≤ 1.6 N
Dimension of working table	130x130mm			
Flatness of working table	1.5 μ m			
Power supply	5V/1A adapter			
Working temperature	0°C - 40°C			
Weight	11.6kg			


*Working temperature is 20 \pm 1°C

INCLUDED ACCESSORIES

Main unit	1pc
Stand with ceramic table	1pc
Needle contact point	1pc
Ball contact point	1pc
AD/DC adapter	1pc
Spindle lift knob	2pcs

SERIES 181

DIGITAL HEIGHT GAGE



- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, inch/mm, ABS/INC, data hold, tolerance measurement, data preset, set data
- ◆ Carbide tipped scribe
- ◆ Made of stainless steel (except the base)
- ◆ Data output (cable code: 100-03L or 100-04L)
- ◆ With clamps (Ø8mm holder)

Clamp (included)




Carbide tipped jaws




181-024-11

type A



type B



unit: mm


Code	Range	Type	Accuracy	a1	a2	b1	b2	c	h	L
181-012-11	0-300mm/0-12"	A	±0.04mm	76	25	135	45	23	80	470
181-020-11	0-500mm/0-20"	A	±0.05mm	103	25	180	55	30	95	720
181-024-11	0-600mm/0-24"	A	±0.05mm	103	25	180	55	30	95	820
181-040-11	0-1000mm/0-40"	B	±0.07mm	110	39	250	80	50	125	1275
181-060-11	0-1500mm/0-60"	B	±0.11mm	110	39	280	80	50	125	1790
181-080-11	0-2000mm/0-80"	B	±0.15mm	110	39	280	80	50	125	2290

Application with clamps (optional)



SERIES 182

DIGITAL HEIGHT GAGE




- ◆ Resolution: 0.01mm/0.001"
- ◆ Buttons: on/off, inch/mm, ABS/INC, data preset, set data
- ◆ Carbide tipped scribe
- ◆ Made of stainless steel beam
- ◆ With driving wheel
- ◆ Optional accessory: 267 series clamps


Application with clamps (optional)



182-012-11



type A




type B

unit: mm

Carbide tipped jaws



Scriber (included)



Code	Range	Type	Accuracy	a1	a2	c	Ød	h	L
182-012-11	0-300mm/0-12"	A	±0.04mm	135	43	33	15	84	475
182-018-11	0-450mm/0-18"	A	±0.05mm	180	54	38	20	88	660
182-024-11	0-600mm/0-24"	A	±0.05mm	180	54	38	20	88	810
182-040-11	0-1000mm/0-40"	B	±0.05mm	265	68	38	20	88	1230

Driving wheel




SERIES 184

DIGITAL HEIGHT GAGE WITH DRIVING WHEEL



- Buttons: on/off, zero, mm/inch, ABS/INC, hold
- Automatic power off, move the digital unit to turn on power
- Carbide tipped scriber
- Made of stainless steel
- Data output(cable code: 100-15)
- Optional accessories: dial test indicator holder (267-050-01)


Application with clamps(optional)



Carbide tipped jaws




184-012-11



Code	Range	Accuracy	Resolution	b1	b2	L	c	a1	a2	E
184-012-11	0-300mm/0-12"	±0.03mm	0.01mm/0.0005"	180	55	515	32	80	30	9
184-024-11	0-600mm/0-24"	±0.05mm	0.01mm/0.0005"	180	55	815	32	80	30	9
184-040-11	0-1000mm/0-40"	±0.07mm	0.01mm/0.001"	265	70	1220	40	92	48	12

Scriber (included)



SERIES 185


DIAL HEIGHT GAGE

- Indicator graduation: 0.01mm
- Carbide tipped scriber
- Made of stainless steel (except the base)
- With driving wheel
- Optional accessory: 267 series clamps


Application with clamps(optional)



185-012-11



Scriber (included)



Carbide tipped jaws

Driving wheel



Code	Range	Accuracy	b1	b2	c	Ød	h	L
185-012-11	0-300mm	±0.04mm	135	43	33	15	84	475
185-018-11	0-450mm	±0.05mm	180	54	38	20	88	660
185-024-11	0-600mm	±0.05mm	180	54	38	20	88	810

SERIES 186

VERNIER HEIGHT GAGE

- ◆ Graduation: 0.02mm/0.001"
- ◆ Move main scale to set zero
- ◆ Carbide tipped scriber
- ◆ Made of stainless steel (except the base)
- ◆ Satin chrome plated scale
- ◆ With magnifier
- ◆ Optional accessory: 267 series clamps

Application with clamps (optional)




with series 261/267

with series 267/222


186-012-11

Carbide tipped jaws



Code	Range	Accuracy	a	b1	b2	c	h	D	E	L
186-012-11	0-300mm/0-12"	±0.04mm	30	135	43	28	75	9	9	545
186-018-11	0-450mm/0-18"	±0.05mm	41	180	54	35	85	9	9	720
186-024-11	0-600mm/0-24"	±0.05mm	41	180	54	35	85	9	9	870
186-040-11	0-1000mm/0-40"	±0.07mm	50	270	70	40	85	10	16	1310

Scriber (included)




SERIES 180

SCRIBER FOR HEIGHT GAGE



180-000-SC1

- ◆ Carbide tipped



Code	For height gage	Type	a1	a2	D	E
180-000-SC1	181-012-11	A	76	25	6	8
180-000-SC2	181-024-11	A	103	25	10	12
180-000-SC3	181-040-11, 181-060-11, 181-080-11	A	110	39	10	15
180-000-SC4	185-012-11, 185-018-11, 185-024-11, 182-012-11, 182-018-11, 182-024-11	B	78	15	9	9
180-000-SC6	186-012-11, 184-012-11	A	80	30	9	9
180-000-SC7	186-024-11, 186-018-11, 184-024-11	A	80	41	9	9

Carbide tipped jaws



SERIES 183


MINI DIGITAL HEIGHT GAGE



- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Carbide tipped scribe
- ◆ Made of stainless steel (except the base)
- ◆ Data output(cable code:100-03 or 100-04)
- ◆ Automatic power off



183-006-11



Carbide tipped jaws



Code	Range	Accuracy	a	c	d	L
183-006-11	0-150mm/0-6"	±0.03mm	75	43	16	265
183-008-11	0-200mm/0-8"	±0.03mm	90	49	16	325
183-010-11	0-250mm/0-10"	±0.03mm	90	49	16	380



183

MINI DIGITAL HEIGHT GAGE




- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Carbide tipped scribe
- ◆ With fine adjustment
- ◆ Made of stainless steel (except the base)
- ◆ Data output(cable code:100-11 or 100-12)
- ◆ Automatic power off

Carbide tipped jaws



Scriber (included)



Code	Range	Accuracy
183-006-12	0-150mm/0-6"	±0.03mm


SERIES 187

MINI VERNIER HEIGHT GAGE

- ◆ Graduation 0.02mm/0.001"
- ◆ Carbide tipped scribe
- ◆ Made of stainless steel (except the base)
- ◆ Satin chrome plated scale



187-008-11



Code	Range	Accuracy	a	b	c	d	L
187-006-11	0-150mm/0-6"	±0.03mm	75	57	43	16	265
187-008-11	0-200mm/0-8"	±0.03mm	90	70	49	20	325
187-010-11	0-250mm/0-10"	±0.03mm	90	70	49	20	380

Carbide tipped jaws



SERIES 187


MINI VERNIER HEIGHT GAGE

- ◆ Graduation: 0.02mm/0.001"
- ◆ Carbide tipped scribe
- ◆ Made of stainless steel (except the base)
- ◆ Satin chrome plated scale


Carbide tipped jaws



187-006-12



Scriber (included)




Code	Range	Accuracy	a	b	d	L
187-006-12	0-150mm/0-6"	±0.03mm	75	57	16	265
187-008-12	0-200mm/0-8"	±0.03mm	90	70	20	325

SERIES 313

DIGITAL OUTSIDE MICROMETER
WITH DATA OUTPUT

313-001-01S

- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, mm/inch, set, zero
- ◆ Automatic power off
- ◆ Data output
- ◆ Carbide measuring faces, ratchet stop
- ◆ Setting standards are included(except 313-001-01S)




Setting standards (included)



Data output interface



spherical anvil



measure tube wall thickness

Code	Range	Accuracy	a	c	h	L	Setting standards(included)
313-001-01S*	0-25mm/0-1"	±2μm	6	3	25	34.5	-
313-002-01S*	25-50mm/1-2"	±2μm	8	3	32	59.5	25mm
313-003-01S*	50-75mm/2-3"	±3μm	8	3	44.5	84.5	50mm
313-004-01S*	75-100mm/3-4"	±3μm	8	3	57	109.5	75mm
313-005-01S	100-125mm/4-5"	±3μm	10	3	70	135	100mm
313-006-01S	125-150mm/5-6"	±3μm	10	3	82	160.5	125mm
313-007-01S	150-175mm/6-7"	±4μm	12	5.5	94.5	186	150mm
313-008-01S	175-200mm/7-8"	±4μm	12	5.5	107	211.5	175mm
313-009-01S	200-225mm/8-9"	±4μm	23	5.5	129.5	236	200mm
313-010-01S	225-250mm/9-10"	±4μm	23	5.5	142.5	261.5	225mm
313-011-01S	250-275mm/10-11"	±5μm	23	5.5	155	287	250mm
313-012-01S	275-300mm/11-12"	±5μm	23	5.5	167.5	312.5	275mm


Set

Code	Range	Total QTY.	Included micrometers	Package
313-003-03S*	0-75mm/0-3"	3pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3"	blow mould case
313-004-04S*	0-100mm/0-4"	4pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3", 75-100mm/3-4"	blow mould case
313-006-06S	0-150mm/0-6"	6pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3", 75-100mm/3-4", 100-125mm/4-5", 125-150mm/5-6"	aluminum box


* With manufacturer inspection certificate


313-001-01

- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, mm/inch, set, zero
- ◆ Automatic power off
- ◆ Carbide measuring faces, ratchet stop
- ◆ Setting standards are included
(except **313-001-01**)



Setting standards (included)



Code	Range	Accuracy	a	c	h	L	Setting standards(included)
313-001-01*	0-25mm/0-1"	±2μm	6	3	25	34.5	-
313-002-01*	25-50mm/1-2"	±2μm	8	3	32	59.5	25mm
313-003-01*	50-75mm/2-3"	±3μm	8	3	44.5	84.5	50mm
313-004-01*	75-100mm/3-4"	±3μm	8	3	57	109.5	75mm
313-005-01	100-125mm/4-5"	±3μm	10	3	70	135	100mm
313-006-01	125-150mm/5-6"	±3μm	10	3	82	160.5	125mm
313-007-01	150-175mm/6-7"	±4μm	12	5.5	94.5	186	150mm
313-008-01	175-200mm/7-8"	±4μm	12	5.5	107	211.5	175mm

Set


Code	Range	Total QTY.	Included micrometers	Package
313-003-03*	0-75mm/0-3"	3pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3"	blow mould case
313-004-04*	0-100mm/0-4"	4pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3", 75-100mm/3-4"	blow mould case
313-006-06	0-150mm/0-6"	6pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3", 75-100mm/3-4", 100-125mm/4-5", 125-150mm/5-6"	aluminum box

* With manufacturer inspection certificate




312-001-03

- ◆ Resolution: 0.001mm/0.00005"
- ◆ Button: ON/OFF/SET, ABS/INC/UNIT
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting standards are included
(except 312-001-03)



unit: mm

Setting standards (included)



spherical anvil

measure tube wall thickness

Code	Range	Accuracy	a	h	L	Setting standards(included)
312-001-03*	0-25mm/0-1"	±2μm	6	27.5	32	-
312-002-03*	25-50mm/1-2"	±2μm	8	37	57	25mm
312-003-03*	50-75mm/2-3"	±3μm	8	50	82	50mm
312-004-03*	75-100mm/3-4"	±3μm	10	61	107	75mm
312-005-03	100-125mm/4-5"	±3μm	10	73	132	100mm
312-006-03	125-150mm/5-6"	±3μm	10	85	157	125mm
312-007-03	150-175mm/6-7"	±4μm	21	104	182	150mm
312-008-03	175-200mm/7-8"	±4μm	21	117	207	175mm

Set

Code	Range	Total QTY.	Included micrometers	Package
312-003-33*	0-75mm/0-3"	3pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3"	blow mould case
312-004-44*	0-100mm/0-4"	4pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3", 75-100mm/3-4"	blow mould case
312-006-66	0-150mm/0-6"	6pcs	0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3", 75-100mm/3-4", 100-125mm/4-5", 125-150mm/5-6"	aluminum box

* With manufacturer inspection certificate

SERIES 314


DIGITAL SNAP MICROMETER



- ◆ Quick measurement with lever
- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, mm/inch, origin, ABS/zero
- ◆ Automatic power off
- ◆ Carbide measuring faces
- ◆ Setting standards are included (except 314-001-02)



314-001-02



Code	Range	Accuracy	h	L	Setting standards (included)
314-001-02	0-25mm/0-1"	3μm	25	31	-
314-002-02	25-50mm/1-2"	3μm	32	57	25mm
314-003-02	50-75mm/2-3"	4μm	44.5	82	50mm
314-004-02	75-100mm/3-4"	4μm	57	107	75mm

Setting standards (included)



Quick movement



SERIES 390

OUTSIDE MICROMETER WITH COUNTER




- ◆ Counter resolution: 0.01mm
- ◆ Thimble graduation: 0.01mm
- ◆ Carbide measuring faces
- ◆ Meet DIN863-1
- ◆ Ratchet stop
- ◆ Setting standards are included (except 0-25mm)



390-001-01

Code	Range	Accuracy	a	h	L	Setting standards (included)
390-001-01*	0-25mm	4μm	6	26	32	-
390-002-01*	25-50mm	4μm	8	32	57	25mm
390-003-01*	50-75mm	5μm	8	44.5	82	50mm
390-004-01*	75-100mm	5μm	8	57	107	75mm
390-005-01	100-125mm	6μm	17	71.5	132.5	100mm
390-006-01	125-150mm	6μm	17	84	157.5	125mm
390-007-01	150-175mm	7μm	20	98.5	185	150mm
390-008-01	175-200mm	7μm	20	111	210.5	175mm
390-009-01	200-225mm	8μm	20	124	236	200mm
390-010-01	225-250mm	8μm	20	136.5	261	225mm
390-011-01	250-275mm	9μm	20	149	287	250mm
390-012-01	275-300mm	9μm	20	162	312	275mm



Setting standards (included)



* With manufacturer inspection certificate

SERIES 321

OUTSIDE MICROMETER




- ◆ Graduation: 0.01mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting standards are included (except 321-001-01)



321-001-01

Setting standards(included)



Code	Range	Accuracy	a	h	L	Setting standards (included)
321-001-01*	0-25mm	4μm	9	29	32	-
321-002-01*	25-50mm	4μm	9	39	58	25mm
321-003-01*	50-75mm	5μm	10	53	83	50mm
321-004-01*	75-100mm	5μm	10	65	109	75mm
321-005-01	100-125mm	6μm	11.5	76	133	100mm
321-006-01	125-150mm	6μm	11.5	88	159	125mm
321-007-01	150-175mm	7μm	11.5	101	185	150mm
321-008-01	175-200mm	7μm	11.5	114	210	175mm
321-009-01	200-225mm	8μm	11.5	126	235	200mm
321-010-01	225-250mm	8μm	12	139	260	225mm
321-011-01	250-275mm	9μm	12.5	151	286	250mm
321-012-01	275-300mm	9μm	12.5	164	311	275mm



321-006-06



321-012-06

Code	Range	Total QTY.	Included micrometers	Setting standards(included)	Package
321-003-03*	0-75mm	3pcs	0-25, 25-50, 50-75mm	25, 50mm	blow mould case
321-004-04*	0-100mm	4pcs	0-25, 25-50, 50-75, 75-100mm	25, 50, 75mm	blow mould case
321-006-06	0-150mm	6pcs	0-25, 25-50, 50-75, 75-100, 100-125, 125-150mm	25, 50, 75, 100, 125mm	blow mould case
321-012-06	150-300mm	6pcs	150-175, 175-200, 200-225, 225-250, 250-275, 275-300mm	150, 175, 200, 225, 250, 275mm	aluminum box
321-012-12	0-300mm	12pcs	0-25, 25-50, 50-75, 75-100, 100-125, 125-150, 150-175, 175-200, 200-225, 225-250, 250-275, 275-300mm	25, 50, 75, 100, 125, 150, 175, 200, 225, 250, 275mm	aluminum box


* With manufacturer inspection certificate

SERIES 322

MICRO GRADUATION OUTSIDE MICROMETER



- ◆ Graduation: 0.001mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting standards are included (except 322-001-01)



Code	Range	Accuracy	a	h	L	Setting standards(included)
322-001-01 *	0-25mm	4μm	9	29	32	-
322-002-01 *	25-50mm	4μm	9	39	58	25mm
322-003-01 *	50-75mm	5μm	10	53	83	50mm
322-004-01 *	75-100mm	5μm	10	65	109	75mm
322-005-01	100-125mm	6μm	11.5	76	133	100mm
322-006-01	125-150mm	6μm	11.5	88	159	125mm
322-007-01	150-175mm	7μm	11.5	101	185	150mm
322-008-01	175-200mm	7μm	11.5	114	210	175mm

* With manufacturer inspection certificate

Setting standards (included)



SERIES 323

OUTSIDE MICROMETER



- ◆ Graduation 0.01mm
- ◆ Carbide measuring faces
- ◆ Meet DIN863-1
- ◆ Supplied with setting standards (except 0-25mm)



Code	Range	Accuracy	a	h	L	Setting standards(included)
323-001-01 *	0-25mm	4μm	6	24	32	-
323-002-01 *	25-50mm	4μm	8	32	57	25mm
323-003-01 *	50-75mm	5μm	8	45	82	50mm
323-004-01 *	75-100mm	5μm	8	57	107	75mm
323-005-01	100-125mm	6μm	8	70	133	100mm
323-006-01	125-150mm	6μm	8	82	125	125mm
323-007-01	150-175mm	7μm	8	95	183	150mm
323-008-01	175-200mm	7μm	8	107	209	175mm

Setting standards (included)



Set

Code	Range	Total QTY.	Included micrometers
323-003-03 *	0-75mm	3pcs	0-25mm, 25-50mm/, 50-75mm
323-004-04 *	0-100mm	4pcs	0-25mm, 25-50mm, 50-75mm, 75-100mm
323-006-06	0-150mm	6pcs	0-25mm, 25-50mm, 50-75mm, 75-100mm, 100-125mm, 125-150mm

* With manufacturer inspection certificate




SERIES 324

OUTSIDE MICROMETER

- ◆ Graduation: 0.0001in
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting standards are included (except 324-001-01)



324-003-01



324-001-01

Code	Range	Accuracy	a	h	L	Setting standards (included)
324-001-01	0-1"	±0.00016"	9	29	32	-
324-002-01	1-2"	±0.00016"	14	39	58	1"
324-003-01	2-3"	±0.0002"	15	53	83	2"
324-004-01	3-4"	±0.0002"	15	65	109	3"
324-005-01	4-5"	±0.00024"	16.5	76	133	4"
324-006-01	5-6"	±0.00024"	16.5	88	159	5"
324-007-01	6-7"	±0.00028"	19.4	101	32	6"
324-008-01	7-8"	±0.00028"	19.4	114	58	7"
324-009-01	8-9"	±0.00031"	19.4	126	83	8"
324-010-01	9-10"	±0.00031"	19.4	139	109	9"
324-011-01	10-11"	±0.00035"	19.4	151	133	10"
324-012-01	11-12"	±0.00035"	19.4	164	159	11"

Setting standards (included)



324-006-06



324-012-06


MICROMETER SET

Code	Range	Total quantity	Included micrometers	Setting standards(included)	Package
324-003-03	0-3"	3pcs	0-1", 1-2", 2-3"	1", 2"	blow mould case
324-004-04	0-4"	4pcs	0-1", 1-2", 2-3", 3-4"	1", 2", 3"	blow mould case
324-006-06	0-6"	6pcs	0-1", 1-2", 2-3", 3-4", 4-5", 5-6"	1", 2", 3", 4", 5"	blow mould case
324-012-06	6-12"	6pcs	6-7", 7-8", 8-9", 9-10", 10-11", 11-12"	6", 7", 8", 9", 10", 11"	aluminum box
324-012-12	0-12"	12pcs	0-1", 1-2", 2-3", 3-4", 4-5", 5-6", 6-7", 7-8", 8-9", 9-10", 10-11", 11-12"	1", 2", 3", 4", 5", 6", 7", 8", 9", 10", 11"	aluminum box

320

MINI OUTSIDE MICROMETER

- ◆ Chrome plated frame
- ◆ Pocket size, easy to carry



Code	Range	Graduation
320-015-01	0-15mm	0.01mm



- ◆ Resolution 0.001mm/0.0001"
(resolution of **315-004-01** and **315-006-01**
is 0.001mm/0.00005")
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC,
data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards

Setting standards (included)

315-004-01

315-020-01

unit: mm


type A

type B

Code	Range	Accuracy	L	h	Type	Setting standards (included)
315-004-01	0-100mm/0-4"	±5μm	105	57	A	25,50,75mm
315-006-01	0-150mm/0-6"	±6μm	155	82	A	25,50,75,100,125mm
315-012-01	150-300mm/6-12"	±8μm	305	165	A	150,175,200,225,250,275mm
315-012-02	200-300mm/8-12"	±8μm	305	165	A	200,225,250,275mm
315-016-01	300-400mm/12-16"	±9μm	405	224	B	325,375mm
315-020-01	400-500mm/16-20"	±11μm	505	275	B	425,475mm
315-024-01	500-600mm/20-24"	±12μm	605	321	B	525,575mm
315-028-01	600-700mm/24-28"	±13μm	705	371	B	625,675mm
315-032-01	700-800mm/28-32"	±15μm	805	426	B	725,775mm
315-036-01	800-900mm/32-36"	±16μm	905	476	B	825,875mm
315-040-01	900-1000mm/36-40"	±17μm	1005	576	B	925,975mm



SERIES 325

OUTSIDE MICROMETER WITH INTERCHANGEABLE ANVILS

- ◆ Graduation: 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards






325-006-01

unit: mm

Setting standards (included)



Interchangeable anvils (included)



Code	Range	Type	Accuracy	L	h	Setting standards(included)
325-002-01	0-50mm	A	4μm	58	35	25mm
325-004-01	0-100mm	A	5μm	108	57	25,50,75mm
325-006-01	0-150mm	A	6μm	158	82	25,50,75,100,125mm
325-008-01	100-200mm	A	7μm	208	114	100,125,150,175mm
325-012-01	150-300mm	A	9μm	308	165	150,175,200,225,250,275mm
325-006-02	50-150mm	A	6μm	158	82	50,75,100,125mm
325-012-02	200-300mm	A	9μm	308	165	200,225,250,275mm
325-016-02	300-400mm	B	11μm	409	224	325,375mm
325-020-02	400-500mm	B	13μm	509	275	425,475mm
325-024-02	500-600mm	B	14μm	609	321	525,575mm
325-028-02	600-700mm	B	16μm	709	371	625,675mm
325-032-02	700-800mm	B	18μm	809	426	725,775mm
325-036-02	800-900mm	B	20μm	909	476	825,875mm
325-040-02	900-1000mm	B	22μm	1009	576	925,975mm

SERIES 325

OUTSIDE MICROMETER WITH INTERCHANGEABLE ANVILS

- ◆ Graduation: .0001" (within 12")
.001" (over 12")
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards





325-006-E01


Setting standards (included)



Interchangeable anvils (included)



type A



type B


Code	Range	Type	Accuracy	L	h	Setting standards (included)
325-002-E01	0-2"	A	.00015"	2.283"	1.378"	1"
325-004-E01	0-4"	A	.00020"	4.252"	2.244"	1", 2", 3"
325-006-E01	0-6"	A	.00025"	6.220"	3.228"	1", 2", 3", 4", 5"
325-008-E01	4-8"	A	.00030"	8.189"	4.488"	4", 5", 6", 7"
325-012-E01	6-12"	A	.00035"	12.126"	6.496"	6", 7", 8", 9", 10", 11"
325-016-E02	12-16"	B	.00045"	16.102"	8.819"	13", 15"
325-020-E02	16-20"	B	.00050"	20.039"	10.827"	17", 19"
325-024-E02	20-24"	B	.00055"	23.976"	12.638"	21", 23"
325-028-E02	24-28"	B	.00065"	27.913"	14.606"	25", 27"
325-032-E02	28-32"	B	.00070"	31.850"	16.772"	29", 31"
325-036-E02	32-36"	B	.00080"	35.787"	18.740"	33", 35"
325-040-E02	36-40"	B	.00085"	39.724"	22.677"	37", 39"



SERIES 329

OUTSIDE MICROMETER WITH EXTENSION ANVIL



- ◆ Adjust collars for different measuring ranges
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards



329-016-01

unit: mm

Adjust collars for different measuring ranges



Setting standards(included)




Code	Range	Accuracy	L	h	Setting standards(included)
329-016-01	300-400mm	11μm	410	250	325,375mm
329-020-01	400-500mm	13μm	510	275	425,475mm
329-024-01	500-600mm	14μm	610	320	525,575mm
329-028-01	600-700mm	16μm	710	370	625,675mm
329-032-01	700-800mm	18μm	810	425	725,775mm
329-036-01	800-900mm	20μm	910	475	825,875mm
329-040-01	900-1000mm	22μm	1010	575	925,975mm
329-048-01	1000-1200mm	22μm	1210	645	1050,1150mm
329-056-01	1200-1400mm	24μm	1410	745	1250,1350mm
329-064-01	1400-1600mm	28μm	1610	845	1450,1550mm
329-072-01	1600-1800mm	31μm	1810	945	1650,1750mm
329-080-01	1800-2000mm	34μm	2010	1045	1850,1950mm



430-012-01


- ◆ Meet DIN863-3
- ◆ Graduation 0.01 mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards
- ◆ Optional accessory: dial indicators or digital indicators

unit: mm



Type A

Optional indicators(optional)



Type B

Code	Range	Type	Accuracy	L	h
430-004-01	0-100mm	A	6μm	115	68
430-008-01	100-200mm	A	7μm	215	120
430-012-01	200-300mm	A	8μm	315	170
430-016-01	300-400mm	B	9μm	415	225
430-020-01	400-500mm	B	10μm	515	275
430-024-01	500-600mm	B	11μm	615	325
430-028-01	600-700mm	B	12μm	715	375
430-032-01	700-800mm	B	13μm	815	430
430-036-01	800-900mm	B	14μm	915	480
430-040-01	900-1000mm	B	15μm	1015	530

Setting standards(included)



SERIES 316


DIGITAL BLADE MICROMETER



- ◆ Measure the groove diameter of shafts and keyways
- ◆ Resolution 0.001mm/0.00005"
- ◆ Non-rotating spindle
- ◆ Button: on/off, set, mm/inch, ABS/INC
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Supplied with setting standards(except 0-25mm/0-1")




316-001-01





Code	Range	Accuracy	Type	h	L	Setting standards (included)
316-001-01	0-25mm/0-1"	±4μm	A	32	57	-
316-002-01	25-50mm/1-2"	±4μm	A	44.5	82	25mm
316-003-01	50-75mm/2-3"	±5μm	A	57	107	50mm
316-004-01	75-100mm/3-4"	±5μm	A	70	133	75mm
316-005-01	100-125mm/4-5"	±6μm	A	82	158	100mm
316-006-01	125-150mm/5-6"	±6μm	A	94.5	183.4	125mm
316-007-01	150-175mm/6-7"	±7μm	A	107	208.8	150mm
316-001-02	0-25mm/0-1"	±4μm	B	32	57	-
316-002-02	25-50mm/1-2"	±4μm	B	44.5	82	25mm

Application



Setting standards (included)




SERIES 326

BLADE MICROMETER

- ◆ Measure the small groove diameter
- ◆ Graduation: 0.01mm
- ◆ Non-rotating spindle
- ◆ Ratchet stop
- ◆ Setting standards are included (except 0-25mm)



326-001-03






Code	Range	Anvil	Accuracy	h	L	Setting standards (included)
326-001-03	0-25mm	A	4μm	35	57	-
326-002-03	25-50mm	A	4μm	46	82	25mm
326-003-03	50-75mm	A	5μm	58	107	50mm
326-004-03	75-100mm	A	5μm	70	133	75mm
326-005-03	100-125mm	A	6μm	83	158	100mm
326-006-03	125-150mm	A	6μm	96	183	125mm
326-007-03	150-175mm	A	7μm	109	209	150mm
326-001-04	0-25mm	B	4μm	35	57	-
326-002-04	25-50mm	B	4μm	46	82	25mm

Setting standards (included)



Application



SERIES 317


DIGITAL POINT MICROMETER



- ◆ Measure the web thickness of drills, small grooves and keyways
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Carbide tips
- ◆ Supplied with setting standards (except 0-25mm/0-1")



317-002-02



Code	Range	Accuracy	Type	h	L	Setting standards (included)
317-001-01	0-25mm/0-1"	±4μm	A	32	57	-
317-002-01	25-50mm/1-2"	±4μm	A	44.5	82	25mm
317-003-01	50-75mm/2-3"	±5μm	A	57	107	50mm
317-004-01	75-100mm/3-4"	±5μm	A	70	133	75mm
317-001-02	0-25mm/0-1"	±4μm	B	32	57	-
317-002-02	25-50mm/1-2"	±4μm	B	44.5	82	25mm
317-003-02	50-75mm/2-3"	±5μm	B	57	107	50mm
317-004-02	75-100mm/3-4"	±5μm	B	70	133	75mm


SERIES 327

POINT MICROMETER

- ◆ Measure the thickness of drills, small grooves and keyways
- ◆ Graduation: 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Setting standards are included (except 0-25mm)



327-002-03



Code	Range	Anvil	Accuracy	h	L	Setting standards (included)
327-001-03	0-25mm	A	4μm	39	58	-
327-002-03	25-50mm	A	4μm	53	83	25mm
327-003-03	50-75mm	A	5μm	65	109	50mm
327-004-03	75-100mm	A	5μm	76	133	75mm
327-001-04	0-25mm	B	4μm	39	58	-
327-002-04	25-50mm	B	4μm	53	83	25mm
327-003-04	50-75mm	B	5μm	65	109	50mm
327-004-04	75-100mm	B	5μm	76	133	75mm

SERIES 318


DIGITAL SPLINE MICROMETER



- ◆ Measure splined shafts, slots and keyways
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards (except 0-25mm/0-1")



318-001-02






Code	Range	Accuracy	Type	h	L	Setting standards (included)
318-001-01	0-25mm/0-1"	±4μm	A	32	57	-
318-002-01	25-50mm/1-2"	±4μm	A	44.5	82	25mm
318-003-01	50-75mm/2-3"	±5μm	A	57	107	50mm
318-004-01	75-100mm/3-4"	±5μm	A	70	133	75mm
318-001-02	0-25mm/0-1"	±4μm	B	32	57	-
318-002-02	25-50mm/1-2"	±4μm	B	44.5	82	25mm
318-003-02	50-75mm/2-3"	±5μm	B	57	107	50mm
318-004-02	75-100mm/3-4"	±5μm	B	70	133	75mm

Setting standards(included)



Application






SERIES 328

SPLINE MICROMETER

- ◆ Measure grooves and sharped parts
- ◆ Graduation: 0.01mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting standards are included (except 0-25mm)



328-001-03




Code	Range	Anvil	Accuracy	h	L	Setting standards(included)
328-001-03	0-25mm	B	4μm	39	58	-
328-002-03	25-50mm	B	4μm	53	83	25mm
328-003-03	50-75mm	B	5μm	65	109	50mm
328-004-03	75-100mm	B	5μm	76	133	75mm
328-005-03	100-125mm	B	6μm	82	158	100mm
328-006-03	125-150mm	B	6μm	94.5	183.4	125mm
328-007-03	150-175mm	B	7μm	107	208.8	150mm
328-001-04	0-25mm	A	4μm	39	58	-

Setting standards (included)





Application





- ◆ Measure the height of crimp contact
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop




Code	Range	Accuracy
319-001-01	0-25mm/0-1"	±4μm

SERIES 346




CRIMP HEIGHT MICROMETER

- ◆ Measure the height of crimp contact
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except 0-25mm)



346-001-01

Setting standards(included)





Code	Range	Accuracy	Type	L	h	Setting standards (included)
346-001-01	0-25mm	4μm	A	34	24	-
346-001-02	0-25mm	4μm	B	34	24	-
346-002-02	25-50mm	4μm	B	59	32	25
346-003-02	50-75mm	5μm	B	85	45	50
346-004-02	75-100mm	5μm	B	110	57	75

319

DIGITAL POINT MICROMETER



- ◆ Measure the height of crimp contact
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop



Code	Range	Accuracy
319-001-21	0-25mm/0-1"	±4μm

SERIES 331



DIGITAL SPHERICAL ANVIL TUBE MICROMETER



- ◆ Measure wall thickness of tubes
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards (except 0-25mm/0-1")





331-001-02



Code	Range	Accuracy	Type	L	h	Setting standards(included)
331-001-01	0-25mm/0-1"	4μm	A	32	24	-
331-002-01	25-50mm/1-2"	4μm	A	57	32	25mm
331-003-01	50-75mm/2-3"	5μm	A	82	44.5	50mm
331-004-01	75-100mm/3-4"	5μm	A	107	57	75mm
331-001-02	0-25mm/0-1"	4μm	B	32	24	100mm
331-002-02	25-50mm/1-2"	4μm	B	57	32	125mm
331-003-02	50-75mm/2-3"	5μm	B	82	44.5	150mm
331-004-02	75-100mm/3-4"	5μm	B	107	57	175mm



Setting standards (included)



SERIES 340

SPHERICAL ANVIL TUBE MICROMETER


- ◆ Measure wall thickness of tubes
- ◆ Graduation: 0.01mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting standards are included (except 0-25mm)



Setting standards
(included)




340-001-01



Code	Range	Type	Accuracy	L	h	Setting standards (included)
340-001-01	0-25mm	A	4μm	32	24	-
340-002-01	25-50mm	A	4μm	57	32	25mm
340-003-01	50-75mm	A	5μm	82	44.5	50mm
340-004-01	75-100mm	A	5μm	107	57	75mm
340-005-01	100-125mm	A	6μm	133	70	100mm
340-006-01	125-150mm	A	6μm	158	82	125mm
340-007-01	150-175mm	A	7μm	183	95	150mm
340-001-02	0-25mm	B	4μm	32	24	-
340-002-02	25-50mm	B	4μm	57	32	25mm
340-003-02	50-75mm	B	5μm	82	44.5	50mm
340-004-02	75-100mm	B	5μm	107	57	75mm
340-005-02	100-125mm	B	6μm	133	70	100mm
340-006-02	125-150mm	B	6μm	158	82	125mm
340-007-02	150-175mm	B	7μm	183	95	150mm

Application



SERIES 380


DIGITAL CYLINDRICAL ANVIL TUBE MICROMETER

- ◆ Measure wall thickness of tubes
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Carbide spindle tip




380-001-04

unit: mm




380-001-01

Application



Code	Range	Accuracy	Type
380-001-01	0-25mm/0-1"	±6μm	A
380-001-02	0-25mm/0-1"	±6μm	B
380-001-03	0-25mm/0-1"	±6μm	C
380-001-04	0-25mm/0-1"	±6μm	D






SERIES 341

TUBE MICROMETER

- ◆ Measure the wall thickness of tube, bearing and rings
- ◆ Graduation: 0.01mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting standards are included (except 0-25mm)




341-001-01




Setting standards(included)



Application



Code	Range	Anvil	Accuracy	h	L	Setting standards (included)
341-001-01	0-25mm	A	6μm	24	32	-
341-002-01	25-50mm	A	6μm	32	57	25mm
341-001-02	0-25mm	B	6μm	24	34	-
341-002-02	25-50mm	B	6μm	32	57	25mm
341-001-03	0-25mm	C	6μm	24	31	-
341-002-03	25-50mm	C	6μm	32	61	25mm
341-001-04	0-25mm	D	6μm	24	30	-
341-002-04	25-50mm	D	6μm	32	61	25mm
341-001-05	0-25mm	E	6μm	25	30	-
341-002-05	25-50mm	E	6μm	32	61	25mm
341-001-06	0-25mm	F	6μm	25	31	-
341-002-06	25-50mm	F	6μm	32	61	25mm



332

DIGITAL NON ROTATING SPINDLE DISK MICROMETER




- ◆ Measure root tangent length of gear
- ◆ Resolution 0.001mm/0.00005"
- ◆ Non-rotating spindle
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except 332-001-01)




332-001-01


Setting standards(included)



Application



Code	Range	Accuracy	L	h	ØD	Setting standards (included)
332-001-01	0-25mm/0-1"	±4μm	43	32	20	-
332-002-01	25-50mm/1-2"	±4μm	68	44.5	20	25mm
332-003-01	50-75mm/2-3"	±5μm	93	57	20	50mm
332-004-01	75-100mm/3-4"	±5μm	118.5	70	20	75mm
332-005-01	100-125mm/4-5"	±6μm	144	82	30	100mm
332-006-01	125-150mm/5-6"	±6μm	169.5	94.5	30	125mm



SERIES 342


DISK MICROMETER

- ◆ Measure root tangent length of gear
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except 0-25mm)



Setting standards(included)



342-002-02



Application



Code	Range	Accuracy	L	h	c	ØD	Setting standards (included)
342-001-02	0-25mm	4µm	34	24	3.3	20	-
342-002-02	25-50mm	4µm	59	32	3.3	20	25mm
342-003-02	50-75mm	5µm	85	45	3.3	20	50mm
342-004-02	75-100mm	5µm	110	57	3.3	20	75mm
342-005-02	100-125mm	6µm	138	70	4.3	30	100mm
342-006-02	125-150mm	6µm	163	82	4.3	30	125mm
342-007-02	150-175mm	7µm	188	95	4.3	30	150mm
342-008-02	175-200mm	7µm	214	107	4.3	30	175mm

SERIES 342


NON-ROTATING SPINDLE DISK MICROMETER(ECONOMIC TYPE)

- ◆ Measure root tangent length of gear
- ◆ Graduation 0.01mm
- ◆ Non-rotating spindle
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except 0-25mm)



Setting standards(included)



342-002-01



Application






Code	Range	Accuracy	Parallelism	L	h	c	ØD	Setting standards (included)
342-001-01	0-25mm	4µm	5µm	34	24	3.3	20	-
342-002-01	25-50mm	4µm	5µm	59	32	3.3	20	25mm
342-003-01	50-75mm	5µm	5µm	85	45	3.3	20	50mm
342-004-01	75-100mm	5µm	5µm	110	57	3.3	20	75mm
342-005-01	100-125mm	6µm	5µm	138	70	4.3	30	100mm
342-006-01	125-150mm	6µm	5µm	163	82	4.3	30	125mm





334-020-01

- ◆ Measure the diameter of parts or cutting tools with odd grooves such as taps, reamers and end mills
- ◆ Resolution: 0.001mm/0.00005"
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off, Ratchet stop
- ◆ Data output
- ◆ Carbide measuring faces



Setting standards
(included)








Code	Range	Accuracy	Flutes	α	Type	Setting standards (included)
334-015-01	1-15mm/0.04-0.6"	$\pm 4\mu\text{m}$	3	60°	A	5mm
334-020-01	5-20mm/0.2-0.8"	$\pm 4\mu\text{m}$	3	60°	B	5mm
334-035-01	20-35mm/0.8-1.4"	$\pm 5\mu\text{m}$	3	60°	B	20mm
334-050-01	35-50mm/1.4-2.0"	$\pm 5\mu\text{m}$	3	60°	B	35mm
334-065-01	50-65mm/2.0-2.6"	$\pm 6\mu\text{m}$	3	60°	B	50mm
334-080-01	65-80mm/2.6-3.2"	$\pm 6\mu\text{m}$	3	60°	B	65mm
334-095-01	80-95mm/3.2-3.6"	$\pm 6\mu\text{m}$	3	60°	B	80mm
334-025-55	5-25mm/0.2-1.0"	$\pm 4\mu\text{m}$	5	108°	B	5mm
334-045-55	25-45mm/1.0-1.8"	$\pm 5\mu\text{m}$	5	108°	B	25mm
334-065-55	45-65mm/1.8-2.6"	$\pm 6\mu\text{m}$	5	108°	B	50mm
334-085-55	65-85mm/2.6-3.4"	$\pm 6\mu\text{m}$	5	108°	B	65mm
334-105-55	85-105mm/3.3-4.2"	$\pm 6\mu\text{m}$	5	108°	B	85mm
334-025-77	5-25mm/0.2-1.0"	$\pm 4\mu\text{m}$	7	$128^\circ 34' 17''$	B	5mm
334-045-77	25-45mm/1.0-1.8"	$\pm 4\mu\text{m}$	7	$128^\circ 34' 17''$	B	25mm
334-065-77	45-65mm/1.8-2.6"	$\pm 5\mu\text{m}$	7	$128^\circ 34' 17''$	B	50mm
334-085-77	65-85mm/2.6-3.4"	$\pm 5\mu\text{m}$	7	$128^\circ 34' 17''$	B	65mm


334-006-01

- ◆ Measure the diameter of parts or cutting tools with odd grooves such as taps, reamers and end mills
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards

Setting standards
(included)



Code	Range	Accuracy	Flutes	α	Type	Setting standards(included)
334-006-01	1-15mm	4 μ m	3	60°	A	5mm
334-008-01	5-20mm	4 μ m	3	60°	B	5mm
334-012-01	20-35mm	5 μ m	3	60°	B	20mm
334-019-01	35-50mm	5 μ m	3	60°	B	35mm
334-024-01	50-65mm	6 μ m	3	60°	B	50mm
334-032-01	65-80mm	6 μ m	3	60°	B	65mm
334-036-01	80-95mm	7 μ m	3	60°	B	80mm
334-025-05	5-25mm	4 μ m	5	108°	B	5mm
334-045-05	25-45mm	5 μ m	5	108°	B	25mm
334-065-05	45-65mm	6 μ m	5	108°	B	50mm
334-085-05	65-85mm	7 μ m	5	108°	B	65mm
334-025-07	5-25mm	4 μ m	7	128°34'17"	B	5mm
334-045-07	25-45mm	5 μ m	7	128°34'17"	B	25mm
334-065-07	45-65mm	6 μ m	7	128°34'17"	B	50mm
334-085-07	65-85mm	7 μ m	7	128°34'17"	B	65mm

SERIES 333

DIGITAL SCREW THREAD MICROMETER





ACEUD



- ◆ Measure pitch diameter of screw threads
- ◆ Resolution 0.001mm/0.00005"
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Non- rotating spindle
- ◆ Ratchet stop
- ◆ Supplied with 60° setting standards (except 333-001-01)
- ◆ Optional accessory: 55° setting standards



333-001-01



Setting standards



Accuracy of micrometers with tips

Pitch	Range (mm)							
	0-25	25-50	50-75	75-100	100-125	125-200	200-225	225-300
0.4-0.5	±0.01	-	-	-	-	-	-	-
0.6-0.8	±0.01	±0.013	-	-	-	-	-	-
1-1.25	±0.012	±0.015	±0.017	±0.017	-	-	-	-
1.5-2.0	±0.014	±0.017	±0.019	±0.019	±0.020	±0.023	±0.025	±0.028
2.5-3.5	±0.016	±0.019	±0.021	±0.021	±0.023	±0.025	±0.028	±0.031
4.0-7.0	-	±0.021	±0.023	±0.023	±0.025	±0.028	±0.031	±0.033

Code	Range	Micrometer head accuracy	L	h	Setting standards (included)
333-001-01	0-25mm/0-1"	±4μm	42	26	-
333-002-01	25-50mm/1-2"	±4μm	67	38	25mm
333-003-01	50-75mm/2-3"	±5μm	92	50	50mm
333-004-01	75-100mm/3-4"	±5μm	117.6	62	75mm
333-005-01	100-125mm/4-5"	±6μm	143	70	100mm
333-006-01	125-150mm/5-6"	±6μm	168	82	125mm
333-007-01	150-175mm/6-7"	±7μm	192	94.5	150mm
333-008-01	175-200mm/7-8"	±7μm	217	107	175mm
333-009-01	200-225mm/8-9"	±8μm	242	130	200mm
333-010-01	225-250mm/9-10"	±8μm	267	142	225mm
333-011-01	250-275mm/10-11"	±9μm	291	155	250mm
333-012-01	275-300mm/11-12"	±9μm	317	167	275mm

SERIES 335


LIMIT MICROMETER

- ◆ Used as Go/No-Go gauge by setting upper and lower limits
- ◆ Graduation 0.002mm
- ◆ Carbide measuring faces
- ◆ Supplied with setting standard (except 335-001-01)




335-001-01

Setting standards(included)



Application



Code	Range	Accuracy	L	a	h	Setting standards(included)
335-001-01	0-25mm	4μm	32	12	24	-
335-002-01	25-50mm	4μm	57	15	32	25mm

MICROMETER



SERIES 350

DIGITAL SHEET METAL MICROMETER







- ◆ Deep frame suitable for sheet metal, paper and plastic
- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, mm/inch, set, zero, ABS/INC, date output
- ◆ Automatic power off
- ◆ Data output
- ◆ Carbide measuring faces, ratchet stop



350-001-11

unit: mm


Code	Range	Accuracy	Type	h
350-001-11	0-25mm/0-1"	±3μm	A	50
350-001-12	0-25mm/0-1"	±5μm	A	100
350-001-13	0-25mm/0-1"	±7μm	A	150
350-001-21	0-25mm/0-1"	±3μm	B	50
350-001-22	0-25mm/0-1"	±5μm	B	100
350-001-23	0-25mm/0-1"	±7μm	B	150
350-001-24	0-25mm/0-1"	±10μm	B	310
350-001-31	0-25mm/0-1"	±3μm	C	50
350-001-32	0-25mm/0-1"	±5μm	C	100
350-001-33	0-25mm/0-1"	±7μm	C	150



SERIES 336


SHEET METAL MICROMETER

- ◆ Deep frame suitable for sheet metal, paper and plastic
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces






336-001-01

unit: mm



Code	Range	Accuracy	Type	h
336-001-11	0-25mm	4μm	A	50
336-001-21	0-25mm	4μm	B	50
336-001-31	0-25mm	4μm	C	50
336-001-01	0-25mm	7μm	B	100
336-001-02	0-25mm	7μm	A	155
336-001-03	0-25mm	7μm	B	155
336-001-04	0-25mm	7μm	C	155
336-001-05	0-25mm	10μm	B	310



SERIES 339


DIGITAL JAW TYPE MICROMETER




- ◆ Resolution: 0.001mm/0.00005"
- ◆ Buttons: on/off, set, mm/inch, ABS/INC data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Non-rotating spindle
- ◆ Supplied with setting standards (except 339-001-01)





339-001-01



Setting standards(included)



Application



Code	Range	Accuracy	L	a	h	R	D	Setting standards(included)
339-001-01	0-25mm/0-1"	4μm	43	6.5	32	10	8	-
339-002-01	25-50mm/1-2"	4μm	85	6.5	44.5	10	8	25mm
339-003-01	50-75mm/2-3"	5μm	110	6.5	57	10	8	50mm
339-004-01	75-100mm/3-4"	5μm	135	6.5	70	10	8	75mm
339-005-01	100-125mm/4-5"	6μm	160	11.5	86	15	12	100mm
339-006-01	125-150mm/5-6"	6μm	186	11.5	94.5	15	12	125mm
339-007-01	150-175mm/6-7"	7μm	211	11.5	107	15	12	150mm
339-008-01	175-200mm/7-8"	7μm	236	11.5	120	15	12	175mm

SERIES 330


JAW TYPE MICROMETER

- ◆ Graduation :0.01mm
- ◆ Non-rotating spindle, painted frame,
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except 330-001-01)

Setting standards(included)





330-001-01



unit: mm

Code	Range	Accuracy	L	a	R	D	Setting standards (included)
330-001-01	0-25mm	4μm	34	6	10	8	-
330-002-01	25-50mm	4μm	59	6	10	8	25mm
330-003-01	50-75mm	5μm	85	6	10	8	50mm
330-004-01	75-100mm	5μm	110	6	10	8	75mm
330-005-01	100-125mm	6μm	138	9	15	12	100mm
330-006-01	125-150mm	6μm	163	9	15	12	125mm
330-007-01	150-175mm	7μm	188	9	15	12	150mm
330-008-01	175-200mm	7μm	214	9	15	12	175mm

Application



SERIES 338



DIGITAL CALIPER TYPE MICROMETER



- ◆ Resolution: 0.001mm/0.0005"
- ◆ Buttons: on/off, set, mm/inch, ABS/INC data output
- ◆ Automatic power off
- ◆ Date output
- ◆ Supplied with setting standards (except **338-001-01**)



338-001-01



Code	Range	Accuracy	L	Setting standards(included)
338-001-01	0-25mm/0-1"	10µm	56	-
338-002-01	25-50mm/1-2"	10µm	81	25mm
338-003-01	50-75mm/2-3"	11µm	106	50mm
338-004-01	75-100mm/3-4"	11µm	131	75mm

Setting standards(included)



**SERIES 378**

CALIPER TYPE MICROMETER

- ◆ Graduation 0.01 mm
- ◆ Non-rotating spindle
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards
(except **378-001-01**)



378-001-01



Code	Range	Accuracy	L	Setting standards(included)
378-001-01	0-25mm	10μm	56	-
378-002-01	25-50mm	10μm	81	25mm
378-003-01	50-75mm	11μm	106	50mm
378-004-01	75-100mm	11μm	131	75mm

Setting standards(included)



SERIES 337



HUB MICROMETER

- ◆ Measure hub thickness and shoulder inside a bore
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards (except 337-001-01)



337-002-01

unit: mm



Code	Range	Accuracy	h1	h2	H	Setting standards(included)
337-001-01	0-25mm	4μm	6	9	18.7	-
337-002-01	25-50mm	4μm	6.5	11	21.2	25mm
337-003-01	50-75mm	5μm	6.5	11	21.2	50mm
337-004-01	75-100mm	5μm	6.5	11	21.2	75mm

Setting standards(included)





SERIES 308

LARGE ANVIL MICROMETER

- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except 0-25mm)




308-001-01



unit: mm

Application



Code	Range	Accuracy	a	h	L
308-001-01	0-25mm	4μm	50	26	42
308-002-01	25-50mm	4μm	60	38	67



SERIES 302

DIGITAL UNIVERSAL MICROMETER




- ◆ Resolution 0.001mm/0.00005"
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Supplied with 7 pairs of anvil/spindle tips
- ◆ Setting standards are included (except 0-25mm/0-1")
- ◆ Optional accessory: 55° anvil/spindle tip



302-001-01

Standard anvil/spindle tip

Flat		
Spherical		
Spline		
Disk		
Blade		
Knife-edge		
Point		



Optional 55° anvil/spindle tip

301-000-01 Knife-edge		
301-000-02 Point		

Code	Range	Accuracy	L	h	Setting standards(included)
302-001-01	0-25mm/0-1"	4μm	42	26	-
302-002-01	25-50mm/1-2"	4μm	67	38	25mm
302-003-01	50-75mm/2-3"	5μm	92	50	50mm
302-004-01	75-100mm/3-4"	5μm	118	62	75mm
302-005-01	100-125mm/4-5"	6μm	143	70	100mm
302-006-01	125-150mm/5-6"	6μm	168	82	125mm
302-007-01	150-175mm/6-7"	7μm	192	95	150mm
302-008-01	175-200mm/7-8"	7μm	217	107	175mm


Setting standards(included)



- ◆ Graduation 0.01mm
- ◆ Non-rotating spindle
- ◆ Ratchet stop
- ◆ Supplied with 7 pairs of anvil/spindle tips
- ◆ Setting standards are included (except 0-25mm)
- ◆ Optional accessory: 55° anvil/spindle tip


301-001-01
Standard anvil/spindle tip

Flat		
Spherical		
Spline		
Disk		
Blade		
Knife-edge		
Point		


Optional 55° anvil/spindle tip

301-000-01 Knife-edge		
301-000-02 Point		

Code	Range	Accuracy	L	h	Setting standards(included)
301-001-01	0-25mm	4μm	42	26	-
301-002-01	25-50mm	4μm	67	38	25mm
301-003-01	50-75mm	5μm	92	50	50mm
301-004-01	75-100mm	5μm	118	62	75mm
301-005-01	100-125mm	6μm	143	70	100mm
301-006-01	125-150mm	6μm	168	82	125mm
301-007-01	150-175mm	7μm	192	95	150mm
301-008-01	175-200mm	7μm	217	107	175mm

Setting standards(included)




SERIES 301


UNIVERSAL MICROMETER TIPS




301-000-11



301-000-12




301-000-13




unit: mm




301-000-14




301-000-15



301-000-16



301-000-17



Code	Name
301-000-11	Knife-edge
301-000-12	Point
301-000-13	Blade
301-000-14	Disk
301-000-15	Spline
301-000-16	Spherical
301-000-17	Flat
301-000-TS	7pairs/set, including all above tips

♦ For series 301 non rotating spindle universal micrometer and series 302 digital universal micrometer

SERIES 310

OUTSIDE MICROMETER FOR LEFT OR RIGHT HAND

- ♦ Graduation: 0.01mm
- ♦ Graduations on two sides
- ♦ Ratchet stop
- ♦ Carbide measuring faces
- ♦ Meet DIN863-1
- ♦ Supplied with setting standards (except 0-25mm)

Setting standards (included)




front side

310-001-01



reverse side

Code	Range	Accuracy	a	h	L	Setting standards (included)
310-001-01	0-25mm	4µm	6	24	32	-
310-002-01	25-50mm	4µm	8	32	57	25mm
310-003-01	50-75mm	5µm	8	45	82	50mm
310-004-01	75-100mm	5µm	8	57	107	75mm
310-005-01	100-125mm	6µm	8	70	133	100mm
310-006-01	125-150mm	6µm	8	82	158	125mm
310-007-01	150-175mm	7µm	8	95	183	150mm
310-008-01	175-200mm	7µm	8	107	209	175mm



unit: mm

SERIES 397

DIGITAL INTERCHANGEABLE ANVIL MICROMETER




ACCUD

- ◆ Measure tube thickness, shoulder edge distance, rivet head height, etc.
- ◆ Supplied with flat anvil and rod anvil
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 dust/waterproof
- ◆ Button function: on/off, set, mm/inch, data transmit
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Carbide spindle tip
- ◆ Setting standards are included (except 0-25mm/0-1")



397-001-01




Setting standards (included)



Code	Range	Accuracy	L	d
397-001-01	0-25mm/0-1"	±4μm	28.5	Ø3
397-002-01	25-50mm/1-2"	±4μm	53.5	Ø5

Application



SERIES 377

INTERCHANGEABLE ANVIL MICROMETER



- ◆ Measure tube thickness, shoulder edge distance, rivet head height, etc.
- ◆ Supplied with flat anvil and rod anvil
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide spindle tip
- ◆ Setting standards are included (except 0-25mm)




377-001-01

unit: mm

Setting standards (included)



Application



Code	Range	Accuracy	L	d
377-001-01	0-25mm	4μm	28.5	Ø3
377-002-01	25-50mm	4μm	53.5	Ø5

MICROMETER

SERIES 304


DIGITAL GEAR TOOTH MICROMETER




- ◆ Measure over-pin diameter of gears
- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 dust/waterproof
- ◆ Button function: on/off, set, mm/inch, ABS/INC
- ◆ Data output (cable code: 300-03 or 300-04)
- ◆ Automatic power off
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except **304-001-01**)
- ◆ Optional accessory: ball tips (code: series **345-000-XX**)



304-002-01



Application



Install points



Setting standards (included)




Code	Range	Accuracy	L	h	Setting standards (included)
304-001-01	0-25mm/0-1"	4μm	67	38	-
304-002-01	25-50mm/1-2"	4μm	92.4	50	25mm
304-003-01	50-75mm/2-3"	5μm	117.6	62	50mm
304-004-01	75-100mm/3-4"	5μm	143	70	75mm
304-005-01	100-125mm/4-5"	6μm	168.2	82	100mm
304-006-01	125-150mm/5-6"	6μm	192	94.5	125mm
304-007-01	150-175mm/6-7"	7μm	217	107	150mm


SERIES 345

GEAR TOOTH MICROMETER

- ◆ Measure over-pin diameter of gears
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except **345-001-01**)
- ◆ Optional accessory: ball tips



345-001-01




Setting standards (included)



Code	Range	Accuracy	L	h	Setting standards(included)
345-001-01	0-25mm	4μm	67	38	-
345-002-01	25-50mm	4μm	92.4	50	25mm
345-003-01	50-75mm	5μm	117.6	62	50mm
345-004-01	75-100mm	5μm	143	70	75mm
345-005-01	100-125mm	6μm	168.2	82	100mm
345-006-01	125-150mm	6μm	192	94.5	125mm
345-007-01	150-175mm	7μm	217	107	150mm

Application



SERIES 345

BALL TIPS FOR GEAR TOOTH MICROMETER

- ◆ Supplied in pair



345-000-01


unit: mm



Code	Ball dia.(D)
345-000-01	SØ1mm
345-000-02	SØ1.5mm
345-000-03	SØ2.0mm
345-000-04	SØ2.5mm
345-000-05	SØ3.0mm
345-000-06	SØ3.5mm

Code	Ball dia.(D)
345-000-07	SØ4.0mm
345-000-08	SØ4.5mm
345-000-09	SØ5.0mm
345-000-10	SØ6.0mm
345-000-TS	10 pairs/set, including all above tips

Install points



SERIES 344

GROOVE MICROMETER

- ◆ Graduation 0.01mm
- ◆ Measure width of grooves inside bores
- ◆ Non-rotating spindle
- ◆ Two graduations for inside and outside measurement



344-004-01



344-002-11

unit: mm


Two-directional ratchet stop

Code	Range (outside B)	Range (inside A)	Accuracy	Ød	Ød1	Ød2	L
344-001-11	0-25mm	1.6-26.5mm	10µm	13	6.5	10	120
344-002-11	25-50mm	26.5-51.5mm	10µm	13	6.5	10	120
344-003-11	50-75mm	51.5-76.5mm	10µm	13	6.5	10	120
344-004-11	75-100mm	76.5-101.5mm	10µm	13	6.5	10	120
344-001-12	0-25mm	1.6-26.5mm	10µm	6.5	3	5	90


No ratchet stop

Code	Range (outside B)	Range (inside A)	Accuracy	Ød	Ød1	Ød2	L
344-001-01	0-25mm	1.6-26.5mm	10µm	13	6.5	10	120
344-002-01	25-50mm	26.5-51.5mm	10µm	13	6.5	10	120
344-003-01	50-75mm	51.5-76.5mm	10µm	13	6.5	10	120
344-004-01	75-100mm	76.5-101.5mm	10µm	13	6.5	10	120
344-001-02	0-25mm	1.6-26.5mm	10µm	6.5	3	5	90

*344-001-02 and 344-001-12 do not have sleeve.



Application



MICROMETER



SERIES 348

CAN SEAM MICROMETER



- ◆ Measure the width, height and depth of can seams
- ◆ Graduation 0.01mm





348-001-01



348-001-02



348-001-03




Code	Range	Accuracy
348-001-01	0-13mm	4μm
348-001-02	0-13mm	4μm
348-001-03	0-13mm	4μm

SERIES 349

INDICATING MICROMETER



349-001-01



- ◆ Dial indicator: range 40μm, graduation 0.001mm, accuracy 0.001mm
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards (except 0-25mm)

Code	Micrometer head range	Micrometer head graduation	Micrometer head accuracy	L	h	Setting standards (included)	Support
349-001-01	0-25mm	0.002mm	3μm	28.5	19	-	with
349-002-01	25-50mm	0.002mm	3μm	53.5	30	25mm	with
349-003-01	50-75mm	0.002mm	5μm	78.5	45	50mm	without
349-004-01	75-100mm	0.002mm	5μm	103.5	57	75mm	without
349-005-01	100-125mm	0.002mm	5μm	128.5	69	100mm	without
349-006-01	125-150mm	0.002mm	5μm	153.5	82	125mm	without
349-007-01	150-175mm	0.002mm	5μm	178.5	94	150mm	without

Setting standards(included)



SERIES 349


DIAL SNAP GAUGE



- ◆ Quick measurement for mass production
- ◆ Dial indicator: range ± 0.04 mm, graduation 0.001mm, accuracy 0.001mm
- ◆ IP54 dust/waterproof
- ◆ Measuring force: 5-10N
- ◆ Carbide measuring faces



349-001-21



Code	Range	h	L
349-001-21	0-25mm	25	28.5
349-002-22	25-50mm	35	53.5
349-003-23	50-75mm	47.5	78.5
349-004-24	75-100mm	60	103.5





347

SHEET METAL MICROMETER

- ◆ Measure thickness of sheet metal, paper, plastic and rubber parts
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces

Application




unit: mm

Code	Range	Accuracy	a	h	L
347-015-01	0-15mm	4μm	8	50	22
347-001-01	0-25mm	4μm	8	50	32
347-002-01	0-50mm	5μm	12	100	57

370


WIRE MICROMETER

- ◆ Measure diameter of wires and small balls
- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces



unit: mm

Code	Range	Accuracy
370-010-01	0-10mm	4μm



SERIES 305

NON MAGNETIC MICROMETER




- ◆ Suitable for magnetic materials
- ◆ Graduation: 0.01 mm
- ◆ Non magnetic carbide measuring faces
- ◆ Ratchet stop
- ◆ Supplied with setting standards (except 0-25mm)



305-001-01

Setting standards(included)



Code	Range	Accuracy	L	h	Setting standards (included)
305-001-01	0-25mm	4μm	32	24	-
305-002-01	25-50mm	4μm	57	32	25
305-003-01	50-75mm	5μm	82	45	50
305-004-01	75-100mm	5μm	105	57	75

SERIES 307


DIGITAL DISK BRAKE MICROMETER



- ◆ Measure thickness of disk brakes
- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, mm/inch, set, zero
- ◆ Data output
- ◆ Automatic power off
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards



307-001-01



Setting standards (included)



Code	Range	Accuracy	L	Setting standards (included)
307-001-01	7.6-33mm	±5μm	64.5	25mm
307-002-01	25-50mm	±5μm	82	25mm



SERIES 306


DISK BRAKE MICROMETER

- ◆ Measure thickness of disk brakes
- ◆ Graduation: 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Supplied with setting standards



306-001-01

Setting standards (included)




Code	Range	Accuracy	L	Setting standards (included)
306-001-01	7.6-33mm	5µm	64.5	25mm
306-002-01	25-50mm	5µm	82	25mm

379

LONG SPINDLE OUTSIDE MICROMETER

- ◆ Graduation 0.01mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces



Code	Range	Accuracy	L	a	h
379-001-01	0-25mm	4µm	57	14	38

SERIES 376


DIGITAL MICROMETER HEAD




- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop




376-001-04




376-001-03



376-001-01




376-001-02



376-001-04

Rotating spindle

Code	Range	Accuracy	Stem	Spindle tip
376-001-01	0-25mm/0-1"	±2μm	with clamp nut	flat(carbide)
376-001-02	0-25mm/0-1"	±2μm	plain	flat(carbide)
376-001-03	0-25mm/0-1"	±2μm	with clamp nut	spherical(SR5)
376-001-04	0-25mm/0-1"	±2μm	plain	spherical(SR5)



376-001-05

Non-rotating spindle

Code	Range	Accuracy	Stem	Spindle tip
376-001-05	0-25mm/0-1"	±2μm	plain	flat(carbide)

SERIES 376


DIGITAL MICROMETER HEAD




- ◆ Resolution 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop



376-002-03



376-002-03



376-002-04

Code	Range	Accuracy	Stem	Spindle tip
376-002-03	0-50mm/0-2"	4μm	plain	flat(carbide)
376-002-04	0-50mm/0-2"	4μm	plain	spherical(SR5)


SERIES 371

MICROMETER HEAD


- ◆ Graduation: 0.01mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop




371-001-02




371-001-02




371-001-04




371-001-06



371-001-03



371-001-05




371-001-11


Code	Range	Accuracy	Stem	Spindle tip	Remark
371-001-02	0-25mm	3μm	with clamp nut	flat (carbide)	
371-001-03	0-25mm	3μm	with clamp nut	spherical (SR5)	
371-001-04	0-25mm	3μm	plain	spherical (SR5)	
371-001-05	0-25mm	3μm	with clamp nut	flat (carbide)	with spindle lock
371-001-06	0-25mm	3μm	plain	flat (carbide)	with spindle lock
371-001-11	0-25mm	3μm	plain	flat (carbide)	



371-002-11



371-002-02



371-002-11

Code	Range	Accuracy	Stem	Spindle tip
371-002-02	0-50mm	5μm	with clamp nut	flat (carbide)
371-002-11	0-50mm	5μm	plain	flat (carbide)

SERIES 373


MICROMETER HEAD

◆ Graduation 0.01mm




373-001-01

unit: mm



373-001-01



373-001-04

Code	Range	Accuracy	Stem	Spindle tip
373-001-01	0-15mm	3μm	with clamp nut	flat (carbide)
373-001-02	0-15mm	3μm	plain	flat (carbide)
373-001-03	0-15mm	3μm	with clamp nut	spherical (SR5)
373-001-04	0-15mm	3μm	plain	spherical (SR5)

SERIES 373

MICROMETER HEAD




373-013-02




373-013-05


unit: mm




373-013-01



373-013-04



373-013-05




373-013-06

Code	Range	Accuracy	Stem	Spindle tip	Remark
373-013-01	0-13mm	3μm	with clamp nut	flat (carbide)	
373-013-02	0-13mm	3μm	plain	flat (carbide)	
373-013-03	0-13mm	3μm	with clamp nut	spherical (SR5)	
373-013-04	0-13mm	3μm	plain	spherical (SR5)	
373-013-05	0-13mm	3μm	with clamp nut	flat (carbide)	with spindle lock
373-013-06	0-13mm	3μm	plain	flat (carbide)	with spindle lock

◆ Meet DIN863-2
◆ Graduation 0.01mm

◆ For standard value setting



321-004-ST


unit: mm



type A




321-015-ST



type B



321-042-ST



type C

Code	Length	Accuracy	D	Type
321-001-ST	25mm	±1.5μm	Ø7mm	A
321-002-ST	50mm	±2μm	Ø7mm	A
321-003-ST	75mm	±2.5μm	Ø7mm	A
321-004-ST	100mm	±3μm	Ø8mm	A
321-005-ST	125mm	±3.5μm	Ø8mm	A
321-006-ST	150mm	±4μm	Ø8mm	A
321-007-ST	175mm	±4.5μm	Ø8mm	A
321-008-ST	200mm	±5μm	Ø8mm	A
321-009-ST	225mm	±5.5μm	Ø8mm	A
321-010-ST	250mm	±6μm	Ø8mm	A
321-011-ST	275mm	±6.5μm	Ø8mm	A
321-012-ST	300mm	±7μm	Ø16mm	B
321-013-ST	325mm	±7.5μm	Ø16mm	B
321-014-ST	350mm	±8μm	Ø16mm	B
321-015-ST	375mm	±8.5μm	Ø16mm	B
321-016-ST	400mm	±9μm	Ø16mm	B
321-017-ST	425mm	±9.5μm	Ø16mm	B
321-018-ST	450mm	±10μm	Ø16mm	B
321-019-ST	475mm	±10.5μm	Ø16mm	B
321-020-ST	500mm	±11μm	Ø16mm	B
321-021-ST	525mm	±11.5μm	Ø16mm	B
321-022-ST	550mm	±12μm	Ø16mm	B
321-023-ST	575mm	±12.5μm	Ø16mm	B
321-024-ST	600mm	±13μm	Ø16mm	B
321-025-ST	625mm	±13.5μm	Ø16mm	B
321-026-ST	650mm	±14μm	Ø16mm	B
321-027-ST	675mm	±14.5μm	Ø16mm	B

Code	Length	Accuracy	D	Type
321-028-ST	700mm	±15μm	Ø16mm	B
321-029-ST	725mm	±15.5μm	Ø16mm	B
321-030-ST	750mm	±16μm	Ø16mm	B
321-031-ST	775mm	±16.5μm	Ø16mm	B
321-032-ST	800mm	±17μm	Ø16mm	B
321-033-ST	825mm	±17.5μm	Ø16mm	B
321-034-ST	850mm	±18μm	Ø16mm	B
321-035-ST	875mm	±18.5μm	Ø16mm	B
321-036-ST	900mm	±19μm	Ø16mm	B
321-037-ST	925mm	±19.5μm	Ø16mm	B
321-038-ST	950mm	±20μm	Ø16mm	B
321-039-ST	975mm	±20.5μm	Ø16mm	B
321-040-ST	1000mm	±21μm	Ø16mm	B
321-042-ST	1050mm	±22μm	Ø23mm	C
321-046-ST	1150mm	±24μm	Ø23mm	C
321-050-ST	1250mm	±26μm	Ø23mm	C
321-054-ST	1350mm	±28μm	Ø23mm	C
321-058-ST	1450mm	±30μm	Ø23mm	C
321-062-ST	1550mm	±32μm	Ø23mm	C
321-066-ST	1650mm	±34μm	Ø23mm	C
321-070-ST	1750mm	±36μm	Ø23mm	C
321-074-ST	1850mm	±38μm	Ø23mm	C
321-078-ST	1950mm	±40μm	Ø23mm	C



SERIES 324

INCH MICROMETER SETTING STANDARD

◆ For standard value setting




324-004-ST



324-012-ST



type A



type B


Code	Length	Accuracy	D	Type
324-001-ST	1"	±0.00006"	Ø0.276"	A
324-002-ST	2"	±0.00008"	Ø0.276"	A
324-003-ST	3"	±0.00010"	Ø0.276"	A
324-004-ST	4"	±0.00012"	Ø0.315"	A
324-005-ST	5"	±0.00014"	Ø0.315"	A
324-006-ST	6"	±0.00016"	Ø0.315"	A
324-007-ST	7"	±0.00018"	Ø0.315"	A
324-008-ST	8"	±0.00020"	Ø0.315"	A
324-009-ST	9"	±0.00022"	Ø0.315"	A
324-010-ST	10"	±0.00024"	Ø0.315"	A
324-011-ST	11"	±0.00026"	Ø0.315"	A
324-012-ST	12"	±0.00028"	Ø0.630"	B
324-013-ST	13"	±0.00030"	Ø0.630"	B
324-014-ST	14"	±0.00032"	Ø0.630"	B
324-015-ST	15"	±0.00034"	Ø0.630"	B
324-016-ST	16"	±0.00036"	Ø0.630"	B
324-017-ST	17"	±0.00038"	Ø0.630"	B
324-018-ST	18"	±0.00040"	Ø0.630"	B
324-019-ST	19"	±0.00042"	Ø0.630"	B
324-020-ST	20"	±0.00044"	Ø0.630"	B

Code	Length	Accuracy	D	Type
324-021-ST	21"	±0.00046"	Ø0.630"	B
324-022-ST	22"	±0.00048"	Ø0.630"	B
324-023-ST	23"	±0.00050"	Ø0.630"	B
324-024-ST	24"	±0.00052"	Ø0.630"	B
324-025-ST	25"	±0.00054"	Ø0.630"	B
324-026-ST	26"	±0.00056"	Ø0.630"	B
324-027-ST	27"	±0.00058"	Ø0.630"	B
324-028-ST	28"	±0.00060"	Ø0.630"	B
324-029-ST	29"	±0.00062"	Ø0.630"	B
324-030-ST	30"	±0.00064"	Ø0.630"	B
324-031-ST	31"	±0.00066"	Ø0.630"	B
324-032-ST	32"	±0.00068"	Ø0.630"	B
324-033-ST	33"	±0.00070"	Ø0.630"	B
324-034-ST	34"	±0.00072"	Ø0.630"	B
324-035-ST	35"	±0.00074"	Ø0.630"	B
324-036-ST	36"	±0.00076"	Ø0.630"	B
324-037-ST	37"	±0.00078"	Ø0.630"	B
324-038-ST	38"	±0.00080"	Ø0.630"	B
324-039-ST	39"	±0.00082"	Ø0.630"	B
324-040-ST	40"	±0.00084"	Ø0.630"	B


SERIES 343

SCREW THREAD MICROMETER SETTING STANDARD

◆ For screw thread micrometer (series 333 or 343)



343-001-ST



343-001-ST1

unit: mm



55° thread angle



60° thread angle

Code	Length	Accuracy
343-001-ST	25mm	±3μm
343-002-ST	50mm	±3.5μm
343-003-ST	75mm	±4μm
343-004-ST	100mm	±4.5μm
343-005-ST	125mm	±5μm
343-006-ST	150mm	±5.5μm
343-007-ST	175mm	±6μm
343-008-ST	200mm	±6μm


Code	Length	Accuracy
343-001-ST1	25mm	±3μm
343-002-ST1	50mm	±3.5μm
343-003-ST1	75mm	±4μm
343-004-ST1	100mm	±4.5μm
343-005-ST1	125mm	±5μm
343-006-ST1	150mm	±5.5μm
343-007-ST1	175mm	±6μm
343-008-ST1	200mm	±6μm



387

MICROMETER MEASURING FORCE DETECTOR

- ◆ For outside micrometers
0-25mm, 25-50mm, 50-75mm
and 75-100mm



Code	Measuring force
387-000-00	5-12N


SERIES 551

OPTICAL PARALLEL

- ◆ Check the flatness and parallelism of measuring faces of micrometer
- ◆ Flatness of A and B $\leq 0.1\mu\text{m}$
- ◆ Parallelism between A and B $\leq 0.6\mu\text{m}$



551-001-02



Application



Code	Parallels included
551-001-02	12, 12.12, 12.25, 12.37mm
551-002-02	25, 25.12, 25.25, 25.37mm




SERIES 551

OPTICAL PARALLELS



551-001-01

unit: mm



- ◆ Check the flatness and parallelism of measuring faces of micrometer
- ◆ Flatness of A and B: $0.03\mu\text{m}$
- ◆ Parallelism between A and B: $0.6\mu\text{m}$

Application



Code	Parallels included (b)	ØD	Applicable micrometer
551-001-01	15.62mm, 15.75mm, 15.87mm, 16.00mm	30	0-25mm
551-002-01	40.62mm, 40.75mm, 40.87mm, 41.00mm	30	25-50mm
551-003-01	65.62mm, 65.75mm, 65.87mm, 66.00mm	40	50-75mm
551-004-01	90.62mm, 90.75mm, 90.87mm, 91.00mm	50	75-100mm

SERIES 553

OPTICAL FLAT

- ◆ Check the flatness of measuring faces



553-045-01

unit: mm



Code	Flatness	Parallels included(h)	ØD
553-045-01	$0.1\mu\text{m}$	15mm	45
553-060-01	$0.1\mu\text{m}$	20mm	60



381

MICROMETER STAND

- ◆ For micrometers which measuring range is less than 100mm


Application



micrometer is optional

Code

381-000-00



383

MICROMETER STAND

- ◆ For micrometers which measuring range is less than 100mm


Application



micrometer is optional

Code

383-000-00



SERIES 361

DIGITAL THREE POINTS INSIDE MICROMETER



- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Carbide measuring faces (over 12mm series)
- ◆ Extension rod are included
- ◆ Setting rings are included (Range<100mm)




VIDEO




361-002-01




361-007-01



Range 6-20mm



Range 20-50mm




Range 50-300mm

unit: mm

Code	Range	Accuracy	Setting ring	Extension rod	a	b	c	L
361-001-01*	6-8mm/0.24-0.31"	4μm	Ø6mm(included)	100mm	1.5	2.5	/	57
361-002-01*	8-10mm/0.31-0.39"	4μm	Ø8mm(included)	100mm	1.5	2.5	/	57
361-003-01*	10-12mm/0.39-0.47"	4μm	Ø10mm(included)	100mm	1.5	2.5	/	57
361-004-01*	12-16mm/0.47-0.63"	4μm	Ø16mm(included)	150mm	0.5	6	4.5	72
361-005-01*	16-20mm/0.63-0.79"	4μm	Ø16mm(included)	150mm	0.5	6	4.5	72
361-006-01*	20-25mm/0.79-0.98"	4μm	Ø25mm(included)	150mm	0.5	8	6	105
361-007-01*	25-30mm/0.98-1.18"	4μm	Ø25mm(included)	150mm	0.5	8	6	105
361-008-01*	30-40mm/1.18-1.57"	4μm	Ø40mm(included)	150mm	0.5	14	12	110
361-009-01*	40-50mm/1.57-1.97"	5μm	Ø40mm(included)	150mm	0.5	14	12	110
361-010-01*	50-63mm/1.97-2.48"	5μm	Ø62mm(included)	150mm	0.5	17.5	14.5	127
361-011-01*	62-75mm/2.44-2.95"	5μm	Ø62mm(included)	150mm	0.5	17.5	14.5	127
361-012-01*	75-88mm/2.95-3.46"	5μm	Ø87mm(included)	150mm	0.5	17.5	14.5	127
361-013-01*	87-100mm/3.43-3.94"	5μm	Ø87mm(included)	150mm	0.5	17.5	14.5	127
361-014-01	100-125mm/3.94-4.92"	6μm	optional	150mm	0.9	29	25	175
361-015-01	125-150mm/4.92-5.91"	6μm	optional	150mm	0.9	29	25	175
361-016-01	150-175mm/5.91-6.89"	7μm	optional	150mm	0.9	29	25	175
361-017-01	175-200mm/6.89-7.87"	7μm	optional	150mm	0.9	29	25	175
361-018-01	200-225mm/7.87-8.86"	8μm	optional	150mm	0.9	29	25	175
361-019-01	225-250mm/8.86-9.84"	8μm	optional	150mm	0.9	29	25	175
361-020-01	250-275mm/9.84-10.83"	9μm	optional	150mm	0.9	29	25	175
361-024-01	275-300mm/10.83-11.81"	9μm	optional	150mm	0.9	29	25	175

Setting ring



Range<100mm (included)
Range>100mm (optional)

Extension rod(included)



* With manufacturer inspection certificate

SERIES 361

DIGITAL TWO POINTS INSIDE MICROMETER




- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP65 protection level
- ◆ Button: on/off, set, mm/inch, ABS/INC, data output
- ◆ Automatic power off
- ◆ Data output
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Setting rings are included



361-000-50

unit: mm



Code	Range	Accuracy	Setting ring	L
361-000-25	2-2.5mm/0.08-0.10"	6μm	Ø2.5mm	12
361-000-30	2.5-3mm/0.10-0.12"	6μm	Ø2.5mm	12
361-000-40	3-4mm/0.12-0.16"	6μm	Ø4mm	22
361-000-50	4-5mm/0.16-0.20"	6μm	Ø5mm	22
361-000-60	5-6mm/0.20-0.24"	6μm	Ø6mm	22

Setting ring(included)



SERIES 361

DIGITAL TWO/THREE POINTS INSIDE MICROMETER SET



Extension rod(included) Setting ring(included)



Digital two points inside micrometer set

Code	Range	Micrometers included	Setting ring
361-000-02	2-3mm/0.08-0.12"	2-2.5mm, 2.5-3mm	Ø2.5mm
361-000-03	3-6mm/0.12-0.24"	3-4mm, 4-5mm, 5-6mm	Ø4mm, Ø5mm, Ø6mm

Digital three points inside micrometer set

Code	Range	Micrometers included	Setting ring	Extension rod
361-103-03	6-12mm	6-8, 8-10, 10-12mm	Ø6, Ø8, Ø10mm	100mm
361-305-03	12-20mm	12-16, 16-20mm	Ø16mm	150mm
361-509-05	20-50mm	20-25, 25-30, 30-40, 40-50mm	Ø25mm, Ø40mm	150mm
361-913-05	50-100mm	50-63, 62-75, 75-88, 87-100mm	Ø62mm, Ø87mm	150mm



361-103-03


INSIDE/OUTSIDE
MEASUREMENT

SERIES 362

THREE POINTS INSIDE MICROMETER




- ◆ 6-12mm graduation: 0.001mm
Steel measuring faces
- ◆ 12-300mm graduation: 0.005mm
Carbide measuring faces
- ◆ Ratchet stop
- ◆ Extension rod are included
- ◆ Setting rings are included (Range<100mm)



Range 6-12mm

362-003-01




Range 12-50mm



362-008-01



362-014-01




Range 50-300mm

unit: mm

Code	Range	Accuracy	Setting ring	Extension rod	a	b	c	L
362-001-01 *	6-8mm	4μm	Ø6mm(included)	100mm	1.5	2.5	/	54.5
362-002-01 *	8-10mm	4μm	Ø8mm(included)	100mm	1.5	2.5	/	54.5
362-003-01 *	10-12mm	4μm	Ø10mm(included)	100mm	1.5	2.5	/	54.5
362-004-01 *	12-16mm	4μm	Ø16mm(included)	150mm	0.5	6	4.5	80
362-005-01 *	16-20mm	4μm	Ø16mm(included)	150mm	0.5	6	4.5	80
362-006-01 *	20-25mm	4μm	Ø25mm(included)	150mm	0.5	8	6	90
362-007-01 *	25-30mm	4μm	Ø25mm(included)	150mm	0.5	8	6	90
362-008-01 *	30-40mm	4μm	Ø40mm(included)	150mm	0.5	14	12	97
362-009-01 *	40-50mm	5μm	Ø40mm(included)	150mm	0.5	14	12	97
362-010-01 *	50-63mm	5μm	Ø62mm(included)	150mm	0.5	17.5	14.5	114
362-011-01 *	62-75mm	5μm	Ø62mm(included)	150mm	0.5	17.5	14.5	114
362-012-01 *	75-88mm	5μm	Ø87mm(included)	150mm	0.5	17.5	14.5	114
362-013-01 *	87-100mm	5μm	Ø87mm(included)	150mm	0.5	17.5	14.5	114
362-014-01	100-125mm	6μm	optional	150mm	0.9	29	25	140
362-015-01	125-150mm	6μm	optional	150mm	0.9	29	25	140
362-016-01	150-175mm	7μm	optional	150mm	0.9	29	25	140
362-017-01	175-200mm	7μm	optional	150mm	0.9	29	25	140
362-018-01	200-225mm	8μm	optional	150mm	0.9	29	25	140
362-019-01	225-250mm	8μm	optional	150mm	0.9	29	25	140
362-020-01	250-275mm	9μm	optional	150mm	0.9	29	25	140
362-024-01	275-300mm	9μm	optional	150mm	0.9	29	25	140

Setting ring



Extension rod(included)



* With manufacturer inspection certificate


SERIES 362

TWO POINTS INSIDE MICROMETER

- ◆ Graduation: 0.001mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Setting rings are included



362-000-25



Code	Range	Accuracy	Setting ring	L
362-000-25	2-2.5mm	6μm	Ø2.5mm	12
362-000-30	2.5-3mm	6μm	Ø2.5mm	12
362-000-40	3-4mm	6μm	Ø4mm	22
362-000-50	4-5mm	6μm	Ø5mm	22
362-000-60	5-6mm	6μm	Ø6mm	22

Setting ring(included)



SERIES 362

TWO/THREE POINTS INSIDE MICROMETER SET



362-913-05

Two points inside micrometer set

Code	Range	Micrometers included	Setting ring
362-000-02	2-3mm	2-2.5mm, 2.5-3mm	Ø2.5mm
362-000-03	3-6mm	3-4mm, 4-5mm, 5-6mm	Ø4mm, Ø5mm, Ø6mm

Three points inside micrometer set

Code	Range	Micrometers included	Setting ring	Extension rod
362-103-03	6-12mm	6-8, 8-10, 10-12mm	Ø6, Ø8, Ø10mm	100mm
362-305-03	12-20mm	12-16, 16-20mm	Ø16mm	150mm
362-509-05	20-50mm	20-25, 25-30, 30-40, 40-50mm	Ø25mm, Ø40mm	150mm
362-913-05	50-100mm	50-63, 62-75, 75-88, 87-100mm	Ø62mm, Ø87mm	150mm

Extension rod(included)



Setting ring(included)



SERIES 363

WIDE RANGE THREE POINTS INTERNAL MICROMETER

- ◆ Graduation 0.001mm
- ◆ Ratchet stop
- ◆ Carbide measuring faces
- ◆ Setting rings are included(except 200-300mm)


Setting ring



Code	Range	Accuracy	Setting ring
363-003-01	50-70mm	5μm	Ø50mm(included)
363-004-01	70-100mm	5μm	Ø70mm(included)
363-006-01	100-150mm	6μm	Ø100mm(included)
363-010-01	150-250mm	8μm	Ø150mm(included)
363-012-01	200-300mm	9μm	Ø200mm(optional)



363-003-01



SERIES 364

DIGITAL WIDE RANGE THREE POINTS INTERNAL MICROMETER


- ◆ Resolution: 0.001mm/0.00005"
- ◆ IP54 protection level
- ◆ Buttons: on/off, set, mm/inch, ABS/INC
- ◆ Data output
- ◆ Automatic power off
- ◆ Carbide measuring faces
- ◆ Ratchet stop
- ◆ Supplied with extension rods
- ◆ Setting rings are included(except 200-300mm)



unit: mm




364-003-01



Code	Range	Accuracy	Setting ring	Extension rod
364-003-01	50-70mm/1.97-2.76"	5μm	Ø50mm(included)	150mm
364-004-01	70-100mm/2.76-3.94"	5μm	Ø70mm(included)	150mm
364-006-01	100-150mm/3.94-5.91"	6μm	Ø100mm(included)	150mm
364-010-01	150-250mm/5.91-9.84"	8μm	Ø150mm(included)	150mm
364-012-01	200-300mm/7.87-11.81"	9μm	Ø200mm(optional)	150mm

Extension rod(included)

Setting ring



SERIES 365

PISTOL GRIP THREE POINTS BORE GAUGE




Accud

- Optional accessory:
digital indicator (code: series 211 or 216)
setting ring (code: series 531)






216-010-01
digital indicator
is optional

365-007-01



Extension rod (included)



INDIVIDUAL

Code	Range	Accuracy	Setting ring	Extension rod	a	b	c	L
365-001-01	6-8mm/0.275-0.35"	4µm	Ø6mm (included)	100mm	1.5	2.5	/	50
365-002-01	8-10mm/0.35-0.425"	4µm	Ø8mm (included)	100mm	1.5	2.5	/	50
365-003-01	10-12mm/0.425-0.5"	4µm	Ø10mm (included)	100mm	1.5	2.5	/	50
365-004-01	12-16mm/0.5-0.65"	4µm	Ø16mm (included)	150mm	0.5	6	4.5	65
365-005-01	16-20mm/0.65-0.8"	4µm	Ø16mm (included)	150mm	0.5	6	4.5	65
365-006-01	20-25mm/0.8-1"	4µm	Ø25mm (included)	150mm	0.5	8	6	91
365-007-01	25-30mm/1-1.2"	4µm	Ø25mm (included)	150mm	0.5	8	6	91
365-008-01	30-40mm/1.2-1.6"	4µm	Ø40mm (included)	150mm	0.5	14	12	97
365-009-01	40-50mm/1.6-2"	5µm	Ø40mm (included)	150mm	0.5	14	12	97
365-010-01	50-63mm/2-2.5"	5µm	Ø62mm (included)	150mm	0.5	17.5	14.5	112
365-011-01	62-75mm/2.5-3"	5µm	Ø62mm (included)	150mm	0.5	17.5	14.5	112
365-012-01	75-88mm/3-3.5"	5µm	Ø87mm (included)	150mm	0.5	17.5	14.5	112
365-013-01	87-100mm/3.5-4"	5µm	Ø87mm (included)	150mm	0.5	17.5	14.5	112
365-014-01	100-125mm/4-5"	6µm	optional	150mm	0.9	29	25	140
365-015-01	125-150mm/5-6"	6µm	optional	150mm	0.9	29	25	140
365-016-01	150-175mm/6-7"	7µm	optional	150mm	0.9	29	25	140
365-017-01	175-200mm/7-8"	7µm	optional	150mm	0.9	29	25	140
365-018-01	200-225mm/8-9"	8µm	optional	150mm	0.9	29	25	140
365-019-01	225-250mm/9-10"	8µm	optional	150mm	0.9	29	25	140
365-020-01	250-275mm/10-11"	9µm	optional	150mm	0.9	29	25	140
365-024-01	275-300mm/11-12"	9µm	optional	150mm	0.9	29	25	140

Setting ring



Indicators (optional)



SET

Code	Range	Micrometers included	Setting ring (included)	Extension rod (included)
365-103-03	6-12mm	6-8, 8-10, 10-12mm	Ø6, Ø8, Ø10mm	100mm
365-305-03	12-20mm	12-16, 16-20mm	Ø16mm	150mm
365-509-05	20-50mm	20-25, 25-30, 30-40, 40-50mm	Ø25mm, Ø40mm	150mm
365-913-05	50-100mm	50-63, 62-75, 75-88, 87-100mm	Ø62mm, Ø87mm	150mm

INSIDE/OUTSIDE
MEASUREMENT


SERIES 351

INSIDE MICROMETER


- ◆ Graduation: 0.01mm
- ◆ Carbide measuring faces
- ◆ Ratchet stop




351-001-01



351-002-01



351-003-01



Code	Range	Accuracy	Type	Setting ring
351-001-01	5-30mm	5μm	A	5mm
351-002-01	25-50mm	6μm	B	25mm
351-003-01	50-75mm	7μm	C	optional
351-004-01	75-100mm	8μm	C	optional
351-005-01	100-125mm	9μm	C	optional
351-006-01	125-150mm	9μm	C	optional
351-007-01	150-175mm	10μm	C	optional
351-008-01	175-200mm	10μm	C	optional
351-009-01	200-225mm	11μm	C	optional
351-010-01	225-250mm	11μm	C	optional
351-011-01	250-275mm	12μm	C	optional
351-012-01	275-300mm	14μm	C	optional

Setting ring



SERIES 356

DIGITAL INSIDE MICROMETER





ATTENTION: LOW PARALLELISM
OF TWO MEASURING FACES



- ◆ Resolution 0.001mm/0.00005"
- ◆ Button function: on/off, set, mm/inch, ABS/INC, data output
- ◆ Data output
- ◆ Automatic power off
- ◆ Ratchet stop
- ◆ Carbide measuring faces



356-003-01



Code	Range	Accuracy	Type	Setting ring
356-001-01	5-30mm/0.2-1.2"	±5μm	A	5mm
356-002-01	25-50mm/1-2"	±6μm	B	25mm
356-003-01	50-75mm/2-3"	±7μm	C	optional
356-004-01	75-100mm/3-4"	±8μm	C	optional
356-005-01	100-125mm/4-5"	±9μm	C	optional
356-006-01	125-150mm/5-6"	±9μm	C	optional
356-007-01	150-175mm/6-7"	±10μm	C	optional
356-008-01	175-200mm/7-8"	±10μm	C	optional


SERIES 352

TUBULAR INSIDE MICROMETER

- ◆ Graduation: 0.01mm
- ◆ Travel of micrometer head: 13mm
- ◆ Accuracy: $(3+n+L/50)\mu\text{m}$, n is number of rods, L is max. measuring length in mm
- ◆ Supplied with setting standards
- ◆ Carbide measuring faces



352-006-01



Set zero



Code	Range	Extension rods (mm)
352-002-01	50-63mm	—
352-006-01	50-150mm	13, 25, 50
352-012-01	50-300mm	13, 25, 50(2pcs), 100
352-020-01	50-500mm	13, 25, 50(2pcs), 100, 200
352-024-01	50-600mm	13, 25, 50, 100, 150, 200
352-040-01	50-1000mm	13, 25, 50(2pcs), 100, 200(2pcs), 300
352-060-01	50-1500mm	13, 25, 50(2pcs), 100, 200(3pcs), 300(2pcs)

INSIDE/OUTSIDE
MEASUREMENT



SERIES 352


TUBULAR INSIDE MICROMETER

- ◆ Graduation: .001"
- ◆ Accuracy: $[\pm 0.0005(3+n+L/2)]$ ", n = number of rods, L = maximum measuring length (inch)
- ◆ Supplied with setting standards
- ◆ Carbide measuring faces




352-024-E01

Code	Range	Travel of micrometer head	Extension rods
352-002-E01	2-2.5"	.5"	-
352-006-E01	2-6"	.5"	.5", 1", 2"
352-012-E01	2-12"	.5"	.5", 1", 2"(2pcs), 4"
352-020-E01	2-20"	.5"	.5", 1", 2"(2pcs), 4", 8"
352-024-E01	2-24"	.5"	.5", 1", 2", 4", 6", 8"
352-040-E01	2-40"	.5"	.5", 1", 2"(2pcs), 4", 8"(2pcs), 12"
352-060-E01	2-60"	.5"	.5", 1", 2"(2pcs), 4", 8"(3pcs), 12"(2pcs)



Set zero



SERIES 359


DIGITAL TUBULAR INSIDE MICROMETER



- ◆ Micrometer head: 150-175mm
- ◆ Graduation: 0.001mm/0.00005"
- ◆ Accuracy: $(3+n+L/50)\mu\text{m}$
n = number of rods
L = maximum measuring length (mm)
- ◆ Carbide measuring faces
- ◆ The diameter of extension rods is 22mm
- ◆ IP65 dust/waterproof
- ◆ Button function: on/off, set, mm/inch, ABS/INC
- ◆ Data output
- ◆ Automatic power off
- ◆ Supplied with setting standards



359-007-01



Set zero



Code	Range	Travel of micrometer head	Extension rods
359-007-01	150-175mm	25mm	-
359-040-01	150-1000mm	25mm	25, 50(2pcs), 100, 200, 400
359-060-01	150-1500mm	25mm	25, 50(2pcs), 100(2pcs), 200, 400(2pcs)
359-080-01	150-2000mm	25mm	25, 50(2pcs), 100, 200(2pcs), 400(3pcs)

SERIES 353

TUBULAR INSIDE MICROMETER


- ◆ Graduation 0.01mm
- ◆ Accuracy: $(3+n+L/50)\mu\text{m}$
n is number of rods, L is maximum measuring length in mm
- ◆ Travel of micrometer head: 25mm
- ◆ Supplied with setting standards
- ◆ Carbide measuring faces

Set zero



353-020-01

Code	Range	Extension rods (mm)
353-005-01	100-125mm	—
353-020-01	100-500mm	25, 50, 100, 200
353-036-01	100-900mm	25, 50, 100, 200, 400
353-052-01	100-1300mm	25, 50, 100, 200, 400(2pcs)
353-068-01	100-1700mm	25, 50, 100, 200, 400(3pcs)
353-084-01	100-2100mm	25, 50, 100, 200, 400(4pcs)




SERIES 354

TUBULAR INSIDE MICROMETER



354-005-01



- ◆ Graduation 0.01mm
- ◆ Carbide measuring faces

Code	Range	Type	Accuracy
354-003-01	50-75mm	A	5μm
354-004-01	75-100mm	B	5μm
354-005-01	100-125mm	C	6μm
354-006-01	125-150mm	C	6μm
354-007-01	150-175mm	C	7μm
354-008-01	175-200mm	C	7μm
354-009-01	200-225mm	C	8μm
354-010-01	225-250mm	C	8μm
354-011-01	250-275mm	C	9μm

Code	Range	Type	Accuracy
354-012-01	275-300mm	C	9μm
354-013-01	300-325mm	C	9μm
354-014-01	325-350mm	C	9μm
354-015-01	350-375mm	C	10μm
354-016-01	375-400mm	C	10μm
354-017-01	400-425mm	C	10μm
354-018-01	425-450mm	C	10μm
354-019-01	450-475mm	C	11μm
354-020-01	475-500mm	C	11μm

INSIDE/OUTSIDE
MEASUREMENT

SERIES 355

TUBULAR INSIDE MICROMETER


- ◆ Graduation 0.01mm
- ◆ Accuracy: $(6+L/50)\mu\text{m}$
L=maximum measuring length(mm)
- ◆ Optional accessory: setting ring (code 531)

Setting ring (optional)



355-008-01

Code	Range	Extension rods	Travel of micrometer head
355-001-01	25-32mm	—	7mm
355-002-01	25-50mm	2pcs	7mm
355-003-01	50-63mm	—	13mm
355-008-01	50-200mm	6pcs	13mm
355-009-01	200-225mm	—	25mm
355-012-01	50-300mm	10pcs	13mm
355-020-01	200-500mm	3pcs	25mm
355-040-01	200-1000mm	8pcs	25mm



unit: mm


SERIES 357

TUBULAR INSIDE MICROMETER

- ◆ Graduation 0.01mm
- ◆ Accuracy: $(7+n+L/50)\mu\text{m}$
n=number of rods
L=maximum measuring length(mm)
- ◆ Carbide measuring faces



357-080-01




unit: mm

Code	Range	Travel of micrometer head	Extension rods
357-080-01	1000-2000mm	50mm	50mm, 100mm(2pcs), 200mm, 500mm
357-120-01	1000-3000mm	50mm	50mm, 100mm(2pcs), 200mm, 500mm, 1000mm
357-160-01	1000-4000mm	50mm	50mm, 100mm(2pcs), 200mm, 500mm, 1000mm(2pcs)
357-200-01	1000-5000mm	50mm	50mm, 100mm(2pcs), 200mm, 500mm, 1000mm(3pcs)

SERIES 358

INTERNAL SCREW THREAD MICROMETER

◆ Graduation: 0.01mm



Measuring tips for internal screw thread micrometer (optional)



Code	Range
358-004-01	75-100mm
358-005-01	100-125mm
358-006-01	125-150mm

Code	Range
358-007-01	150-175mm
358-008-01	175-200mm
358-009-01	200-225mm

Code	Range
358-010-01	225-250mm
358-011-01	250-275mm
358-012-01	275-300mm


SERIES 358

MEASURING TIPS FOR INTERNAL SCREW THREAD MICROMETER


- ◆ Supplied in pair
- ◆ For 358 series micrometers



358-000-19



60° thread angle



55° thread angle

unit: mm

Metric and unified thread (60° thread angle)

Code	Pitch
358-000-01	0.4-0.5mm/ 64-48TPI
358-000-02	0.6-0.9mm/ 44-28TPI
358-000-03	1-1.75mm/ 24-14TPI
358-000-04	2-3mm/ 13-9TPI
358-000-05	3.5-5mm/ 8-5TPI
358-000-06	5.5-7mm/ 4.5-3.5TPI
358-000-TS	6 pairs/set, including all above tips

Whitworth thread (55° thread angle)

Code	Pitch
358-000-11	60-48TPI
358-000-12	48-40TPI
358-000-13	40-32TPI
358-000-14	32-24TPI
358-000-15	24-18TPI
358-000-16	18-14TPI
358-000-17	14-10TPI

Code	Pitch
358-000-18	10-7TPI
358-000-19	7-4.5TPI
358-000-20	4.5-3.5TPI
358-000-2TS	10 pairs/set, including all above tips



SERIES 251

DIAL BORE GAUGE SET

◆ Optional accessory: series 531 setting rings



Bore gauge setter for setting zero(**optional**)

Setting ring(**optional**)



Measuring tips(**included**)

Gasket(**included**)



Series 215(**optional**)



251-046-11



251-346-13

Code	Range	indicator	Accuracy	Repeatability	Bore gages included
251-046-11	35-160mm	range 10mm graduation 0.01mm	35-50mm $\pm 0.018\text{mm}$ 50-160mm $\pm 0.018\text{mm}$	0.003mm	35-50mm anvil (dial indicator and handle are not included) 50-160mm bore gage
251-346-13	18-160mm	range 10mm graduation 0.01mm	18-35mm $\pm 0.015\text{mm}$ 35-60mm $\pm 0.018\text{mm}$ 50-160mm $\pm 0.018\text{mm}$	0.003mm	18-35mm bore gage 35-60mm (dial indicator is not included) 50-160mm (dial indicator is not included)

SERIES 251

DIAL BORE GAUGE

◆ Optional accessory: series 531 setting rings





Bore gauge setter for setting zero(optional)

Setting ring(optional)



251-160-11



Measuring tips(included)


Gasket(included)



Series 215(optional)



Install tips



Code	Range	Dial indicator	Tips	Gasket	Accuracy	Repeatability	a	b	c	Ød	ØD	e	L
251-010-11	6-10mm	Range: 3mm graduation: 0.01mm	9pcs	2pcs	±0.012mm	3µm	3.6	5.7	/	/	4.5	SR1	48
251-018-11	10-18mm		9pcs	2pcs	±0.012mm	3µm	5.6	7.8	/	/	6	SR1	105
251-035-11	18-35mm		9pcs	2pcs	±0.015mm	3µm	12.2	6.4	/	12.7	9	SR1	141
251-060-11	35-60mm		6pcs	4pcs	±0.018mm	3µm	26	9	27	13	12.8	SR2	141
251-100-11	50-100mm		11pcs	4pcs	±0.018mm	3µm	26	9	35	13	12.8	SR2	141
251-160-11	50-160mm		12pcs	4pcs	±0.018mm	3µm	26	9	35	13	12.8	SR2	141
251-160-12	100-160mm		12pcs	4pcs	±0.018mm	3µm	26	9	35	13	12.8	SR2	141
251-250-11	160-250mm		5pcs	5pcs	±0.018mm	3µm	56.5	13	74.5	15	14.5	SR3.5	400
251-450-11	250-450mm		5pcs	5pcs	±0.018mm	3µm	86.5	15	101.5	15	14.5	SR3.5	400

INSIDE/OUTSIDE MEASUREMENT

SERIES 251

PRECISION DIAL BORE GAUGE

- Optional accessory: series 531 setting rings and long handle series 250.





Bore gauge setter for setting zero (optional)

Setting ring (optional)



251-160-01



Measuring tips (included)


Gasket (included)



Series 215 (optional)



Install tips



Code	Range	Dial indicator	Tips	Gasket	Accuracy	Repeatability	a	b	c	Ød	ØD	e	L
251-010-01	6-10mm	Range: 1mm graduation: 0.001mm	9pcs	2pcs	±0.005mm	2µm	3.6	5.7	/	/	4.5	SR1	48
251-018-01	10-18mm		9pcs	2pcs	±0.005mm	2µm	5.6	7.8	/	/	6	SR1	105
251-035-01	18-35mm		9pcs	2pcs	±0.006mm	2µm	12.2	6.4	/	12.7	9	SR1	141
251-060-01	35-60mm		6pcs	4pcs	±0.007mm	2µm	26	9	27	13	12.8	SR2	141
251-100-01	50-100mm		11pcs	4pcs	±0.007mm	2µm	26	9	35	13	12.8	SR2	141
251-160-01	50-160mm		12pcs	4pcs	±0.007mm	2µm	26	9	35	13	12.8	SR2	141
251-160-02	100-160mm		12pcs	4pcs	±0.007mm	2µm	26	9	35	13	12.8	SR2	141
251-250-01	160-250mm		5pcs	5pcs	±0.007mm	2µm	56.5	13	74.5	15	14.5	SR3.5	400
251-450-01	250-450mm		5pcs	5pcs	±0.007mm	2µm	86.5	15	101.5	15	14.5	SR3.5	400


SERIES 241

DIGITAL PRECISION BORE GAUGE



ACCUD

- ◆ With min. value tracking function, get the diameter automatically
- ◆ Optional accessory: series 531 setting rings



Bore gauge setter for setting zero(optional)

Setting ring(optional)




Measuring tips(included)

Gasket(included)




241-035-01



Range: 6-10mm


Range: 10-18mm



Range: 18-35mm

Range: 35-450mm

Install tips



Code	Range	Digital indicator	Tips	Gasket	Accuracy	Repeatability	a	b	c	Ød	ØD	e	L
241-010-01	6-10mm	Range: 12.7mm resolution: 0.001mm	9pcs	2pcs	±0.005mm	2µm	3.6	5.7	/	/	4.5	SR1	48
241-018-01	10-18mm		9pcs	2pcs	±0.005mm	2µm	5.6	7.8	/	/	6	SR1	105
241-035-01	18-35mm		9pcs	2pcs	±0.006mm	2µm	12.2	6.4	/	12.7	9	SR1	141
241-060-01	35-60mm		6pcs	4pcs	±0.007mm	2µm	26	9	27	13	12.8	SR2	141
241-100-01	50-100mm		11pcs	4pcs	±0.007mm	2µm	26	9	35	13	12.8	SR2	141
241-160-01	50-160mm		12pcs	4pcs	±0.007mm	2µm	26	9	35	13	12.8	SR2	141
241-160-02	100-160mm		12pcs	4pcs	±0.007mm	2µm	26	9	35	13	12.8	SR2	141
241-250-01	160-250mm		5pcs	5pcs	±0.007mm	2µm	56.5	13	74.5	15	14.5	SR3.5	400
241-450-01	250-450mm		5pcs	5pcs	±0.007mm	2µm	86.5	15	101.5	15	14.5	SR3.5	400


INSIDE/OUTSIDE
MEASUREMENT

SERIES 241

DIGITAL BORE GAUGE



- ◆ With min. value tracking function, get the diameter automatically
- ◆ Optional accessory: series 531 setting rings



Bore gauge setter for setting zero(**optional**)



Setting ring(**optional**)




Measuring tips(**included**)




Gasket(**included**)



Install tips




241-160-11



Range: 6-10mm

Range: 10-18mm



Range: 18-35mm

Range: 35-450mm

Code	Range	Digital indicator	Tips	Gasket	Accuracy	Repeatability	a	b	c	Ød	ØD	e	L
241-010-11	6-10mm	Range: 12.7mm resolution: 0.002mm	9pcs	2pcs	±0.012mm	3µm	3.6	5.7	/	/	4.5	SR1	48
241-018-11	10-18mm		9pcs	2pcs	±0.012mm	3µm	5.6	7.8	/	/	6	SR1	105
241-035-11	18-35mm		9pcs	2pcs	±0.015mm	3µm	12.2	6.4	/	12.7	9	SR1	141
241-060-11	35-60mm		6pcs	4pcs	±0.018mm	3µm	12.2	9	27	13	12.8	SR2	141
241-100-11	50-100mm		11pcs	4pcs	±0.018mm	3µm	26	9	35	13	12.8	SR2	141
241-160-11	50-160mm		12pcs	4pcs	±0.018mm	3µm	26	9	35	13	12.8	SR2	141
241-160-12	100-160mm		12pcs	4pcs	±0.018mm	3µm	26	9	35	13	12.8	SR2	141
241-250-11	160-250mm		5pcs	5pcs	±0.018mm	3µm	56.5	13	74.5	15	14.5	SR3.5	400
241-450-11	250-450mm		5pcs	5pcs	±0.018mm	3µm	86.5	15	101.5	15	14.5	SR3.5	400

SERIES 245

LARGE DIAMETER DIAL BORE GAUGE

- ◆ Carbide tipped contact point, wheel guide
- ◆ Optional accessory: series 531 setting rings

Tips style



Bore gauge setter for setting zero (optional)



Setting ring (optional)



245-050-11

Measuring tips (included)



Measuring tips (included)




Gasket (included)




Code	Range	Dial indicator	Tips	Gasket	Probe Travel	Extension rod	L
245-050-11	18-50mm	Range: 10mm graduation: 0.01mm	8pcs	2pcs	1.5mm	1	150
245-100-11	30-100mm		5pcs	3pcs	1.8mm	2	150
245-100-12	50-100mm		10pcs	2pcs	4mm	-	200
245-160-11	100-160mm		7pcs	4pcs	4mm	-	300
245-250-11	160-250mm		6pcs	4pcs	3mm	2	250
245-300-11	100-300mm		5pcs	4pcs	4mm	2	400
245-450-11	250-450mm		5pcs	4pcs	6mm	2	500
245-700-11	450-700mm		5pcs	4pcs	8mm	4	500
245-1000-11	700-1000mm		5pcs	4pcs	8mm	5	500

unit: mm




Range: 18-50mm




Range: 30-1000mm

Install tips (245-050-11)



Install tips (except 245-050-11)




INSIDE/OUTSIDE
MEASUREMENT

243/253

BORE GAUGE

Digital indicator for
243-800-11



253-800-11

Code	Range	Accuracy	Repeatability	Indicator
253-800-11	400-800mm	±0.025mm	0.003mm	dial indicator (Code: 222-010-12) range 10mm, graduation 0.01mm
243-800-11	400-800mm	±0.025mm	0.003mm	digital indicator (Code: 215-010-12) range 12.7mm, resolution 0.002mm/0.0001"

SERIES 244/254


BORE GAUGE

- ♦ Accuracy: 0.018mm
- ♦ Repeatability: 0.003mm

Digital indicator for
series 244



254-060-11



unit: mm


Dial type

Code	Range	Indicator
254-060-11	35-60mm	dial indicator: (Code: 222-010-12) range 10mm, graduation 0.01mm
254-160-11	50-160mm	
254-250-11	160-250mm	
254-450-11	250-450mm	

Digital type

Code	Range	Indicator
244-060-11	35-60mm	digital indicator (Code: 215-010-12) range: 12.7mm/0.5", graduation: 0.002mm/0.0001"
244-160-11	50-160mm	
244-250-11	160-250mm	
244-450-11	250-450mm	

Range	Øa	b	c	Ød	e	L	L1
35-60mm	12.8	22	9	13	27	141	75
50-160mm	12.8	28.5	9.2	13	35	141	76.2
160-250mm	14.5	62.0	12.7	15	74.5	391	100
250-450mm	14.5	91.5	15.0	15	101.5	391	100



SERIES 240

SPLIT TYPE DIAL BORE GAGE SET FOR BLIND HOLES


- ◆ Split type contact points
- ◆ Accuracy (without indicator): 3μm (measuring range 1.5~10mm),
4μm (measuring range 10~20.6mm)
- ◆ Repeatability (without indicator): 1μm
- ◆ Dial indicators are optional

240-120-11M



Code	Range	Quantity of points	Measuring range of point	Measuring depth (L1)	Total length (L)	Material of points	Setting ring (optional)
240-040-11M	1.5-4.2	10	1.5-1.9	17	93	carbide	Ø1.75
			1.8-2.2	17	93	carbide	Ø2
			2.05-2.45	17	93	carbide	Ø2.25
			2.3-2.7	25	101	carbide	Ø2.5
			2.55-2.95	25	101	carbide	Ø2.75
			2.8-3.2	25	101	carbide	Ø3
			3.05-3.45	25	101	carbide	Ø3.25
			3.3-3.7	25	101	carbide	Ø3.5
			3.55-3.9	25	101	carbide	Ø3.75
			5 3.8-4.2	25	101	carbide	Ø4
240-075-11M	4.15-7.8	7	4.15-4.8	41	118	hard chromed	Ø4.5
			4.7-5.3	41	118	hard chromed	Ø5
			5.2-5.8	41	118	hard chromed	Ø5.5
			5.7-6.3	41	118	hard chromed	Ø6
			6.2-6.8	41	118	hard chromed	Ø6.5
			6.7-7.3	41	118	hard chromed	Ø7
			7.2-7.8	45	118	hard chromed	Ø7.5
240-120-11M	7.7-12.5	6	7.7-8.3	45	118	hard chromed	Ø8
			8.2-8.8	45	118	hard chromed	Ø8.5
			8.7-9.3	45	118	hard chromed	Ø9
			9.2-10.5	45	118	hard chromed	Ø10
			10.2-11.5	45	118	hard chromed	Ø11
			11.2-12.5	45	118	hard chromed	Ø12
240-200-11M	12.2-20.6	8	12.2-13.5	45	118	hard chromed	Ø13
			13.4-14.6	45	118	hard chromed	Ø14
			14.4-15.6	45	118	hard chromed	Ø15
			15.4-16.6	45	118	hard chromed	Ø16
			16.4-17.6	45	118	hard chromed	Ø17
			17.4-18.6	45	118	hard chromed	Ø18
			18.4-19.6	45	118	hard chromed	Ø19
			19.4-20.6	45	118	hard chromed	Ø20

unit: mm



Setting ring (optional)



Optional indicators (optional)




INSIDE/OUTSIDE
MEASUREMENT

SERIES 240

SPLIT TYPE DIAL BORE GAUGE SET

unit: mm



- ◆ Split type contact points
- ◆ Accuracy (without indicator):
3μm (measuring range 0.95~10mm),
4μm (measuring range 10~20.6mm)
- ◆ Repeatability (without indicator): 1μm
- ◆ Dial indicators are optional

Setting ring (optional)



Optional indicators (optional)



Code	Range	Quantity of points	Measuring range of point	Measuring depth (L1)	Total length (L)	Material of points	Type of point	Setting ring (optional)
240-014-11	0.95-1.55	5	0.95-1.15	13	89	carbide	A	Ø1
			1.07-1.25	13	89	carbide	A	Ø1.1
			1.17-1.35	13	89	carbide	A	Ø1.2
			1.27-1.45	13	89	carbide	A	Ø1.3
			1.37-1.55	13	89	carbide	A	Ø1.4
240-040-11	1.5-4.2	10	1.5-1.9	17	93	carbide	A	Ø1.75
			1.8-2.2	17	93	carbide	A	Ø2
			2.05-2.45	17	93	carbide	A	Ø2.25
			2.3-2.7	25	101	carbide	A	Ø2.5
			2.55-2.95	25	101	carbide	A	Ø2.75
			2.8-3.2	25	101	carbide	A	Ø3
			3.05-3.45	25	101	carbide	A	Ø3.25
			3.3-3.7	25	101	carbide	A	Ø3.5
			3.55-3.95	25	101	carbide	A	Ø3.75
			3.8-4.2	25	101	carbide	A	Ø4
			0.95-1.15	13	89	carbide	A	1
			1.07-1.25	13	89	carbide	A	Ø1.1
			1.17-1.35	13	89	carbide	A	Ø1.2




Code	Range	Quantity of points	Measuring range of point	Measuring depth (L1)	Total length (L)	Material of points	Type of point	Setting ring (optional)
240-040-12	0.95-4.2	15	1.27-1.45	13	89	carbide	A	Ø1.3
			1.37-1.55	13	89	carbide	A	Ø1.4
			1.5-1.9	17	93	carbide	A	Ø1.75
			1.8-2.2	17	93	carbide	A	Ø2
			2.05-2.45	17	93	carbide	A	Ø2.25
			2.3-2.7	25	101	carbide	A	Ø2.5
			2.55-2.95	25	101	carbide	A	Ø2.75
			2.8-3.2	25	101	carbide	A	Ø3
			3.05-3.45	25	101	carbide	A	Ø3.25
			3.3-3.7	25	101	carbide	A	Ø3.5
			3.55-3.95	25	101	carbide	A	Ø3.75
			3.8-4.2	25	101	carbide	A	Ø4
240-075-11	4.15-7.8	7	4.15-4.8	41	118	hard chromed	B	Ø4.5
			4.7-5.3	41	118	hard chromed	B	Ø5
			5.2-5.8	41	118	hard chromed	B	Ø5.5
			5.7-6.3	41	118	hard chromed	B	Ø6
			6.2-6.8	41	118	hard chromed	B	Ø6.5
			6.7-7.3	41	118	hard chromed	B	Ø7
			7.2-7.8	45	118	hard chromed	C	Ø7.5
240-120-11	7.7-12.5	6	7.7-8.3	45	118	hard chromed	C	Ø8
			8.2-8.8	45	118	hard chromed	C	Ø8.5
			8.7-9.3	45	118	hard chromed	C	Ø9
			9.2-10.5	45	118	hard chromed	C	Ø10
			10.2-11.5	45	118	hard chromed	C	Ø11
			11.2-12.5	45	118	hard chromed	C	Ø12
240-120-12	4.15-12.5	13	4.15-4.8	41	118	hard chromed	B	Ø4.5
			4.7-5.3	41	118	hard chromed	B	Ø5
			5.2-5.8	41	118	hard chromed	B	Ø5.5
			5.7-6.3	41	118	hard chromed	B	Ø6
			6.2-6.8	41	118	hard chromed	B	Ø6.5
			6.7-7.3	41	118	hard chromed	B	Ø7
			7.2-7.8	45	118	hard chromed	C	Ø7.5
			7.7-8.3	45	118	hard chromed	C	Ø8
			8.2-8.8	45	118	hard chromed	C	Ø8.5
			8.7-9.3	45	118	hard chromed	C	Ø9
			9.2-10.5	45	118	hard chromed	C	Ø10
			10.2-11.5	45	118	hard chromed	C	Ø11
			11.2-12.5	45	118	hard chromed	C	Ø12
240-200-11	12.2-20.6	8	12.2-13.5	45	118	hard chromed	C	Ø13
			13.4-14.6	45	118	hard chromed	C	Ø14
			14.4-15.6	45	118	hard chromed	C	Ø15
			15.4-16.6	45	118	hard chromed	C	Ø16
			16.4-17.6	45	118	hard chromed	C	Ø17
			17.4-18.6	45	118	hard chromed	C	Ø18
			18.4-19.6	45	118	hard chromed	C	Ø19
			19.4-20.6	45	118	hard chromed	C	Ø20

SERIES 252

INCH DIAL BORE GAUGE

◆ Optional accessory: Long handle series 250



Setting ring (optional)




Measuring tips (included)




Gasket (included)




252-015-11




Range: 0.24-0.4"



Range: 0.4-0.7"



Range: 0.7-1.5"



Range: 1.4-16"

Code	Range	Dial indicator	Accuracy	Repeatability	a	b	c	Ød	ØD	e	L
252-004-11	0.24-0.4"	dial indicator, range 0.25", graduation 0.0005"	±0.00075"	0.00015"	3.6	5.7	/	/	4.5	SR1	48
252-007-11	0.4-0.7"		±0.00075"	0.00015"	5.6	7.8	/	/	6	SR1	105
252-015-11	0.7-1.5"		±0.00075"	0.00015"	12.2	6.4	/	12.7	9	SR1	141
252-024-11	1.4-2.4"		±0.0009"	0.00015"	26	9	27	13	12.8	SR2	141
252-060-11	2-6"		±0.0009"	0.00015"	26	9	35	13	12.8	SR2	141
252-100-11	6-10"		±0.0009"	0.00015"	56.5	13	74.5	15	14.5	SR3.5	400
252-160-11	10-16"		±0.0009"	0.00015"	86.5	15	101.5	15	14.5	SR3.5	400

SERIES 250

ANVIL FOR BORE GAUGES

- ◆ Measuring face is made of ceramic




250-060-11

Code	For bore gauges	QTY. per set	Measuring tip material	Measuring range of anvil (mm)
250-010-11	6-10mm	9pcs	steel	6, 6.5, 7, 7.5, 8, 8.5, 9, 9.5, 10
250-018-11	10-18.5mm	9pcs	ceramic	10, 11, 12, 13, 14, 15, 16, 17, 18
250-035-11	18-35mm	9pcs	ceramic	18, 20, 22, 24, 26, 28, 30, 32, 34
250-060-11	35-60mm	6pcs	ceramic	35, 40, 45, 50, 55, 60
250-100-11	50-100mm	11pcs	ceramic	50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100
250-160-11	50-160mm	12pcs	ceramic	50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105
250-160-12	100-160mm	12pcs	ceramic	50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105
250-250-11	160-250mm	5pcs	ceramic	160, 170, 180, 190, 200
250-450-11	250-450mm	5pcs	ceramic	250, 260, 270, 280, 290

SERIES 250


LONG HANDLE

- ◆ To assist deep-hole measurement



Install


Code	For bore gauges	A	ØD
250-000-01	35-60mm, 50-100mm, 50-160mm, 100-160mm	473	13
250-000-02		980	13
250-000-03	160-250mm, 250-450mm	480	14.5
250-000-04		980	14.5




255

BORE GAUGE CHECKER

- ◆ Used together with gauge blocks to set bore gauges



Code	Range
255-016-11	18-400mm



INSIDE/OUTSIDE
MEASUREMENT

SERIES 256

BORE GAUGE SETTER




- ◆ Can be used in vertical and horizontal
- ◆ To be used with gauge blocks

Gauge block set (grade 2,ISO3650) for 256-160-11

Blocks per set	Size(mm)	Step(mm)	Quantity(pcs)
33	1.005	—	1
	1.01-1.09	0.01	9
	1.1-1.9	0.1	9
	1-9	1	9
	10-30	10	3
	50	—	1
	100	—	1

Code	Range	Repeatability	Gauge block set
256-160-11*	0-160mm	1.2μm	with
256-160-10	0-160mm	1.2μm	without

* With manufacturer inspection certificate for gauge block set



Application



Gauge block set for 256-160-11



SERIES 401


UNIVERSAL GAUGE

- ◆ For external, internal dimensions and center line space
- ◆ Tips movable range:8mm
- ◆ Tips effective measuring range:±2mm




Indicator is not included
(211-010-03)


unit: mm




Included(mounting attachments/1 pairs)



Included(disk head with round measuring blades/1 pairs)



Included(stops/1 pairs)



Code	Range		Accuracy	Repeatability
	outside	inside		
401-012-01	0-270mm	35-300mm	±5μm	2μm
401-024-01	0-570mm	35-600mm	±5μm	2μm
401-040-01	570-1000mm	600-1000mm	±5μm	2μm

The direction of the measuring force can be changed with an Allen key for either external or internal dimensions






- ◆ Measure radius of internal and external arcs
- ◆ Accuracy: $\pm 0.01R$, R is the radius to be measured in mm
- ◆ Data output (cable code: 200-01 or 200-02), can't output radius
- ◆ Supplied with 5 jaws for different sizes of arc



Measure shaft



Measure bore



Code	Range of radius	Resolution
296-700-11	5-700mm/0.2-27.5"	0.01mm/0.001"



Code	Range of external radius (R1)	Range of internal radius (R2)	Accuracy
406-590-44	100-15000mm/4-590"	100-15000mm/4-590"	$\pm 0.005R^*$

* R is the radius to be measured. For example, radius is 100mm, the accuracy is $\pm 0.005 \times 100 = \pm 0.5\text{mm}$

- ◆ Measure radius of internal or external arcs
- ◆ Resolution: 0.01mm/0.001"
- ◆ Buttons: on/off, hold, mm/inch, c (select jaws), MODE(zero)
- ◆ Supplied with 4 jaws for different sizes of arc
- ◆ Automatic power off (time is adjustable)
- ◆ Data output (cable code: 200-05 or 200-06, output radius)




SERIES 956

CIRCUMFERENCE TAPE

- ◆ Measure diameter and circumference of pipes, trees, etc.
- ◆ Graduation: 0.1mm
- ◆ Accuracy:
Circumference: $\pm 1.5\text{mm}$
Diameter: $\pm 0.5\text{mm}$
- ◆ Laser engraved scale
- ◆ Made of stainless steel



956-012-11



Code	Range	
	Diameter	Circumference
956-012-11	20 - 300mm	60 - 950mm
956-028-11	300 - 700mm	940 - 2200mm
956-044-11	700 - 1100mm	2190 - 3460mm


SERIES 955

CIRCUMFERENCE TAPE

- ◆ Measure diameter and circumference of pipes, trees, tires, etc.
- ◆ Laser engraved scale
- ◆ Made of stainless steel




955-122-11



Code	Range		Graduation	Accuracy	
	Diameter	Circumference		Diameter	Circumference
955-012-11	20 - 300mm	60-950mm	0.1mm	$\pm 0.20\text{mm}$	$\pm 0.60\text{mm}$
955-028-11	300 - 700mm	940-2200mm	0.1mm	$\pm 0.20\text{mm}$	$\pm 0.60\text{mm}$
955-044-11	700 - 1100mm	2190-3460mm	0.1mm	$\pm 0.20\text{mm}$	$\pm 0.60\text{mm}$
955-060-11	1100-1500mm	3450-4720mm	0.1mm	$\pm 0.30\text{mm}$	$\pm 0.90\text{mm}$
955-075-11	1500-1900mm	4710-5980mm	0.1mm	$\pm 0.30\text{mm}$	$\pm 0.90\text{mm}$
955-090-11	1900-2300mm	5960-7230mm	0.1mm	$\pm 0.35\text{mm}$	$\pm 1.05\text{mm}$
955-106-11	2300-2700mm	7220-8500mm	0.1mm	$\pm 0.40\text{mm}$	$\pm 1.20\text{mm}$
955-122-11	2700-3100mm	8480-9760mm	0.1mm	$\pm 0.45\text{mm}$	$\pm 1.35\text{mm}$
955-138-11	3100-3500mm	9730-11010mm	0.1mm	$\pm 0.50\text{mm}$	$\pm 1.50\text{mm}$

Application






- ◆ Suitable for measuring the height, thickness, squareness, coaxiality and so on.
- ◆ IP65 protection level
- ◆ High frequency: 100 times/s, can measure high speed workpiece
- ◆ Output signal: 90° phase difference wave
- ◆ Standard cable length: 2m
- ◆ Long working life due to the special bearing


201-010-11

Interface(RS232)




Interface(Pin4)





unit: mm

Single gauge application



Multi-gauges application


Resolution 0.001mm

Code	Interface	Range	Measuring force	Stem	Accuracy	Hysteresis
201-010-01	Pin4	0-12.7mm	1.5N	Ø8mm	5µm	2µm
201-010-02	RS232	0-12.7mm	1.5N	Ø8mm	5µm	2µm


Resolution 0.01mm

Code	Interface	Range	Measuring force	Stem	Accuracy	Hysteresis
201-010-11	Pin4	0-12.7mm	1.5N	Ø8mm	20µm	10µm
201-010-12	RS232	0-12.7mm	1.5N	Ø8mm	20µm	10µm



- ◆ High and low limits with judgement
- ◆ With control signal input interface
- ◆ With input/output interface
- ◆ Power: supply DC9-24V




Software(included)




unit: mm




Signal



Connected digital indicator



Connected linear gauge



Code	206-010-01
Display	6 digits
Quantity of linear gauge or digital indicator to be connected	1pc
Tolerance signal	tolerance and judgement with alarm and lights(out of upper tolerance, within tolerance, out of lower tolerance)
Output control	output the tolerance judgement (out of upper tolerance, within tolerance, out of lower tolerance) to control external devices
External control	control the display units from external devices (set zero, hold reading and collect data)
Data output	connect to computer software and serial communication port
Power supply	DC 9~24V

206-13(Optional)




OPTIONAL ACCESSORIES


Code	Name	Power	Remark
206-13	alarm lamp	12V	with buzzer

- ◆ With data recording software, can transfer the data into Excel


Software(included)




back



208-004-01



unit: mm




back




208-008-01

Connected digital indicator



Connected linear gauge



Code	Gauges input	Interface
208-004-01	4	RS232/485
208-008-01	8	RS232/485





SERIES 205

LINEAR GAUGES AND DISPLAY UNIT





205-010-01

Spindle lift knob is included



205-000-01

- ◆ Linear gage type: optical grating
- ◆ Display unit: display displacement data in real time, data preset tolerance and make judgment (out of upper tolerance, within tolerance, out of lower tolerance), set zero, change measuring direction, resolution (0.1μm/1 μm), unit switch (μm/mm/inch)
- ◆ Two data transmission methods: can output keyboard signal and data can be transmitted to excel, word, txt etc, can also output serial signal and transmit data to serial communication software



LINEAR GAGE SPECIFICATION

Code	205-010-01	205-010-11
Range	12.7mm	12.7mm
Resolution	0.1μm	1μm
Accuracy (19~20°C)	1μm	3μm
Repeatability	0.2μm	2μm
Linear gage type	optical grating	
Working life	ten million times	
Dust/waterproof	IP50	
Measuring force	0.7±0.3N	
Cable length	900mm	
Operation environment	0~40°C, 20~80%RH	
Power supply	5~24V	
Dimension (LxWxH)	33.6x15x115mm	
Weight	133g	

Application



DISPLAY UNIT SPECIFICATION

Code	205-000-01
Display	4" LCD screen
Unit	μm, mm
Quantity of linear gage to be connected	1pc
Dimension (LxWxH)	170x195x87.5mm
Weight	1.45kg


SERIES 210

DIGITAL INDICATOR

- ◆ Button: tolerance set, data preset, inch/mm conversion, measuring direction set, max./min./range measurement, absolute/incremental measurement
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Automatic power off
- ◆ Supplied with flat and lug back



210-010-03



Range: 0-12.7mm

Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis
210-010-03	12.7mm/0.5"	5µm	2µm
210-025-03	25.4mm/1"	5µm	3µm
210-050-03	50.8mm/2"	6µm	3µm

Resolution 0.01mm/0.0005"


Code	Range	Accuracy	Hysteresis
210-010-13	12.7mm/0.5"	20µm	10µm
210-025-13	25.4mm/1"	20µm	10µm
210-050-13	50.8mm/2"	30µm	10µm

With manufacturer inspection certificate

Styli(optional)



Application



Range: 0-25.4mm

Range: 0-50.8mm


SERIES 211

DIGITAL INDICATOR

- ◆ With analog reading
- ◆ Button: tolerance set, data preset, inch/mm conversion, measuring direction set, max./min./range measurement, absolute/incremental measurement
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Automatic power off
- ◆ Supplied with flat and lug back



211-010-13



Range: 0-12.7mm

Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis
211-010-03	12.7mm/0.5"	5µm	2µm
211-025-03	25.4mm/1"	5µm	3µm
211-050-03	50.8mm/2"	6µm	3µm

Resolution 0.01mm/0.0005"


Code	Range	Accuracy	Hysteresis
211-010-13	12.7mm/0.5"	20µm	10µm
211-025-13	25.4mm/1"	20µm	10µm
211-050-13	50.8mm/2"	30µm	10µm

With manufacturer inspection certificate

Styli(optional)



Application



Range: 0-25.4mm

Range: 0-50.8mm

INDICATOR



SERIES 212

DIGITAL INDICATOR

- ◆ Button: on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Automatic power off
- ◆ Supplied with flat and lug back



VIDEO



212-010-13




Certificate



Data output




CR2032




unit: mm

Range: 0-12.7mm



Range: 0-25.4mm



Range: 0-50.8mm

Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis
212-010-03	12.7mm/0.5"	5μm	2μm
212-025-03	25.4mm/1"	5μm	3μm
212-050-03	50.8mm/2"	6μm	3μm

Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Hysteresis
212-010-13	12.7mm/0.5"	20μm	10μm
212-025-13	25.4mm/1"	20μm	10μm
212-050-13	50.8mm/2"	30μm	10μm

With manufacturer inspection certificate

Styli(optional)



Series 270

Application



SERIES 215

DIGITAL INDICATOR FOR BORE GAUGE

- ◆ Specially designed for bore gauges
- ◆ The minimum value tracking function can find the diameter automatically
- ◆ Read the diameter directly, after inputting the size of setting ring
- ◆ Reading in digit and analog
- ◆ Button: minimum value tracking, calibration, data preset, inch/metric conversion, absolute/incremental measurement
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)



VIDEO



215-010-12




Certificate



Data output



CR2032



unit: mm

Resolution 0.001mm/0.00005"

Code	Range	Accuracy(f _{ges})	Hysteresis(f _u)	Remark
215-010-02	12.7mm/0.5"	5μm	2μm	flat back

Resolution 0.002mm/0.0001"

Code	Range	Accuracy(f _{ges})	Hysteresis(f _u)	Remark
215-010-12	12.7mm/0.5"	20μm	10μm	flat back

With manufacturer inspection certificate

Application






Series 251(optional)



- ◆ Reading in digital and analog
- ◆ Display can be rotated by 320°
- ◆ Button : on/off, zero, tolerance Go and No-Go display, data preset, measuring direction change, max./min./TIR, absolute/incremental measurement, mm/inch, data output
- ◆ Keep preset data and tolerance data in memory after restart
- ◆ Automatic power off
- ◆ Data output (cable code: 200-01 or 200-02)
- ◆ Supplied with lug and flat back


216-010-01

unit: mm


Range: 0-12.7mm

Range: 0-25.4mm

Range: 0-50.8mm
Resolution 0.001mm/0.00005"


Code	Range	Accuracy	Hysteresis
216-010-01	12.7mm/0.5"	5µm	2µm
216-025-01	25.4mm/1"	5µm	3µm
216-050-01	50.8mm/2"	6µm	3µm

Resolution 0.002mm/0.0005"

Code	Range	Accuracy	Hysteresis
216-010-11	12.7mm/0.5"	20µm	10µm
216-025-11	25.4mm/1"	20µm	10µm
216-050-11	50.8mm/2"	30µm	10µm

With manufacturer inspection certificate

Contact points (optional)



Application



SERIES 213

WATERPROOF DIGITAL INDICATOR

- ◆ Dust/waterproof
- ◆ Button: on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement
- ◆ Automatic power off
- ◆ Data output(cable code:200-01 or 200-02)
- ◆ Supplied with lug and flat back



VIDEO



Certificate



Data output



CR2032



IP65



IP54



213-010-01


unit: mm

Styli(optional)




Series 270


Application



Range: 0-12.7mm



Range: 0-25.4mm



Range: 0-50.8mm

Resolution 0.001mm/0.00005"

Code	Range	Proof level	Accuracy	Hysteresis
213-010-01	12.7mm/0.5"	IP65	5µm	2µm
213-025-01	25.4mm/1"	IP54	5µm	3µm
213-050-01	50.8mm/2"	IP54	6µm	3µm

Resolution 0.01mm/0.0005"

Code	Range	Proof level	Accuracy	Hysteresis
213-010-11	12.7mm/0.5"	IP65	20µm	10µm
213-025-11	25.4mm/1"	IP54	20µm	10µm
213-050-11	50.8mm/2"	IP54	30µm	10µm

With manufacturer inspection certificate

SERIES 214

DIGITAL INDICATOR



- ◆ Button: on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement
- ◆ Automatic power off
- ◆ Data output(cable code:200-01 or 200-02)
- ◆ Supplied with flat back



VIDEO



214-005-12

Styli(optional)



Series 270

Application




Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis
214-005-02	5mm/0.2"	5μm	3μm

Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Hysteresis
214-005-12	5mm/0.2"	20μm	10μm

With manufacturer inspection certificate



SERIES 214

DIGITAL INDICATOR



- ◆ Button: on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement
- ◆ Automatic power off
- ◆ Data output(cable code:200-01 or 200-02)
- ◆ Supplied with lug and flat back



VIDEO



214-100-11

Styli(optional)



Series 270

Application




Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis
214-100-01	100mm/4"	9μm	3μm

Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Hysteresis
214-100-11	100mm/4"	30μm	10μm



INDICATOR

- ◆ With analog reading
- ◆ Supplied with cable for communication
- ◆ Button: data output, on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement, max./min./range measurement, tolerance set, hold
- ◆ IP54 protection level
- ◆ Automatic power off
- ◆ Power: rechargeable battery, for 30 hours continuous working(full charge)



217-015-01

Contact points (optional)



Series 270


Cable (Included)




Application



display can be rotated by 270°



217-015-01



217-010-01, 217-025-01 and 217-050-01

unit: mm

Code	Range	Resolution	Accuracy	Hysteresis	Styli
217-015-01	15mm/0.6"	0.0005mm/0.00002"	2μm	1.5μm	Carbide

Code	Range	Resolution	Accuracy	Hysteresis	Styli	a	b	c
217-010-01	12.7mm/0.5"	0.0005mm/ 0.00002"	2μm	1.5μm	Carbide	118.7	61	14.7
217-025-01	25.4mm/1"		2μm	1.5μm	Carbide	151.7	81	27.7
217-050-01	50.8mm/2"		2μm	1.5μm	Carbide	222.2	126	53.2



- ◆ Built-in bluetooth
- ◆ Supplied with cable for communication
- ◆ Button: data output, on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement, max./min./range measurement, tolerance set, hold, resolution adjustment
- ◆ IP54 protection level
- ◆ Automatic power off
- ◆ Power: rechargeable battery, for 30 hours continuous working(full charge)


217-015-01H
Cable (Included)

Application


Contact points (optional)

Series 270


display can be rotated by 270°


Blue tooth

Smart phone, Computer, Ipad



Code	Range	Resolution(adjustable)	Accuracy	Hysteresis	Styli	a	b	c
217-010-01H	12.7mm/0.5"	0.0005mm/0.00002" 0.001mm/0.00005"	2µm	1.5µm	Carbide	118.7	61	14.7
217-015-01H	15mm/0.6"		2µm	1.5µm	Carbide	123.7	63.5	17
217-025-01H	25.4mm/1"		2µm	1.5µm	Carbide	151.7	81	27.7
217-050-01H	50.8mm/2"		2µm	1.5µm	Carbide	222.2	126	53.2

- ◆ Linear ball bearings for ten million times use
- ◆ Absolute encoder, the original data remains after power off
- ◆ Reading in digital and analog
- ◆ Supplied with RS232 cable (with software)
- ◆ Button: tolerance, data preset, data hold, measuring direction change, max./min./TIR, power off time, on/off, mm/inch, resolution adjustment
- ◆ Power: rechargeable battery, for 24 hours continuous working(full charge)



VIDEO

RS232 cable (Included)



218-010-01



218-025-01

unit: mm

Lifting lever (Included)



Application




Contact points (optional)




Series 270




display can be rotated by 320°



Range:0-12.7mm



Range:0-25.4mm



Range:0-50.8mm

Code	Range	Resolution(adjustable)	Accuracy	Hysteresis	Styli	Back
218-010-01	12.7mm/0.5"	0.0002mm/0.00001"	1.5μm	1μm	Ruby	flat
218-025-01	25.4mm/1"	0.001mm/0.00005" 0.01mm/0.0005"	1.8μm	1μm	Ruby	flat

Code	Range	Resolution(adjustable)	Accuracy	Hysteresis	Styli	Back
218-010-11	12.7mm/0.5"	0.0005mm/0.00002"	3μm	1.5μm	Carbide	flat
218-025-11	25.4mm/1"	0.001mm/0.00005" 0.01mm/0.0005"	3μm	1.5μm	Carbide	flat
218-050-11	50.8mm/2"	0.01mm/0.0005"	3μm	1.5μm	Carbide	flat

SERIES 218

WIRELESS HIGH PRECISION DIGITAL INDICATOR



ACCUD



- ◆ Built-in wireless transmission, Zigbee signal
- ◆ Built-in bluetooth
- ◆ Absolute encoder, the original data remains after power off
- ◆ Reading in digital and analog
- ◆ Supplied with RS232 cable (with software)
- ◆ Button: data output, tolerance, data preset, data hold, measuring direction change, max./min./TIR, power off time, on/off, mm/inch, resolution adjustment
- ◆ Power: rechargeable battery, for 24 hours continuous working(full charge)



VIDEO

Lifting lever (Included)



218-010-01W



218-025-01W

unit: mm



display can be rotated by 320°



Blue tooth

Smart phone, Ipad

RS232 cable (Included)




Contact points (optional)




Series 270


Application



0-12.7mm



0-25.4mm



0-50.8mm

Code	Range	Resolution(adjustable)	Accuracy	Hysteresis	Styli	Back
218-010-01W	12.7mm/0.5"	0.0002mm/0.00001"	1.5µm	1µm	Ruby	flat
218-025-01W	25.4mm/1"	0.001mm/0.00005"	1.8µm	1µm	Ruby	flat
		0.01mm/0.0005"				

Code	Range	Resolution(adjustable)	Accuracy	Hysteresis	Styli	Back
218-010-11W	12.7mm/0.5"	0.0005mm/0.00002"	3µm	1.5µm	Carbide	flat
218-025-11W	25.4mm/1"	0.001mm/0.00005"	3µm	1.5µm	Carbide	flat
218-050-11W	50.8mm/2"	0.01mm/0.0005"	3µm	1.5µm	Carbide	flat

INDICATOR

SERIES 227

DIGITAL INDICATOR WITH LIFTING LEVER




- ◆ Button: on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Automatic power off



VIDEO



unit: mm



Styli(optional)



Series 270

Application



Resolution 0.001mm/0.00005"

227-010-12

Code	Range	Accuracy(fges)	Hysteresis(fu)	Remark
227-010-02	10mm/0.4"	5µm	2µm	flat back

Resolution 0.01mm/0.0005"

Code	Range	Accuracy(fges)	Hysteresis(fu)	Remark
227-010-12	10mm/0.4"	20µm	10µm	flat back

SERIES 222


DIAL INDICATOR



- ◆ Graduation: 0.001mm
- ◆ With limit hands
- ◆ Jeweled bearing
- ◆ Rang per revolution: 0.2mm
- ◆ With lock screw



unit: mm




Styli(optional)



Series 270

Application




222-001-01

Code	Range	Back	Scale	Accuracy	Hysteresis
222-001-01	1mm	lug	0-100-0	5µm	2µm
222-001-02	1mm	flat	0-100-0	5µm	2µm


With manufacturer inspection certificate



- ◆ Graduation: 0.001mm
- ◆ With limit hands
- ◆ Jeweled bearing
- ◆ Rang per revolution: 0.2mm
- ◆ Supplied with lug and flat back



Series 270




221-001-01

Code	Range	Scale	Accuracy	Hysteresis	a	b	c	d
221-001-01	1mm	0-200	5µm	2µm	15	19.5	62.5	45
221-003-01	3mm	0-200	10µm	4µm	10	21.5	59.5	41.5
221-005-01	5mm	0-200	10µm	4µm	10	21.5	59.5	41.5

With manufacturer inspection certificate



- ◆ Bezel: Ø40mm
- ◆ Graduation: 0.001mm
- ◆ With limit hands
- ◆ Jeweled bearing
- ◆ Supplied with lug and flat back



228-001-01

Code	Range	Accuracy	Hysteresis	Range/rev	Scale
228-001-01	1mm	5µm	2µm	0.1mm	0-100

With manufacturer inspection certificate



Series 270

SERIES 222

DIAL INDICATOR



- ◆ Graduation: 0.01mm
- ◆ With limit hands
- ◆ Jeweled bearing
- ◆ Range per revolution: 1mm
- ◆ With lock screw



222-010-11

Styli(**optional**)




Series 270

Application



Code	Range	Back	Accuracy	Hysteresis	Scale
222-003-11	3mm	lug	14μm	3μm	0-100
222-005-11	5mm	lug	16μm	3μm	0-100
222-010-11	10mm	lug	17μm	3μm	0-100
222-003-12	3mm	flat	14μm	3μm	0-100
222-005-12	5mm	flat	16μm	3μm	0-100
222-010-12	10mm	flat	17μm	3μm	0-100

With manufacturer inspection certificate



SERIES 223

DIAL INDICATOR



- ◆ Graduation: 0.01mm
- ◆ With limit hands
- ◆ Range per revolution: 1mm
- ◆ With lock screw



223-010-11

Styli(**optional**)




Series 270

Application



Code	Range	Back	Accuracy	Hysteresis	Scale
223-010-11	10mm	lug	20μm	3μm	0-100
223-010-12	10mm	flat	20μm	3μm	0-100

With manufacturer inspection certificate



SERIES 228


DIAL INDICATOR



- ◆ Bezel: Ø40mm
- ◆ Graduation: 0.01mm
- ◆ With limit hands
- ◆ Jeweled bearing
- ◆ Rang per revolution: 1mm
- ◆ Supplied with lug and flat back



228-005-11



Styli(optional)



Series 270

Application



Code	Range	Accuracy	Hysteresis	Scale	b	c
228-003-11	3mm	14µm	3µm	0-100	11	44
228-005-11	5mm	16µm	3µm	0-100	12.5	45.5

With manufacturer inspection certificate

SERIES 229


DIAL INDICATOR



- ◆ Graduation: 0.01mm
- ◆ With limit hands
- ◆ Rang per revolution: 1mm
- ◆ Supplied with lug and flat back



229-030-11



Styli(optional)



Series 270

Application



Code	Range	Accuracy	Hysteresis	Scale	a	b	c	d	e	f
229-020-11	20mm	25µm	5µm	0-100	20	35	83	37.5	Ø8	Ø58
229-030-11	30mm	35µm	7µm	0-100	20	40	88	37.5	Ø8	Ø58

With manufacturer inspection certificate

229

DIAL INDICATOR




- ◆ Graduation: 0.01mm
- ◆ With limit hands
- ◆ Rang per revolution: 1mm
- ◆ Supplied with lug and flat back



Styli(**optional**)



Application



Code	Range	Accuracy	Hysteresis	Scale
229-025-11	25mm	35µm	7µm	0-100

With manufacturer inspection certificate

SERIES 229

DIAL INDICATOR

Note: 229-100-21
can only be used vertically



- ◆ Graduation: 0.01mm
- ◆ With limit hands
- ◆ Rang per revolution: 1mm
- ◆ Supplied with lug and flat back


Stem clamp Ø10mm
for 229-100-21 (included)



Styli(**optional**)



Application



Code	Range	Accuracy	Hysteresis	Scale	a	b	c	d	e	f
229-050-21 *	50mm	40µm	8µm	0-100	40	58	127	108	Ø8	Ø58
229-100-21	100mm	50µm	9µm	0-100	60	108	207	168	Ø10	Ø78

* With manufacturer inspection certificate

AECUD



INDICATOR

231

WATERPROOF DIAL INDICATOR





- ◆ IP54 dust/waterproof
- ◆ Graduation:0.01mm
- ◆ Jeweled bearing

Styli(optional)



Series 270

Application




Code	Range	Accuracy(f _{ges})	Hysteresis(f _u)	Range/rev	Dial reading
231-010-11	10mm	17µm	3µm	1mm	0-100

With manufacturer inspection certificate

231

WATERPROOF DIAL INDICATOR




- ◆ Meet DIN878
- ◆ Graduation:0.01mm
- ◆ IP54 dust/waterproof
- ◆ Jeweled bearing
- ◆ Supplied with lug and flat back

Styli(optional)



Series 270

Application



Code	Range	Accuracy	Hysteresis	Range/rev	Dial reading
231-010-21	10mm	17µm	3µm	1mm	0-100

With manufacturer inspection certificate

SERIES 232

ONE REVOLUTION DIAL INDICATOR




- ◆ Shock proof
- ◆ Supplied with lug and flat back


Styli (optional)



Application



232-001-11



Code	Range	Graduation	Accuracy	Hysteresis	Dial reading
232-0005-11	0.5mm	0.01mm	9μm	3μm	25-0-25
232-001-11	1mm	0.01mm	9μm	3μm	50-0-50

With manufacturer inspection certificate

233

DOUBLE FACE DIAL INDICATOR




- ◆ Meet DIN878
- ◆ Read from both sides
- ◆ Jeweled bearing
- ◆ Supplied with limit pointers

Styli (optional)



Application



Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading
233-010-11	10mm	0.01mm	17μm	3μm	1mm	0-100

With manufacturer inspection certificate

SERIES 230

DIAL INDICATOR

- ◆ Supplied with limit pointers and bezel clamp

Styli(optional)




Series 270

Application




230-030-11



Code	Range	Graduation	Accuracy(fges)	Hysteresis(fu)	Range/rev	Dial reading	Remark	h	d
230-010-11	10mm	0.1mm	40µm	20µm	10mm	0-10mm	lug back	70	20
230-030-11	30mm	0.1mm	60µm	20µm	10mm	0-10mm	lug back	90	40

291

REVERSE DIAL INDICATOR




- ◆ Shockproof
- ◆ Graduation: 0.01mm
- ◆ Reverse reading
- ◆ With limit hands
- ◆ Jeweled bearing
- ◆ Rang per revolution: 1mm
- ◆ Supplied with lug and flat back

Styli(optional)



Series 270


Application



Code	Range	Accuracy	Hysteresis	Scale
291-010-I	10mm	17µm	3µm	0-100

REVERSE DIAL INDICATOR

- ◆ Graduation: 0.01mm
- ◆ Reverse reading
- ◆ With limit hands
- ◆ Rang per revolution: 1mm
- ◆ Supplied with lug and flat back



Styli(optional)



Application




Code	Range	Accuracy	Hysteresis	Scale
292-030-I	30mm	35µm	7µm	0-100

SERIES 225

INCH DIAL INDICATOR



- ◆ Meet ASME B89.1.10M-2001
- ◆ Supplied with limit hands and bezel clamp
- ◆ Lug back



Application



225-025-11

Code	Range	Graduation	Dial reading	Range/rev	Accuracy		a	b	c	d
					First 2.5 rew	Overall				
225-006-11	0.25"	0.001"	0-100	0.1"	±0.001"	±0.001"	20	25	75	46
225-012-11	0.5"	0.001"	0-100	0.1"	±0.001"	±0.002"	20	25	75	46
225-025-11	1"	0.001"	0-100	0.1"	±0.001"	±0.002"	20	35	85	46
225-050-11	2"	0.001"	0-100	0.1"	±0.001"	±0.004"	50	59	139	111

With manufacturer inspection certificate

SERIES 261

DIAL TEST INDICATOR




- ◆ Jeweled bearing
- ◆ Double scale spacing
- ◆ Anti-magnetic copper body
- ◆ With two clamps: Ø4mm and Ø8mm


Application




Clamps (included)



261-002-01



unit: mm



Code	Range	Bezel(d)	Graduation	Styli	Accuracy	Hysteresis	Scale
261-002-01	0.2mm	Ø33mm	0.002mm	carbide	6µm	2µm	0-100-0
261-002-02	0.2mm	Ø37.5mm	0.002mm	carbide	6µm	2µm	0-100-0

With manufacturer inspection certificate

SERIES 261

DIAL TEST INDICATOR




- ◆ Economic type
- ◆ Jeweled bearing
- ◆ Double scale spacing
- ◆ Anti-magnetic copper body
- ◆ With two clamps: Ø4mm and Ø8mm


Application




Clamps (included)



261-002-61P



unit: mm



Code	Range	Bezel(d)	Graduation	Styli	Accuracy	Hysteresis	Scale
261-002-61P	0.2mm	Ø33mm	0.002mm	carbide	6µm	2µm	0-100-0
261-002-62P	0.2mm	Ø37.5mm	0.002mm	carbide	6µm	2µm	0-100-0

With manufacturer inspection certificate

SERIES 261

DIAL TEST INDICATOR



- ◆ Jeweled bearing
- ◆ Double scale spacing
- ◆ Anti-magnetic copper body
- ◆ With two clamps: Ø4mm and Ø8mm





261-008-12

Application



Clamps (included)



Code	Range	Bezel(d)	Graduation	Styli	Accuracy	Hysteresis	Scale
261-008-11	0.8mm	Ø30mm	0.01mm	carbide	13µm	3µm	0-40-0
261-008-12	0.8mm	Ø37.5mm	0.01mm	carbide	13µm	3µm	0-40-0

With manufacturer inspection certificate

SERIES 261

DIAL TEST INDICATOR



- ◆ Economic type
- ◆ Jeweled bearing
- ◆ Double scale spacing
- ◆ Anti-magnetic copper body
- ◆ With two clamps: Ø4mm and Ø8mm





261-008-62P

Application



Clamps (included)



Code	Range	Bezel(d)	Graduation	Styli	Accuracy	Hysteresis	Scale
261-008-61P	0.8mm	Ø30mm	0.01mm	carbide	13µm	3µm	0-40-0
261-008-62P	0.8mm	Ø37.5mm	0.01mm	carbide	13µm	3µm	0-40-0

With manufacturer inspection certificate

261

PRECISION DIAL TEST INDICATOR





- ◆ Meet DIN2270
- ◆ Jeweled bearing
- ◆ Double scale spacing
- ◆ With two clamps: Ø6mm and Ø8mm




Application



Clamps (included)



unit: mm



Code	Range	Bezel(d)	Graduation	Styli	Accuracy	Hysteresis	Scale
261-014-01	0.14mm	Ø38mm	0.001mm	carbide	4µm	2µm	0-70-0

With manufacturer inspection certificate

SERIES 261



DIAL TEST INDICATOR



- ◆ Jeweled bearing
- ◆ Carbide contact point
- ◆ Two measuring directions
- ◆ Anti magnetic body
- ◆ Supplied with two clamps: 5/32" DIA and 3/8" DIA



261-030-51



Graduation 0.001"

Code	Range	Accuracy	Dial reading	d	L
261-030-11	0.03"	±0.001"	0-15-0	1.181"DIA	0.50"

Graduation 0.0001"

Code	Range	Accuracy	Dial reading	d	L
261-080-01	0.008"	±0.0001"	0-40-0	1.181"DIA	0.563"

Graduation 0.0005"


Code	Range	Accuracy	Dial reading	d	L
261-030-51	0.03"	±0.0005"	0-15-0	1.181"DIA	0.50"
261-030-52	0.03"	±0.0005"	0-15-0	1.457"DIA	0.50"

With manufacturer inspection certificate

Application



Clamp (included)



SERIES 263

LONG STYLI DIAL TEST INDICATOR



- ◆ Jeweled bearing
- ◆ Double scale spacing
- ◆ Anti-magnetic copper body
- ◆ With two clamps: Ø4mm and Ø8mm






263-008-11L

Application



Clamps (included)




unit: mm

Code	Range	Bezel(d)	Graduation	Styli	Accuracy	Hysteresis	Scale	L
263-008-11	0.8mm	Ø37.5mm	0.01mm	carbide	13µm	3µm	0-40-0	30.5
263-008-11L	0.8mm	Ø37.5mm	0.01mm	ruby	13µm	9µm	0-40-0	46.4



With manufacturer inspection certificate

264

BACK PLUNGER TYPE DIAL TEST INDICATOR



- ◆ Jeweled bearing
- ◆ Carbide contact point
- ◆ Two measuring directions
- ◆ Anti magnetic body
- ◆ Supplied with two clamps: diameter Ø4mm and Ø8mm
- ◆ Optional accessory: styli




unit: mm

Application



Clamps (included)




Code	Range	Graduation	Accuracy(fgcs)	Hysteresis(fu)	Dial Reading
264-008-11	0.8mm	0.01mm	13µm	3µm	0-40-0

With manufacturer inspection certificate

SERIES 260


STYLI FOR DIAL TEST INDICATOR

Accu-D



unit: mm

Code	For products	Tip material	D	L
260-001-01	261-008-11	steel	SØ1	16.5
260-002-02	261-008-12 266-016-11	carbide	SØ2	16.5
260-003-02	264-008-11	carbide	SØ3	16.5
260-010-01	265-008-11	ruby	SØ2	16.5
260-009-01	261-002-01 261-002-02	ruby	SØ2	15
260-010-02	263-008-11	carbide	SØ2	30.5
260-010-03	263-008-11L	ruby	SØ2	46.4



SERIES 267

HOLDER FOR INDICATOR


- ◆ Use as holder for dial/digital indicators, dial test indicators and height gages




267-100-01

unit: mm

Application(optional)



267-050-01 and 267-100-01



267-115-02


Code	Section size	Size(L)
267-050-01	9x9mm	50mm
267-100-01	9x9mm	100mm
267-115-02	Ø8mm	115mm

INDICATOR

268

UNIVERSAL HOLDER FOR DIAL TEST INDICATOR

- ◆ Universal head



Application



Code

268-055-01


Section size

Ø8mm

269

DIAL TEST INDICATOR CENTERING HOLDER

- ◆ Center cylinders or holes on a machine tool



Application




Code

269-060-01


273

SHAFT SLEEVE

- ◆ For dial indicators and probes with shaft diameter Ø8mm
- ◆ Made of stainless steel



Application





Code

273-001-01


type A

Code	Material	L
270-001-01	carbide	7.3
270-001-02	ceramic	7.3
270-001-03	carbide	8.3
270-001-04	carbide	12.1
270-001-05	carbide	14
270-001-06	carbide	15
270-001-07	ceramic	15
270-001-08	carbide	17
270-001-09	carbide	19.3
270-001-10	carbide	20
270-001-11	ceramic	20
270-001-12	carbide	22
270-001-13	carbide	25
270-001-14	ceramic	25
270-001-15	carbide	30
270-001-16	ceramic	30

Ball Point

270-001-03


unit: mm


type B

Code	Material	ØD
270-001-21	steel	1
270-001-22	carbide	1.5
270-001-23	carbide	1.8
270-001-24	carbide	2.5
270-001-25	carbide	4


Shell Type Point

270-002-02

Code	Material	L
270-002-01	steel	5
270-002-02	steel	10
270-002-03	steel	15
270-002-04	steel	20
270-002-05	steel	25
270-002-06	steel	30



unit: mm

Spherical Point



unit: mm

Code	Material
270-003-01	steel


Conical Point



270-004-02




270-004-01




270-004-02

unit: mm



270-004-03



270-004-04

Code	Material
270-004-01	steel
270-004-02	steel
270-004-03	steel
270-004-04	steel

type A

Code	Material	L
270-005-01	steel	8
270-005-02	steel	10

Flat Point





270-005-12



270-010-16

type B



Code	Material	ØD
270-005-11	steel	10
270-005-12	steel	15
270-005-13	steel	20
270-005-14	steel	25
270-005-15	steel	30



unit: mm

type C

Code	Material	ØD
270-010-16	ceramic	10




type D

Code	Material
270-005-21	carbide



type A

Code	Material	ØD	L
270-006-01	steel	0.45	3
270-006-02	steel	0.45	5
270-006-03	carbide	1	3
270-006-04	carbide	1	5
270-006-05	carbide	1	8
270-006-06	carbide	1	10
270-006-07	carbide	1	20
270-006-08	carbide	1	40
270-006-09	carbide	1.5	5
270-006-10	carbide	1.5	10
270-006-11	carbide	1.5	13
270-006-12	carbide	1.5	20
270-006-13	carbide	1.5	40
270-006-14	carbide	2	8
270-006-15	carbide	2	18
270-006-16	carbide	2	28
270-006-17	carbide	2	40




Needle Point

270-006-16
270-006-22
type A

type B

unit: mm


type B


Code	Material	L1	L	SR
270-006-21	steel	11	15	0.4
270-006-22	steel	13	17	0.2
270-006-23	steel	21	25	0.4
270-006-24	steel	31	35	0.4

Knife Edge Point



unit: mm

Code	Material
270-007-01	steel

Blade Point

270-008-03


unit: mm



Code	Material	D	W
270-008-01	steel	0.4	2
270-008-02	steel	0.6	2
270-008-03	steel	1	4

SERIES 270


CONTACT POINTS

Ball Point

Code	Material	SØD
270-011-01	carbide	1
270-011-02	carbide	1.5
270-011-03	carbide	2
270-011-04	carbide	2.5
270-011-05	carbide	3
270-011-06	carbide	3.5
270-011-07	carbide	4
270-011-08	carbide	4.5
270-011-09	carbide	5
270-011-10	carbide	5.5
270-011-11	carbide	6
270-011-12	carbide	6.5
270-011-14	carbide	7
270-011-16	carbide	8
270-011-18	carbide	9
270-011-20	carbide	10
270-011-24	carbide	12



270-011-08




270


ROLLER POINT



unit: mm



Code	Material of measuring face
270-009-01	steel



Code	Material of measuring face
270-100-06	steel


SERIES 270

EXTENSION ROD FOR CONTACT POINTS



270-000-15

Package



Code	Material	L
270-000-01	steel	10
270-000-02	steel	15
270-000-03	steel	20
270-000-04	steel	25
270-000-05	steel	30
270-000-06	steel	35


Code	Material	L
270-000-07	steel	40
270-000-08	steel	45
270-000-09	steel	50
270-000-10	steel	55
270-000-11	steel	60
270-000-12	steel	65

Code	Material	L
270-000-13	steel	70
270-000-14	steel	75
270-000-15	steel	80
270-000-16	steel	90
270-000-17	steel	100

SERIES 270

EXTENSION ROD FOR CONTACT POINTS

- ◆ For series 225 Inch indicator



Code	Material	L
270-000-01I	steel	1"
270-000-02I	steel	2"
270-000-03I	steel	3"
270-000-04I	steel	4"

271

SPINDLE LIFT KNOB

- ◆ For dial/digital indicators with spindle diameter Ø4.5mm or Ø5mm



Code


271-045-01

SERIES 272


LUG AND FLAT BACK




272-000-01




272-000-01



272-000-02




272-000-03



272-000-04

Code	Type	Material
272-000-01	lug	metal
272-000-02	flat	plastic
272-000-03	lug	metal
272-000-04	flat	plastic


- ◆ To calibrate dial indicators, test indicators and dial bore gauges
- ◆ Dimension: 270x210x205mm
- ◆ Weight: 11kg



Inspect accuracy of dial indicators
(range 0-25mm)



Inspect accuracy of dial bore gauges
(range 6-450mm)



Inspect accuracy of test indicators



Check force of dial indicators



Check repeatability of dial indicators



Check the effect of lateral force on
accuracy of dial indicators



Check the effect of lateral force on
accuracy of test indicators

Micrometer head

Range	Sampling interval	Accuracy	Hysteresis
0-25mm	0.1mm	4μm(0-25mm), 3μm(any section 10mm), 2μm(any section 1mm)	1μm

Force gauge

Range	Graduation	Accuracy
0-1.6N	0.05N	±5%

Stage

Diameter	Flatness	Roughness
0-1.6N	1μm	0.05μm

Half round gauge block (included)

Dimension	Parallelism
10mm	1μm



half round gauge block
(included)

Code

499-025-01




SERIES 281

MAGNETIC STAND

- ◆ For dial/digital indicators and dial test indicators
- ◆ V-block base

Application



281-060-02




281-060-02




281-060-01

unit: mm




60(L)x50(W)

281-060-01




60(L)x50(W)

281-080-01



75(L)x50(W)

281-100-01



117(L)x50(W)

281-130-01

Code	Stem hole	Magnetic force	Fine adjustment
281-060-01	Ø8mm, Ø4mm, 3/8"	60kgf	With
281-060-02	Ø8mm, Ø4mm, 3/8"	60kgf	Without
281-080-01	Ø8mm, Ø4mm, 3/8"	80kgf	With
281-100-01	Ø8mm, Ø4mm, 3/8"	100kgf	With
281-130-01	Ø8mm, Ø4mm, 3/8"	130kgf	With

SERIES 282


UNIVERSAL MAGNETIC STAND

- ◆ For dial/digital indicators and dial test indicators
- ◆ Stem hole: Ø8mm
- ◆ With find adjustment and dovetail
- ◆ V-block base



Application



Code	Magnetic force
282-080-01	80kgf
282-080-02	80kgf
282-100-01	100kgf



282-080-01



283


UNIVERSAL MAGNETIC STAND

- ◆ Economic type
- ◆ For dial/digital indicators and dial test indicators
- ◆ Stem hole: Ø8mm
- ◆ With find adjustment and dovetail
- ◆ V-block base

Application



Code	Magnetic force
283-080-01	80kgf



SERIES 279


UNIVERSAL MAGNETIC STAND

- ◆ For dial/digital indicators and dial test indicators
- ◆ Aluminum arm
- ◆ With fine adjustment and dovetail
- ◆ V-block base

Application



279-080-01




Code	Magnetic force	Base (LxWxH)	L1	L2	L3
279-030-01	30kgf	35x30x35	56	51	73
279-080-01	80kgf	60x50x55	110	101	76
279-100-01	100kgf	73x50x55	147	130	76

SERIES 277


HYDRAULIC UNIVERSAL MAGNETIC STAND

- ◆ For dial/digital indicators and dial test indicators
- ◆ With fine adjustment and dovetail
- ◆ V-block base
- ◆ Magnetic switch made of metal

Application



277-080-01



Code	Magnetic force	Base(LxWxH)	L1	L2	L3
277-080-01	80kgf	60x50x55	65	55	70
277-080-02	80kgf	60x50x55	125	90	70
277-100-01	100kgf	75x50x55	160	125	70

SERIES 278


UNIVERSAL MAGNETIC STAND

- ◆ For dial/digital indicators and dial test indicators
- ◆ Super strong arm
- ◆ With fine adjustment and dovetail
- ◆ V-block base

Application



278-080-01




Code	Magnetic force	Base (LxWxH)	L1	L2	L3
278-050-01	50kgf	40x40x40	62	52	79
278-080-01	80kgf	60x50x55	100	81	67
278-100-01	100kgf	73x50x55	145	95	81

288

MINI MAGNETIC STAND

- ◆ For dial test indicators

Application



Code	Magnetic force	Stem hole
288-010-01	10kgf	Ø8mm, Ø6mm




286

MINI MAGNETIC STAND

- ◆ For dial test indicators
- ◆ Stem hole: Ø8mm
- ◆ With find adjustment and dovetail
- ◆ V-block base

Application




Code	Magnetic force	Stem hole
286-040-01	40kgf	Ø8mm

285

FLEX ARM MAGNETIC STAND

- ◆ For dial test indicators

Application




Code	Magnetic force	Applicable holding stem
285-080-01	80kgf	Ø8mm, Ø4mm, 3/8" DIA.

284

VACUUM STAND

- ◆ To be used on granite plates
- ◆ For digital/dial indicators and dial test indicators

Application




Code	Applicable holding stem	Remark
284-080-01	Ø8mm	with fine adjustment and dovetail groove

287

UNIVERSAL STAND

- ◆ For dial/digital indicators and dial test indicators

Application



Code	Applicable holding stem	Remark
287-001-01	Ø8mm, Ø4mm	with fine adjustment

SERIES 289


INDICATOR STAND WITH GRANITE BASE

- ◆ Holder vertical travel: 150mm
- ◆ Fine adjustment range: 2mm

Application



289-008-01



Code	Stem hole	Base flatness	Base size (WxD)
289-008-01	Ø8mm	3.2µm	200x150mm
289-012-01	Ø8mm	3.2µm	300x200mm

SERIES 290

INDICATOR STAND WITH CERAMIC BASE


- ◆ Working table is made of ceramic
- ◆ Holder vertical travel: 150mm



290-080-01



290-100-01



Code	Stem hole	Ceramic flatness	Ceramic size
290-080-01	Ø8mm	1.5µm	Ø80mm

Code	Stem hole	Ceramic flatness	Ceramic size
290-100-01	Ø8mm	1.5µm	100x100mm



SERIES 294

INDICATOR STAND


- ◆ Working table is made of steel
- ◆ Holder vertical travel: 100mm
- ◆ With fine adjustment: $\pm 1.5\text{mm}$
- ◆ Working table surface hardness is $60\pm 2\text{HRC}$



294-080-12



294-060-11



Code	Working table flatness	Working table size
294-060-11	1.5 μm	$\varnothing 60\text{mm}$

Code	Working table flatness	Working table size
294-080-12	1.5 μm	80x80mm



660

CONCENTRICITY GAUGE

- ◆ Optional accessories: dial test indicator (code: 261-002-01 or 261-002-02) and Mini magnetic stand (code: 286-040-01)



unit: mm




Code	Applicable diameter	Accuracy
660-001-01	$\varnothing 3-35\text{mm}$	0.002mm




661

QUICK POSITIONING CONCENTRICITY GAUGE

Dial test indicator
is not included



- ◆ Quick positioning, suitable for mass measurement
- ◆ Optional accessories: dial test indicator (code: 261-002-01 or 261-002-02)



Code	Diameter range	Workpiece length	Accuracy	Center height (h)
661-002-01	Ø1-35mm	15-100mm	2µm	70mm


662

CONCENTRICITY GAUGE

Dial test indicator is not included



- ◆ Double guide
- ◆ Holding height can be adjusted



Code	Applicable diameter	Workpiece length
662-300-01	Ø3-40mm	300mm

SERIES 410

DIGITAL INTERNAL CALIPER GAUGE




- ◆ Measure the internal dimension
- ◆ Resolution: 0.01mm/0.0005"




410-055-11

unit: mm

Code	Range	Accuracy	a	b	L
410-035-11	15-35mm/0.6-1.4"	±0.04mm	3	Ø3	50
410-035-11L	15-35mm/0.6-1.4"	±0.04mm	3	Ø3	200
410-055-11	35-55mm/1.4-2.2"	±0.04mm	6	Ø3	80
410-055-11L	35-55mm/1.4-2.2"	±0.04mm	6	Ø3	250
410-075-11	55-75mm/2.2-3"	±0.04mm	8	Ø3	90
410-075-11L	55-75mm/2.2-3"	±0.04mm	8	Ø3	250
410-095-11	75-95mm/3-3.8"	±0.04mm	8	Ø3	100
410-095-11L	75-95mm/3-3.8"	±0.04mm	8	Ø3	250
410-115-11	95-115mm/3.8-4.6"	±0.04mm	10	Ø3.2	120
410-115-11L	95-115mm/3.8-4.6"	±0.04mm	10	Ø3.2	250
410-135-11	115-135mm/4.6-5.4"	±0.04mm	10	Ø3.2	120
410-135-11L	115-135mm/4.6-5.4"	±0.04mm	10	Ø3.2	250



Setting ring (optional)



SERIES 411

INTERNAL DIAL CALIPER GAUGE


- ◆ Measure the internal dimension
- ◆ Graduation: 0.01mm




411-035-11

unit: mm

Code	Range	Accuracy	a	b	L
411-035-11	15-35mm	±0.04mm	3	Ø3	50
411-035-11L	15-35mm	±0.04mm	3	Ø3	200
411-055-11	35-55mm	±0.04mm	6	Ø3	80
411-055-11L	35-55mm	±0.04mm	6	Ø3	250
411-075-11	55-75mm	±0.04mm	8	Ø3	90
411-075-11L	55-75mm	±0.04mm	8	Ø3	250
411-095-11	75-95mm	±0.04mm	8	Ø3	100
411-115-11	95-115mm	±0.04mm	10	Ø3.2	120
411-135-11	115-135mm	±0.04mm	10	Ø3.2	120
411-155-11	135-155mm	±0.04mm	10	Ø3.4	190
411-175-11	155-175mm	±0.04mm	10	Ø3.4	190
411-195-11	175-195mm	±0.04mm	10	Ø3.4	190
411-215-11	195-215mm	±0.04mm	10	Ø3.4	190



Setting ring (optional)



THICKNESS



SERIES 420


DIGITAL EXTERNAL CALIPER GAUGE




- ◆ Measure the external dimension
- ◆ Resolution: 0.01mm/0.0005"



420-020-11



Code	Range	Accuracy	L
420-020-11	0-20mm/0-0.8"	±0.04mm	60
420-040-11	20-40mm/0.8-1.6"	±0.04mm	60
420-060-11	40-60mm/1.6-2.4"	±0.04mm	55
420-080-11	60-80mm/2.4-3.2"	±0.04mm	55
420-100-11	80-100mm/3.2-4"	±0.04mm	55




SERIES 421

EXTERNAL DIAL CALIPER GAUGE


- ◆ Measure the external dimension
- ◆ Graduation: 0.01mm



421-020-11



Code	Range	Accuracy	L
421-020-11	0-20mm	±0.04mm	60
421-040-11	20-40mm	±0.04mm	60
421-060-11	40-60mm	±0.04mm	55
421-080-11	60-80mm	±0.04mm	55
421-100-11	80-100mm	±0.04mm	55



SERIES 412

DIGITAL INTERNAL CALIPER GAUGE





- ◆ Resolution: 0.005mm/0.0002"
- ◆ Reading in digit and analog
- ◆ Display can be rotated by 170°
- ◆ Button function: tolerance Go and No-Go display, data preset, max./min. measurement, data holding, inch/metric conversion, absolute/incremental measurement
- ◆ Automatic power off



412-015-11

unit: mm



display can be rotated by 170°

Code	Range	Repeatability	Accuracy	L	H	W	R
412-015-11	5-15mm	0.01mm	±0.03mm	20	2	1.5	R0.3
412-025-11	5-25mm	0.01mm	±0.03mm	35	1.5	1.0	R0.3
412-030-11	10-30mm	0.01mm	±0.03mm	55	5.5	2.5	R0.5
412-040-11	20-40mm	0.01mm	±0.03mm	80	6.0	3.0	R0.5
412-050-11	30-50mm	0.01mm	±0.03mm	80	8.0	3.0	R0.5
412-060-11	40-60mm	0.01mm	±0.03mm	80	8.0	3.0	R0.5


SERIES 413

INTERNAL DIAL CALIPER GAUGE



413-025-11

unit: mm



Code	Range	Graduation	Accuracy	L	H	W	R
413-015-11	5-15mm	0.01mm	±0.03mm	20	2	1.5	R0.3
413-025-11	5-25mm	0.01mm	±0.03mm	35	1.5	1.0	R0.3
413-030-11	10-30mm	0.01mm	±0.03mm	55	5.5	2.5	R0.5
413-040-11	20-40mm	0.01mm	±0.03mm	80	6.0	3.0	R0.5
413-050-11	30-50mm	0.01mm	±0.03mm	80	8.0	3.0	R0.5
413-060-11	40-60mm	0.01mm	±0.03mm	80	8.0	3.0	R0.5

THICKNESS



SERIES 422


DIGITAL EXTERNAL CALIPER GAUGE



- ◆ Resolution: 0.005mm/0.0002"
- ◆ Reading in digit and analog
- ◆ Display can be rotated by 170°
- ◆ Button function: tolerance Go and No-Go display, data preset, max./min. measurement, data holding, inch/metric conversion, absolute/incremental measurement
- ◆ Automatic power off



422-020-11



Code	Range	Repeatability	Accuracy	L	H	W	R
422-020-11	0-20mm	0.01mm	±0.03mm	80	25	6.5	R0.5
422-030-11	10-30mm	0.01mm	±0.03mm	80	25	6.5	R0.5
422-040-11	20-40mm	0.01mm	±0.03mm	80	25	6.5	R0.5
422-050-11	30-50mm	0.01mm	±0.03mm	80	25	6.5	R0.5
422-060-11	40-60mm	0.01mm	±0.03mm	80	25	6.5	R0.5




SERIES 423

EXTERNAL DIAL CALIPER GAUGE



423-020-11





Code	Range	Graduation	Accuracy	L	H	W	R
423-020-11	0-20mm	0.01mm	±0.03mm	80	25	6.5	R0.5
423-030-11	10-30mm	0.01mm	±0.03mm	80	25	6.5	R0.5
423-040-11	20-40mm	0.01mm	±0.03mm	80	25	6.5	R0.5
423-050-11	30-50mm	0.01mm	±0.03mm	80	25	6.5	R0.5
423-060-11	40-60mm	0.01mm	±0.03mm	80	25	6.5	R0.5



428

EXTERNAL DIAL CALIPER GAUGE

- ◆ Measure the external dimension



Code	Range	Graduation	Accuracy
428-050-05	0-50mm	0.05mm	±0.1mm


SERIES 425

EXTERNAL DIAL CALIPER GAUGE


- ◆ Measure the external dimension



425-010-11



Code	Range	Graduation	Accuracy	L	H
425-010-11	0-10mm	0.01mm	±0.03mm	140	41
425-020-11	0-20mm	0.01mm	±0.03mm	192	92



THICKNESS



SERIES 419


DIGITAL INTERNAL CALIPER GAUGE



- ◆ For measuring the internal dimension
- ◆ Buttons: on/off, zero, data preset, mm/inch, data hold
- ◆ With fraction reading
- ◆ Automatic power off




419-008-11



unit: mm

Code	Range	Resolution	Accuracy	L	H
419-006-11	12.7-165mm/0.5-6.5"	0.1mm/0.01"/1/64"	0.2mm/0.01"	252	85
419-008-11	12.7-216mm/0.5-8.5"	0.1mm/0.01"/1/64"	0.3mm/0.02"	327	160



SERIES 429


DIGITAL EXTERNAL CALIPER GAUGE



- ◆ For measuring the thickness
- ◆ Buttons: on/off, zero, data preset, mm/inch, data hold
- ◆ With fraction reading
- ◆ Automatic power off




429-008-11



unit: mm

Code	Range	Resolution	Accuracy	L	H	W
429-006-11	0-150mm/0-6"	0.1mm/0.01"/1/64"	0.2mm/0.01"	273	105	75
429-008-11	0-200mm/0-8"	0.1mm/0.01"/1/64"	0.3mm/0.02"	328	160	106




457

DIGITAL THICKNESS GAUGE




- ◆ Buttons: on/off, zero, mm/inch, data hold
- ◆ Automatic power off



Code	Range	Resolution	Accuracy	Repeatability
457-001-01	0-25.4mm/0-1"	0.01mm, 0.001"	0.05mm	0.02mm

451

THICKNESS GAUGE



Code	Range	Graduation	Accuracy
451-010-11	0-10mm	0.05mm	±0.1mm


THICKNESS

SERIES 452

THICKNESS GAUGE



452-010-11




Code	Range	Graduation	Accuracy	L	L1
452-010-11	0-10mm	0.05mm	±0.1mm	35	85
452-010-12	0-10mm	0.05mm	±0.1mm	60	110

453

THICKNESS GAUGE WITH POINTED TIPS

- ◆ Pointed tips can be used for small grooves and recesses




Code	Range	Graduation	Accuracy
453-010-11	0-10mm	0.05mm	±0.1mm



dial indicator is
not included

431-025-11

- ◆ For quick Go/No-Go judgment of diameter of cylinders and shafts
- ◆ Anvil retracting stroke: 3mm
- ◆ Measuring force: 6-9N
- ◆ Carbide measuring faces
- ◆ Front edges of anvils are chamfered for easy workpiece insertion
- ◆ Optional indicators:
 - dial indicator, range 10mm, graduation 0.01mm
(code **222-010-11**)
 - digital indicator, range 12.7mm/0.5", resolution 0.001mm/0.0005"
(code **211-010-03**)
 - digital indicator, range 12.7mm/0.5", resolution 0.01mm/0.0005"
(code **211-010-13**)



Optional indicators (optional)

Code	Range	a	h
431-025-11	0-25mm	42	20
431-050-11	25-50mm	69	32.5
431-075-11	50-75mm	94	45
431-100-11	75-100mm	119	57.5
431-125-11	100-125mm	144	70
431-150-11	125-150mm	169	82.5
431-175-11	150-175mm	194	95
431-200-11	175-200mm	219	107
431-225-11	200-225mm	244	120
431-250-11	225-250mm	269	132
431-275-11	250-275mm	294	145
431-300-11	275-300mm	319	157



222-010-11

211-010-03

211-010-13



SERIES 442

HIGH PRECISION DIGITAL THICKNESS GAUGE






442-105-15



442-101-30



442-101-60



- ◆ Absolute encoder, the original data remains after power off
- ◆ With recharge cable (only 442-105-15 recharge and data output shared)
- ◆ Button: data output, on/off, zero, inch/mm conversion, measuring direction set, data preset absolute/incremental measurement, max./min./range measurement, tolerance set, hold
- ◆ Measuring force: 0.5-1N
- ◆ With analog reading
- ◆ Power: rechargeable battery, for 12 hours continuous working (full charge)

Cable (included)



Code	Range	Resolution	Accuracy	Repeatability	L
442-105-15	0-10mm/0-0.4"	0.0005mm/0.00002"	±0.0015mm	0.0005mm	-
442-101-15	0-10mm/0-0.4"	0.001mm/0.00005"	±0.002mm	0.001mm	-
442-101-30	0-10mm/0-0.4"	0.001mm/0.00005"	±0.002mm	0.001mm	-
442-101-60	0-10mm/0-0.4"	0.001mm/0.00005"	±0.003mm	0.001mm	60
442-101-00	0-10mm/0-0.4"	0.001mm/0.00005"	±0.004mm	0.001mm	100

SERIES 441

THICKNESS GAUGE



- ◆ Ceramic anvil
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)




441-010-11

Resolution 0.001mm/0.00005"

Code	Range	Accuracy
441-010-01	0-10mm/0-0.4"	±0.005mm

Resolution 0.01mm/0.0005"

Code	Range	Accuracy
441-010-11	0-10mm/0-0.4"	±0.02mm




441

THICKNESS GAUGE



- ◆ Ceramic spindle tip and anvil
- ◆ Buttons: on/off, zero, mm/inch, ABS
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)



Code	Range	Resolution	Accuracy
441-010-11B	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm



443


THICKNESS GAUGE



- ◆ Ceramic spindle tip and anvil



unit: mm





Code	Range	Graduation	Accuracy
443-001-01	0-1mm	0.001mm	±0.005mm

SERIES 443

THICKNESS GAUGE




- ◆ Graduation: 0.01mm



443-010-11

unit: mm




Code	Range	Accuracy	Anvil	d	h
443-010-11	0-10mm	±0.02mm	A	20	120
443-010-12	0-10mm	±0.02mm	B	20	120
443-030-11	0-30mm	±0.02mm	A	38	140

460

DIGITAL THICKNESS GAUGE



- ◆ Ceramic spindle tip and anvil
- ◆ Buttons: on/off, zero, mm/inch, ABS
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)




Code	Range	Resolution	Accuracy
460-010-11	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm

460

DIGITAL THICKNESS GAUGE



- ◆ Ceramic spindle tip and anvil
- ◆ Buttons: on/off, zero, mm/inch, ABS
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ With metal base



Code	Range	Resolution	Accuracy
460-010-11B	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm



THICKNESS

SERIES 444


THICKNESS GAUGE



- ◆ Large throat depth, for large workpiece measurement
- ◆ Graduation: 0.01mm



444-010-11





Code	Range	Accuracy	Anvil
444-010-11	0-10mm	±0.02mm	A
444-020-11	0-20mm	±0.03mm	A
444-010-12	0-10mm	±0.02mm	B
444-020-12	0-20mm	±0.03mm	B

SERIES 444


THICKNESS GAUGE



- ◆ Large throat depth, for large workpiece measurement
- ◆ Graduation: 0.01mm



444-010-11B





Code	Range	Accuracy	Anvil
444-010-11B	0-10mm	±0.02mm	A
444-020-11B	0-20mm	±0.03mm	A
444-010-12B	0-10mm	±0.02mm	B
444-020-12B	0-20mm	±0.03mm	B

448

THICKNESS GAUGE



- ◆ Measure the wall thickness of tube





Code	Range	Accuracy	Graduation
448-010-11	0-10mm	±0.02mm	0.01mm

461

DIGITAL TUBE THICKNESS GAUGE



- ◆ Buttons: on/off, zero, mm/inch, ABS
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)



Code	Range	Resolution	Accuracy
461-010-11	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm

Accud






THICKNESS

462

DIGITAL TUBE THICKNESS GAUGE



- Buttons: on/off, zero, mm/inch, ABS
- Automatic power off
- Data output(cable code:200-03 or 200-04)





unit: mm

Code	Range	Resolution	Accuracy
462-010-11	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm

464

POINT THICKNESS GAUGE

- Pointed tips can be used for small grooves and recesses



unit: mm



Code	Range	Accuracy	Graduation
464-010-11	0-10mm	±0.02mm	0.01mm

463

DIGITAL TUBE THICKNESS GAUGE



- ◆ Buttons: on/off, zero, mm/inch, ABS
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)




Code	Range	Resolution	Accuracy
463-010-11	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm

449

THICKNESS GAUGE

- ◆ Graduation: 0.01mm
- ◆ Ceramic anvil, diameter: Ø10mm



Code	Range	Accuracy
449-010-11	0-10mm	±0.02mm




445

THICKNESS GAUGE WITH ROLLING WHEEL



- ◆ For continuous measurement



Code	Range	Graduation	Accuracy
445-010-11	0-10mm	0.01mm	±0.02mm

SERIES 465

DIGITAL THICKNESS GAUGE WITH CONSTANT MEASURING FORCE




- ◆ Buttons: on/off, zero, unit (mm/in/fraction)
- ◆ Automatic power off
- ◆ With 50g standard weight block

Aluminum alloy stage




465-010-01



Code	Range	Resolution	Accuracy
465-010-01	0-12.7mm/0.5"	0.001mm/0.00005"	±0.005mm
465-010-11	0-12.7mm/0.5"	0.01mm/0.0005"	±0.02mm

446

THICKNESS GAUGE




Code	Range	Graduation	Accuracy
446-010-11	0-10mm	0.1mm	±0.05mm

447

THICKNESS GAUGE

- ◆ Stainless steel spindle tip and anvil



Code	Range	Graduation	Accuracy
447-010-11	0-10mm	0.01mm	±0.02mm

450


PET BOTTLE WALL THICKNESS GAUGE

- Optional accessories: digital indicator (code: 212-010-13)

Digital indicator is not included



Application




Code	Measuring thickness	Accuracy
450-010-11	12.7mm	±0.02mm

433

DIGITAL SNAP GAUGE



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power on/off
- Data output
- Made of stainless steel




Code	Range	Accuracy
433-002-11	0-50mm/0-2"	±0.03mm

432

DIGITAL SNAP GAUGE

LR44
+

- Buttons: on/off, zero, mm/inch




Code	Range	Resolution	Accuracy
432-012-11	0-12.7mm/0-0.5"	0.01mm/0.0005"	±0.03mm

434

DIGITAL SNAP GAUGE

LR44
+

- Buttons: on/off, zero, mm/inch
- Automatic power on/off




Code	Range	Resolution	Accuracy
434-001-11	0-25mm/0-1"	0.01mm/0.0005"	±0.03mm

435

DIGITAL SNAP GAUGE



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/in, INC
- Automatic power on/off
- Data output(cable code: 100-03 or 100-04)
- Made of stainless steel



Code	Range	Accuracy
435-001-11	0-25mm/0-1"	±0.03mm

Accud





THICKNESS

436

DIGITAL 3-PURPOSE SNAP GAUGE



- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Made of stainless steel




unit: mm

Code	Range	Accuracy
436-001-11	0-25mm/0-1"	±0.03mm


SERIES 298

CRANKSHAFT TESTER


- ◆ To test crankshaft deflection
- ◆ The balance block is mounted on the back of dial indicator to keep the dial indicator facing up




298-012-11




dial indicator



balance block



anvils



extension rods

Code	Range	Dial indicator range	Graduation	Accuracy	Extension rods
298-012-11	60-300mm	3mm	0.01mm	±0.016mm	16mm, 32mm, 64mm, 128mm
298-020-11	60-500mm	3mm	0.01mm	±0.016mm	16mm, 32mm, 64mm, 96mm, 128mm, 192mm

- ◆ Made of ceramic
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

511-□□□-□X
 → 0: grade 0
 → 1: grade 1

Example:


Code	Quantity	Grade
511-112-00	112	0
511-112-01	112	1



511-087-00

Size:

Size (L)	W	H
0.5mm ≤ L ≤ 10mm	9mm	30mm
L > 10mm	9mm	35mm



Code	Blocks per set	Block allocation		
		Size(mm)	Step(mm)	Quantity
511-122-0X	122	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		1.6-1.9	0.1	4
		0.5-24.5	0.5	49
		30-100	10	8
		25-75		2
511-112-0X	112	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-24.5	0.5	49
		25-100	25	4
511-103-0X	103	1.005		1
		1.01-1.49	0.01	49
		0.5-24.5	0.5	49
		25-100	25	4
511-088-0X	88	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-9.5	0.5	19
		10-100	10	10
511-087-0X	87	1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-9.5	0.5	19
		10-100	10	10
511-076-0X	76	1.005		1
		1.01-1.49	0.01	49
		0.5-9.5	0.5	19
		10-40	10	4
		50-100	25	3

Code	Blocks per set	Block allocation		
		Size(mm)	Step(mm)	Quantity
511-056-0X	56	0.5		1
		1.001-1.009	0.001	9
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-24	1	24
511-047-0X	47	25-100	25	4
		1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-24	1	24
511-047-1X	47	25-100	25	4
		1.005		1
		1.01-1.19	0.01	19
		1.2-1.9	0.1	8
		1-9	1	9
511-046-0X	46	10-100	10	10
		1.001-1.009	0.001	9
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-9	1	9
511-034-0X	34	10-100	10	10
		1.0005		1
		1.001-1.009	0.001	9
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
511-032-0X	32	1-5	1	5
		10		1
		1.005		1
		1.01-1.09		9
		1.1-1.9	0.01	9
		1-9	0.1	9
		10-30	1	3
		60	10	1

SERIES 512

CARBIDE GAUGE BLOCK SET



- ◆ Made of carbide
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

512-□□□-□XT


→0: grade0
→1: grade1

Example:

Code	Grade	Quantity
512-112-00T	0	112
512-112-01T	1	112

Size:

Size (L)	W	H
0.5mm≤L≤10mm	9mm	30mm
L>10mm	9mm	35mm



512-087-01T

Plastic box



Code	Blocks per set	Block allocation		
		Size(mm)	Step(mm)	Quantity
512-122-0XT	122	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		1.6-1.9	0.1	4
		0.5-24.5	0.5	49
		30-100	10	8
512-112-0XT	112	25-75	50	2
		1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-24.5	0.5	49
		25-100	25	4
512-103-0XT	103	1.005		1
		1.01-1.49	0.01	49
		0.5-24.5	0.5	49
		25-100	25	4
512-087-0XT	87	1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-9.5	0.5	19
		10-100	10	10
512-083-0XT	83	0.5		1
		1		1
		1.005		1
		1.01-1.49	0.01	49
		1.5-1.9	0.1	5
		2-9.5	0.5	16
		10-100	10	10
		1.005		1
512-076-0XT	76	1.01-1.49	0.01	49
		0.5-9.5	0.5	19
		10-40	10	4
		50-100	25	3
		1.005		1

Code	Blocks per set	Block allocation		
		Size(mm)	Step(mm)	Quantity
512-047-0XT	47	1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-24	1	24
		25-100	25	4
512-047-1XT	47	1.005		1
		1.01-1.19	0.01	19
		1.2-1.9	0.1	8
		1-9	1	9
512-046-0XT	46	10-100	10	10
		1.001-1.009	0.001	9
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
512-034-0XT	34	1-9	1	9
		1.005		1
		1.001-1.009	0.001	9
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-5	1	5
512-032-0XT	32	10		1
		1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-9	1	9
		10-30	10	3
		50		1



- ◆ Made of steel
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

512-□□□-□X

- 0: grade0
- 1: grade1
- 2: grade2


Example:

Code	Grade	Quantity
512-112-00	0	112
512-112-01	1	112
512-112-02	2	112

Plastic box



512-087-02



Size:

Size (L)	W	H
0.5mm≤L≤10mm	9mm	30mm
L>10mm	9mm	35mm

Code	Blocks per set	Block allocation		
		Size(mm)	Step (mm)	Quantity
512-122-0X	122	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		1.6-1.9	0.1	4
		0.5-24.5	0.5	49
		30-100	10	8
		25-75	50	2
512-112-0X	112	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-24.5	0.5	49
512-103-0X	103	1.0005		1
		1.01-1.49	0.01	49
		0.5-24.5	0.5	49
		25-100	25	4
512-088-0X	88	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-9.5	0.5	19
512-087-0X	87	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.49	0.01	49
		0.5-9.5	0.5	19

Code	Blocks per set	Block allocation		
		Size(mm)	Step (mm)	Quantity
512-083-0X	83	0.5		1
		1		1
		1.005		1
		1.01-1.49	0.01	49
		1.5-1.9	0.1	5
		2-9.5	0.5	16
		10-100	10	10
512-076-0X	76	1.005		1
		1.01-1.49	0.01	49
		0.5-9.5	0.5	19
		10-40	10	4
512-056-0X	56	1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-24	1	24
512-047-0X	47	1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-24	1	24
512-047-1X	47	1.005		1
		1.01-1.19	0.01	19
		1.2-1.9	0.1	8
		1-9	1	9

Code	Blocks per set	Block allocation		
		Size(mm)	Step (mm)	Quantity
512-046-0X	46	1.001-1.009	0.001	9
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-9	1	9
		10-100	10	10
512-038-0X	38	1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-9	1	9
		10-100	10	10
512-034-0X	34	1.0005		1
		1.001-1.009	0.001	9
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-5	1	5
512-032-0X	32	10		1
		1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
		1-9	1	9
512-032-1X	32	10-30	10	3
		50		1
		1.005		1
		1.01-1.09	0.01	9
		1.1-1.9	0.1	9
512-008-0X	8	1-9	1	9
		10-30	10	3
		60		1
		125-175	25	3

SERIES 512

STEEL GAUGE BLOCK SET



- ◆ Made of alloy steel
- ◆ Meet ASME B89.1.9
- ◆ With manufacturer inspection certificate
- ◆ Code explanation


512-□□□-□XI

- 0: grade 0
- 1: grade 1
- 2: grade 2

Plastic box



512-081-00I



Size:

Size(L)	W	H
0.02≤L≤0.394"	0.354"	1.181"
L > 0.394"	0.354"	1.378"

Example:

Code	Quantity	Grade
512-036-00I	36	0
512-036-01I	36	1
512-036-02I	36	2

Code	Blocks per set	Block allocation		
		Size(inch)	Step(inch)	Quantity
512-008-0XI	8	5-8	1	4
		10-12	2	2
		16		1
		20		1
512-081-0XI	81	0.1001-0.1009	0.0001	9
		0.101-0.149	0.001	49
		0.05-0.95	0.05	19
		1-4	1	4

Code	Blocks per set	Block allocation		
		Size(inch)	Step(inch)	Quantity
512-036-0XI	36	0.05		1
		0.1001-0.1009	0.0001	9
		0.101-0.109	0.001	9
		0.11-0.19	0.01	9
		0.1-0.5	0.1	5
		1		1
		2		1
		4		1

SERIES 515


CERAMIC INDIVIDUAL GAUGE BLOCK (<10MM)




- ◆ Made of ceramic
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

515-□□□-□X

- 0: grade 0
 - 1: grade 1
- decimal ← integer



515-700-70



Size:

Size(L)	W	H
0.5mm≤L≤10mm	9mm	30mm
L>10mm	9mm	35mm

Supplied below size, unit:mm

0.5	1.01	1.13	1.25	1.37	1.49	5
1	1.02	1.14	1.26	1.38	1.5	5.1
1.0005	1.03	1.15	1.27	1.39	1.6	5.5
1.001	1.04	1.16	1.28	1.4	1.7	6
1.002	1.05	1.17	1.29	1.41	1.8	6.5
1.003	1.06	1.18	1.3	1.42	1.9	7
1.004	1.07	1.19	1.31	1.43	2	7.5
1.005	1.08	1.2	1.32	1.44	2.5	7.7
1.006	1.09	1.21	1.33	1.45	3	8
1.007	1.1	1.22	1.34	1.46	3.5	8.5
1.008	1.11	1.23	1.35	1.47	4	9
1.009	1.12	1.24	1.36	1.48	4.5	9.5

Example:

Code	Grade	Size(mm)
515-500-00	0	0.5
515-500-01	1	0.5
515-000-10	0	1
515-0005-11	1	1.0005
515-400-11	1	1.4
515-480-11	1	1.48

SERIES 516

CERAMIC INDIVIDUAL GAUGE BLOCK (≥10MM)




- ◆ Made of ceramic
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

516-□□□-□X
 →0: grade0
 →1: grade1



516-800-01



Example:

Code	Grade	Size(mm)
516-200-00	0	20
516-200-01	1	20

Size:

Size(L)	W	H
0.5mm≤L≤10mm	9mm	30mm
L>10mm	9mm	35mm

Code	Size(mm)
516-100-0X	10
516-103-0X	10.3
516-105-0X	10.5
516-110-0X	11
516-115-0X	11.5
516-120-0X	12
516-125-0X	12.5
516-129-0X	12.9
516-130-0X	13
516-135-0X	13.5

Code	Size(mm)
516-140-0X	14
516-145-0X	14.5
516-150-0X	15
516-155-0X	15.5
516-160-0X	16
516-165-0X	16.5
516-170-0X	17
516-175-0X	17.5
516-176-0X	17.6
516-180-0X	18

Code	Size(mm)
516-185-0X	18.5
516-190-0X	19
516-195-0X	19.5
516-200-0X	20
516-202-0X	20.2
516-205-0X	20.5
516-210-0X	21
516-215-0X	21.5
516-220-0X	22
516-225-0X	22.5

Code	Size(mm)
516-228-0X	22.8
516-230-0X	23
516-235-0X	23.5
516-240-0X	24
516-245-0X	24.5
516-250-0X	25
516-300-0X	30
516-400-0X	40
516-413-0X	41.3
516-500-0X	50

Code	Size(mm)
516-600-0X	60
516-700-0X	70
516-750-0X	75
516-800-0X	80
516-900-0X	90
516-004-1X	100
516-005-1X	125
516-006-1X	150

SERIES 513

STEEL INDIVIDUAL GAUGE BLOCK(<10MM)

CUSTOM-MADE

other sizes are available upon request




- ◆ Made of steel
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

513-□□□-□X
 decimal ← integer
 →0: grade0
 →1: grade1
 →2: grade2



513-700-70



Size:

Size (L)	W	H
0.5mm≤L≤10mm	9mm	30mm
L>10mm	9mm	35mm

Supplied below size, unit:mm

0.5	0.69	0.88	0.998	1.07	1.26	1.45	2.008	2.19	2.38	4
0.51	0.7	0.89	0.999	1.08	1.27	1.46	2.009	2.2	2.39	4.5
0.52	0.71	0.9	1	1.09	1.28	1.47	2.01	2.21	2.4	5
0.53	0.72	0.91	1.0005	1.1	1.29	1.48	2.02	2.22	2.41	5.1
0.54	0.73	0.92	1.001	1.11	1.3	1.49	2.03	2.23	2.42	5.5
0.55	0.74	0.93	1.002	1.12	1.31	1.5	2.04	2.24	2.43	6
0.56	0.75	0.94	1.003	1.13	1.32	1.6	2.05	2.25	2.44	6.5
0.57	0.76	0.95	1.004	1.14	1.33	1.7	2.06	2.26	2.45	7
0.58	0.77	0.96	1.005	1.15	1.34	1.8	2.07	2.27	2.46	7.5
0.59	0.78	0.97	1.006	1.16	1.35	1.9	2.08	2.28	2.47	7.7
0.6	0.79	0.98	1.007	1.17	1.36	2	2.09	2.29	2.48	8
0.61	0.8	0.99	1.008	1.18	1.37	2.0005	2.1	2.3	2.49	8.5
0.62	0.81	0.991	1.009	1.19	1.38	2.001	2.11	2.31	2.5	9
0.63	0.82	0.992	1.01	1.2	1.39	2.002	2.12	2.32	2.6	9.5
0.64	0.83	0.993	1.02	1.21	1.4	2.003	2.13	2.33	2.7	
0.65	0.84	0.994	1.03	1.22	1.41	2.004	2.14	2.34	2.8	
0.66	0.85	0.995	1.04	1.23	1.42	2.005	2.15	2.35	2.9	
0.67	0.86	0.996	1.05	1.24	1.43	2.006	2.16	2.36	3	
0.68	0.87	0.997	1.06	1.25	1.44	2.007	2.17	2.37	3.5	

SERIES 514

STEEL INDIVIDUAL GAUGE BLOCK (≥10MM)


- ◆ Made of steel
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

514-□□□-□X
 → 0: grade0
 → 1: grade1
 → 2: grade2



514-004-1X

CUSTOM-MADE
 other sizes are available
 upon request



Size: With hole (size ≥125mm)


Size (L)	W	H
0.5mm ≤ L ≤ 10mm	9mm	30mm
L > 10mm	9mm	35mm

Code	Size(mm)
514-100-0X	10
514-103-0X	10.3
514-105-0X	10.5
514-110-0X	11
514-115-0X	11.5
514-120-0X	12
514-125-0X	12.5
514-129-0X	12.9
514-130-0X	13
514-135-0X	13.5
514-140-0X	14
514-145-0X	14.5
514-150-0X	15

Code	Size(mm)
514-155-0X	15.5
514-160-0X	16
514-165-0X	16.5
514-170-0X	17
514-175-0X	17.5
514-176-0X	17.6
514-180-0X	18
514-185-0X	18.5
514-190-0X	19
514-195-0X	19.5
514-200-0X	20
514-202-0X	20.2
514-205-0X	20.5

Code	Size(mm)
514-210-0X	21
514-215-0X	21.5
514-220-0X	22
514-225-0X	22.5
514-228-0X	22.8
514-230-0X	23
514-235-0X	23.5
514-240-0X	24
514-245-0X	24.5
514-250-0X	25
514-300-0X	30
514-350-0X	35
514-400-0X	40

Code	Size(mm)
514-413-0X	41.3
514-450-0X	45
514-500-0X	50
514-600-0X	60
514-700-0X	70
514-750-0X	75
514-800-0X	80
514-900-0X	90
514-004-1X	100
514-005-1X	125
514-006-1X	150
514-007-1X	175
514-008-1X	200



Code	Size(mm)
514-010-1X	250
514-012-1X	300
514-016-1X	400
514-020-1X	500
514-024-1X	600
514-028-1X	700
514-030-1X	750
514-032-1X	800
514-036-1X	900
514-040-1X	1000

SERIES 514


INDIVIDUAL STEEL GAUGE BLOCKS

- ◆ Made of alloy steel
- ◆ Meet ASME B89.1.9
- ◆ With manufacturer inspection certificate
- ◆ Code explanation

514-□□□-□XI
 → 0: grade0
 → 1: grade1
 → 2: grade2



514-000-4XI



With hole (size ≥5")

Size:


Size (L)	W	H
.02" ≤ L ≤ .394"	.354"	1.181"
L > .394"	.354"	1.378"

Example:

Code	Grade	Size (L)
514-000-10I	0	1"
514-000-11I	1	1"
514-000-12I	2	1"

Code	Size(L)
514-000-1XI	1"
514-000-2XI	2"
514-000-3XI	3"
514-000-4XI	4"
514-000-5XI	5"
514-000-6XI	6"

Code	Size(L)
514-000-7XI	7"
514-000-8XI	8"
514-010-0XI	10"
514-012-0XI	12"
514-016-0XI	16"
514-020-0XI	20"



SERIES 517**GAUGE BLOCK SET FOR CALIPER INSPECTION**

- ◆ For checking calipers accuracy
- ◆ With ring gauges
- ◆ Meet ISO 3650
- ◆ Gauge blocks are made of alloy steel
- ◆ With manufacturer inspection certificate



517-005-01

Code	Gauge block allocation	Quantity	Grade	Ring gauge
517-005-01	30, 41.3, 131.4mm	5pcs	1	Ø4, Ø25mm
517-006-01	30, 41.3, 131.4, 243.5mm	6pcs	1	Ø4, Ø25mm

SERIES 517**GAUGE BLOCK SET FOR CALIPER INSPECTION**

- ◆ For checking calipers accuracy
- ◆ Meet ISO 3650
- ◆ Gauge blocks are made of alloy steel
- ◆ With manufacturer inspection certificate



517-012-01

Code	Gauge block allocation	Quantity	Grade
517-012-01	10, 20, 20, 41.2, 51.2, 81.5, 101.2, 121.5, 121.8, 191.8, 201.5, 291.8mm	12pcs	0
517-012-02	10, 20, 20, 41.2, 51.2, 81.5, 101.2, 121.5, 121.8, 191.8, 201.5, 291.8mm	12pcs	1
517-012-03	10, 20, 20, 41.2, 51.2, 81.5, 101.2, 121.5, 121.8, 191.8, 201.5, 291.8mm	12pcs	2

SERIES 518

GAUGE BLOCK SET FOR MICROMETER
INSPECTION

- ◆ For checking micrometers accuracy
- ◆ With optical parallel
- ◆ Grade 0
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate

Measure



518-001-03

Code	Quantity	For micrometers	Material	Block allocation
518-001-02	11pcs	0-25mm	ceramic	2.5, 5.1, 7.7, 10.3, 12.9, 15, 17.6, 20.2, 22.8, 25mm
518-001-03	11pcs	0-25mm	alloy steel	2.5, 5.1, 7.7, 10.3, 12.9, 15, 17.6, 20.2, 22.8, 25mm

SERIES 518

GAUGE BLOCK SET FOR MICROMETER
INSPECTION

- ◆ For checking micrometers accuracy
- ◆ Grade 0
- ◆ Meet ISO 3650
- ◆ With manufacturer inspection certificate



518-001-01

Code	Quantity	For micrometers	Material	Block allocation
518-001-01	10pcs	0-25mm	alloy steel	2.5, 5.1, 7.7, 10.3, 12.9, 15, 17.6, 20.2, 22.8, 25mm
518-002-01	11pcs	25-50mm	alloy steel	25, 27.5, 30.1, 32.7, 35.3, 37.9, 40, 42.6, 45.2, 47.8, 50mm
518-003-01	11pcs	50-75mm	alloy steel	50, 52.5, 55.1, 57.7, 60.3, 62.9, 65, 67.6, 70.2, 72.8, 75mm
518-004-01	11pcs	75-100mm	alloy steel	75, 77.5, 80.1, 82.7, 85.3, 87.9, 90, 92.6, 95.2, 97.8, 100mm

518

GAUGE BLOCK SET FOR MICROMETER INSPECTION



- ◆ Meet ISO3650
- ◆ Grade 0
- ◆ With manufacturer inspection certificate



AECUD



Code	Quantity	Applicable micrometer	Material	Gauge blocks included in set
518-104-01	20pcs	0-100mm	alloy steel	5.12mm, 10.24mm, 15.36mm, 21.5mm, 25mm, 30.12mm, 35.24mm, 40.36mm, 46.5mm, 50mm, 55.12mm, 60.24mm, 65.36mm, 71.5mm, 75mm, 80.12mm, 85.24mm, 90.36mm, 96.5mm, 100mm

508

GAUGE BLOCK SET FOR MICROMETER INSPECTION

- ◆ Use to check the accuracy of micrometer with series 518 gauge block set



Application



GAUGE

Code	Applicable micrometer
508-001-00	0-25mm

519

GAUGE BLOCK ACCESSORIES

- ◆ To expand gage block applications



Code	Total quantity	Accessory allocation
519-016-01	17pcs	3pcs holder (50mm, 100mm, 200mm) 6pcs half round jaw (2mm, 5mm, 10mm, 2pcs each) 1pc holder base, 2pcs 100mm plain jaws, 1pc scriber point, 1pc center point, 2pcs triangular straight edge jaw 60mm 1pc 100mm straight edge


519

GAUGE BLOCK ACCESSORIES




Code	Remark	Accessory allocation
519-016-01H	16pcs	4pcs holder(0-50mm, 50-100mm, 100-200mm, 200-300mm); 1pc base; 1pair plain jaw; 1pc parallel jaw; 3pairs half round jaw(2.5mm, 5mm, 6mm); 1pc scriber; 1pc center point

Code	Name	Clamping range (L)
520-002-11	holder	0-50mm
520-004-11	holder	50-100mm
520-008-11	holder	100-200mm
520-012-11	holder	200-300mm
520-016-11	holder	300-400mm
520-020-11	holder	400-500mm




Code	Name
520-100-11	base



Code	Name	Size	Material
520-200-11	half round jaw	2mm	carbide
520-201-11	half round jaw	5mm	carbide
520-202-11	half round jaw	10mm	carbide




supplied a pair




Code	Name	Material
520-300-11	plain jaw	carbide




supplied a pair



Code	Name	Material
520-400-11	scriber	carbide



Code	Name	Tip Material
520-500-11	center point	carbide



Application




<p>(plain jaw+holder) set zero</p>	<p>(half round jaw+holder) set a standard inside length L</p>	<p>(half round jaw+holder) measure inside diameter</p>
	<p>(base+holder+scriber) measure height or scribe</p>	<p>(scriber+centre point+holder) scribe circle</p>

510


GAUGE BLOCK HOLDER

- ◆ For gauge blocks over 100mm with clamping holes
- ◆ Optional accessory: gauge block holder accessory, gauge block accessory

Application



510-000-01




Code

510-000-01



50mm gage block



510-000-02

Code

510-000-02

Code	Include
510-302-01	510-000-01 (3 set) 510-000-02 (1pairs)


SERIES 561

CHECK MASTER

- ◆ For checking the accuracy of measuring tools like calipers, height gage and so on
- ◆ Can be used in vertical and horizontal orientation
- ◆ With manufacturer inspection certificate



561-024-01








Code	Range	Parallelism of blocks	Accuracy	W	H	L1	L
561-012-01	300mm	1.2µm	±2.5µm	35	32	310	350
561-018-01	450mm	1.5µm	±3.5µm	42	50	470	510
561-024-01	600mm	1.5µm	±3.5µm	42	50	610	650

- ◆ To check calipers and height gages
- ◆ Constructed with steel gage blocks
- ◆ With manufacturer inspection certificate



vertical use


560-024-01

560-024-01

560-040-01


Check upper jaws of calipers



Check lower jaws of calipers



Check height gage



Code	Size	Range of inside measurement	Range of outside measurement	Range of height measurement	Accuracy
560-012-01	0-300mm	20, 50, 100, 150, 200, 250, 300, 330mm	20, 50, 100, 150, 200, 250, 300, 330, 360mm	20, 50, 100, 150, 200, 250, 300, 330, 360mm	±3μm
560-024-01	0-600mm	20, 50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 630mm	20, 50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 630, 660mm	20, 50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 630, 660mm	±5μm
560-040-01	0-1000mm	20, 50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 650, 700, 750, 800, 850, 900, 950, 1000, 1030mm	20, 50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 650, 700, 750, 800, 850, 900, 950, 1000, 1030, 1060mm	20, 50, 100, 150, 200, 250, 300, 350, 400, 450, 500, 550, 600, 650, 700, 750, 800, 850, 900, 950, 1000, 1030, 1060mm	±7μm

SERIES 570

ANGLE GAUGE BLOCK SET



- ◆ Accuracy: $\pm 2''$
- ◆ To inspect protractor, taper gage, index plate, index head and goniometer. can also be used to set angle
- ◆ Made of special alloy steel, hardness HRC64, high stability, wear resistance and easy combination
- ◆ Can be combined to any angle with interval 6 seconds after combination (6", 12", 18", ..., 360)
- ◆ With manufacturer inspection certificate




570-015-01

Code	Angle	Total quantity
570-013-01	1°, 3°, 9°, 27°, 41°, 1', 3', 9', 27', 6", 18", 30", 90°/90°/90°/90°	13pcs
570-015-01	1°, 3°, 5°, 15°, 30°, 45°, 1', 3', 5', 20', 30', 6", 12", 30", 90°/90°/90°/90°	15pcs

571

ANGLE GAUGE BLOCK SET



571-007-01

- ◆ For angle comparison
- ◆ One angle can be as used in triangle blocks
four angles can be as used in rectangle blocks
- ◆ With manufacturer inspection certificate

Code	Angle	Blocks per set	Accuracy	Sharp
571-007-01	15°10', 30°20', 45°30', 50°, 60°40', 75°50', 90°	7	$\pm 10''$	triangle/rectangle

SERIES 522

INDIVIDUAL PIN GAUGE

- ♦ Accuracy:
 - $\pm 1\mu\text{m}$ (range: 0.1-13mm)
 - $\pm 2\mu\text{m}$ (range: 13-40mm)
- ♦ Made of alloy steel
- ♦ Hardness HRC62-65
- ♦ Code explanation:

522-□□□□-2
 |
 diameter


CUSTOM-MADE

Standard size above 40mm are available upon request



522-06933-2

unit: mm



Package



Example:

Code	Size(mm)	Accuracy
522-00125-2	0.125	$\pm 1\mu\text{m}$
522-09125-2	9.125	$\pm 1\mu\text{m}$
522-19125-2	19.125	$\pm 2\mu\text{m}$

522

INDIVIDUAL CARBIDE PIN GAUGE

- ♦ Supplied diameter from 0.3 to 30mm,
- ♦ Accuracy:
 - $\pm 1\mu\text{m}$ (range: 0.3-13mm)
 - $\pm 2\mu\text{m}$ (range: 13-30mm)
- ♦ Carbide material
- ♦ Hardness HRA90-90.5
- ♦ Length 50mm
- ♦ Code explanation:

522-□□□□-2T
 |
 diameter


CUSTOM-MADE

Size between 13 to 30mm, are available upon request



522-06000-2T

unit: mm



Package



Example:

Code	Size(mm)	Accuracy
522-10000-2T	10	$\pm 1\mu\text{m}$

SERIES 528

INDIVIDUAL CERAMIC PIN GAUGE


- ◆ Meet DIN2269, grade 1
- ◆ Diameter range: 01.000-10.000mm
- ◆ Diameter accuracy: $\pm 1\mu\text{m}$
- ◆ Made of ceramic, extremely wear resistance, corrosion resistance and dimensional stability
- ◆ Code explanation:

528-□□□□-1
 |
 diameter



528-10000-1

unit: mm



Example:

Code	Size(mm)
528-05000-1	5
528-10000-1	10

SERIES 521


PIN GAUGE HANDLE

- ◆ Supplied with wrench for installing pin gauges
- ◆ Clamping bushes are made of brass



handle

Before assemble



After assemble



Code	Applicable pin gauge diameter
521-001-11	0.2-1.0mm
521-002-11	1.0-2.0mm
521-003-11	2.0-3.0mm
521-004-11	3.0-4.0mm
521-005-11	4.0-5.0mm
521-006-11	5.0-6.0mm

Code	Applicable pin gauge diameter
521-007-11	6.0-7.0mm
521-008-11	7.0-8.0mm
521-009-11	8.0-9.0mm
521-010-11	9.0-10.0mm
521-011-11	10.0-11.0mm
521-012-11	11.0-12.0mm

Code	Applicable pin gauge diameter
521-013-11	12.0-13.0mm
521-014-11	13.0-14.0mm
521-015-11	14.0-15.0mm
521-016-11	15.0-16.0mm
521-017-11	16.0-17.0mm
521-018-11	17.0-18.0mm

Code	Applicable pin gauge diameter
521-019-11	18.0-19.0mm
521-020-11	19.0-20.0mm
521-021-11	20.0-21.0mm
521-022-11	21.0-22.0mm


523-650-51

523-300-101
Blow mould case

Code	Diameter(mm)	Step	Quantity
523-100-091	0.1-1.00	0.01mm	91
523-200-101	1.00-2.00	0.01mm	101
523-300-101	2.00-3.00	0.01mm	101
523-400-101	3.00-4.00	0.01mm	101
523-500-101	4.00-5.00	0.01mm	101
523-600-101	5.00-6.00	0.01mm	101
523-700-101	6.00-7.00	0.01mm	101
523-800-101	7.00-8.00	0.01mm	101
523-900-101	8.00-9.00	0.01mm	101
523-1000-101	9.00-10.00	0.01mm	101

Aluminum box

Code	Diameter(mm)	Step	Quantity
523-010-41	0.10-0.50	0.01mm	41
523-020-31	0.20-0.50	0.01mm	31
523-050-51	0.50-1.00	0.01mm	51
523-100-51	1.00-1.50	0.01mm	51
523-150-51	1.50-2.00	0.01mm	51
523-200-51	2.00-2.50	0.01mm	51
523-250-51	2.50-3.00	0.01mm	51
523-300-51	3.00-3.50	0.01mm	51
523-350-51	3.50-4.00	0.01mm	51
523-400-51	4.00-4.50	0.01mm	51
523-450-51	4.50-5.00	0.01mm	51
523-500-51	5.00-5.50	0.01mm	51
523-550-51	5.50-6.00	0.01mm	51
523-600-51	6.00-6.50	0.01mm	51
523-650-51	6.50-7.00	0.01mm	51
523-700-51	7.00-7.50	0.01mm	51
523-750-51	7.50-8.00	0.01mm	51
523-800-51	8.00-8.50	0.01mm	51
523-850-51	8.50-9.00	0.01mm	51
523-900-51	9.00-9.50	0.01mm	51
523-950-51	9.50-10.00	0.01mm	51

- ◆ Made of alloy steel
- ◆ Hardness HRC62-65
- ◆ Accuracy:
 - ±1μm (range:0.1-13mm)
 - ±2μm (range:13-40mm)

Code	Diameter(mm)	Step	Quantity
523-0110-100	0.1-10.00	0.1mm	100
523-500-41	1.0-5.0	0.1mm	41
523-500-51	5.0-10.0	0.1mm	51
523-1000-01	10.0-15.0	0.1mm	51
523-1500-01	15.0-20.0	0.1mm	51

Aluminum box

Code	Diameter(mm)	Step	Quantity
523-1000-51	10.00-10.50	0.01mm	51
523-1050-51	10.50-11.00	0.01mm	51
523-1100-51	11.00-11.50	0.01mm	51
523-1150-51	11.50-12.00	0.01mm	51
523-1200-51	12.00-12.50	0.01mm	51
523-1250-51	12.50-13.00	0.01mm	51
523-1300-51	13.00-13.50	0.01mm	51
523-1350-51	13.50-14.00	0.01mm	51
523-1400-51	14.00-14.50	0.01mm	51
523-1450-51	14.50-15.00	0.01mm	51
523-1500-51	15.00-15.50	0.01mm	51
523-1550-51	15.50-16.00	0.01mm	51
523-1600-51	16.00-16.50	0.01mm	51
523-1650-51	16.50-17.00	0.01mm	51
523-1700-51	17.00-17.50	0.01mm	51
523-1750-51	17.50-18.00	0.01mm	51
523-1800-51	18.00-18.50	0.01mm	51
523-1850-51	18.50-19.00	0.01mm	51
523-1900-51	19.00-19.50	0.01mm	51
523-1950-51	19.50-20.00	0.01mm	51

SERIES 523

CARBIDE PIN GAUGE SET

- ◆ Meet DIN2269, grade 1
- ◆ Made of carbide
- ◆ Hardness HRA90-90.5
- ◆ Diameter accuracy: $\pm 1\mu\text{m}$



523-1000-51T



523-300-101T

Aluminum box

Code	Diameter(mm)	Step	Quantity
523-1000-51T	10.00-10.50	0.01mm	51
523-1050-51T	10.50-11.00	0.01mm	51
523-1100-51T	11.00-11.50	0.01mm	51
523-1150-51T	11.50-12.00	0.01mm	51
523-1200-51T	12.00-12.50	0.01mm	51
523-1250-51T	12.50-13.00	0.01mm	51
523-1300-51T	13.00-13.50	0.01mm	51
523-1350-51T	13.50-14.00	0.01mm	51
523-1400-51T	14.00-14.50	0.01mm	51
523-1450-51T	14.50-15.00	0.01mm	51

Blow mould case

Code	Diameter(mm)	Step	Quantity
523-100-091T	0.10-1.00	0.01mm	91
523-200-101T	1.00-2.00	0.01mm	101
523-300-101T	2.00-3.00	0.01mm	101
523-400-101T	3.00-4.00	0.01mm	101
523-500-101T	4.00-5.00	0.01mm	101
523-600-101T	5.00-6.00	0.01mm	101
523-700-101T	6.00-7.00	0.01mm	101
523-800-101T	7.00-8.00	0.01mm	101
523-900-101T	8.00-9.00	0.01mm	101
523-1000-101T	9.00-10.00	0.01mm	101

SERIES 528

CERAMIC PIN GAUGE SET

- ◆ Meet DIN2269, grade 1
- ◆ Diameter range: 1.00-10.00mm
- ◆ Diameter accuracy: $\pm 1\mu\text{m}$
- ◆ Made of ceramic, extremely wear resistance, corrosion resistance and dimensional stability



528-0650-51



528-0300-101

Aluminum box

Code	Diameter(mm)	Step	Quantity
528-0150-51	1.00-1.50	0.01mm	51
528-0200-51	1.50-2.00	0.01mm	51
528-0250-51	2.00-2.50	0.01mm	51
528-0300-51	2.50-3.00	0.01mm	51
528-0350-51	3.00-3.50	0.01mm	51
528-0400-51	3.50-4.00	0.01mm	51
528-0450-51	4.00-4.50	0.01mm	51
528-0500-51	4.50-5.00	0.01mm	51
528-0550-51	5.00-5.50	0.01mm	51
528-0600-51	5.50-6.00	0.01mm	51
528-0650-51	6.00-6.50	0.01mm	51
528-0700-51	6.50-7.00	0.01mm	51
528-0750-51	7.00-7.50	0.01mm	51
528-0800-51	7.50-8.00	0.01mm	51
528-0850-51	8.00-8.50	0.01mm	51
528-0900-51	8.50-9.00	0.01mm	51
528-0950-51	9.00-9.50	0.01mm	51
528-1000-51	9.50-10.00	0.01mm	51

Blow mould case

Code	Diameter(mm)	Step	Quantity
528-0200-101	1.00-2.00	0.01mm	101
528-0300-101	2.00-3.00	0.01mm	101
528-0400-101	3.00-4.00	0.01mm	101
528-0500-101	4.00-5.00	0.01mm	101
528-0600-101	5.00-6.00	0.01mm	101
528-0700-101	6.00-7.00	0.01mm	101
528-0800-101	7.00-8.00	0.01mm	101
528-0900-101	8.00-9.00	0.01mm	101
528-1000-101	9.00-10.00	0.01mm	101

Code	Diameter(mm)	Step	Quantity
528-0105-41	1.00-5.00	0.1mm	41
528-0510-51	5.00-10.00	0.1mm	51
528-0110-91	1.00-10.00	0.1mm	91

SERIES 524

BOX FOR PIN GAUGE SET

- ◆ For containing pin gauges



524-001-01



524-101-01

Aluminum box

Code	Gauge range	Max. packed QTY
524-001-01	0.10-10mm	51
524-001-02	10-13mm	72
524-001-03	13-20mm	50
524-001-04	20-34mm	32

Blow mould case


Code	Gauge range	Max. packed QTY
524-101-01	0.10-10mm	101

526


STEEL BALL SET



- ◆ To measure diameter and angle of taper holes
- ◆ Each size has a pair of steel ball
- ◆ Material: tool steel
- ◆ Hardness: HRC63
- ◆ Diameter accuracy: $\pm 2\mu\text{m}$
- ◆ Roundness: $0.6\mu\text{m}$



Calculate angle (α) and diameter (D_{max}) according to the ball diameter (D, d), height (A) and depth (B)



Code	Steel balls per set	Diameter(mm)
526-025-01	25 pairs	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25

SERIES 525

MASTER SETTING DISC

CUSTOM-MADE

other sizes are available upon request

- ◆ Hardness: HRC60-62
- ◆ Conforms to standard ASME B89.1.5



525-020-01

Diameter	Supplied difference	Roundness and conicity
3-21mm	±0.8μm	0.5μm
21-30mm	±0.8μm	0.7μm
30-40mm	±1.1μm	0.7μm
40-65mm	±1.5μm	1.0μm

Diameter	Supplied difference	Roundness and conicity
65-110mm	±1.9μm	1.2μm
110-120mm	±1.9μm	1.6μm
120-130mm	±2.4μm	1.6μm

Code	Size(mm)
525-003-01	Ø3
525-004-01	Ø4
525-005-01	Ø5
525-006-01	Ø6
525-007-01	Ø7
525-008-01	Ø8
525-009-01	Ø9
525-010-01	Ø10
525-011-01	Ø11
525-012-01	Ø12
525-013-01	Ø13
525-014-01	Ø14
525-015-01	Ø15

Code	Size(mm)
525-016-01	Ø16
525-017-01	Ø17
525-018-01	Ø18
525-019-01	Ø19
525-020-01	Ø20
525-021-01	Ø21
525-022-01	Ø22
525-023-01	Ø23
525-024-01	Ø24
525-025-01	Ø25
525-026-01	Ø26
525-027-01	Ø27
525-028-01	Ø28

Code	Size(mm)
525-029-01	Ø29
525-030-01	Ø30
525-031-01	Ø31
525-032-01	Ø32
525-033-01	Ø33
525-034-01	Ø34
525-035-01	Ø35
525-036-01	Ø36
525-037-01	Ø37
525-038-01	Ø38
525-039-01	Ø39
525-040-01	Ø40
525-041-01	Ø41

Code	Size(mm)
525-042-01	Ø42
525-043-01	Ø43
525-044-01	Ø44
525-045-01	Ø45
525-046-01	Ø46
525-047-01	Ø47
525-048-01	Ø48
525-049-01	Ø49
525-050-01	Ø50
525-055-01	Ø55
525-060-01	Ø60
525-065-01	Ø65
525-070-01	Ø70

Code	Size(mm)
525-075-01	Ø75
525-080-01	Ø80
525-085-01	Ø85
525-090-01	Ø90
525-095-01	Ø95
525-100-01	Ø100
525-105-01	Ø105
525-110-01	Ø110
525-115-01	Ø115
525-120-01	Ø120
525-125-01	Ø125
525-130-01	Ø130

SERIES 529

THREE WIRE MEASURING UNITS

- ◆ Made of alloy steel
- ◆ One unit includes 3pcs same size
- ◆ Hardness HRC60-62
- ◆ Accuracy:
±0.25μm (grade 0), ±0.5μm (grade 1)
- ◆ Roundness:
0.25μm (grade 0), 0.5μm (grade 1)
- ◆ Code explanation

529-□□□□-0X


→0: grade0
→1: grade1

Example:

Code	Size(mm)	Grade
529-2886-00	2.886	0
529-2886-01	2.886	1


Supplied all 55 size as a set

Code	Quantity	Grade
529-055-00	55×3pcs	0
529-055-01	55×3pcs	1




529-4773-01


unit: mm



d ≤ 0.572mm



0.572mm < d < 1.591mm



d ≥ 1.591mm

Supplied 55 different size, unit: mm

0.118	0.260	0.572	1.302	2.020	2.886	3.580	4.773
0.142	0.291	0.724	1.441	2.050	3.106	3.666	5.150
0.170	0.343	0.796	1.553	2.071	3.177	4.091	5.176
0.185	0.402	0.866	1.591	2.217	3.287	4.120	5.493
0.201	0.433	1.008	1.732	2.311	3.310	4.141	6.212
0.232	0.461	1.047	1.833	2.595	3.468	4.211	6.585
0.250	0.511	1.157	1.883	2.866	3.550	4.400	

SERIES 531

SETTING RING

CUSTOM-MADE

other sizes are available
upon request

- ◆ For inside micrometer and bore gage setting
- ◆ The size marked on the setting ring is checked at the direction of the marking line
- ◆ Size difference (difference between the ordered size and the size marked on the setting ring when supplied): For example, the ordered size is 20mm, the real size marked on the setting ring when supplied may be 20.003mm
- ◆ Range: Ø2-300mm



531-040-01

Application



Diameter d	Size difference	Roundness and cylindricity	Accuracy
Ø2~≤10	±3.0µm	0.4µm	±1.5µm
Ø10~≤20		0.5µm	±3.0µm
Ø20~≤30		0.6µm	
Ø30~≤50		0.7µm	
Ø50~≤80		0.8µm	±4.0µm
Ø80~≤100		1.0µm	
Ø100~≤130	±5.0µm	1.0µm	±5µm
Ø130~≤150		1.2µm	
Ø150~≤210		1.5µm	
Ø210~≤250		2.5µm	
Ø250~≤300		3.0µm	

Code	Size(mm)
531-002-01	Ø2
531-003-01	Ø3
531-004-01	Ø4
531-005-01	Ø5
531-006-01	Ø6
531-007-01	Ø7
531-008-01	Ø8
531-009-01	Ø9
531-010-01	Ø10
531-011-01	Ø11
531-012-01	Ø12
531-013-01	Ø13
531-014-01	Ø14
531-015-01	Ø15
531-016-01	Ø16
531-017-01	Ø17
531-018-01	Ø18
531-019-01	Ø19

Code	Size(mm)
531-020-01	Ø20
531-021-01	Ø21
531-022-01	Ø22
531-023-01	Ø23
531-024-01	Ø24
531-025-01	Ø25
531-026-01	Ø26
531-027-01	Ø27
531-028-01	Ø28
531-029-01	Ø29
531-030-01	Ø30
531-031-01	Ø31
531-032-01	Ø32
531-033-01	Ø33
531-034-01	Ø34
531-035-01	Ø35
531-036-01	Ø36
531-037-01	Ø37

Code	Size(mm)
531-038-01	Ø38
531-039-01	Ø39
531-040-01	Ø40
531-041-01	Ø41
531-042-01	Ø42
531-043-01	Ø43
531-044-01	Ø44
531-045-01	Ø45
531-046-01	Ø46
531-047-01	Ø47
531-048-01	Ø48
531-049-01	Ø49
531-050-01	Ø50
531-055-01	Ø55
531-060-01	Ø60
531-062-01	Ø62
531-065-01	Ø65
531-070-01	Ø70

Code	Size(mm)
531-075-01	Ø75
531-080-01	Ø80
531-085-01	Ø85
531-087-01	Ø87
531-090-01	Ø90
531-095-01	Ø95
531-100-01	Ø100
531-125-01	Ø125
531-150-01	Ø150
531-175-01	Ø175
531-200-01	Ø200
531-225-01	Ø225
531-250-01	Ø250
531-275-01	Ø275
531-300-01	Ø300

GAUGE

SERIES 541

PLAIN PLUG GAUGE

CUSTOM-MADE

other sizes are available
upon request

- ◆ Grade H7
- ◆ Hardness HRC 60±2
- ◆ Confirms to standard GB/T 1957-2006
- ◆ Supplied range from 1mm to 100mm




541-020-17




541-006-17

unit: mm




type A



type B

Diameter Ød (mm)	Ød1 size tolerance of Go gage (mm)	Ød2 size tolerance of Go gage (mm)	L1	L2	L	L3	L4
≥2 ≤3	+0.0010, +0.0022	+0.0088, +0.010	6.5	4.5	62		
>3 ≤6	+0.0013, +0.0027	+0.0106, +0.012	8	6	74		
>6, ≤10	+0.0015, +0.0033	+0.0132, +0.015	10	7	87		
>10, ≤14	+0.0018, +0.0038	+0.0160, +0.018	12	8	99		
>14, ≤18	+0.0018, +0.0038	+0.0160, +0.018	14	10	114		
>18, ≤24	+0.0023, +0.0046	+0.0186, +0.021	16	12	132		
>24, ≤30	+0.0023, +0.0046	+0.0186, +0.021	18	14	136		
>30, ≤40	+0.0023, +0.0055	+0.0220, +0.025	20	15	155		
>40, ≤50	+0.0023, +0.0055	+0.0220, +0.025	25	18	169		
>50, ≤65	+0.0028, +0.0064	+0.0264, +0.030	30	18		164	165
>65, ≤80	+0.0028, +0.0064	+0.0264, +0.030	35	25		169	159
>80, ≤100	+0.0032, +0.0075	+0.0308, +0.035	35	25		169	159



type C

Code	Diameter Ød (mm)	Type
541-002-17	2	A
541-003-17	3	A
541-004-17	4	A
541-005-17	5	A
541-006-17	6	A
541-007-17	7	A
541-008-17	8	A
541-009-17	9	B
541-010-17	10	B
541-011-17	11	B
541-012-17	12	B
541-013-17	13	B
541-014-17	14	B
541-015-17	15	B
541-016-17	16	B

Code	Diameter Ød (mm)	Type
541-017-17	17	B
541-018-17	18	B
541-019-17	19	B
541-020-17	20	B
541-021-17	21	B
541-022-17	22	B
541-023-17	23	B
541-024-17	24	B
541-025-17	25	B
541-026-17	26	B
541-027-17	27	B
541-028-17	28	B
541-029-17	29	B
541-030-17	30	B
541-031-17	31	B



Code	Diameter Ød (mm)	Type
541-032-17	32	B
541-033-17	33	B
541-034-17	34	B
541-035-17	35	B
541-036-17	36	B
541-037-17	37	B
541-038-17	38	B
541-039-17	39	B
541-040-17	40	B
541-041-17	41	B
541-042-17	42	B
541-043-17	43	B
541-044-17	44	B
541-045-17	45	B
541-046-17	46	B

Code	Diameter Ød (mm)	Type
541-047-17	47	B
541-048-17	48	B
541-049-17	49	B
541-050-17	50	B
541-052-17	52	C
541-055-17	55	C
541-060-17	60	C
541-065-17	65	C
541-070-17	70	C
541-075-17	75	C
541-080-17	80	C
541-085-17	85	C
541-090-17	90	C
541-095-17	95	C
541-100-17	100	C


541-020-17T

541-006-17T

unit: mm

type A

type B


- ◆ Grade H7
- ◆ Hardness HRC 85-89
- ◆ Supplied range from 1mm to 30mm

Diameter Ød (mm)	Ød1 size tolerance of Go gage (mm)	Ød2 size tolerance of Go gage (mm)	L1	L2	L
≥2 ≤3	+0.0010, +0.0022	+0.0088, +0.010	6.5	4.5	62
>3 ≤6	+0.0013, +0.0027	+0.0106, +0.012	8	6	74
>6, ≤10	+0.0015, +0.0033	+0.0132, +0.015	10	7	87
>10, ≤14	+0.0018, +0.0038	+0.0160, +0.018	12	8	99
>14, ≤18	+0.0018, +0.0038	+0.0160, +0.018	14	10	114
>18, ≤24	+0.0023, +0.0046	+0.0186, +0.021	16	12	132
>24, ≤30	+0.0023, +0.0046	+0.0186, +0.021	18	14	136

Code	Diameter Ød (mm)	Type
541-002-17T	2	A
541-003-17T	3	A
541-004-17T	4	A
541-005-17T	5	A
541-006-17T	6	A
541-007-17T	7	A
541-008-17T	8	A
541-009-17T	9	B
541-010-17T	10	B
541-011-17T	11	B
541-012-17T	12	B
541-013-17T	13	B
541-014-17T	14	B
541-015-17T	15	B
541-016-17T	16	B

Code	Diameter Ød (mm)	Type
541-017-17T	17	B
541-018-17T	18	B
541-019-17T	19	B
541-020-17T	20	B
541-021-17T	21	B
541-022-17T	22	B
541-023-17T	23	B
541-024-17T	24	B
541-025-17T	25	B
541-026-17T	26	B
541-027-17T	27	B
541-028-17T	28	B
541-029-17T	29	B
541-030-17T	30	B

SERIES 589

LIMIT SNAP GAUGE

CUSTOM-MADE

Grade: h6, g7
Size: 1 to 250mm
are available upon request

- ◆ Grade H7
- ◆ Type A: size ≤ 80mm;
Type B: size > 80mm
- ◆ Code explanation:

589-□□-07

size ←

Type A



589-060-07

Type B



589-150-07

Example:

Code	Size(mm)	Type
589-060-07	60	A
589-070-07	70	A
589-080-07	80	A
589-100-07	100	B
589-120-07	120	B
589-150-07	150	B

SERIES 585

KEY SLOT LIMIT GAUGE

CUSTOM-MADE

Size between 3 to 50mm,
are available upon request



front side



reverse side

Code

585-xxxxx-xx

- ◆ Grade 6g
- ◆ Meet ISO1502
- ◆ Hardness HRC60-62



532-020-01



533-020-01

STANDARD THREAD

Code(GO)	Code(NOGO)	Size(mm)
532-002-01	533-002-01	M2x0.4
532-002-21	533-002-21	M2.2x0.45
532-002-51	533-002-51	M2.5x0.45
532-003-01	533-003-01	M3x0.5
532-003-51	533-003-51	M3.5x0.6
532-004-01	533-004-01	M4x0.7
532-005-01	533-005-01	M5x0.8
532-006-01	533-006-01	M6x1
532-008-01	533-008-01	M8x1.25

Code(GO)	Code(NOGO)	Size(mm)
532-010-01	533-010-01	M10x1.5
532-012-01	533-012-01	M12x1.75
532-014-01	533-014-01	M14x2
532-016-01	533-016-01	M16x2
532-018-01	533-018-01	M18x2.5
532-020-01	533-020-01	M20x2.5
532-022-01	533-022-01	M22x2.5
532-024-01	533-024-01	M24x3
532-027-01	533-027-01	M27x3

Code(GO)	Code(NOGO)	Size(mm)
532-030-01	533-030-01	M30x3.5
532-033-01	533-033-01	M33x3.5
532-036-01	533-036-01	M36x4
532-042-01	533-042-01	M42x4.5
532-048-01	533-048-01	M48x5
532-052-01	533-052-01	M52x5
532-060-01	533-060-01	M60x5.5

FINE THREAD

Code(GO)	Code(NOGO)	Size(mm)
534-002-01	535-002-01	M2x0.25
534-002-21	535-002-21	M2.2x0.25
534-002-51	535-002-51	M2.5x0.35
534-003-01	535-003-01	M3x0.35
534-003-51	535-003-51	M3.5x0.35
534-004-01	535-004-01	M4x0.5
534-005-01	535-005-01	M5x0.5
534-006-01	535-006-01	M6x0.5
534-006-02	535-006-02	M6x0.75
534-007-01	535-007-01	M7x0.5
534-007-02	535-007-02	M7x0.75
534-008-01	535-008-01	M8x0.5
534-008-02	535-008-02	M8x0.75
534-008-03	535-008-03	M8x1
534-009-01	535-009-01	M9x0.5
534-009-02	535-009-02	M9x0.75
534-009-03	535-009-03	M9x1
534-010-01	535-010-01	M10x0.5
534-010-02	535-010-02	M10x0.75
534-010-03	535-010-03	M10x1
534-010-04	535-010-04	M10x1.25
534-011-02	535-011-02	M11x0.75
534-011-03	535-011-03	M11x1
534-012-01	535-012-01	M12x0.5
534-012-02	535-012-02	M12x0.75
534-012-03	535-012-03	M12x1
534-012-04	535-012-04	M12x1.25
534-012-05	535-012-05	M12x1.5
534-014-01	535-014-01	M14x0.5
534-014-02	535-014-02	M14x0.75
534-014-03	535-014-03	M14x1
534-014-04	535-014-04	M14x1.25
534-014-05	535-014-05	M14x1.5
534-016-01	535-016-01	M16x0.5
534-016-02	535-016-02	M16x0.75
534-016-03	535-016-03	M16x1
534-016-04	535-016-04	M16x1.5

Code(GO)	Code(NOGO)	Size(mm)
534-018-01	535-018-01	M18x0.5
534-018-02	535-018-02	M18x0.75
534-018-03	535-018-03	M18x1
534-018-04	535-018-04	M18x1.5
534-018-05	535-018-05	M18x2
534-020-01	535-020-01	M20x0.5
534-020-02	535-020-02	M20x0.75
534-020-03	535-020-03	M20x1
534-020-04	535-020-04	M20x1.5
534-020-05	535-020-05	M20x2
534-022-01	535-022-01	M22x0.5
534-022-02	535-022-02	M22x0.75
534-022-03	535-022-03	M22x1
534-022-04	535-022-04	M22x1.5
534-022-05	535-022-05	M22x2
534-024-01	535-024-01	M24x0.75
534-024-02	535-024-02	M24x1
534-024-03	535-024-03	M24x1.5
534-024-04	535-024-04	M24x2
534-027-01	535-027-01	M27x0.75
534-027-02	535-027-02	M27x1
534-027-03	535-027-03	M27x1.5
534-027-04	535-027-04	M27x2
534-030-01	535-030-01	M30x0.75
534-030-02	535-030-02	M30x1
534-030-03	535-030-03	M30x1.5
534-030-04	535-030-04	M30x2
534-030-05	535-030-05	M30x3
534-033-01	535-033-01	M33x0.75
534-033-02	535-033-02	M33x1
534-033-03	535-033-03	M33x1.5
534-033-04	535-033-04	M33x2
534-033-05	535-033-05	M33x3
534-036-01	535-036-01	M36x1
534-036-02	535-036-02	M36x1.5
534-036-03	535-036-03	M36x2
534-036-04	535-036-04	M36x3

Code(GO)	Code(NOGO)	Size(mm)
534-039-01	535-039-01	M39x1
534-039-02	535-039-02	M39x1.5
534-039-03	535-039-03	M39x2
534-039-04	535-039-04	M39x3
534-042-01	535-042-01	M42x1
534-042-02	535-042-02	M42x1.5
534-042-03	535-042-03	M42x2
534-042-04	535-042-04	M42x3
534-042-05	535-042-05	M42x4
534-045-01	535-045-01	M45x1
534-045-02	535-045-02	M45x1.5
534-045-03	535-045-03	M45x2
534-045-04	535-045-04	M45x3
534-045-05	535-045-05	M45x4
534-048-01	535-048-01	M48x1
534-048-02	535-048-02	M48x1.5
534-048-03	535-048-03	M48x2
534-048-04	535-048-04	M48x3
534-048-05	535-048-05	M48x4
534-052-01	535-052-01	M52x1
534-052-02	535-052-02	M52x1.5
534-052-03	535-052-03	M52x2
534-052-04	535-052-04	M52x3
534-052-05	535-052-05	M52x4
534-056-01	535-056-01	M56x1
534-056-02	535-056-02	M56x1.5
534-056-03	535-056-03	M56x2
534-056-04	535-056-04	M56x3
534-056-05	535-056-05	M56x4
534-060-01	535-060-01	M60x1
534-060-02	535-060-02	M60x1.5
534-060-03	535-060-03	M60x2
534-060-04	535-060-04	M60x3
534-060-05	535-060-05	M60x4

SERIES 542

THREAD PLUG GAUGE

CUSTOM-MADE

other sizes are available
upon request

- ◆ Grade 6H
- ◆ Meet ISO1502
- ◆ Hardness HRC60-62



542-024-01

Code	Size(mm)
542-002-01	M2x0.4
542-002-21	M2.2x0.45
542-002-51	M2.5x0.45
542-003-01	M3x0.5
542-003-02	M3.5x0.6
542-004-01	M4x0.7
542-005-01	M5x0.8
542-006-01	M6x1

Code	Size(mm)
542-007-01	M7x1
542-008-01	M8x1.25
542-009-01	M9x1.25
542-010-01	M10x1.5
542-011-01	M11x1.5
542-012-01	M12x1.75
542-014-01	M14x2
542-016-01	M16x2

Code	Size(mm)
542-018-01	M18x2.5
542-020-01	M20x2.5
542-022-01	M22x2.5
542-024-01	M24x3
542-027-01	M27x3
542-030-01	M30x3.5
542-033-01	M33x3.5
542-036-01	M36x4

Code	Size(mm)
542-039-01	M39x4
542-042-01	M42x4.5
542-045-01	M45x4.5
542-048-01	M48x5
542-052-01	M52x5
542-056-01	M56x5.5
542-060-01	M60x5.5

SERIES 543

FINE THREAD PLUG GAUGE

CUSTOM-MADE

other sizes are available
upon request

- ◆ Grade 6H
- ◆ Meet ISO1502
- ◆ Hardness HRC60-62, good wear resistance



543-020-01

Code	Size(mm)
543-002-01	M2x0.25
543-002-21	M2.2x0.25
543-002-31	M2.5x0.35
543-003-01	M3x0.35
543-003-02	M3.5x0.35
543-004-01	M4x0.5
543-005-01	M5x0.5
543-006-01	M6x0.5
543-006-02	M6x0.75
543-007-01	M7x0.5
543-007-02	M7x0.75
543-008-01	M8x0.5
543-008-02	M8x0.75
543-008-03	M8x1
543-009-01	M9x0.5
543-009-02	M9x0.75
543-009-03	M9x1
543-010-01	M10x0.5
543-010-02	M10x0.75
543-010-03	M10x1
543-010-04	M10x1.25
543-011-01	M11x0.5

Code	Size(mm)
543-011-02	M11x0.75
543-011-03	M11x1
543-012-01	M12x0.5
543-012-02	M12x0.75
543-012-03	M12x1
543-012-04	M12x1.25
543-012-05	M12x1.5
543-014-01	M14x0.5
543-014-02	M14x0.75
543-014-03	M14x1
543-014-04	M14x1.25
543-014-05	M14x1.5
543-016-01	M16x0.5
543-016-02	M16x0.75
543-016-03	M16x1
543-016-04	M16x1.5
543-018-01	M18x0.5
543-018-02	M18x0.75
543-018-03	M18x1
543-018-04	M18x1.5
543-018-05	M18x2
543-020-01	M20x0.5

Code	Size(mm)
543-020-02	M20x0.75
543-020-03	M20x1
543-020-04	M20x1.5
543-020-05	M20x2
543-022-01	M22x0.5
543-022-02	M22x0.75
543-022-03	M22x1
543-022-04	M22x1.5
543-022-05	M22x2
543-024-01	M24x0.75
543-024-02	M24x1
543-024-03	M24x1.5
543-024-04	M24x2
543-027-01	M27x0.75
543-027-02	M27x1
543-027-03	M27x1.5
543-027-04	M27x2
543-030-01	M30x0.75
543-030-02	M30x1
543-030-03	M30x1.5
543-030-04	M30x2
543-030-05	M30x3

Code	Size(mm)
543-033-01	M33x0.75
543-033-02	M33x1
543-033-03	M33x1.5
543-033-04	M33x2
543-033-05	M33x3
543-036-01	M36x1
543-036-02	M36x1.5
543-036-03	M36x2
543-036-04	M36x3
543-039-01	M39x1
543-039-02	M39x1.5
543-039-03	M39x2
543-039-04	M39x3
543-042-01	M42x1
543-042-02	M42x1.5
543-042-03	M42x2
543-042-04	M42x3
543-042-05	M42x4
543-045-01	M45x1
543-045-02	M45x1.5
543-045-03	M45x2
543-045-04	M45x3

Code	Size(mm)
543-045-05	M45x4
543-048-01	M48x1
543-048-02	M48x1.5
543-048-03	M48x2
543-048-04	M48x3
543-048-05	M48x4
543-052-01	M52x1
543-052-02	M52x1.5
543-052-03	M52x2
543-052-04	M52x3
543-052-05	M52x4
543-056-01	M56x1
543-056-02	M56x1.5
543-056-03	M56x2
543-056-04	M56x3
543-056-05	M56x4
543-060-01	M60x1
543-060-02	M60x1.5
543-060-03	M60x2
543-060-04	M60x3
543-060-05	M60x4

SERIES 537/538**AMERICAN STANDARD THREAD
RING GAUGE****CUSTOM-MADE**other sizes are available
upon request

- ◆ Class 2A
- ◆ Conforms to standard ANSI B1.2
- ◆ Made of Oil Hardened Non-shrinking steel
- ◆ Hardness HRC60-62

**537-71620-UNF**

Code(GO)	Code(NOGO)	Size
537-00440-UNC	538-00440-UNC	4-40UNC
537-04048-UNF	538-04048-UNF	4-48UNF
537-00632-UNC	538-00632-UNC	6-32UNC
537-06040-UNF	538-06040-UNF	6-40UNF
537-00832-UNC	538-00832-UNC	8-32UNC
537-08036-UNF	538-08036-UNF	8-36UNF
537-01024-UNC	538-01024-UNC	10-24UNC
537-01032-UNF	538-01032-UNF	10-32UNF
537-01420-UNC	538-01420-UNC	1/4-20UNC
537-01428-UNF	538-01428-UNF	1/4-28UNF
537-51618-UNC	538-51618-UNC	5/16-18UNC
537-51624-UNF	538-51624-UNF	5/16-24UNF
537-03816-UNC	538-03816-UNC	3/8-16UNC
537-03824-UNF	538-03824-UNF	3/8-24UNF

Code(GO)	Code(NOGO)	Size
537-71614-UNC	538-71614-UNC	7/16-14UNC
537-71620-UNF	538-71620-UNF	7/16-20 UNF
537-01213-UNC	538-01213-UNC	1/2-13 UNC
537-01220-UNF	538-01220-UNF	1/2-20 UNF
537-91612-UNC	538-91612-UNC	9/16-12UNC
537-91618-UNF	538-91618-UNF	9/16-18UNF
537-05811-UNC	538-05811-UNC	5/8-11UNC
537-05818-UNF	538-05818-UNF	5/8-18UNF
537-03410-UNC	538-03410-UNC	3/4-10UNC
537-03416-UNF	538-03416-UNF	3/4-16UNF
537-07809-UNC	538-07809-UNC	7/8-9UNC
537-07814-UNF	538-07814-UNF	7/8-14UNF
537-01080-UNC	538-01080-UNC	1-8 UNC
537-01012-UNF	538-01012-UNF	1-12UNF

SERIES 547**AMERICAN STANDARD THREAD
PLUG GAUGE****CUSTOM-MADE**other sizes are available
upon request

- ◆ Class 2B
- ◆ Conforms to standard ANSI B1.2
- ◆ Made of Oil Hardened Non-shrinking steel
- ◆ Hardness HRC60-62

**547-71620-UNF**

Code(GO)	Size
547-00440-UNC	4-40UNC
547-04048-UNF	4-48UNF
547-00632-UNC	6-32UNC
547-06040-UNF	6-40UNF
547-00832-UNC	8-32UNC
547-08036-UNF	8-36UNF
547-01024-UNC	10-24UNC
547-01032-UNF	10-32UNF
547-01420-UNC	1/4-20UNC
547-01428-UNF	1/4-28UNF

Code(GO)	Size
547-51618-UNC	5/16-18UNC
547-51624-UNF	5/16-24UNF
547-03816-UNC	3/8-16UNC
547-03824-UNF	3/8-24UNF
547-71614-UNC	7/16-14UNC
547-71620-UNF	7/16-20 UNF
547-01213-UNC	1/2-13 UNC
547-01220-UNF	1/2-20 UNF
547-91612-UNC	9/16-12UNC
547-91618-UNF	9/16-18UNF

Code(GO)	Size
547-05811-UNC	5/8-11UNC
547-05818-UNF	5/8-18UNF
547-03410-UNC	3/4-10UNC
547-03416-UNF	3/4-16UNF
547-07809-UNC	7/8-9UNC
547-07814-UNF	7/8-14UNF
547-01080-UNC	1-8 UNC
547-01012-UNF	1-12UNF

GAUGE

SERIES 544

NPT THREAD GAUGE

- ◆ Conforms to standard ANSI/ASME B1.20.1
- ◆ Taper: 1:16
- ◆ Made of Oil Hardened Non-shrinking steel

PLUG GAUGE



544-014-01

Code	Size	Code	Size
544-027-04	NPT 1/16" x 27	544-11D5-12	NPT1-1/4"x11.5
544-027-03	NPT 1/8" x 27	544-11D5-11	NPT1-1/2"x11.5
544-018-02	NPT1/4" x 18	544-11D5-20	NPT2"x11.5
544-018-33	NPT3/8"x18	544-008-21	NPT2-1/2"X8
544-014-01	NPT1/2" x 14	544-008-30	NPT3"X8
544-014-32	NPT3/4"x14	544-008-32	NPT3-1/2"X8
544-11D5-10	NPT1"x11.5	544-008-40	NPT4"X8

SERIES 544

NPT THREAD GAUGE

- ◆ Conforms to standard ANSI/ASME B1.20.1
- ◆ Taper: 1:16
- ◆ Made of Oil Hardened Non-shrinking steel

RING GAUGE



Front

Back

544-014-01R

Code	Size	Code	Size
544-027-04R	NPT 1/16" x 27	544-11D5-12R	NPT1-1/4"x11.5
544-027-03R	NPT 1/8" x 27	544-11D5-11R	NPT1-1/2"x11.5
544-018-02R	NPT1/4" x 18	544-11D5-20R	NPT2"x11.5
544-018-33R	NPT3/8"x18	544-008-21R	NPT2-1/2"X8
544-014-01R	NPT1/2" x 14	544-008-30R	NPT3"X8
544-014-32R	NPT3/4"x14	544-008-32R	NPT3-1/2"X8
544-11D5-10R	NPT1"x11.5	544-008-40R	NPT4"X8

SERIES 545

WITHWORTH PIPE THREAD GAUGE (G SERIES)

◆ Conforms to standard ISO228

PLUG GAUGE



545-0500-01

Code	Size
545-0125-01	G1/8-28
545-0250-01	G1/4-19
545-0375-01	G3/8-19
545-0500-01	G1/2-14
545-0625-01	G5/8-14
545-0750-01	G3/4-14

Code	Size
545-0875-01	G7/8-14
545-1000-01	G1-11
545-1125-01	G1-1/8-11
545-1250-01	G1-1/4-11
545-1500-01	G1-1/2-11
545-1750-01	G1-3/4-11

Code	Size
545-2000-01	G2-11
545-2500-01	G2-1/2-11
545-3000-01	G3-11
545-4000-01	G4-11

SERIES 535/536

WITHWORTH PIPE THREAD GAUGE (G SERIES)

◆ Conforms to standard ISO228

◆ Class B

RING GAUGE



535-0250-01



536-0250-01

Code(GO)	Code(NOGO)	Size
535-0125-01	536-0125-01	G1/8-28
535-0250-01	536-0250-01	G1/4-19
535-0375-01	536-0375-01	G3/8-19
535-0500-01	536-0500-01	G1/2-14
535-0625-01	536-0625-01	G5/8-14
535-0750-01	536-0750-01	G3/4-14
535-0875-01	536-0875-01	G7/8-14
535-1000-01	536-1000-01	G1-11

Code(GO)	Code(NOGO)	Size
535-1125-01	536-1125-01	G1-1/8-11
535-1250-01	536-1250-01	G1-1/4-11
535-1500-01	536-1500-01	G1-1/2-11
535-1750-01	536-1750-01	G1-3/4-11
535-2000-01	536-2000-01	G2-11
535-2500-01	536-2500-01	G2-1/2-11
535-3000-01	536-3000-01	G3-11
535-4000-01	536-4000-01	G4-11

SERIES 594

AIR GAUGE

CUSTOM-MADE

Inside air plug gauge and standard ring



594-xxxxx-01

Outside air snap gauge and standard column gauge



594-xxxxx-05

Code	Range	Remark
594-XXXXX-01	Ø2-150mm	measure diameter of hole

Code	Range	Remark
594-XXXXX-05	Ø4-120mm	measure diameter of shaft

GAUGE



VIDEO

- ◆ Can store 10 measuring programs, and the program can be switched quickly
- ◆ Data storage function, support manual and automatic storing, 1000 groups data can be stored
- ◆ Automatically detect internal or external dimension measurement
- ◆ Automatic grouping function for workpiece sorting

LED column

zero point

Application



Back of display



RS232 port

I/O interface

USB

on/off

power socket

air inlet

display

key panel

air outlet

rate regulating valve

Air filter and pressure regulating valve



Work in groups



SPECIFICATION

Code		595-101-01			
LED quantity		101 pcs			
LED color		red, orange, green			
LED height		254mm			
Range		10μm	20μm	50μm	100μm
Resolution	LED column	0.1μm	0.2μm	0.5μm	1μm
	Display	0.1μm			
Accuracy		0.2μm	0.4μm	0.5μm	1μm
Air supply		dir and clean, 0.4~0.8MPa			
Output		RS232/USB, I/O interface			
Operation temperature		0~45°C			
Power		100-240V, 50/60Hz			
Power consumption		<20W			
Max. current		2A			
Dimension(LxWxH)		170x65x475mm			
Weight		3kg			


OPTIONAL ACCESSORIES

Air filter

Pressure regulating valve

RS232 cable

unit: mm




SERIES 559

THREAD DEPTH GAUGE

CUSTOM-MADE

other sizes are available upon request



- ◆ Supplied with GO and NO-GO gages together
- ◆ Check GO and NO-GO while measuring the depth thread
- ◆ The GO gage can be replaced after wear
- ◆ Graduation: 0.1mm
- ◆ Accuracy: $\pm 0.1\text{mm}$



559-004-01



Code	Size	Depth range
559-003-01	M3x0.5-6H	4-25mm
559-004-01	M4x0.7-6H	4-25mm
559-005-01	M5x0.8-6H	4-25mm
559-006-01	M6x1-6H	4-25mm
559-008-01	M8x1.25-6H	5-45mm
559-010-01	M10x1.5-6H	5-45mm
559-012-01	M12x1.75-6H	5-45mm
559-014-01	M14x2-6H	5-45mm




822

DIGITAL PROTRACTOR



- ◆ Button function:
SET: preset the reading and change the measuring direction
MODE: choose range 90°, 180°, 360°
ZERO/ON/OFF: set zero and power on/off
- ◆ Data output
- ◆ With a 150mm blade and a 90° square
- ◆ Made of stainless steel




Code	Range	Resolution	Accuracy
822-360-01	0-360°	10"/0.005°	$\pm 5'$

PROTRACTOR


GAUGE

814


UNIVERSAL PROTRACTOR



- ◆ Graduation : 2'
- ◆ Made of stainless steel
- ◆ Satin chrome plated scale



Application





Code	Range	Accuracy
814-320-01	0 - 320°	±2'


815

UNIVERSAL PROTRACTOR

- ◆ Graduation : 5'
- ◆ Parallax-free reading
- ◆ With one blade: 150mm
- ◆ Made of stainless steel
- ◆ Optional accessory: clamp for height gages



Application






Code	Range	Accuracy
815-360-01	0 - 360°	±5'


816

UNIVERSAL PROTRACTOR

- ◆ Graduation: 5'
- ◆ With one blade: 150mm
- ◆ Made of carbon steel
- ◆ Optional accessory: clamp for height gages



Application




Code	Range	Accuracy
816-360-01	0 - 360°	±5'

726


DIGITAL PROTRACTOR



- ◆ Buttons: ON/OFF, HOLD, ZERO, ABS
- ◆ Measuring ranges can be set 0°~225°, -225°~0°, -45°~180°, -180°~45°
- ◆ Remove the locking screw for 360° range
- ◆ With level vial
- ◆ Automatic power off



Application



Code	Range	Resolution	Accuracy	Size(L)
726-360-01	0 - 360°	0.05°	±0.15°	250mm

823


DIGITAL PROTRACTOR




- ◆ Suitable for setting horizontal and vertical mitre angles of cutting machines
- ◆ Buttons: on/off, HOLD/SUP, SPR/CNR/MTR/BVL
- ◆ IP54 dust/waterproof
- ◆ With transverse and longitudinal level
- ◆ Absolute level, zero setting is not needed when batteries are replaced
- ◆ Backlight turns off in one minute after reading is stable, automatic power off in 5 minutes



Application



Code	Range	Resolution	Accuracy
823-225-01	0 - 225°	0.05°	±0.10°



SERIES 824


DIGITAL PROTRACTOR



- ◆ Button function:
Hold/Rev: hold/flip
ZERO: set zero
ON/OFF: power on/off
- ◆ With locking screw
- ◆ Side with magnetic force
- ◆ Resolution: 0.05°



824-004-11




Code	Size	Range	Accuracy	L
824-004-11	100mm	0-360°	±0.2°	103
824-008-11	200mm	0-360°	±0.2°	205
824-012-11	300mm	0-360°	±0.2°	306

SERIES 821

DIGITAL PROTRACTOR




- ◆ Resolution: 0.1°
- ◆ Buttons: on/off, zero
- ◆ With locking attachment
- ◆ Rule graduation: 1mm and 1/32"
- ◆ Automatic power off



821-008-01

Application



Code	Size(L)	Range	Accuracy
821-008-01	200mm	0-360°	±0.3°
821-012-01	300mm	0-360°	±0.3°

SERIES 821

DIGITAL PROTRACTOR




- ◆ Economic type
- ◆ Resolution: 0.1°
- ◆ Buttons: on/off, zero
- ◆ With locking attachment
- ◆ Rule graduation: 1mm and 1/32"
- ◆ Automatic power off



821-008-01N

Application




Code	Size(L)	Range	Accuracy
821-008-01N	200mm	0-360°	±0.3°
821-012-01N	300mm	0-360°	±0.3°

SERIES 817

COMBINATION SQUARE SET

- ◆ Protractor (made of cast iron), only for **817-180-02**:
Used to set an angle or angle measurement,
measuring range: 0-180°, accuracy: $\pm 20'$
- ◆ Square (made of cast iron):
Used as 90° square or 45° square
accuracy of 90° square: $\pm 8'$,
accuracy of 45° square: $\pm 10'$
- ◆ Blade (made of stainless steel):
Used as rule, measuring range: 300mm/12"
front side graduation: 0.5mm and 1/32"
reverse side graduation: 1mm and 1/64"
Used as rule, measuring range: 600mm/24"
front side graduation: 0.5mm and 1/32"
reverse side graduation: 1mm and 1/64"
- ◆ Center finder (made of cast iron), only for **817-090-13**
and **817-180-02**:
To locate center of cylinders with diameter
($\varnothing d$): 30-100mm, accuracy: $\pm 0.15\text{mm}$

Application



Code	L	Remark
817-090-12	305	2-piece set
817-090-13	305	3-piece set
817-180-02	305	4-piece set


Code	L
817-000-24	610



817-090-12



817-090-13




817-180-02




817-000-24

unit: mm




Application




811

PROTRACTOR

- ◆ Economic type
- ◆ Made of stainless steel
- ◆ With locking screw



Package



Code	Size	Range	Graduation	Accuracy
811-180-11	90x52mm	0 - 180°	1°	±0.5°


SERIES 811

PROTRACTOR

- ◆ Graduation : 1°
- ◆ Made of stainless steel
- ◆ Satin chrome plated scale
- ◆ With locking screw




811-180-01



Package



811-180-02



Code	Size	Range	Accuracy
811-180-01	85x150mm	0 - 180°	±0.3°
811-180-02	91x158mm	0 - 180°	±0.3°

SERIES 812


PROTRACTOR

- ◆ Graduation : 1°
- ◆ Made of stainless steel
- ◆ Satin chrome plated scale
- ◆ With locking screw



812-005-01

unit: mm




Code	Size(AxL)	Range	Accuracy	b	L1
812-003-01	80x120mm	0 - 180°	±0.3°	11	165
812-005-01	120x150mm	0 - 180°	±0.3°	13	215
812-006-01	150x200mm	0 - 180°	±0.3°	16	280
812-008-01	200x300mm	0 - 180°	±0.3°	20	410
812-012-01	300x500mm	0 - 180°	±0.3°	30	675


SERIES 813

PROTRACTOR


- ◆ Graduation : 1°
- ◆ Made of stainless steel
- ◆ Satin chrome plated scale
- ◆ The blade is moveable



813-012-01



unit: mm



Code	Size(AxL)	Range	Accuracy	C
813-006-01	100x150mm	10 - 170°	±0.3°	18
813-012-01	150x300mm	10 - 170°	±0.3°	18
813-016-01	200x400mm	10 - 170°	±0.3°	20
813-020-01	250x500mm	10 - 170°	±0.3°	20
813-024-01	300x600mm	10 - 170°	±0.3°	20

SERIES 832

90° BEVELED EDGE SQUARE


- ◆ Two beveled measuring faces
- ◆ Made of hardened stainless steel

Grade 00

Code	Size(LxW)	Squareness(α)	Squareness(β)	Chrome plating	a	b	h
832-002-00	50x40mm	2.4 μ m	2.5 μ m	With	13	13	4
832-003-00	75x50mm	2.6 μ m	2.8 μ m	With	15	15	4
832-004-00	100x70mm	2.8 μ m	3.0 μ m	With	20	20	5
832-006-00	150x100mm	3.2 μ m	3.5 μ m	With	30	30	6
832-008-00	200x130mm	3.7 μ m	4.0 μ m	With	34	34	7
832-010-00	250x165mm	4.2 μ m	4.5 μ m	Without	35	35	7
832-012-00	300x200mm	4.6 μ m	5.0 μ m	Without	40	40	8

Grade 0

Code	Size(LxW)	Squareness(α)	Squareness(β)	Chrome plating	a	b	h
832-002-10	50x40mm	6 μ m	6 μ m	With	13	13	4
832-003-10	75x50mm	6 μ m	7 μ m	With	15	15	4
832-004-10	100x70mm	7 μ m	7 μ m	With	20	20	5
832-006-10	150x100mm	7 μ m	8 μ m	With	30	30	6
832-008-10	200x130mm	8 μ m	9 μ m	With	34	34	7
832-010-10	250x165mm	9 μ m	10 μ m	Without	35	35	7
832-012-10	300x200mm	10 μ m	11 μ m	Without	40	40	8



SERIES 840


90° BEVELED EDGE SQUARE WITH WIDE BASE

- ◆ DIN875 grade 0
- ◆ Beveled edges for inside and outside measurement
- ◆ Made of hardened stainless steel



840-006-10

Code	Size(LxW)	Squareness		a	b	H	E
		Inside(α)	Outside(β)				
840-002-10	50x40mm	6 μ m	6 μ m	12	12	3	10
840-003-10	75x50mm	6 μ m	7 μ m	14	14	3	10
840-004-10	100x70mm	7 μ m	7 μ m	18	18	3	10
840-006-10	150x100mm	8 μ m	8 μ m	22	22	4	12
840-008-10	200x130mm	9 μ m	9 μ m	25	25	4	12




SERIES 841

90° FLAT EDGE SQUARE

- ◆ DIN875 grade 0
- ◆ Made of hardened stainless steel



841-004-10



Code	Size(LxW)	Squareness(α)	Squareness(β)	a	b	h
841-002-10	50x40mm	6μm	6μm	15	15	4
841-003-10	75x50mm	6μm	7μm	15	15	4
841-004-10	100x70mm	7μm	7μm	20	20	5
841-006-10	150x100mm	7μm	8μm	30	30	6
841-008-10	200x130mm	8μm	9μm	34	34	7
841-010-10	250x165mm	9μm	10μm	35	35	7
841-012-10	300x200mm	10μm	11μm	40	40	8


SERIES 842

90° FLAT EDGE SQUARE WITH WIDE BASE

- ◆ DIN875 grade 0
- ◆ Made of hardened stainless steel



842-004-10



Code	Size(LxW)	Squareness(α)	Squareness(β)	a	b	c	h
842-002-10	50x40mm	6μm	6μm	13	13	13	4
842-003-10	75x50mm	6μm	7μm	15	15	15	4
842-004-10	100x70mm	7μm	7μm	20	20	20	5
842-006-10	150x100mm	7μm	9μm	30	30	30	6
842-008-10	200x130mm	8μm	9μm	34	34	30	7
842-010-10	250x165mm	9μm	10μm	35	35	35	7
842-012-10	300x200mm	10μm	11μm	40	40	40	8


SERIES 843

90° FLAT EDGE SQUARE WITH WIDE BASE

- ◆ DIN875 grade 0
- ◆ Made of hardened stainless steel



843-004-10




Code	Size(LxW)	Squareness(α)	Squareness(β)	a	b	c	h
843-002-10	50x40mm	6μm	6μm	12	12	10	3
843-003-10	75x50mm	6μm	7μm	14	14	10	3
843-004-10	100x70mm	7μm	7μm	18	18	10	3
843-006-10	150x100mm	8μm	8μm	22	22	12	4
843-008-10	200x130mm	9μm	9μm	25	25	12	4

SERIES 850

MACHINIST SQUARE

- ◆ Made of carbon steel, no anti-rust treatment, not hardened

Code	Size(LxW)	Squareness		a	b	h
		Inside(α)	Outside(β)			
850-002-02	50x30mm	24μm	25μm	12	12	3
850-003-02	75x50mm	26μm	28μm	16	16	3
850-004-02	100x70mm	28μm	30μm	19	19	5
850-005-02	125x80mm	30μm	33μm	22	22	5
850-006-02	150x100mm	33μm	35μm	25	25	6
850-008-02	200x130mm	38μm	40μm	25	25	6
850-010-02	250x165mm	43μm	45μm	25	25	6
850-012-02	300x200mm	47μm	50μm	30	30	6
850-014-02	350x200mm	51μm	55μm	38	38	6
850-016-02	400x200mm	56μm	60μm	38	38	9
850-018-02	450x250mm	58μm	65μm	38	38	9
850-020-02	500x300mm	65μm	70μm	38	38	9



850-006-02


PROTRACTOR

SERIES 851

MACHINIST SQUARE WITH SCALE

- ◆ Made of carbon steel, no anti-rust treatment, not hardened

Code	Size(LxW)	Squareness		a	b	h
		Inside(α)	Outside(β)			
851-002-02	50x30mm	24 μ m	25 μ m	12	12	3
851-003-02	75x50mm	26 μ m	28 μ m	16	16	3
851-004-02	100x70mm	28 μ m	30 μ m	19	19	5
851-005-02	125x80mm	30 μ m	33 μ m	22	22	5
851-006-02	150x100mm	33 μ m	35 μ m	25	25	6
851-008-02	200x130mm	38 μ m	40 μ m	25	25	6
851-010-02	250x165mm	43 μ m	45 μ m	25	25	6
851-012-02	300x200mm	47 μ m	50 μ m	30	30	6
851-014-02	350x200mm	51 μ m	55 μ m	38	38	6
851-016-02	400x200mm	56 μ m	60 μ m	38	38	9
851-018-02	450x250mm	58 μ m	65 μ m	38	38	9
851-020-02	500x300mm	65 μ m	70 μ m	38	38	9




SERIES 845

MACHINIST SQUARE WITH WIDE BASE

- ◆ DIN875 grade 2
- ◆ Made of carbon steel

Code	Size(LxW)	Squareness(α)	Squareness(β)	a	b	c	h
845-002-02	50x40mm	24 μ m	25 μ m	16	12	9	3
845-003-02	75x50mm	26 μ m	28 μ m	16	16	9	3
845-004-02	100x70mm	28 μ m	30 μ m	19	19	12	3
845-006-02	150x100mm	33 μ m	35 μ m	25	25	16	3
845-008-02	200x130mm	37 μ m	40 μ m	30	32	16	4
845-010-02	250x165mm	42 μ m	45 μ m	30	32	19	4
845-012-02	300x200mm	47 μ m	50 μ m	32	32	19	4
845-016-02	400x250mm	56 μ m	60 μ m	38	38	22	5
845-020-02	500x300mm	65 μ m	70 μ m	45	50	25	6
845-024-02	600x350mm	75 μ m	80 μ m	50	50	30	6
845-030-02	750x400mm	90 μ m	95 μ m	55	55	50	6
845-036-02	900x500mm	103 μ m	110 μ m	65	75	50	9
845-040-02	1000x550mm	113 μ m	120 μ m	65	75	50	9




SERIES 855

MACHINIST SQUARE WITH WIDE BASE AND SCALE

- ◆ Made of carbon steel, no anti-rust treatment, not hardened

Code	Size(LxW)	Squareness		a	b	h	c
		Inside(α)	Outside(β)				
855-002-02	50x30mm	24 μ m	25 μ m	16	12	2.5	9
855-003-02	75x50mm	26 μ m	28 μ m	16	16	2.5	9
855-004-02	100x70mm	28 μ m	30 μ m	19	19	3	12
855-005-02	125x80mm	31 μ m	33 μ m	22	19	3	12
855-006-02	150x100mm	33 μ m	35 μ m	25	25	3	16
855-008-02	200x130mm	37 μ m	40 μ m	30	32	3	16
855-010-02	250x165mm	42 μ m	45 μ m	30	32	3	19
855-012-02	300x200mm	47 μ m	50 μ m	32	32	3	19
855-014-02	350x200mm	51 μ m	55 μ m	38	38	4.5	22
855-016-02	400x200mm	56 μ m	60 μ m	38	38	4.5	22
855-018-02	450x250mm	61 μ m	65 μ m	44	38	4.5	22
855-020-02	500x300mm	65 μ m	70 μ m	44	50	6	25
855-024-02	600x350mm	75 μ m	80 μ m	50	50	6	30
855-030-02	750x400mm	90 μ m	95 μ m	55	55	6	50
855-036-02	900x500mm	103 μ m	110 μ m	65	75	9	50
855-040-02	1000x550mm	113 μ m	120 μ m	65	75	9	50



SERIES 833


90° TOOL MAKER SQUARE

- ◆ DIN875 grade 00
- ◆ Beveled edge for inside measurement
- ◆ Made of hardened stainless steel



833-040-00

Code	Size(LxW)	Squareness	
		Inside(α)	Outside(β)
833-025-00	25x20mm	2.2 μ m	2.3 μ m
833-040-00	40x28mm	2.3 μ m	2.4 μ m



PROTRACTOR

839

SQUARE SET

◆ Includes:

- 90° tool maker square 25x20mm
DIN875 grade 00 (code **833-025-00**)
- 90° tool maker square 40x28mm
DIN875 grade 00 (code **833-040-00**)
- 90° beveled edge square 75x50mm
DIN875 grade 00 (code **832-003-00**)
- straight edge 100mm
DIN874 (code **994-004-01**)
- scriber

- ◆ Made of hardened stainless steel



unit: mm

Code

839-000-05



831

ADJUSTABLE SQUARE

- ◆ The straight edge can move and can be locked by the screw
- ◆ Made of hardened stainless steel



unit: mm



Code

831-002-10

Squareness (a, b, c, d)

7μm

SERIES 846


45° SQUARE

- ◆ Made of hardened stainless steel



846-006-02

Code	Size(LxW)	Accuracy		a	b
		Inside(α)	Outside(β)		
846-005-02	120x80mm	29 μ m	32 μ m	20	20
846-006-02	150x100mm	32 μ m	35 μ m	20	20
846-008-02	200x130mm	36 μ m	40 μ m	25	25




SERIES 856

45° SQUARE WITH WIDE BASE

- ◆ Made of hardened stainless steel



856-006-02



Code	Size(LxW)	Accuracy		a	b	H	E
		Inside(α)	Outside(β)				
856-005-02	120x80mm	29 μ m	32 μ m	20	20	5	20
856-006-02	150x100mm	32 μ m	35 μ m	20	20	5	20
856-008-02	200x130mm	36 μ m	40 μ m	25	25	5	25


SERIES 847

60° SQUARE

◆ Made of hardened stainless steel



847-006-02



Code	Size(LxW)	Accuracy		a	b
		Inside(α)	Outside(β)		
847-004-02	100x70mm	28μm	30μm	20	20
847-005-02	120x80mm	30μm	32μm	20	20
847-006-02	150x100mm	32μm	35μm	20	20
847-008-02	200x130mm	37μm	40μm	25	25


SERIES 857

60° SQUARE WITH WIDE BASE

◆ Made of hardened stainless steel



857-006-02



Code	Size(LxW)	Accuracy		a	b	H	E
		Inside(α)	Outside(β)				
857-005-02	120x80mm	30μm	33μm	20	20	5	20
857-006-02	150x100mm	33μm	36μm	20	20	5	20
857-008-02	200x130mm	37μm	41μm	25	25	5	25

SERIES 848


120° SQUARE

◆ Made of hardened stainless steel



848-004-02

Code	Size(LxW)	Accuracy		a	b	h
		Inside(α)	Outside(β)			
848-002-02	50x50mm	24 μ m	25 μ m	15	15	4
848-003-02	75x75mm	26 μ m	28 μ m	20	20	5
848-004-02	100x100mm	29 μ m	30 μ m	20	20	5
848-006-02	150x150mm	34 μ m	35 μ m	25	25	5
848-008-02	200x200mm	38 μ m	40 μ m	30	30	7




unit: mm

SERIES 849


135° SQUARE WITH WIDE BASE

◆ Made of hardened stainless steel



849-006-02

unit: mm



Code	Size(LxW)	Accuracy		a	b	c	h
		Inside(α)	Outside(β)				
849-005-02	120x80mm	31 μ m	33 μ m	20	20	20	5
849-006-02	150x100mm	34 μ m	36 μ m	20	20	20	5
849-008-02	200x130mm	39 μ m	41 μ m	30	30	30	7

PROTRACTOR

SERIES 643

GRANITE SQUARE




CUSTOM-MADE

other sizes are available upon request



643-010-01



Code	Size(HxW)	Flatness (A)	Flatness (B)	Squareness(A and B)	D
643-010-01	250x160mm	1μm	1μm	2μm	50mm
643-016-01	400x250mm	1.5μm	1μm	3μm	50mm
643-024-01	630x400mm	2μm	1.5μm	4μm	60mm

With manufacturer inspection certificate

SERIES 644

GRANITE SQUARE




CUSTOM-MADE

other sizes are available upon request



644-012-01





Code	Size(LxH)	Flatness (A, B, C and D)	Parallelism or squareness (A, B, C and D)	W
644-012-01	315x315mm	1.1μm	2.6μm	40
644-020-01	500x500mm	1.5μm	3.5μm	60

With manufacturer inspection certificate

645

GRANITE SQUARE AND V-BLOCK

◆ Thread holes: M8




Code	Size(LxWxH)	Range of shafts (Ød)	Parallelism or squareness A, B, C, D, E and F	Parallelism or squareness of V grooves to A, B, C, D, E and F
645-006-01	160x160x160mm	6 - 42mm	6µm	6µm

SERIES 649

MAGNETIC SQUARE AND V-BLOCK



649-004-01




Code	Size(LxWxH)	Magnetic force		Range of shafts (Ød)	Parallelism or squareness between top, bottom, left, right and back sides	Parallelism or squareness of both V grooves to top, bottom, left, right and back sides
		V-groove	Surface			
649-004-01	100x100x100mm	25kgf	50kgf	6 - 36mm	20µm	20µm
649-006-01	150x150x150mm	50kgf	140kgf	6 - 44mm	25µm	25µm

SERIES 642


GRANITE STRAIGHT EDGE



642-020-01



642-020-01



642-040-01

Code	Length(L)	Flatness of A and B	Parallelism between A and B	W	H
642-020-01	500mm	2.1 μ m	3.2 μ m	50	100
642-040-01	1000mm	3 μ m	4.5 μ m	50	120

With manufacturer inspection certificate

SERIES 648



GRANITE PARALLEL SET



- ◆ Made of granite
- ◆ Two parallels per set



unit: mm



Code	Size(LxWxH)	Parallelism between A and B	Parallelism between C and D	Height difference of a matched pair
648-250-01	250x25x40mm	3 μ m	3 μ m	3 μ m

With manufacturer inspection certificate


SERIES 647

MAGNALIUM STRAIGHT EDGES

- ◆ Made of magnalium, light weight, non-deform, no rusty



647-040-01



Code	Length(L)	Flatness of top and bottom	Parallelism between top and bottom	H	W	D
647-020-01	500mm	3μm	4μm	60	30	5
647-040-01	1000mm	5μm	8μm	60	30	5
647-060-01	1500mm	15μm	22μm	100	40	7
647-080-01	2000mm	18μm	27μm	100	40	7
647-100-01	2500mm	22μm	33μm	100	40	7
647-120-01	3000mm	48μm	72μm	150	80	8
647-140-01	3500mm	56μm	84μm	150	80	8
647-160-01	4000mm	64μm	110μm	150	80	10
647-200-01	5000mm	80μm	130μm	175	80	10
647-240-01	6000mm	100μm	150μm	175	80	10

SERIES 994


STRAIGHT EDGE

- ◆ Beveled edge to check the flatness
- ◆ DIN874
- ◆ Made of stainless steel
- ◆ Stain chrome plating



994-004-01

Code	Size (L)	Straightness	W	H
994-002-01	50mm	1.0μm	5	20
994-003-01	75mm	1.0μm	5	25
994-004-01	100mm	1.0μm	5	25
994-005-01	125mm	1.0μm	5	25
994-006-01	150mm	1.0μm	6	30
994-008-01	200mm	2.0μm	6	30
994-010-01	250mm	2.0μm	8	40
994-012-01	300mm	3.0μm	8	40
994-016-01	400mm	3.0μm	10	50
994-020-01	500mm	4.0μm	10	50



PARALLEL


SERIES 991

STRAIGHT EDGE RULE




991-012-01

unit: mm



- ◆ Check straightness, as well as for measurement
- ◆ Made of hardened tool steel, chrome plated
- ◆ Graduation: 1mm

Application



Code	Range(L)	Straightness	W	L1
991-012-01	300mm	0.02mm	40	310
991-020-01	500mm	0.03mm	40	510
991-040-01	1000mm	0.04mm	50	1010


SERIES 907

PRECISION STRAIGHT EDGE WITH BEVELED EDGE




907-012-11

unit: mm



- ◆ Check flatness and for marking
- ◆ Made of tool steel

Application




Code	Range(L)	Flatness of A and B	Flatness of C and D	W	H
907-012-11	305mm	0.005mm	0.05mm	41	6.3
907-024-11	610mm	0.006mm	0.06mm	51	7.9
907-036-11	914mm	0.007mm	0.06mm	64	9.5

SERIES 906

PRECISION STRAIGHT EDGE




906-012-11



- ◆ Check flatness and for marking
- ◆ Made of tool steel

Code	Range(L)	Flatness of A and B	Flatness of C and D	W	H
906-012-11	305mm	0.005mm	0.05mm	41	6.3
906-024-11	610mm	0.006mm	0.06mm	51	7.9
906-036-11	914mm	0.007mm	0.06mm	64	9.5

Application



SERIES 713

BLOCK LEVEL

- ◆ For use in setting machined surfaces precisely horizontal
- ◆ Sensibility: 0.02mm/m per division
- ◆ Vee angle : 140°



713-006-02



Code	Size (L)	H	W
713-006-02	150mm	42	47
713-008-02	200mm	45	47
713-012-02	300mm	45	49




SERIES 715

BLOCK LEVEL


- ◆ For use in setting machined surfaces precisely horizontal
- ◆ Vee angle : 140°



715-008-05



unit: mm



Sensibility 0.05mm/m

Code	Size (L)	W
715-006-05	150mm	38
715-008-05	200mm	44
715-012-05	300mm	44

Sensibility 0.1mm/m

Code	Size (L)	W
715-006-10	150mm	38
715-008-10	200mm	44
715-012-10	300mm	44

SERIES 711

FRAME LEVEL

- ◆ For using setting machined surfaces precisely horizontal and vertical
- ◆ Sensibility: 0.02mm/m per division
- ◆ V-groove on the bottom and left for shafts (711-004-02 only has v-groove on the bottom)





711-006-02



711-004-02

unit: mm




Code	Size (LxHxW)
711-004-02	100x100x32mm
711-006-02	150x150x38mm
711-008-02	200x200x40mm
711-012-02	300x300x45mm




- ◆ Sensibility: 0.01mm/m(0.001°)
- ◆ Accuracy: 10mm range $\leq \pm 0.01$ mm/m
10mm-50mm range $\leq \pm 0.02$ mm/m
- ◆ For use in setting machined surfaces precisely horizontal
- ◆ With longitudinal level
- ◆ Buttons: on/off, zero, mm/inch, save/mode, ABS
- ◆ 3.6V li-ion battery for 15 hours working
- ◆ Memory: 6





Use as protractor



Use as level



unit: mm





Code	Range	Graduation
712-006-01	± 50 mm/m	0.01mm/m

- ◆ Sensibility: 0.01mm/m(0.001°)
- ◆ Accuracy: ± 0.01 mm/m(range: ± 1 mm)
 ± 0.02 mm/m(other)
- ◆ For use in setting machined surfaces precisely horizontal



unit: mm



Code	Range	Graduation
714-006-01	0-10mm/m(± 5 mm/m)	0.01mm/m

- ◆ Measures flatness, parallelism and straightness
- ◆ Built-in bluetooth, can be connected to computers, transmission distance is 50m
- ◆ The LCD can be rotated for easy observation in different directions
- ◆ V-groove on bottom for shafts
- ◆ Supplied with measuring software



Rechargeable battery



Lithium battery socket





Charging cable



Control box



Wireless transmitter



SPECIFICATION

Code	720-250-01	
Resolution(adjustable)	10μm/m	1μm/m
Range	±5000μm/m	±500μm/m
Display range	0-±500(numbers)	0-±2500(numbers)
Accuracy	±(1+A×2%)note: A is the absolute value of the nominal value of the identification location	
Response time	<3 sec	
Data output	433	
Repeatability	≤1 number	
Working temperature	20°C±2°C	
Working humidity	<75%	
Power supply	rechargeable battery	
Size	150x47x170mm	
Weight	1.8kg	

INCLUDED ACCESSORIES


Charging cable	1pc
Control box	1pc
Rechargeable battery	2pcs
Wireless transmitter	1pc
Lithium battery socket	1pc
Measuring software	1pc

721


DIGITAL LEVEL




- ◆ Use as level or protractor
- ◆ Accuracy: $\pm 0.1^\circ$ (vertical and horizontal), $\pm 0.2^\circ$ (other direction)
- ◆ Absolute horizontal reference can save in memory for ever
- ◆ Button: on/off, zero
- ◆ Magnetic base
- ◆ Use in 4 directions
- ◆ Automatic power off



Use as level



Use as protractor




Code	Range	Resolution
721-180-01	0 - 360° (90°x4)	0.05°

722


DIGITAL LEVEL




- ◆ Use as level or protractor
- ◆ Resolution: 0.05°
- ◆ Accuracy: $\pm 0.1^\circ$ (vertical and horizontal), $\pm 0.2^\circ$ (other direction)
- ◆ Magnetic base, with groove
- ◆ Aluminum frame provides with high rigidity and low weight
- ◆ Absolute horizontal reference can save in memory for ever




use in 4 directions



Use as level



Use as protractor



Code	Range	Dimension(LxWxH)
722-360-01	0 - 360° (90°x4)	150x60x33mm



LEVEL

723

DIGITAL LEVEL




- ◆ Use as level or protractor
- ◆ Use in 4 directions
- ◆ Magnetic base
- ◆ Accuracy : $\pm 0.1^\circ$ (vertical and horizontal), $\pm 0.2^\circ$ (other direction)
- ◆ Metal cover
- ◆ Adjust the display direction automatically



unit: mm


Magnetic base

Use as level



absolute horizontal

Use as protractor



set reference

reference

Code	Range	Resolution
723-360-01	0 - 360° (4x90°)	0.05°

725



DIGITAL LEVEL



- ◆ Use as level or protractor
- ◆ Accuracy : $\pm 0.1^\circ$ (vertical and horizontal), $\pm 0.2^\circ$ (other direction)
- ◆ Buttons: on/off, ABS, hold, alarm unit, backlight
- ◆ With vertical and horizontal vials
- ◆ Absolute horizontion reference can save in memory for ever
- ◆ Magnetic base
- ◆ Adjust the display direction automatically



unit: mm




magnet

magnet


magnet

Use as level



absolute horizontal

Use as protractor



set reference



reference

Code	Range	Resolution
725-360-01	0 - 360° (4x90°)	0.05°

160

CHAMFER GAUGE

- ◆ Measure 45° chamfer dimension
- ◆ Graduation 0.02mm
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface



Code	Range	Accuracy
160-001-11	0-6mm	±0.06mm



SERIES 160

CHAMFER GAUGE

- ◆ Measure α chamfer dimension
- ◆ Graduation 0.02mm
- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface



160-010-12





Code	Range	Accuracy	Chamfer(α)
160-010-11	0-10mm	±0.06mm	30°
160-010-12	0-10mm	±0.06mm	45°
160-010-13	0-10mm	±0.06mm	60°

163

DIGITAL CHAMFER GAUGE



- ◆ Measure 45° chamfer dimension
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code :100-03 or 100-04)
- ◆ Made of stainless steel



Code	Range	Accuracy
163-006-11	0-6mm/0-0.24"	±0.06mm

SERIES 163



DIGITAL CHAMFER GAUGE



- ◆ Measure α chamfer dimension
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code :100-03 or 100-04)
- ◆ Made of stainless steel



163-010-12





Code	Range	Accuracy	Chamfer(α)
163-010-11	0-10mm/0-0.39"	±0.06mm	30°
163-010-12	0-10mm/0-0.39"	±0.06mm	45°
163-010-13	0-10mm/0-0.39"	±0.06mm	60°



164-001-11



164-002-11




unit: mm

Setzero




- ◆ Resolution: 0.01mm
- ◆ Made of stainless steel

Measure chamfer radius



Measure leg length of 45° chamfer




Code	Range of radius (R)	Range of leg length (C)	Accuracy
164-001-11	0-15mm	0-6mm	±0.05mm
164-002-11	0-30mm	0-18mm	±0.05mm


967

CHAMFER GAUGE

- ◆ To measure internal and external chamfers
- ◆ Made of stainless steel



unit: mm



Package



Code	Graduation	Accuracy
967-001-11	0.5mm	±0.25mm

195



DIGITAL KEYWAY GAUGE



- ◆ Measure the depth of keyway
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code :100-03 or 100-04)
- ◆ Made of stainless steel



Measure



Code	Range	Accuracy
195-002-11	0-50mm/0-2"	±0.03mm

196



DIGITAL KEYWAY GAUGE



- ◆ Measure the keyway depth of cylindrical workpieces with a diameter of Ø0-100mm
- ◆ Button: on/off, zero, mm/inch, ABS, data preset, change measuring direction
- ◆ Automatic power off
- ◆ Data output(cable code:200-03 or 200-04)
- ◆ Stainless steel base
- ◆ Pointed tip (Code: 270-006-21)



Measure






Code	Range	Resolution	Accuracy
196-001-11	0-25.4mm/0-1"	0.01mm/0.0005"	±0.02mm

998

VERNIER STEP GAUGE

- ◆ Measure the height difference of two surface
- ◆ Resolution: 0.05mm



unit: mm



Code	Range	Accuracy
998-010-11	-10~+10mm	±0.05mm

999

DIGITAL STEP GAUGE



- ◆ Measure the height difference of two surface
- ◆ Resolution: 0.01mm
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code : 100-03 or 100-04)
- ◆ Automatic power off
- ◆ Stainless steel base



unit: mm

Code	Range	Accuracy
999-010-11	-10~+10mm	±0.05mm


STEP GAUGE

SERIES 999


MINI DIGITAL HEIGHT GAUGE



- ◆ Measure height difference of two surfaces
(999-020-12 suitable for surfaces with barrier, such as screw)
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code :100-03 or 100-04)
- ◆ Automatic power off
- ◆ Made of stainless steel




999-020-11



999-020-12

Code	Range	Accuracy
999-020-11	0-±20mm/0-±0.8"	±0.02mm
999-020-12	0-±20mm/0-±0.8"	±0.02mm




437


STEP AND GAP GAUGE




- ◆ Measure step height and gap width
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Automatic power on/off
- ◆ Data output(cable code :100-03 or 100-04)
- ◆ Made of stainless steel
- ◆ Supplied with zero setting block




Code	Range	Accuracy
437-001-11	0-12.7mm/0-0.5"	±0.03mm




Zero setting block(included)



- ◆ Meets DIN2275
- ◆ Accuracy: $\pm(3+T/80)\mu\text{m}$, T is the thickness of leaves, unit: μm
- ◆ Made of hardened spring steel




unit: mm




Code	Range	Quantity	Leaves thickness (mm)
911-100-25	0.04 - 1.00mm	25	0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00

- ◆ Meets DIN2275
- ◆ Accuracy: $\pm(3+T/80)\mu\text{m}$, T is the thickness of leaves, unit: μm
- ◆ Made of hardened spring steel



unit: mm



912-100-20

Code	Range	Quantity	Leaves thickness (mm)
912-050-13	0.03 - 0.50mm	13	0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.30, 0.40, 0.50
912-100-13	0.05 - 1.00mm	13	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, 0.90, 1.00
912-100-17	0.02 - 1.00mm	17	0.02, 0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.75, 1.00
912-100-20	0.05 - 1.00mm	20	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00
912-100-32	0.03 - 1.00mm	32	0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.13, 0.15, 0.18, 0.20, 0.23, 0.25, 0.28, 0.30, 0.33, 0.35, 0.38, 0.40, 0.45, 0.50, 0.55, 0.60, 0.63, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 1.00




SERIES 913/914/915


FEELER

- ◆ Meets DIN2275
- ◆ Accuracy: $\pm(3+T/80)\mu\text{m}$, T is the thickness of leaves, unit: μm
- ◆ Made of hardened spring steel

913-100-20



L	A	B
150	135	295
200	185	395
300	285	590



Code	Range	Quantity	Leaves thickness (mm)	L
913-100-13	0.05 - 1.00mm	13	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, 0.90, 1.00	150
914-100-13	0.05 - 1.00mm	13		200
915-100-13	0.05 - 1.00mm	13		300
913-100-17	0.02 - 1.00mm	17	0.02, 0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.75, 1.00	150
914-100-17	0.02 - 1.00mm	17		200
915-100-17	0.02 - 1.00mm	17		300
913-100-20	0.05 - 1.00mm	20	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00	150
914-100-20	0.05 - 1.00mm	20		200
915-100-20	0.05 - 1.00mm	20		300

SERIES 916

FEELER TAPE

- ◆ Used to check the spacing thickness
- ◆ Made of hardened alloy steel
- ◆ Length 5m
- ◆ Width 13mm



916-010-01

Code	Thickness	Accuracy
916-001-01	0.01mm	$\pm 3\mu\text{m}$
916-002-01	0.02mm	$\pm 4\mu\text{m}$
916-003-01	0.03mm	$\pm 4\mu\text{m}$
916-004-01	0.04mm	$\pm 4\mu\text{m}$
916-005-01	0.05mm	$\pm 4\mu\text{m}$
916-006-01	0.06mm	$\pm 4\mu\text{m}$
916-007-01	0.07mm	$\pm 5\mu\text{m}$
916-008-01	0.08mm	$\pm 5\mu\text{m}$
916-009-01	0.09mm	$\pm 5\mu\text{m}$
916-010-01	0.10mm	$\pm 5\mu\text{m}$

Code	Thickness	Accuracy
916-015-01	0.15mm	$\pm 5\mu\text{m}$
916-018-01	0.18mm	$\pm 7\mu\text{m}$
916-020-01	0.20mm	$\pm 8\mu\text{m}$
916-025-01	0.25mm	$\pm 9\mu\text{m}$
916-030-01	0.30mm	$\pm 9\mu\text{m}$
916-035-01	0.35mm	$\pm 11\mu\text{m}$
916-040-01	0.40mm	$\pm 12\mu\text{m}$
916-045-01	0.45mm	$\pm 12\mu\text{m}$
916-050-01	0.50mm	$\pm 14\mu\text{m}$
916-055-01	0.55mm	$\pm 14\mu\text{m}$


Code	Thickness	Accuracy
916-060-01	0.60mm	$\pm 14\mu\text{m}$
916-065-01	0.65mm	$\pm 14\mu\text{m}$
916-070-01	0.70mm	$\pm 17\mu\text{m}$
916-075-01	0.75mm	$\pm 17\mu\text{m}$
916-080-01	0.80mm	$\pm 19\mu\text{m}$
916-085-01	0.85mm	$\pm 19\mu\text{m}$
916-090-01	0.90mm	$\pm 22\mu\text{m}$
916-095-01	0.95mm	$\pm 22\mu\text{m}$
916-100-01	1.00mm	$\pm 24\mu\text{m}$

917**INCH FEELER GAUGE**


- ◆ .010" is made of brass, others are made of hardened alloy steel
- ◆ Each blade is marked with inch/metric size

Code	Range	Quantity of leaves
917-035-31	.0015" ~ .035"	32

Thickness of leaves included	Accuracy
.010" (brass)	±.00039"
.0015", .002"	±.0002"
.0025"~ .007"	±.00028"
.008", .009"	±.00035"
.010", .011"	±.00039"
.012", .013"	±.00047"
.014", .015"	±.00051"
.016", .017"	±.00055"
.018", .019"	±.00059"
.020", .021"	±.00067"
.022", .023"	±.00071"
.024", .025", .026"	±.00075"
.028"	±.00091"
.030"	±.00094"
.032", .035"	±.00102"

**919****OFFSET DUAL SCALE FEELER GAUGE**

- ◆ Bend end
- ◆ Blade: length 4"
- ◆ Each blade is marked with imperial/metric size
- ◆ Made of hardened spring steel




Code	Range	Quantity	Leaves thickness
919-030-26	0.005-0.020"	26	.005(.127mm), .006(.152mm), .007(.178mm), .008(.203mm), .009(.229mm), .010(.254mm), .011(.279mm), .012(.305mm), .013(.330mm), .014(.356mm), .015(.381mm), .016(.406mm), .017(.432mm), .018(.457mm), .019(.483mm), .020(.508mm), .021(.533mm), .022(.559mm), .023(.584mm), .024(.610mm), .025(.635mm), .026(.660mm), .027(.686mm), .028(.711mm), .029(.737mm), .030(.762mm)

SERIES 921

PITCH GAUGE

- ◆ Measure the pitch of thread
- ◆ Accuracy: $\pm 0.07\text{mm}$
- ◆ Made of medium carbon steel




921-012-16

Code	Range	Thread	Quantity	Leaves pitch(mm)
921-020-12	2 - 20mm	Tr30°	12	2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 16, 20mm
921-012-16	1 - 12TPI	ACME29°	16	1, 1-1/3, 1-1/2, 1-3/4, 2, 2-1/2, 3, 3-1/2, 4, 5, 6, 7, 8, 9, 10, 12TPI

SERIES 922/923/924/925

PITCH GAUGE

- ◆ Measure the pitch of thread
- ◆ Accuracy: $\pm 0.07\text{mm}$
- ◆ Made of medium carbon steel



922-007-22

METRIC 60° SCREW

Code	Range	Quantity	Leaves pitch
922-007-22	0.4 - 7.0mm	22	0.4, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7mm
922-007-24	0.25 - 7.0mm	24	0.25, 0.3, 0.35, 0.4, 0.5, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7mm
922-006-24	0.25 - 6.0mm	24	0.25, 0.3, 0.35, 0.4, 0.45, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6mm
922-025-28	0.25 - 2.5mm	28	0.25, 0.3, 0.35, 0.4, 0.45, 0.5, 0.55, 0.6, 0.65, 0.7, 0.75, 0.8, 0.85, 0.9, 1.0, 1.1, 1.2, 1.25, 1.3, 1.4, 1.5, 1.6, 1.7, 1.75, 1.8, 1.9, 2.0, 2.5mm

UNIFIED 60° SCREW

Code	Range	Quantity	Leaves pitch
923-042-30	4 - 42TPI	30	4, 4-1/2, 5, 5-1/2, 6, 7, 8, 9, 10, 11, 11-1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42TPI

WHITWORTH 55° SCREW

Code	Range	Quantity	Leaves pitch
924-042-30	4 - 42TPI	30	4, 4-1/2, 5, 5-1/2, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 18, 19, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42TPI
924-062-28	4 - 62TPI	28	4, 4-1/2, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 36, 40, 48, 60, 62TPI

METRIC 60° AND WHITWORTH 55° SCREW


Code	Range	Quantity	Leaves pitch
925-062-52	0.25 - 6.0mm and 4 - 62TPI	52	pitch of 922-006-24 and 924-062-28

SERIES 926


CENTER GAUGE

- ◆ Check the screw angle and pitch
- ◆ Accuracy: $\pm 30'$
- ◆ Made of stainless steel


Package



926-060-02




Code	Screw type	Angle(α)	Graduation
926-060-01	metric 60°	60°	0.5mm and 1mm
926-060-02	unified 60°	60°	front side: 1/14" and 1/20", reverse side: 1/24" and 1/32"
926-055-01	whitworth 55°	55°	front side: 1/14" and 1/20", reverse side: 1/24" and 1/32"




SERIES 927

THREAD GAUGE


- ◆ To check and set screw cutting tools
- ◆ Angle accuracy: $\pm 10\text{min}$.
- ◆ Made of medium carbon steel



927-008-01



927-008-01



927-012-01

Package





Code	Range	Thread type	Pitch
927-008-01	1 - 10TPI	ACME 29°	1, 1-1/3, 1-1/2, 1-3/4, 2, 2-1/2, 3, 4, 5, 6, 7, 8, 9, 10TPI
927-012-01	2 - 12mm	Tr 30°	2, 3, 4, 5, 6, 7, 8, 9, 10, 12mm



933

ANGLE GAUGE

- ◆ To check and set screw cutting tools
- ◆ Angle accuracy: $\pm 10'$
- ◆ Made of medium carbon steel



Package



Code	Pitch	Angle(α)
933-008-11	2, 2.5, 3, 3.5, 4, 4.5, 5, 6, 7, 8TPI	45°, 53.8°, 55°, 60°, 70°



930

ANGLE GAUGE

- ◆ Made of stainless steel



Check the angle of screw cutting tools



Code	Range	Accuracy
930-001-01	29°, 30°, 40°, 45°, 50°, 55°, 60°, 65°	$\pm 10'$





934

ANGLE GAUGE

- ◆ Made of stainless steel



Check the angle of screw cutting tools




Code	Range	Accuracy
934-001-11	55°, 60°, 47 1/2° BA, 14 1/2° ACME	±10'

931

ANGLE GAUGE

- ◆ Check the coangle
- ◆ Accuracy: ±30'



Code	Range	Quantity	Leaves angle(α)
931-045-20	1° - 45°	20	1°, 2°, 3°, 4°, 5°, 6°, 7°, 8°, 9°, 10°, 12°, 14°, 16°, 18°, 20°, 25°, 30°, 35°, 40°, 45°



932

ANGLE GAUGE SET

- ◆ Each blade checks primary, 1/2 primary and complementary angles


Code	Quantity of leaves	Accuracy
932-018-01	18	±10'

Primary angle	1/2 primary angle	Complementary angle
5°	2°30'	175°
10°	5°	170°
15°	7°30'	165°
20°	10°	160°
25°	12°30'	155°
30°	15°	150°
35°	17°30'	145°
40°	20°	140°
45°	22°30'	135°
50°	25°	130°
55°	27°30'	125°
60°	30°	120°
65°	32°30'	115°
70°	35°	110°
75°	37°30'	105°
80°	40°	100°
85°	42°30'	95°
90°	45°	90°




SERIES 941

RADIUS GAUGE



941-015-32

- ◆ Check the radius
- ◆ With concave and convex surface in each size




Code	Range	Quantity	Accuracy	Leaves radius (mm)
941-007-34	1 - 7mm	17x2	±0.03mm	1, 1.25, 1.5, 1.75, 2, 2.25, 2.5, 2.75, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7
941-015-32	7.5 - 15mm	16x2	±0.035mm	7.5, 8, 8.5, 9, 9.5, 10, 10.5, 11, 11.5, 12, 12.5, 13, 13.5, 14, 14.5, 15
941-025-30	15.5 - 25mm	15x2	±0.042mm	15.5, 16, 16.5, 17, 17.5, 18, 18.5, 19, 19.5, 20, 21, 22, 23, 24, 25



942

RADIUS GAUGE

- ◆ Each piece has 2 concave and 3 convex surfaces
- ◆ With handle
- ◆ Accuracy: $\pm 0.05\text{mm}$




Code	Range	Quantity	Included radius(mm)
942-013-26	0.5 - 13mm	26	0.5, 1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7, 7.5, 8, 8.5, 9, 9.5, 10, 10.5, 11, 11.5, 12, 12.5, 13

951


TELESCOPING GAUGE SET



- ◆ 6 gauges per set
- ◆ For quick measurement of inside diameter of holes and width of slots
- ◆ Satin chrome finish



Code	Each gauge range	L	a	b	c
951-006-01	8-12.7mm	115mm	Ø3.9mm	Ø2.9mm	Ø6.2mm
	12.7-19mm	115mm	Ø5.3mm	Ø3.8mm	Ø6.2mm
	19-32mm	115mm	Ø5.3mm	Ø3.8mm	Ø6.2mm
	32-54mm	137mm	Ø7.6mm	Ø6.1mm	Ø7.2mm
	54-90mm	137mm	Ø7.6mm	Ø6.1mm	Ø7.2mm
	90-150mm	137mm	Ø7.6mm	Ø6.1mm	Ø7.2mm



952

SMALL HOLE GAUGE SET


- ◆ 4 gauges per set
- ◆ For small holes, slots and grooves, etc.
- ◆ Satin chrome finish



Ball type




unit: mm



Code	Range	L	a	Ød
952-004-01	3-5mm	77	24	6
	5-7.5mm	77	25	6
	7.5-10mm	87	28.5	7
	10-13mm	92	32	7

Use



952

SMALL HOLE GAUGE SET


- ◆ 4 gauges per set
- ◆ For small holes, slots and grooves, etc.
- ◆ Satin chrome finish



Flat type




unit: mm



Code	Range	L	a	Ød
952-004-02	3-5mm	91	24	6
	5-7.5mm	98	31	6
	7.5-10mm	108	41	7
	10-13mm	109	42	7


Use



SERIES 953

LONG HANDLE TELESCOPING GAUGE


- ◆ For quick measuring inside diameter of deep holes and width of slots
- ◆ Satin chrome finish



953-006-01

Code	Range	L	Øa	Øb	Øc
953-001-01	8-12.7mm	250mm	3.9mm	2.9mm	6.2mm
953-002-01	12.7-19mm	250mm	5.3mm	3.8mm	6.2mm
953-003-01	19-32mm	250mm	5.3mm	3.8mm	6.2mm
953-004-01	32-54mm	300mm	7.6mm	6.1mm	7.2mm
953-005-01	54-90mm	300mm	7.6mm	6.1mm	7.2mm
953-006-01	90-150mm	300mm	7.6mm	6.1mm	7.2mm

Use




SERIES 963

DIGITAL TAPER GAUGE




963-010-11




unit: mm

- ◆ Measuring opening, slot width
- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Automatic power on/off
- ◆ Made of stainless steel



963-020-11, 963-030-11 and 963-040-11

Measure slot width(reading/10)



Code	Range	Accuracy	h
963-010-11	0.2-10mm/0.01-0.39"	±0.03mm	-
963-020-11	10-20mm/0.39-0.79"	±0.05mm	10
963-030-11	20-30mm/0.79-1.18"	±0.05mm	20
963-040-11	30-40mm/1.18-1.58"	±0.05mm	30

SIMPLE
MEASURING TOOL




SERIES 961

TAPER GAUGE


- ◆ Measure the gap width
- ◆ Stain chrome plated reading surface
- ◆ Made of the stainless steel



961-010-05



Code	Range	Graduation	Accuracy	L	W	H
961-004-05	0.2 - 4mm	0.05mm	±0.05mm	120	12	4.3
961-006-05	0.4 - 6mm	0.05mm	±0.05mm	166	11.5	6.5
961-010-05	0.5 - 10mm	0.05mm	±0.05mm	225	12.5	10.5
961-015-05	0.5 - 15mm	0.1mm	±0.05mm	184	11	16



SERIES 962

TAPER GAUGE

- ◆ Measure the groove width and hole size
- ◆ Made of the stainless steel

Package



962-015-05





front side



reverse side

unit: mm





Code	Range	Graduation	Accuracy	L	W
962-015-05	0.8-15mm	0.1mm	±0.1mm	146	17
962-030-05	15-30mm	0.1mm	±0.1mm	159	30.4
962-045-05	30-45mm	0.1mm	±0.1mm	166	45.4
962-060-05	45-60mm	0.1mm	±0.1mm	170	60.5



962

TAPER GAUGE SET

- ◆ Include 4 pcs (1-7.5mm, 7.5-14.5mm, 14.5-21.5mm, 21.5-29mm)
- ◆ Measure opening slot width
- ◆ Made of stainless steel



Code	Range	Graduation	Accuracy
962-029-41	1-29mm	0.1mm	±0.05mm

962



TAPER GAUGE SET



front side




reverse side



- ◆ Made of stainless steel

Code	Tool	Range	Graduation	Accuracy
962-909-02	taper gage	0.8-15mm	0.1mm	±0.1mm
	steel ruler	150mm/6"	1mm/1/64"	±0.15mm







SERIES 964

TAPER BORE GAUGE

- ◆ Quick measuring diameter of the bore
- ◆ Graduation: 0.1mm
- ◆ Hardened steel, HRC50-58
- ◆ Satin chrome plated surface
- ◆ Aluminium oxidized handle



964-015-11





Code	Range	Accuracy	L	Ød1	Ød2
964-006-11	1-6.5mm	±0.05mm	62.5	7	0.8
964-015-11	3-15mm	±0.05mm	143	17	2.8
964-030-11	15-30mm	±0.05mm	165	31	14.7
964-045-11	30-45mm	±0.05mm	165	46	29.6
964-060-11	45-60mm	±0.05mm	167	61	44

970

DIGITAL WELDING GAUGE

- ◆ Buttons: zero, mm/inch, on/off
- ◆ Made of stainless steel





Code	Range	Accuracy	Resolution	Application
970-010-11	0 - 10mm	±0.03mm	0.01mm/0.0005"	measure crown height
	0 - 20mm	±0.1mm	0.01mm/0.0005"	measure fillet weld throat size
	60°, 70°, 80°, 90°	±1°	—	measure angle



971

WELDING GAUGE

- ◆ Made of stainless steel
- ◆ Stain chrome plated reading surface




Code	Range	Graduation	Accuracy	Application
971-008-01	0 - 8mm	0.1mm	±0.1mm	measure crown height
	0 - 20mm	0.1mm	±0.3mm	measure fillet weld throat size
	60°, 70°, 80°, 90°	—	±1°	measure angle

972

WELDING GAUGE

- ◆ Double printing in front and reverse side
- ◆ Made of the stainless steel

Package



Code	Leg height	Leg length	Accuracy
972-012-01	4, 5, 6, 7, 8, 9, 10, 12mm	4, 6, 7.5, 10, 12, 14, 16, 18mm	±0.5mm


◆ Made of stainless steel




front side




reverse side




measure crown height




measure leg height




measure undercut depth




measure throat size




measure weld length



measure angle




measure gap




measure length

Code	Application	Range	Graduation	Accuracy
973-014-01	measure crown height	0 - 10mm	1mm	±0.5mm
	measure leg height	0 - 14mm	1mm	±0.5mm
	measure undercut depth	0 - 5mm	0.05mm	±0.05mm
	measure throat size	0 - 13mm	1mm	±0.5mm
	measure weld length	0 - 40mm	1mm	±1mm
	measure angle	90° - 150°	5°	±1°
	measure gap	0.5 - 5mm	1mm	±0.5mm
	measure length	0 - 40mm	1mm	±0.5mm



unit: mm


- ◆ Made of stainless steel
- ◆ Stain chrome plated surface




reverse side




front side




measure leg length




measure leg height




measure crown height




measure throat size



measure angle




measure gap



measure length

Code	Application	Range	Graduation	Accuracy
974-013-01	measure leg length	0 - 10mm	0.1mm	±0.1mm
	measure leg height	0 - 20mm	1mm	±0.5mm
	measure crown height	0 - 10mm	0.1mm	±0.1mm
	measure throat size	0 - 10mm	0.1mm	±0.1mm
	measure angle	0° - 60°	5°	±1°
	measure gap	1 - 3.5mm	0.5mm	±0.5mm
	measure length	0 - 40mm	1mm	±0.5mm



unit: mm


975

WELDING GAUGE


- ♦ Adjustable scale to compensate pointer wear
- ♦ Made of stainless steel




front side




reverse side




measure crown height




measure fillet weld leg height




measure misalignment




measure undercut depth




measure fillet weld throat size



measure angle of preparation




measure length



measure 45° angle


Code	Application	Range	Graduation	Accuracy
975-025-01	measure crown height	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	measure fillet weld leg height	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	measure misalignment	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	measure undercut depth	0 - 2mm (0 - 1/8")	1mm (1/16")	±0.5mm
	measure fillet weld throat size	0 - 20mm (0 - 3/4")	1mm (1/16")	±0.5mm
	measure angle of preparation	0 - 60°	5°	±1°
	measure length	0 - 60mm (0-2")	1mm (1/16")	±0.5mm
	measure 45° angle	—	—	±1°




- ◆ Adjustable scale to compensate pointer wear
- ◆ Made of stainless steel



front side




reverse side




MEASURING TOOL
SIMPLE

Code	Application	Range	Graduation	Accuracy
975-025-02	measure crown height	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	measure fillet weld leg height	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	measure misalignment	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	measure undercut depth	0 - 2mm (0 - 1/8")	1mm (1/16")	±0.5mm
	measure fillet weld throat size	0 - 20mm (0 - 3/4")	1mm (1/16")	±0.5mm
	measure angle of preparation	0 - 60°	5°	±1°
	measure length	0 - 60mm (0 - 2")	1mm (1/16")	±0.5mm
	measure 45° angle	—	—	±1°




- ♦ Adjustable scale to compensate pointer wear
- ♦ Made of stainless steel




front side




reverse side




measure crown height




measure fillet weld leg height




measure fillet weld throat size




measure undercut depth




measure angle of preparation




measure length




measure 45° angle



measure misalignment




measure misalignment





measure gap

Code	Application	Range	Graduation	Accuracy
975-025-21	measure crown height	0 - 25mm	1mm	±0.5mm
	measure fillet weld leg height	0 - 25mm	1mm	±0.5mm
	measure fillet weld throat size	0 - 15mm	1mm	±0.5mm
	measure undercut depth	0 - 25mm	1mm	±0.5mm
	measure angle of preparation	0 - 60°	5°	±1°
	measure length	0 - 60mm	1mm	±0.5mm
	measure 45° angle	—	—	±1°
	measure misalignment	0 - 25mm	1mm	±0.5mm
	measure gap	2 - 5mm	1mm	±0.5mm



♦ Made of stainless steel





Code	Application	Range	Graduation	Accuracy
976-045-01	measure bevel on end preparation	37.5°	—	±1°
	measure pipe wall thickness	0 - 45mm (0 - 1-3/4")	1mm (1/16")	±0.5mm
	measure internal misalignment	0 - 35mm (0 - 1-3/8")	1mm (1/32")	±0.5mm
	measure fit-up gap	1.6mm, 2.2mm	—	±0.1mm
	measure crown height	0 - 35mm (0 - 1-3/8")	1mm (1/32")	±0.5mm
	measure distance between two marking lines of socket weld	0 - 60mm (0 - 2-3/8")	1mm (1/16")	±0.5mm
	measure fillet weld length	0 - 30mm (0 - 1-1/4")	1mm (1/16")	±0.5mm
	measure fillet weld height	0 - 35mm (0 - 1-3/8")	1mm (1/32")	±0.5mm



960


PIP WELDING GAUGE

- ◆ Made of stainless steel



unit: mm


Code	Measurement	Range	Graduation	Accuracy
960-030-01	internal misalignment	0-30mm	1mm	±0.5mm
	fit-up gap	0.7-4mm	0.1mm	±0.1mm




SERIES 977

FILLET WELD GAUGE

- ◆ Measure concave and convex weld sizes
- ◆ 7 blades are included
- ◆ Each blade measures two sizes of concave and convex weld
- ◆ Made of stainless steel



unit: mm





Code	Accuracy	Size
977-025-01	±0.5mm	3, 4, 5, 6, 8, 9, 10, 11, 12, 14, 16, 19, 22, 25
977-025-02	±0.02"	1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", 3/4", 7/8", 1"



745

FILLET WELDING GAUGE

- ◆ Measure convex weld sizes
- ◆ 3 blades are included
- ◆ Made of stainless steel



Code	Measurement	Range	Graduation	Accuracy
745-050-03	convex weld size	4, 6, 8, 10, 12, 14mm	—	±0.5mm
	length	0-50mm	1mm	±0.5mm


749

WELDING GAUGE

- ◆ Made of stainless steel



Application





Code	Size
749-012-01	3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7, 8, 10, 12mm

978

WELDING GAUGE

- ◆ Pointer can be locked for later reference
- ◆ Made of stainless steel






Code	Measurement	Range	Graduation	Accuracy
978-006-01	undercut depth	0 - 6mm	0.5mm	±0.5mm
	crown height	0 - 6mm	0.5mm	±0.5mm
	porosity size comparison	1.5mm, 3mm	—	±0.2mm
	amount of porosity per 25mm	25mm	1mm	—

966



WELDING GAUGE

- ◆ Made of stainless steel



Code	Graduation	Accuracy
966-001-01	0.2mm	±0.3mm





- ◆ Made of stainless steel



Code	Range	Graduation	Accuracy	Measurement
979-020-01	0-20mm	1mm	±0.5mm	leg height
	0-3mm	—	±0.5mm	crown height
	0-20mm	1mm	±0.5mm	theoretical leg height of convex weld
	0-20mm	1mm	±0.5mm	theoretical leg height of concave

- ◆ Calculating card is included
- ◆ Made of stainless steel

Calculating card (included)



Code	Measurement	Range	Graduation	Accuracy
969-050-01	weld seam height H	0 - 50mm / 0-2"	2mm/.050"	±1mm
	angle θ	30° - 90°	2.5°	±1°
	90° angle	—	—	±0.5°





746

WELDING GAUGE

◆ Made of stainless steel



unit: mm




Code	Measurement	Range	Graduation	Accuracy
746-050-01	misalignment (high-low)	-5mm-15mm	1mm	±0.5mm
	angle of preparation	0°-45°	5°	±2.5°
	length	0-50mm	1mm	±0.5mm
	gap	1-4mm	0.5mm	±0.25mm
	thickness	1, 1.2, 2.0, 2.5, 3.0, 3.25, 4.0, 5.0mm	—	±0.1mm


747

WELDING GAUGE


◆ Made of stainless steel



unit: mm



Code	Measurement	Range	Graduation	Accuracy
747-018-01	theoretical throat size (a)	2-12mm	1mm	±0.5mm
	leg height (b)	0-18mm	1mm	±0.5mm
	throat size	4, 5, 6, 7mm	—	±0.5mm
	angle of preparation	50°, 60°	—	±1°
	thickness	1.5, 2, 3.5mm	—	±0.2mm




748


PIPE PIT GAUGE

- ◆ Made of stainless steel


Application



front side



reverse side





Code	Range	Graduation	Accuracy
748-012-01	0-0.5"(0-1/2")	0.01"(1/16")	±0.02"

968

DRILL ANGLE GAUGE

- ◆ Check drills with angle 60°, 70°, 90°, 118°, 125°, 135°, 150° or 160°
- ◆ Made of stainless steel



unit: mm

Code	Accuracy
968-001-01	±0.5°


965

DRILL POINT GAUGE


- ◆ For twist drills with 118° angle, to check if the center of tip is concentric with the drill body
- ◆ Made of stainless steel



unit: mm



Application



Code	Accuracy	
	Angle	Length
965-005-01	±0.5°	±0.5mm




SERIES 741

U.S. STANDARD SHEET METAL GAUGE

Code	Range
741-036-12	0-36(7.938-0.179mm/.3125-.0070")

NO.	W	NO.	W
0	7.938mm(.3125")	19	1.111mm(.0438")
1	7.144mm(.2813")	20	0.953mm(.0375")
2	6.747mm(.2656")	21	0.873mm(.0344")
3	6.350mm(.2500")	22	0.794mm(.0313")
4	5.953mm(.2344")	23	0.714mm(.0281")
5	5.556mm(.2188")	24	0.635mm(.0250")
6	5.159mm(.2031")	25	0.556mm(.0219")
7	4.763mm(.1875")	26	0.476mm(.0188")
8	4.366mm(.1719")	27	0.437mm(.0172")
9	3.969mm(.1563")	28	0.397mm(.0156")
10	3.572mm(.1406")	29	0.357mm(.0141")
11	3.175mm(.1250")	30	0.318mm(.0125")
12	2.778mm(.1094")	31	0.278mm(.0109")
13	2.381mm(.0938")	32	0.258mm(.0102")
14	1.984mm(.0781")	33	0.238mm(.0094")
15	1.786mm(.0703")	34	0.218mm(.0086")
16	1.588mm(.0625")	35	0.198mm(.0078")
17	1.429mm(.0563")	36	0.179mm(.0070")
18	1.270mm(.0500")		




- ◆ For gaging sheet metal, plate iron and steel
- ◆ Hardened

SERIES 741

AMERICAN STANDARD WIRE GAUGE

Code	Range
741-036-11	0-36(8.250-0.127mm/.3249-.0050")

NO.	W	NO.	W
0	8.250mm(.3249")	19	0.912mm(.0359")
1	7.350mm(.2893")	20	0.813mm(.0320")
2	6.540mm(.2576")	21	0.724mm(.0285")
3	5.830mm(.2294")	22	0.643mm(.0253")
4	5.190mm(.2043")	23	0.574mm(.0226")
5	4.620mm(.1819")	24	0.511mm(.0201")
6	4.110mm(.1620")	25	0.440mm(.0179")
7	3.670mm(.1443")	26	0.404mm(.0159")
8	3.260mm(.1285")	27	0.361mm(.0142")
9	2.910mm(.1144")	28	0.320mm(.0126")
10	2.590mm(.1019")	29	0.287mm(.0113")
11	2.300mm(.0907")	30	0.254mm(.0100")
12	2.050mm(.0808")	31	0.226mm(.0089")
13	1.820mm(.0720")	32	0.203mm(.0080")
14	1.630mm(.0641")	33	0.180mm(.0071")
15	1.450mm(.0571")	34	0.160mm(.0063")
16	1.290mm(.0508")	35	0.142mm(.0056")
17	1.150mm(.0453")	36	0.127mm(.0050")
18	1.020mm(.0403")		





- ◆ For gaging non-ferrous wire and metals such as copper, brass and aluminum
- ◆ Hardened

940

GAP/DIAMETER GAUGE

- ◆ Made of stainless steel





Code	Standard diameter	Gap
940-010-01	2, 3, 4, 5, 6, 7, 8, 9, 10mm	0.1-1.7mm

742

THICKNESS GAUGE

- ◆ Made of stainless steel




Code	Application	Range	Graduation	Accuracy
742-003-11	length	0-2 3/4"	1/16"	1/32"
	thickness	24GA.(.0239"), 22GA.(.0299"), 20GA.(.0359")	—	±0.002"
		18GA.(.0478"), 16GA.(.0598"), 14GA.(.0747"), 1/8"(0.125"), 10GA.(.1345"), 3/16"(0.1875"), 1/4"(0.250"), 5/16"(0.3125")	—	±0.004"
		0.024", 0.030", 0.035"	—	±0.002"


SERIES 981

INSIDE CALIPER

◆ Made of carbon steel



981-006-01



Code	Size(L)	Range(W)	h
981-006-01	150mm	15 - 150mm	2
981-008-01	200mm	15 - 200mm	2
981-010-01	250mm	15 - 250mm	3
981-012-01	300mm	15 - 300mm	3
981-016-01	400mm	30 - 400mm	3
981-020-01	500mm	30 - 500mm	3
981-024-01	600mm	30 - 600mm	3
981-032-01	800mm	30 - 800mm	4
981-040-01	1000mm	30 - 1000mm	4


Package (size ≤ 300mm)




SERIES 982

INSIDE SPRING CALIPER

◆ Made of carbon steel



982-006-01



Code	Size(L)	Range(W)	Type
982-005-01	125mm	15 - 115mm	A
982-006-01	150mm	15 - 140mm	A
982-008-01	200mm	18 - 190mm	A
982-010-01	250mm	20 - 240mm	A
982-012-01	300mm	20 - 290mm	A
982-016-01	400mm	20 - 390mm	B
982-020-01	500mm	25 - 490mm	B
982-024-01	600mm	25 - 590mm	B


Package (size ≤ 300mm)




SERIES 983

OUTSIDE CALIPER

◆ Made of carbon steel



983-006-01



unit: mm

Code	Size(L)	Range(W)	h
983-006-01	150mm	0-150mm	2
983-008-01	200mm	0-200mm	2
983-010-01	250mm	0-250mm	3
983-012-01	300mm	0-300mm	3
983-016-01	400mm	0-400mm	3
983-020-01	500mm	0-500mm	3
983-024-01	600mm	0-600mm	3
983-032-01	800mm	0-800mm	4
983-040-01	1000mm	0-1000mm	4


Package (size ≤ 300mm)




SERIES 984

OUTSIDE SPRING CALIPER

◆ Made of carbon steel



984-005-01



unit: mm

Code	Size(L)	Range(W)	Type
984-005-01	125mm	0-115mm	A
984-006-01	150mm	0-140mm	A
984-008-01	200mm	0-190mm	A
984-010-01	250mm	0-240mm	A
984-012-01	300mm	0-290mm	A
984-016-01	400mm	0-390mm	B
984-020-01	500mm	0-490mm	B
984-024-01	600mm	0-590mm	B

Package (size ≤ 300mm)



SERIES 985



SPRING DIVIDER

- ◆ Made of carbon steel
- ◆ Hardened points

Package (size ≤ 300mm)



985-005-01



Code	Size(L)	Range(W)	Type
985-005-01	125mm	0 - 115mm	A
985-006-01	150mm	0 - 140mm	A
985-008-01	200mm	0 - 190mm	A
985-010-01	250mm	0 - 240mm	A
985-012-01	300mm	0 - 290mm	B
985-016-01	400mm	0 - 390mm	B
985-020-01	500mm	0 - 490mm	B
985-024-01	600mm	0 - 590mm	B


SERIES 986

DIVIDER


- ◆ Made of carbon steel
- ◆ Hardened points



986-005-01




Package (size ≤ 300mm)



Code	Size(L)	Range(W)	a	b
986-005-01	125mm	0 - 115mm	8.5	7
986-006-01	150mm	0 - 140mm	8.5	7
986-008-01	200mm	0 - 190mm	10	7
986-010-01	250mm	0 - 240mm	11	7
986-012-01	300mm	0 - 290mm	12	7
986-016-01	400mm	0 - 390mm	12	7
986-020-01	500mm	0 - 490mm	12	7
986-024-01	600mm	0 - 590mm	12	7
986-032-01	800mm	0 - 790mm	16	11
986-040-01	1000mm	0 - 990mm	16	11



990-006-11



Range >1000mm

- ◆ Graduation: 0.5mm, 1mm, 1/64", 1/32", 1/16"
- ◆ Made of stainless steel



Code	Range	Accuracy	T	L	W	Remark
990-006-11	150mm/6"	±0.18mm	1	170	18	graduation on front and back
990-008-11	200mm/8"	±0.18mm	1	220	18	graduation on front and back
990-012-11	300mm/12"	±0.27mm	1	330	25	graduation on front and back
990-020-11	500mm/20"	±0.27mm	1	530	30	graduation on front and back
990-040-11	1000mm/40"	±0.45mm	1.5	1040	32	graduation on front and back
990-060-11	1500mm/60"	±0.63mm	1.5	1550	38	graduation on front
990-080-11	2000mm/80"	±0.80mm	2	2065	38	graduation on front


front side



reverse side



990-012-11H




- ◆ Graduation: 0.5mm, 1mm, 1/64", 1/50", 1/32", 1/20", 1/16", 1/10"
- ◆ Matt finished
- ◆ Made of stainless steel

Code	Range	Accuracy	T	L	W
990-006-11H	150mm/6"	±0.08mm	1	170	14
990-012-11H	300mm/12"	±0.11mm	1	334	25
990-020-11H	500mm/20"	±0.14mm	1.2	534	28.5
990-024-11H	600mm/24"	±0.16mm	1.2	638	28.5
990-040-11H	1000mm/40"	±0.24mm	1.2	1043	35

909

POCKET RULE WITH SLIDING CLIP


- ◆ With sliding clip, clip can be inserted in the pocket, also can be used as depth gage base
- ◆ Inch/metric conversion table on the back
- ◆ Made of stainless steel



front side



reverse side




Code	Range	Graduation	Accuracy
909-006-11	150mm/6"	1mm, 1/64"	±0.15mm

SERIES 989

MEASURING TAPE



989-005-01




- ◆ Matt Nylon coating tape, wear resistance

Code	Range	Graduation	Width of tape L	W	H
989-003-01	0-3m	1mm	16mm	33	60
989-005-01	0-5m	1mm	19mm	33	68

988

MEASURING WHEEL

- ◆ ABS plastic frame, wear-resistant PU tire
- ◆ Three-section adjustable handle



Code	Range	Resolution
988-100-11	0.1-9999.9m	0.1m

SERIES 155


DIGITAL SCRIBING CALIPER



MEASURING TOOL
SIMPLE






Carbide tipped jaws



155-006-11

- ◆ Carbide -tipped jaws facilitate fine scribing on workpiece
- ◆ Resolution:0.01mm/0.0005"
- ◆ Automatic power on/off
- ◆ Buttons: on/off, zero, mm/in, INC
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel





Code	Range	Accuracy	a	b	c	h1	h2	L
155-006-11	0-150mm/0-6"	±0.03mm	21	16.5	16	40	33	236
155-008-11	0-200mm/0-8"	±0.03mm	24	19.5	16	50	43	286
155-012-11	0-300mm/0-12"	±0.04mm	25	20.5	17	60	53	386

900

SCRIBING CALIPER



- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface
- ◆ Carbide scriber tip
- ◆ With accessory: carbide scriber tip





Code	Range	Graduation	Accuracy
900-008-11	0-200mm/0-8"	0.1mm, 1/128"	±0.1mm

902

T-SHAPE MARKING GAUGE

- ◆ Made of stainless steel
- ◆ Satin chrome plated reading surface






Code	Range	Graduation	Accuracy
902-006-51	0-150mm	0.05mm	±0.05mm

903

HEIGHT SCRIBER

- ◆ Grooved bottom for cylinder
- ◆ Two pins to be set against the edge of surface plate



Code

903-012-11

SERIES 992


MARKING GAUGE

- ◆ Made of stainless steel
- ◆ Stain chrome finish




992-008-01

unit: mm



Code	Range	Accuracy	Graduation	H	L
992-008-01	0 - 200mm	±0.1mm	0.1mm	40	250
992-010-01	0 - 250mm	±0.1mm	0.1mm	40	300
992-012-01	0 - 300mm	±0.1mm	0.1mm	40	350





SERIES 993

CENTER MARKING GAUGE

- ♦ Find the center of round plates and shafts
- ♦ Made of stainless steel
- ♦ Stain chrome plated



993-004-01



Code	Size (AxB)	Diameter(Ød)	Accuracy	C	L
993-004-01	100x70mm	4 - 90mm	±0.15mm	12	153
993-006-01	150x130mm	4 - 190mm	±0.15mm	15	245
993-008-01	200x150mm	6 - 220mm	±0.15mm	15	310
993-012-01	300x180mm	6-270mm	±0.15mm	20	435



995

SCRIBER

- ♦ Nickel plated



unit: mm



Package




Code	Tips	L
995-009-01	hardened tips	235




995

SCRIBER

◆ Nickel plated



unit: mm



Package



Code	Tips	L
995-007-01	hardened tips	167


995

SCRIBER


◆ Nickel plated



clip



unit: mm



Code	Tips
995-006-11	carbide



SERIES 996

DIGITAL HORIZONTAL SCALE



Type A

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Buttons: on/off, zero, mm/inch
- ◆ Automatic power off
- ◆ Data output(cable code: 100-03 or 100-04)
- ◆ Made of stainless steel
- ◆ Supplied with bracket
- ◆ Optional accessory: SPC cable


Type B

- ◆ Resolution: 0.01mm/0.0005"
- ◆ Absolute and incremental measurement
- ◆ Data output
- ◆ Made of stainless steel
- ◆ Supplied with bracket



996-006-11

unit: mm




Type A




996-020-11

Bracket(included)




unit: mm



Type B


Code	Range	Accuracy	Type	L
996-004-11	100mm	±0.03mm	A	209
996-006-11	150mm	±0.03mm	A	259
996-008-11	200mm	±0.03mm	A	310
996-012-11	300mm	±0.04mm	A	444
996-020-11	500mm	±0.05mm	B	682
996-024-11	600mm	±0.08mm	B	790
996-032-11	800mm	±0.10mm	B	990
996-040-11	1000mm	±0.10mm	B	1240



997-012-11

- ◆ Resolution: 0.01 mm/0.0005"
- ◆ Data output
- ◆ Button: on/off, zero, mm/inch, ABS, data preset
- ◆ Made of stainless steel
- ◆ Supplied with bracket

Bracket(included)



Code	Range	Accuracy	a	b	c	d	e	L
997-004-11	100mm	±0.03mm	4	6	20	24	40	245
997-006-11	150mm	±0.03mm	4	6	20	24	40	296
997-008-11	200mm	±0.03mm	4	6	20	24	40	345
997-012-11	300mm	±0.04mm	4	6	20	24	40	444
997-020-11	500mm	±0.05mm	5.5	8	24	32	45	682
997-024-11	600mm	±0.08mm	5.5	8	24	32	45	790
997-032-11	800mm	±0.10mm	10.5	9.5	31	32	60	990
997-040-11	1000mm	±0.10mm	10.5	9.5	31	40	60	1240

SERIES 611

GRANITE SURFACE PLATE



- ◆ Made of fine-grained granite
- ◆ Customized size can be ordered



Grade 00

Code	Size(LxWxH)	Flatness	Weight(Kg)
611-032-00	300x200x60mm	2.7μm	11
611-042-00	400x250x60mm	2.9μm	18
611-044-00	400x400x60mm	3.1μm	29
611-053-00	500x315x70mm	3.2μm	33
611-064-00	630x400x80mm	3.5μm	60
611-066-00	630x630x100mm	3.8μm	119
611-085-00	800x500x100mm	3.9μm	120
611-106-00	1000x630x140mm	4.4μm	265
611-107-00	1000x750x150mm	4.5μm	337
611-101-00	1000x1000x150mm	4.8μm	450
611-121-00	1200x800x160mm	4.9μm	461
611-161-00	1600x1000x180mm	5.8μm	864
611-201-00	2000x1000x220mm	6.5μm	1320
611-215-00	2000x1500x250mm	7.0μm	2250

Grade 0

611-032-00

Code	Size(LxWxH)	Flatness	Weight(Kg)
611-032-10	300x200x60mm	5.4μm	11
611-042-10	400x250x60mm	5.9μm	18
611-044-10	400x400x60mm	6.3μm	29
611-053-10	500x315x70mm	6.4μm	33
611-064-10	630x400x80mm	7.0μm	60
611-066-10	630x630x100mm	7.6μm	119
611-085-10	800x500x100mm	7.8μm	120
611-106-10	1000x630x140mm	8.7μm	265
611-107-10	1000x750x150mm	9.0μm	337
611-101-10	1000x1000x150mm	9.7μm	450
611-121-10	1200x800x160mm	9.8μm	461
611-161-10	1600x1000x180mm	11.5μm	864
611-201-10	2000x1000x220mm	12.9μm	1320
611-215-10	2000x1500x250mm	14.0μm	2250

With manufacturer inspection certificate

PLATE

SERIES 621


STAND FOR GRANITE SURFACE PLATE

- ◆ For medium size granite surface plates
- ◆ Adjusting range of jacks: 10mm
- ◆ One foot on the bottom is adjustable
- ◆ The height can be made under customer requirement




621-064-01

unit: mm



Code	L	W	H	For granite surface plate
621-064-01	352	224	700-710	630x400x80mm
621-066-01	352	352	700-710	630x630x100mm
621-085-01	448	280	700-710	800x500x100mm
621-106-01	560	352	685-695	1000x630x140mm
621-107-01	560	416	685-695	1000x750x150mm
621-101-01	560	560	685-695	1000x1000x150mm
621-121-01	672	448	685-695	1200x800x160mm
621-161-01	896	560	585-595	1600x1000x180mm




625

JACK SET FOR GRANITE SURFACE PLATE



- ◆ 5 jacks per set
- ◆ Adjustable height
- ◆ For large granite surface plates:
2000x1000mm
2000x1500mm
2500x1500mm
3000x2000mm



Code

625-000-00



PLATE

633

MAGNETIC V-BLOCK

**ATTENTION:
NOT HARDENED**

- ◆ Hold cylindrical workpiece for inspection and machining



Code	For shaft range(Ød)	Magnetic force	Top and bottom, left and right parallelism	V-grooves and back side squareness
633-044-01	6 - 44mm	56kgf	10µm	10µm

SERIES 634



MAGNETIC V-BLOCK

**ATTENTION:
NOT HARDENED**

- ◆ Hold cylindrical workpiece for inspection and machining
- ◆ Top groove for large shafts
- ◆ Bottom grooves for small shafts



634-067-01



Code	Size(LxWxH)	For shaft range($\varnothing d$)	Magnetic force	V-grooves and back side squareness	Top and bottom, left and right parallelism
634-067-01	80x70x95mm	6-67mm	64kgf	10 μ m	10 μ m
634-067-02	100x70x95mm	6-67mm	80kgf	10 μ m	10 μ m
634-067-03	120x70x95mm	6-67mm	96kgf	10 μ m	10 μ m



SERIES 634

MAGNETIC V-BLOCK (PROFESSIONAL TYPE)

- ◆ Hardened, high accuracy, for grinding, milling, drilling and inspection of round and square workpieces
- ◆ All working surfaces are hardened to HRC55-60°
- ◆ Hold cylindrical workpiece for inspection and machining
- ◆ Top groove for large shafts
- ◆ Bottom grooves for small shafts



634-067-01H



Code	Size(LxWxH)	For shaft range($\varnothing d$)	Magnetic force	V-grooves and back side squareness	Top and bottom, left and right parallelism
634-067-01H	80x70x95mm	6-67mm	64kgf	5 μ m	5 μ m
634-067-02H	100x70x95mm	6-67mm	80kgf	5 μ m	5 μ m
634-067-03H	120x70x95mm	6-67mm	96kgf	6 μ m	6 μ m

SERIES 635




MAGNETIC V-BLOCK SET

**ATTENTION:
NOT HARDENED**

- ◆ Hold cylindrical workpieces for inspection, not suitable for machining due to weak magnetic force
- ◆ Two V-blocks per set
- ◆ Hardness HRB 70



635-150-01




Code	Size(LxWxH)	Range of shafts (Ød)	Magnetic force	Parallelism of V groove to bottom and back sides	Height difference of a matched pair
635-070-01	70x40x50mm	6 - 46mm	8kgf	10µm	10µm
635-150-01	150x50x100mm	6 - 125mm	14kgf	10µm	10µm

SERIES 631



GRANITE V-BLOCK SET



- ◆ Supplied a pair, for holding long cylindrical workpiece



631-075-01



Code	Size(LxWxH)	For shaft range(Ød)	Parallelism between top and bottom, left and right	Height difference between a pair
631-075-01	50x70x70mm	6 - 70mm	5µm	5µm
631-099-01	50x100x70mm	6 - 84mm	5µm	5µm





With manufacturer inspection certificate



SERIES 632

V-BLOCK SET

- ◆ Two V blocks per set
- ◆ Made of hardened tool steel




Code	Size (LxWxH)	Range of shafts(Ød1)	Range of shafts(Ød2)	Range of shafts(Ød3)	Parallelism of V grooves to top and bottom sides	Squareness of V grooves to front and back sides	Height difference of a matched pair
632-002-01	50x19x24mm	3 - 32mm	3 - 16mm	3 - 22mm	5µm	5µm	5µm
632-003-01	75x24x35mm	3 - 50mm	3 - 20mm	3 - 32mm	5µm	5µm	5µm
632-004-01	100x33x52mm	6 - 68mm	5 - 26mm	5 - 40mm	5µm	5µm	5µm
632-006-01	150x50x80mm	6 - 100mm	5 - 40mm	5 - 60mm	5µm	5µm	5µm


SERIES 636

V-BLOCK SET

- ◆ Hold cylindrical workpieces for inspection and machining
- ◆ Two V-blocks per set
- ◆ V groove on the top for large shafts
- ◆ V groove on the bottom for small shafts



636-045-01




Code	Size(LxWxH)	For shaft range(Ød)	V grooves to top and bottom sides parallelism	V grooves to front and back sides squareness	Height difference of a matched pair
636-045-01	45x41x35mm	5 - 40mm	5µm	5µm	5µm
636-070-01	70x63x44mm	7 - 60mm	5µm	5µm	5µm
636-125-01	125x90x70mm	7 - 80mm	5µm	5µm	5µm

SERIES 637



V-BLOCK SET

- ◆ Hold cylindrical workpieces for inspection and machining
- ◆ Two V-blocks per set
- ◆ V groove on the top for large shafts



637-035-01



unit: mm




Code	Size(LxWxH)	For shaft range(Ød)	V grooves to top and bottom sides parallelism	V grooves to front and back sides squareness	Height difference of a matched pair
637-035-01	35x35x30mm	3 - 16mm	5µm	5µm	5µm
637-060-01	60x60x50mm	5 - 34mm	5µm	5µm	5µm
637-105-01	105x105x78mm	8 - 66mm	5µm	5µm	5µm

638

V-BLOCK SET




- ◆ Hold cylindrical or rectangular workpieces for inspection and machining
- ◆ Two V-blocks per set
- ◆ Hardened to HRC60±2
- ◆ Applicable for cylinder with diameter (Ød): 5 - 50mm
- ◆ Applicable for rectangular workpieces with thickness: ≤35mm





Code	Size (LxWxH)	Parallelism of V groove to top and bottom sides	Squareness of V groove to front and back sides	Height difference of a matched pair
638-070-01	60x70x50mm	8µm	8µm	8µm

640

V-BLOCK SET



- ◆ Hold cylindrical workpieces for inspection and machining
- ◆ Two V-blocks per set
- ◆ Side lie-down use is possible
- ◆ Hardened to HRC60±2
- ◆ V groove on the top for large shafts
- ◆ V groove on the bottom for small shafts






Code	Size (LxWxH)	Range of shafts (Ød)	Parallelism of both V grooves to top, bottom, left, right sides	Squareness of both V grooves to front and back sides	Height difference of a matched pair
640-001-01	65x70x45mm	4 -35mm	5µm	5µm	5µm

V-BLOCK

639

V-BLOCK

- ◆ Hold cylindrical workpieces for inspection and machining
- ◆ Hardened to HRC60±2



Code	Size (LxWxH)	Range of shafts (Ød1 and Ød2)	Parallelism of upper groove to bottom, left and right sides	Squareness of upper groove to back side	Parallelism of side groove to back side
639-090-01	90x48x48mm	5 -33mm	5µm	5µm	5µm





SERIES 630

V-BLOCK SET

- ◆ For positioning cylindrical workpieces
- ◆ Two V-blocks per set
- ◆ Each V-block has four 90° V-grooves
- ◆ Hardness HB 170-241



630-006-11




unit: mm

Code	Size(LxHxW)	Range of shafts(Ød)	Parallelism of four grooves to all sides	Height difference of a matched pair
630-006-11	150×130×75mm	8-120mm	15µm	20µm
630-008-11	200×170×90mm	12-180mm	15µm	20µm


641

PARALLEL SET

- ◆ Parallelism between top and bottom: 5µm
- ◆ Height difference of a matched pair: 5µm
- ◆ Hardened to HRC55-60



unit: mm




Code	Parallels per set	Length	Thickness	Height(h)
641-014-01	14pairs	150mm	10mm	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40, 45, 50mm



615

MAGNETIC INDUCTION PARALLEL SET

- ◆ To be used on magnetic chucks
- ◆ Two parallels per set
- ◆ Hardness HRB70
- ◆ Copper magnetic strips



Application



Code	Size(LxWxH)	Pole pitch	Parallelism between A and B	Parallelism between C and D	Height difference of a matched pair
615-004-02	100x50x25mm	2+2mm	10 μ m	10 μ m	10 μ m


SERIES 571

ANGLE GAUGE BLOCK SET

- ◆ For angle set-up in tooling, production and inspection
- ◆ Hardness HRC55



571-010-02




Code	Blocks per set	Accuracy	Sharp	Angle
571-010-02	10	$\pm 20''$	triangle	1°, 2°, 3°, 4°, 5°, 10°, 15°, 20°, 25°, 30°
571-012-01	12	$\pm 20''$	triangle	1/4°, 1/2°, 1°, 2°, 3°, 4°, 5°, 10°, 15°, 20°, 25°, 30°



646


UNIVERSAL ANGLE PLATE SET

- ◆ For angle set-up in tooling, production and inspection
- ◆ Hardness HRC55




unit: mm

type A



type B





Code	Quantity	Angle α	Type	Accuracy
646-009-01	9pcs	$\frac{1}{2}^\circ, 1^\circ, 2^\circ, 3^\circ, 4^\circ, 5^\circ$	type A	$\pm 1'$
		$10^\circ, 15^\circ, 30^\circ$	type B	

SERIES 651

SINE BAR



651-005-01



unit: mm


Code	Roller distance (E)	Table size(AxB)	Accuracy of α at 30°	C
651-005-01	100mm	130x25mm	$\pm 8''$	25
651-005-02	100mm	130x83mm	$\pm 16''$	30
651-010-01	200mm	250x40mm	$\pm 8''$	40
651-010-02	200mm	250x85mm	$\pm 16''$	40



SERIES 652



PRECISION VISE

- ◆ Parallelism: $5\mu\text{m}/100\text{mm}$
- ◆ Squareness: $5\mu\text{m}/100\text{mm}$
- ◆ Made of alloy steel
- ◆ Hardness HRC56-58



652-120-01

unit: mm




Code	Jaw opening(d)	Jaw width(W)	L	H	M
652-073-01	73mm	63mm	176	63	30
652-076-01	76mm	73mm	190	73	35
652-120-01	120mm	98mm	255	82	40

SERIES 653



PRECISION VISE

- ◆ Made of hardened alloy steel
- ◆ Parallelism and squareness between A, B, C, D, E and F: $5\mu\text{m}/100\text{mm}$
- ◆ Hardness HRC56-58



653-003-01

unit: mm






Code	Jaw opening(d)	Jaw width(W)	L	H	M
653-003-01	80mm	50mm	150	53	25
653-005-01	100mm	73mm	190	70	35



656

PRECISION UNIVERSAL VISE

- ◆ Horizontal rotary:
range 360°, graduation 0.05°
Vertical incline: range 45°, graduation 0.05°
- ◆ With vertical incline adjust knob
- ◆ Parallelism and squareness between A, B, C
and D: 5μm/100mm, parallelism between
D and E at 0°: 10μm/100mm
- ◆ Made of tool steel
- ◆ Hardness HRC56-58






Code	Jaw opening(Q)	Jaw width(W)
656-080-01	0-80mm	70mm

657

PRECISION SINE VISE

- ◆ Parallelism: 3μm/100mm
- ◆ Squareness: 5μm/100mm
- ◆ Accuracy of angle: ±20"
- ◆ Made of SKS tool steel, subzero treatment
- ◆ Hardness HRC58-60





Code	Jaw opening (Q)	Jaw width	Adjustable angle
657-090-01	0-90mm	73mm	0-45°

297

CENTERING INDICATOR

- ◆ For quick and accurate centering in boring and milling set-up
- ◆ Jeweled bearing
- ◆ Supplied with 7 type feelers



Code


297-003-11

685

DIAL TEST INDICATOR CENTERING HOLDER

- ◆ Center cylinders or holes on machine tools
- ◆ Can be used with dial test indicators

Application




Code

685-040-01

- ◆ Center cylinders or holes on machine tools
- ◆ Can be used with dial test indicators or dial indicators

Application







Code

686-080-01

SERIES 692

ELECTRONIC EDGE FINDER

- ◆ The LED will be light with alarm when the ball contacts the workpiece
- ◆ Not suitable for rotating use
- ◆ Hardened shank and contact point
- ◆ Battery: 23A, 12V





Code	Shank(A)	Contact point (B)	Accuracy
692-010-03N	Ø20mm	SØ10mm	5µm
692-010-32	Ø32mm	SØ10mm	5µm

SERIES 693

NON-MAGNETIC EDGE FINDER



- ◆ Non-magnetic
- ◆ TIN coating, hardness HV2300, extremely wear resistance
- ◆ Suitable for machine speed 400~600rpm



693-010-01N


693-010-31

Code	Shank(A)	Contact surface(B)	Accuracy	Titanium plated
693-010-01N	Ø10mm	Ø6mm	5µm	without
693-010-31	Ø10mm	Ø6mm	5µm	with


SERIES 691

CERAMIC EDGE FINDER

- ◆ Ceramic contact point, non magnetic
- ◆ Hardened shank
- ◆ Suitable for machine speed: 400-600rpm



691-010-01N





Code	Shank(A)	Contact point (B)	Accuracy
691-010-01N	Ø10mm	Ø10mm	5µm
691-010-02	Ø10mm	Ø10mm	5µm
691-010-03	Ø10mm	Ø10mm	5µm
691-010-04	Ø10mm	Ø10mm	5µm

SERIES 691

CERAMIC EDGE FINDER



- ◆ Non-magnetic
- ◆ CrN coating, hardness HV2000, extremely wear resistance
- ◆ Suitable for machine speed 400~600rpm





Code	Shank(A)	Contact point(B)	Contact point(C)	Accuracy
691-017-01	Ø10mm	Ø10mm	Ø4mm	5µm
691-017-11	Ø10mm	Ø10mm	-	5µm

694

EDGE FINDER

- ◆ Hardened shank and contact point
- ◆ Suitable for machine speed 400~600rpm





Code	Shank(A)	Contact point(B)	Contact point(C)	Accuracy
694-020-01N	Ø10mm	Ø10mm	Ø4mm	5µm

SERIES 694

NON-MAGNETIC EDGE FINDER



- ◆ Non-magnetic
- ◆ TiAlN coating, hardness HV3500;
TIN coating, hardness Hv2300,
extremely wear resistance
- ◆ Suitable for machine speed 400~600rpm





Code	Shank(A)	Contact point(B)	Contact point(C)	Accuracy
694-020-02	Ø10mm	Ø10mm	Ø4mm	5µm
694-020-03	Ø10mm	Ø10mm	Ø4mm	5µm

694

EDGE FINDER

- ◆ Hardened shank and contact point
- ◆ Suitable for machine speed 400~600rpm




Code	Shank(A)	Contact point(B)	Accuracy
694-020-11	Ø10mm	Ø10mm	5µm

SERIES 694

NON-MAGNETIC EDGE FINDER




- ◆ Non-magnetic
- ◆ TiAlN coating, hardness HV3500;
TIN coating, hardness HV2300,
extremely wear resistance
- ◆ Suitable for machine speed 400~600rpm



694-020-12



694-020-13





Code	Shank(A)	Contact point(B)	Accuracy
694-020-12	Ø10mm	Ø10mm	5µm
694-020-13	Ø10mm	Ø10mm	5µm

689

NON-MAGNETIC EDGE FINDER



- ◆ Non-magnetic
- ◆ TIN coating, hardness HV2300,
extremely wear resistance
- ◆ Suitable for machine speed 400~600rpm





Code	Shank(A)	Contact point(B)	Contact point(C)	Accuracy
689-010-02	Ø10mm	Ø10mm	Ø2mm	5µm

690

NON-MAGNETIC EDGE FINDER (DOUBLE HEAD)



- ◆ Non-magnetic
- ◆ TIN coating, hardness HV2300, extremely wear resistance
- ◆ Suitable for machine speed 400~600rpm
- ◆ Find edge or hole center




Code	Shank(A)	Contact point(B)	Contact point(C)	Accuracy
690-010-01	Ø10mm	Ø10mm	Ø6mm	5µm

SERIES 688


EDGE FINDER (WITH ROTARY HEAD)



- ◆ Non-magnetic
- ◆ TIN coating, hardness HV2300, extremely wear resistance
- ◆ Suitable for machine speed 500~2000rpm



688-010-01




Code	Shank(A)	Contact point(B)	Accuracy	Application
688-010-01	Ø10mm	Ø5mm	5µm	flat surface
688-010-12	Ø10mm	Ø5mm	5µm	arc surface

697


DIGITAL ZERO SETTER



- ◆ IP65 protection level
- ◆ Magnetic base
- ◆ With backlight, will turn on automatically when close to zero ($\pm 0.002\text{mm}$)
- ◆ Turn off automatically



Application





Code	Accuracy
697-050-01	$\pm 10\mu\text{m}$

695

ZERO SET

- ◆ Magnetic base






Code	Accuracy
695-050-01	$\pm 10\mu\text{m}$

696

ZERO SET

- ♦ Magnetic base with on/off switch



Code	Height (H)	Accuracy	Force
696-100-01	100mm	±10µm	9N

SERIES 280

2-PIECE MEASURING TOOLS SET



280-000-02

Code	Include
280-000-02	10mm dial indicator (222-010-11) Magnetic stand (281-060-01)
280-001-02	1 inch dial indicator (225-025-11) Magnetic stand (281-060-01)

Package



280

2-PIECE MEASURING TOOLS SET

◆ Include:

- 1) Digital caliper, range 0-150mm/0-6"
(code **111-006-12**)
- 2) Digital outside micrometer, range 0-25mm
(code **312-001-03**)



Code

280-123-02

MEASURING
TOOL SET

280

3-PIECE MEASURING TOOL SET

◆ Includes:

- 1) Vernier caliper, range 0-150mm/0-6",
(code **120-006-12**)
- 2) Outside micrometer, range 0-25mm
(code **321-001-01**)
- 3) 90° beveled edge square, 100x70mm
(code **832-004-10**)



Code

280-000-03

280

3-PIECE MEASURING TOOL SET

◆ Includes:

- 1) Digital caliper, range 0-150mm/0-6"
(code **111-006-12**)
- 2) Outside micrometer, range 0-25mm
(code **321-001-01**)
- 3) 90° beveled edge square, 100x70mm
(code **832-004-10**)



Code

280-000-13

SERIES 280

3-PIECE MEASURING TOOL SET



Digital indicator for
280-200-03



Inch dial indicator for
280-202-03



280-201-03

Code	Include
280-200-03	digital indicator, range 12.7mm/0.5" (code 212-010-13) flex arm locking pliers, adjustable jaw opening from 0 to 25mm
280-201-03	10mm dial indicator (code 222-010-11) flex arm locking pliers, adjustable jaw opening from 0 to 25mm
280-202-03	1" inch dial indicator (code 225-025-11) flex arm locking pliers, adjustable jaw opening from 0 to 25mm

280

5-PIECE MEASURING TOOL SET

◆ Includes:

- 1) Digital caliper, range 0-150mm/0-6"
(code **111-006-12**)
- 2) Outside micrometer, range 0-25mm
(code **321-001-01**)
- 3) Dial indicator, range 10mm
(code **222-010-11**)
- 4) Magnetic stand (code **281-060-01**)
- 5) Micrometer stand (code **383-000-00**)



Code

280-000-05

MEASURING
TOOL SET

280

5-PIECE MEASURING TOOL SET

◆ Includes:

- 1) Digital caliper, range 0-150mm/0-6"
(code **111-006-12**)
- 2) Outside micrometer, range 0-25mm
(code **321-001-01**)
- 3) Dial indicator, range 10mm
(code **222-010-11**)
- 4) 90° beveled edge square, 100x70mm
(code **832-004-10**)
- 5) Scriber, 250mm
(code **995-009-01**)



Code

280-000-15

280

8-PIECE MEASURING TOOL SET

◆ Includes:

- 1) Digital caliper, range 0-150mm/0-6" (code **111-006-12**)
- 2) Outside micrometer, range 0-25mm (code **321-001-01**)
- 3) Protractor (code **812-003-01**)
- 4) Pitch gauge, range 0.25-7mm, 24pcs (code **922-007-24**)
- 5) Radius gauge (code **941-007-34**)
- 6) Feeler gauge, range 0.05-1.00mm, 20pcs (code **912-100-20**)
- 7) 90° beveled edge square, 100x70mm (code **832-004-10**)
- 8) Scriber (code **995-009-01**)



Code

280-000-08

280

12-PIECE MEASURING TOOL SET

◆ Includes:

- 1) Digital caliper, range 0-150mm/0-6" (code **111-006-12**)
- 2) Outside micrometer, range 0-25mm (code **321-001-01**)
- 3) Dial indicator, range 10mm (code **222-010-11**)
- 4) Magnetic stand (code **281-060-01**)
- 5) Protractor (code **812-003-01**)
- 6) Pitch gauge, range 0.25-7mm, 24pcs (code **922-007-24**)
- 7) Radius gauge (code **941-007-34**)
- 8) Feeler gauge, range 0.05-1.00mm, 20pcs (code **912-100-20**)
- 9) 90° beveled edge square, 100x70mm (code **832-004-10**)
- 10) Scriber (code **995-009-01**)
- 11) Depth base (code **179-000-00**)
- 12) Zero setting bar



Code

280-000-12

280

12-PIECE MEASURING TOOL SET

◆ Includes:

- 1) Digital caliper, range 0-150mm/0-6" (code **111-006-12**)
- 2) Digital outside micrometer, range 0-25mm/0-1" (code **313-001-01**)
- 3) Digital indicator, range 12.7mm/0.5" (code **212-010-13**)
- 4) Magnetic stand (code **281-060-01**)
- 5) Protractor (code **812-003-01**)
- 6) Pitch gauge, range 0.25-7mm, 24pcs (code **922-007-24**)
- 7) Radius gauge (code **941-007-34**)
- 8) Feeler gauge, range 0.05-1.00mm, 20pcs (code **912-100-20**)
- 9) 90° beveled edge square, 100x70mm (code **832-004-10**)
- 10) Scriber (code **995-009-01**)
- 11) Depth base (code **179-000-00**)
- 12) Zero setting bar



Code

280-001-12

MEASURING
TOOL SET

280

6-PIECE WELDING GAUGE SET

◆ Includes:

- 1) Outside micrometer, range 0-25mm (code **321-001-01**)
- 2) Pipe welding gauge (code **976-045-01**)
- 3) Welding gauge (code **978-006-01**)
- 4) Welding gauge (code **979-020-01**)
- 5) Steel rule, range 150mm/6" (code **990-006-11**)
- 6) Magnifier



Code

280-000-56




- ◆ The cable with lens can be rotated at 360°
- ◆ With adjustable LED light




VIDEO

HDMI
Micro USB
TF


manual joystick to control the cable




Max.bend angle:220°



360° rotation



focus distance:20-150mm



angle of view field:120°

SPECIFICATION

Probe diameter	6mm
Cable length	1.5m
Cable type	steel wired weaved cable
Dust/waterproof probe	IP65
Camera pixel	1M Pixel
Picture resolution	1280x720
Bend control	manual joystick
Frame rate	30fps
Illumination	6 steps adjustable LED
Display size	3.5inch LCD,Max.20000Lux
Max.magnification	5X
Video format	MP4/JPEG
Memory	16G TF card
Power supply	rechargeable battery(for 4 hours working)
Weight	550g

INCLUDED ACCESSORIES

Main unit	1pc
Cable with probe	1pc
16G TF card	1pc
AC/DC adapter	1pc
USB cable	1pc



- ◆ The cable length into the pipe can be shown the display
- ◆ With adjustable LED light
- ◆ Language: English, Japanese, Korean, Russian, German, French, Italian, Spanish, Portuguese, Thai, Finish, Swedish



46mm support guide




80mm support guide




Remote control



23mm lens



focus distance:15cm



angle of view field:130°

SPECIFICATION

Probe diameter	23mm
Cable length	20m
Probe head material	304 stainless steel
Dust/waterproof probe	IP67
Camera pixel	2MPixel
Picture resolution	1920x1080
Focus distance	15cm
Angle of view field	130°
Illumination	4 steps adjustable LED
Display size	7inch LCD
Max.magnification	3X
Video format	HD 1080P
Memory	16G SD card
Power supply	rechargeable battery(for 7 hours working)
Weight	10kg

INCLUDED ACCESSORIES

Main unit	1pc
16G SD card	1pc
12VAC/DC adapter	1pc

USB cable	1pc
Remote control	1pc
Support guide	2pcs



- ◆ 2-way directions
- ◆ With adjustable LED light
- ◆ Take pictures and record videos



VIDEO



SPECIFICATION

Code	ES5515	ES5530	ES4015
Probe diameter	6mm	6mm	4.0mm
Cable length *	1.5m	3m	1.5m
Dust/waterproof probe	IP65		
Camera	0.45M Pixel		
Picture resolution	640x480		
Frame rate	30fps		
Illumination	8pcs LEDs		4pcs LEDs
Video format	AVI or MPEG4		
Memory	8G SD card		
Power supply	rechargeable battery (for 4 hours working)		
Weight	550g	750g	500g


INCLUDED ACCESSORIES

Main unit	1pc
Cable with probe	1pc
SD card 8G	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc

* The cable length are available upon request



- ◆ Economic type
- ◆ 2-way directions
- ◆ With adjustable LED light
- ◆ Take pictures and record videos



SPECIFICATION

Code	ESE80	ESE60	ESE40
Probe diameter	8.0mm	6.0mm	4.0mm
Cable length	1m		
Dust/waterproof probe	IP65		
Camera	1MPixel		
Picture resolution	1280x720		
Frame rate	30fps		
Screen size	4.5 inch		
Illumination	8pcs LEDs		6pcs LEDs
Video format	AVI		
Memory	32G SD card		
Power supply	rechargeable battery (for 4 hours working)		
Weight	500g	450g	400g

INCLUDED ACCESSORIES


Main unit	1pc
Cable with probe	1pc
SD card 32G	1pc
AC/DC adapter	1pc

EST0810

WIFI ENDOSCOPE



- ◆ The cable can be fixed in any sharp
- ◆ With adjustable LED light



SPECIFICATION

Probe diameter	8.5mm
Cable length	1m
Cable type	steel wired cable (the sharp can be fixed)
Dust/waterproof probe	IP65
Camera pixel	2M Pixel
Picture resolution	1600x1200
Video format	JPEG/MP4
Illumination	6 steps adjustable LED
Power supply	rechargeable battery (for 4 hours working)
Weight	287g

INCLUDED ACCESSORIES

Main unit	1pc
Cable with probe	1pc
Hook	1pc
Mirror	1pc
Magnet	1pc
USB cable	1pc

Magnet



Hook



Mirror



MG305

MAGNIFICATION GLASSES



- ◆ Lenses are made of resin
- ◆ Interchangeable lenses
- ◆ Powered: 3 pcs AAA batteries (included)

Adjustable holder angle



Adjustable lens position



Focus can be adjusted



Adjustable LED angle



2 pcs LED



Interchangeable lenses



Head band (included)



Magnification	1X, 1.5X, 2X, 2.5X, 3.5X
Lens number	5 pcs






MG30X

MEASURING MAGNIFIER (WITH ILLUMINATION)



- ◆ Base with scale
- ◆ With 3 white LED and 3 UV LED
- ◆ Magnification: 30X




MG10

FOLDING MAGNIFIER

- ◆ Glass lens

folding



Magnification	10X
Lens diameter(ØD)	Ø21

DM200

DIGITAL MICROSCOPE



Magnification: 10X-200X



Pixel: 2M



Interface: USB2.0



Snap pictures and record videos



8 pcs adjustable LED lights



With measuring software and calibration rule



VIDEO



Optional Stand



Magnification, View Field and Focus Relationship

Magnification	Focus	View field
50X	21mm	9.5x7.1mm
100X	13mm	4.8x3.6mm
150X	16mm	3.2x2.4mm
200X	19mm	2.4x1.8mm

WIFI200

DIGITAL WIFI MICROSCOPE



Magnification: 10X-200X



Pixel: 2M



Interface: USB2.0 or WiFi



Snap pictures and record videos



8 pcs adjustable LED lights



With measuring software and calibration rule



VIDEO



It can connected to smart phone, Ipad or computer via WIFI



Optional Stand



Universal Stand (MS36B)

Magnification, View Field and Focus Relationship

Magnification	Focus	View field
50X	21mm	9.5x7.1mm
100X	13mm	4.8x3.6mm
150X	16mm	3.2x2.4mm
200X	19mm	2.4x1.8mm

PM100

PORTABLE MEASURING MICROSCOPE



10X eyepiece(scale graduation: 0.1mm)

focus adjustment

LED light

10X objective


SPECIFICATION

Total magnification	100X
Eyepiece	10X
Objective(achromatic)	10X
Working distance	7mm
Focus range	30mm
Viewing field	Ø1.8mm
Graduation	0.01mm
Illumination	LED light
Diameter of base	Ø63mm
Height	210mm
Weight	650g

INCLUDED ACCESSORIES

Main unit	1pc
Pen light	1pc
Battery (AAA)	2pcs

- ◆ High resolution color camera
- ◆ With TF card, can save pictures and videos
- ◆ High frame rate, without any delay in quick movement
- ◆ With crosshair on the screen



SPECIFICATION

Objective		0.7X~5X (zoom)
Total magnification(with 22 inch monitor)		25X-180X
View field		3.2mm-23mm
Working distance		105mm
Camera	Resolution	1920x1080
	Pixel size	2.75*2.75 μ m
	Frame rate	60fps
Illumination		adjustable light
Base size		320mmx285mm(LxW)
Weight		6kg

INCLUDED ACCESSORIES

Main unit	1pc
Wireless mouse	1pc
HDMI connection cable	1pc
Ø95mm black/white plastic plate	1pc
8G TF card	1pc
TF card reader	1pc
AC/DC adapter	1pc



- ◆ 12 inch wide screen HD LCD is included
- ◆ Can take pictures and record videos
- ◆ With USB interface, for transferring pictures or measuring data
- ◆ High frame rate, without any delay in quick movement
- ◆ With measuring function



VIDEO



SPECIFICATION

Objective		0.7X ~ 5X (zoom, fixed at 0.7X, 1X, 1.5X, 2X, 2.5X, 3X, 4X, 5X)
Total magnification		13X-97X
View field		3mm-22.7mm
Working distance		96mm
Camera	Pixel	2M HDMI
	Pixel size	2.75*2.75μm
	Frame rate	60fps
Illumination		144pcs LEDs adjustable light
LCD display		12 inch HD LCD display, 1080P
Base size		260mmx320mm(LxW)
Weight		5.5kg

INCLUDED ACCESSORIES

Main unit	1pc
12 inch HD LCD	1pc
Wireless mouse	1pc
HDMI connection cable	1pc
Calibration rule	1pc
AC/DC adapter	1pc

OPTIONAL ACCESSORIES

0.5X Objective	DVM2000-05-O
2X Objective	DVM2000-20-O

- ◆ 10.6 inch HD LCD is included
- ◆ Can take pictures and record videos
- ◆ High frame rate, without any delay in quick movement
- ◆ Automatic exposure, white balance



SPECIFICATION

Objective		0.7X ~ 4.5X
Total magnification		14X ~ 100X
Max.view field		16.2mmx9.2mm
Working distance		88mm
	Pixel	1.2M
Camera	Resolution	1366x768
	Frame rate	60fps
Illumination		top/side LED adjustable light
LCD display		10.6 inch HD LCD display, 1080P
Base size		260mmx320mm(LxW)
Weight		5.7kg

INCLUDED ACCESSORIES

Main unit	1pc
Stand	1pc
Glass rule	1pc
AC/DC adapter	1pc
SD card	1pc



SERIES DVM4000

AUTO FOCUS VIDEO MICROSCOPE

- ◆ Auto focus
- ◆ High frame rate, without any delay in quick movement
- ◆ Automatic exposure, white balance
- ◆ With measuring functions



DVM4000S

SPECIFICATION

Code		DVM4000	DVM4000S
Display		without	with 21.5" HD monitor
Objective		0.7X ~ 4.5X	
Total magnification		26.5X~170X	
Max.view field		19mmx10.8mm	
Working distance		100mm	
Camera	Pixel	2M	
	Resolution	1920x1080	
	Frame rate	60fps	
Illumination		LED adjustable light	
Base size		380mmx260mm(LxW)	
Weight		5.7kg	

INCLUDED ACCESSORIES

Main unit	1pc
Stand	1pc
Calibration rule	1pc
AC/DC adapter	1pc
U-disk	1pc
Mouse	1pc

OPTIONAL ACCESSORIES

X-Y stage(range: 76x65mm)	DVM-STAGE
0.5X objective	DVM-05-O
2X objective	DVM-20-O

- ◆ 1080P HD image
- ◆ High frame rate, without any delay in quick movement
- ◆ Automatic exposure, white balance
- ◆ With taking photos functions


DVM3DS
SPECIFICATION

Code		DVM3D	DVM3DS
Display		without	with 21.5" HD monitor
Total magnification		25X~150X	
Direction/rotation adjustment		by controller	
Max.view field		16mmx9mm	
Working distance		20mm	
Camera	Pixel	2M	
	Resolution	1920x1080	
	Frame rate	60fps	
Frame rate		LED adjustable light (adjusted by controller)	
Base size		380mmx260mm(LxW)	
Weight		5.7kg	

INCLUDED ACCESSORIES

Main unit	1pc
Stand	1pc
Controller	1pc
AC/DC adapter	1pc
USB flash disk	1pc

OPTIONAL ACCESSORIES

X-Y stage(range: 76x65mm)	DVM-STAGE
---------------------------	-----------





SERIES ZS1045 ZOOM STEREO MICROSCOPE

◆ Trinocular head is used to connect to camera



ZS1045

SPECIFICATION

Code	ZS1045	ZS1045T
Optical	binocular	trinocular
Magnification	10X ~ 45X	
Eyepiece	10X (view field: Ø20mm)	
Objective	1X ~ 4.5X (zoom)	
Pupil distance	55 ~ 75mm	
Diopter adjustment	±5 diopter	
Working distance	97mm	
Illumination	selectable incident and transmitted LED light	
Dimension(L×W×H)	310×250×420mm	
Weight	6kg	

INCLUDED ACCESSORIES

Main unit	1pc
10X eyepiece	1pair
Eyepiece patch	1pair
Ø95mm frosted glass plate	1pc
Ø42mm frosted glass plate	1pc
Ø95mm black/white plastic plate	1pc
Dustproof cover	1pc

OPTIONAL ACCESSORIES

0.5X Eyepiece	ZS1045-05-O
0.75X Eyepiece	ZS1045-75-O
2X Eyepiece	ZS1045-02-O
10X Eyepiece with scale	ZS1045-10-FE
WF15X Eyepiece	ZS1045-15-E
WF20X Eyepiece	ZS1045-20-E
Camera	1300KPA

- ◆ For high magnification observation and metallurgical image analysis
- ◆ Infinite optical system, can add accessories like polarizer, analyzer into optical path without image quality influence



Filter



SPECIFICATION

Eyepiece(wide field)	10X(view field: Ø22mm)			
Objective(plan achromatic)	10X	20X	50X	100X(dry type)
Numerical aperture	0.25	0.40	0.70	0.85
Working distance	5mm	8.8mm	3.68mm	0.4mm
Stage	double layer			
	size: 242×200mm			
	travel: 30×30mm			
Pupil distance	53-75mm(adjustable)			
Diopter adjustment	±5 diopter(one eyepiece)			
Illumination	6V/30W halogen lamp, brightness is adjustable with polarizer and analyzer, built-in green, yellow, blue filters and frosted glass			
Weight	11kg			

INCLUDED ACCESSORIES

Main unit	1pc
Anti-dust cover	1pc
Filter	1set
Camera adapter(1X)	1pc

OPTIONAL ACCESSORIES

10X dividing eyepiece(0.1mm/div.)	MM-EP10D
Digital camera	1300KPA
5X Objective	MM-OB5

40X Objective	MM-OB40
60X Objective	MM-OB60
80X Objective	MM-OB80



- ◆ Large screen of the read out
- ◆ With manufacturer inspection certificate



PP3015

OPTIONAL ACCESSORIES



20X, 50X, 100X
lens with half-reflection mirror (glass diameter 100mm, graduation 2°)




rotary table



5X magnifier



Series 552 glass scale



holder with clamp



swivel center support









V-block with clamp



Overlay chart


SPECIFICATION

Code	PP3015	PP3020
X-Y stage travel	150×50mm	200×100mm
Metal stage size	340×152mm	400×225mm
Glass stage size	195×95mm	245×145mm
Screen diameter	diameter: Ø300mm	
Image	inverted	
Linear scale resolution	1μm	
Accuracy	(4+L/25)μm L is the measuring length in mm	
Z(focus) travel range	80mm	
Max. load capacity	4kg	
Rotation scale	range: 0°~360°, resolution: 1' or 0.01°, accuracy: 6'	
Magnification accuracy	±0.1%	
Illumination	contour illumination: 12V/100W halogen lamp, 2-step(high/low) brightness adjustment	
	surface illumination: 24V/150W halogen lamp	
Readout display	X-Y stage travel, screen rotation	
Output	RS232 and USB	
Readout functions	 measure coordinate of point	
	 measure coordinate of line	
	 measure center coordinate, radius of circle with three points	
	 measure distance between two objects	
	 measure angle with four points or two lines	
	 coordinate transform	
Dimension (L×W×H)	480×780×1150mm	
Weight	135kg	

INCLUDED ACCESSORIES

Main unit	1pc
10X lens with half-reflection mirror	1pc
Overlay chart clip	4pcs
Level	1pc
Anti-dust cover	1pc

OPTIONAL ACCESSORIES

20X lens with half-reflection mirror	PP3000-LENS20X
50X lens with half-reflection mirror	PP3000-LENS50X
100X lens with half-reflection mirror	PP3000-LENS100X
Rotary table	PP3000-TABLE
5X magnifier	PP3000-MAGNIFIER
Holder with clamp	PP3000-HOLDER
Swivel center support	PP3000-SUPPORT
V-block with clamp	PP3000-VBLOCK
Calibration scale	Series 552
Overlay chart	PP3015-CHART

◆ With manufacturer inspection certificate



OPTIONAL ACCESSORIES



20X, 50X, 100X lens



Rotary table



Series 552 glass scale



Series 636 V-block









Series 652 Vise



Overlay chart



SPECIFICATION

X-Y stage travel	200×100mm
Metal stage size	400×150mm
Screen diameter	Ø300mm
Linear scale resolution	1μm
Accuracy	$(4+L/25)\mu\text{m}$ L is the measuring length in mm
Focus travel range	75mm
Focus	77.7mm(10X lens)
Max. load capacity	50kg
Workpiece rotation range	±15°
Rotation scale	range: 0°~360°, resolution: 1' or 0.01°, accuracy: 6'
Magnification accuracy	±0.08%
Illumination	contour illumination: 24V/150W halogen lamp, brightness is adjustable surface illumination: 12V/150W halogen lamp, brightness is adjustable
Readout display	X-Y stage travel, screen rotation
Output	RS232 and USB
Data processing unit	 measure coordinate of point  measure coordinate of line  measure center coordinate, radius of circle with three points  measure distance between two objects  measure angle with four points or two lines  coordinate transform
Dimension(L×W×H)	1090×830×1010mm
Weight	160kg

INCLUDED ACCESSORIES

Main unit	1pc
10X lens	1pc
Overlay chart clip	4pcs
Foot-switch	1pc
Anti-dust cover	1pc

OPTIONAL ACCESSORIES

20X lens	PP3020W-LENS20X
50X lens	PP3020W-LENS50X
100X lens	PP3020W-LENS100X
Rotary table	PP3020W-TABLE
Overlay chart	PP3015-CHART
Vise	Series 652
V-block	Series 636
Glass scale	Series 552

- ◆ With manufacturer inspection certificate



OPTIONAL ACCESSORIES



5X, 20X, 50X, 100X lens









Rotary table



Series 552 glass scale



SPECIFICATION

X-Y stage travel		200×100mm				
Metal stage size		404×265mm				
Screen diameter		Ø600mm				
Linear scale resolution		1μm				
Accuracy		(4+L/25)μm L is the measuring length in mm				
Focus travel range		75mm				
Lens	Magnification	5X (Optional)	10X (Standard)	20X (Optional)	50X (Optional)	100X (Optional)
	View field	Ø120mm	Ø60mm	Ø30mm	Ø12mm	Ø6mm
	Focus	242.8mm	143.2mm	85.5mm	92mm	48.5mm
	Magnification accuracy	0.08%				
Max. load capacity		5kg				
Rotation scale		range: 0°~360°, resolution: 1' or 0.01°				
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable				
		surface illumination: 12V/150W halogen lamp, brightness is adjustable				
Readout display		X-Y stage travel, screen rotation				
Output		RS232 and USB				
Data processing unit		 measure coordinate of point				
		 measure coordinate of line				
		 measure center coordinate, radius of circle with three points				
		 measure distance between two objects				
		 measure angle with four points or two lines				
		 coordinate transform				
Dimension(L×W×H)		1200×1140×1940mm				
Weight		360kg				

INCLUDED ACCESSORIES

Main unit	1pc
10X lens	1pc
Overlay chart clip	4pcs
Foot-switch	1pc
Anti-dust cover	1pc

OPTIONAL ACCESSORIES

5X lens	PP6020-LENS5X
20X lens	PP6020-LENS20X
50X lens	PP6020-LENS50X
100X lens	PP6020-LENS100X
Rotary table	PP6020-TABLE
Glass scale	Series 552

SERIES QVM

QUICK MEASUREMENT VISION MACHINE

- ◆ Put the workpieces in view field, and press one button, the measuring results will be shown immediately
- ◆ Can measure Max. 99 pieces workpieces at a time
- ◆ Workpiece can be put at any position
- ◆ Auto focus

SPECIFICATION

Code	QVM120	QVM80B
Lens	single field telecentric	double field telecentric
Measuring range	120x80mm	82x55mm(wide view field) 20x13mm(small view field)
Accuracy	$\pm(2.5+L/50)\mu\text{m}$	$\pm(2.5+L/50)\mu\text{m}$ (wide view field) $\pm(1.5+L/50)\mu\text{m}$ (small view field)
Repeatability	$\pm 1.5\mu\text{m}$	$\pm 1.5\mu\text{m}/\pm 1\mu\text{m}$ (small view field)
Resolution	0.01 μm	
Focus method	auto	
Focus (mm)	145mm	
Moving range (Z axis)	45mm(motorized)	
Measuring time	<1s (less than 100 measuring dimensions)	
Illumination system	1000 steps programmable light contour light: telecentric parallel light surface light: LED	
Camera pixel	20M	
Image processing	256 gray scale, 20:1 sub-pixel processing technology	
Dimension	540x260x650mm	
Weight	50kg	

QVM120



INCLUDED ACCESSORIES


Main unit	1pc
Computer	1pc
USB dongle	1pc

OPTIONAL ACCESSORIES

Coaxial light *	QVM-LG
Special angle surface light *	QVM-SL

* The light should be bought with main unit if needed

Software interface



- ◆ Put the workpieces in view filed, and press one button, the measuring results will be shown immediately
- ◆ Can measure Max. 99 pieces workpieces at a time
- ◆ Workpiece can be put at any position
- ◆ Auto focus

SPECIFICATION

Lens	double field telecentric
Measuring range	100x80mm
Accuracy	$\pm(3+L/50)\mu\text{m}$
Repeatability	$\pm 2\mu\text{m}$
Resolution	0.01 μm
Focus method	auto
Focus (mm)	80
Moving range (Z axis)	45mm(motorized)
Measuring time	<1s (less than 100 measuring dimensions)
Illumination system	1000 steps programmable light contour light: telecentric parallel light surface light: LED
Camera pixel	20M
Image processing	256 gray scale, 20:1 sub-pixel processing technology
Dimension	260x450x660mm
Weight	28kg



INCLUDED ACCESSORIES


Main unit	1pc
Computer	1pc
USB dongle	1pc

OPTIONAL ACCESSORIES

Coaxial light *	QVM-LG
Special angle surface light *	QVM-SL

* The light should be bought with main unit if needed

Software interface



- ◆ With counter and measuring software
- ◆ With manufacturer inspection certificate



MTM300

SPECIFICATION

Code	MTM200	MTM300	MTM400
Measuring range(X/Y axis)	200×100mm	300×200mm	400×300mm
Z axis travel with scale	150mm, with fine adjustment		
Stage moving method	manual		
Linear scale resolution (X/Y/Z axis)	0.5μm		
Accuracy (X/Y axis)	(3+L/150)μm L is measuring length , unit:mm		
Repeatability	1μm		
Objective magnification	5X/10X/20X/50X		
Eyepiece magnification	10X		
Focus	5X:10.8mm/10X:12.2mm/20X:4mm/50X:7.8mm		
Camera	Color CCD, 1.3M pixel		
Illumination	contour illumination: LED, brightness adjustment		
	surface illumination: coaxial LED, brightness adjustment		
Max. glass stage loading	20kg	20kg	20kg
Dimension (L×W×H)	900×1000×1050mm	1000×1100×1050mm	1200×1300×1200mm
Weight	140kg	175kg	210kg

INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
Software with USB dongle	1pc(Same as series VM)
Controller	1pc
Objective	4pcs
Eyepiece	1pair

OPTIONAL ACCESSORIES

Computer	VM-PC
----------	-------



- ◆ Granite base and column
- ◆ With manufacturer inspection certificate


VM5040
SPECIFICATION

Code	VM2010	VM3020	VM4030	VM5040
Measuring range(X/Y axis)	200×100mm	300×200mm	400×300mm	500×400mm
Z axis travel with scale	200mm*			
Stage moving method	manual			
Linear scale resolution (X/Y/Z axis)	1μm			
Accuracy (X/Y axis)	(3+L/200)μm L is the measuring length in mm			
Repeatability	2μm			
Focus	90mm			
Lens magnification	0.7X-4.5X			
Total magnification	30-220X			
Camera	Color CCD, 1.3M pixel			
Illumination	contour illumination: LED, brightness adjustment			
	surface illumination: LED, brightness adjustment			
Max. glass stage loading	20kg	20kg	20kg	30kg
Dimension (L×W×H)	580×680×880mm	770×650×1080mm	960×750×1080mm	1250×860×1690mm
Weight	140kg	188kg	230kg	450kg

* The Z axis travel are available upon request


INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
Software with USB dongle	1pc
Controller	1pc
Operating table(only VM5040 included)	1pc





OPTIONAL ACCESSORIES





0.5X auxiliary objective	VM-OB05X
2X auxiliary objective	VM-OB2X
Computer	VM-PC
Operating table (except for VM5040)	VM-Table
Calibration scale	Series 552

SOFTWARE FOR ALL MANUAL VISION MACHINES















◆ Single measuring tools:

-  measure coordinate of point
-  measure length of line
-  measure center coordinate, radius, diameter and area of circle
-  measure length and diameter of arc

-  measure length of curve
-  measure width, length and area of rectangle
-  measure length and area of polygon
-  measure center coordinate, axis length and area of ellipse

◆ Combined measuring tools:

-  measure distance between two objects like, two points, two lines, a point to a line, a point to a circle and so on.
-  create a intersection point
-  find midpoint of a line
-  create a line
-  create a line, a circle and a arc based on points
-  measure distance between two points

-  measure distance from point to line
-  create tangent lines between point and circle
-  create angular bisector between two lines
-  measure distance from circle to line
-  measure distance between two circles
-  find tangent lines between two circles



- ◆ The stage can move automatically by programming
- ◆ The light can be changed automatically by programming
- ◆ Automatic focus
- ◆ Granite stage and column
- ◆ With manufacturer inspection certificate



VM400CNC

MCP probe **(optional)**



0.5X auxiliary objective **(optional)**



2X auxiliary objective **(optional)**



SPECIFICATION

Code	VM300CNC	VM400CNC	VM500CNC
Measuring range(X/Y axis)	300×200mm	400×300mm	500×400mm
Z axis travel with scale	200mm* (automatic)		
Stage moving method	automatic		
Linear scale resolution (X/Y/Z axis)	1μm		
Accuracy (X/Y axis)	(2.2+L/200)μm L is the measuring length in mm		
Repeatability	2μm		
Focus	90mm		
Lens magnification	0.7X-4.5X		
Total magnification	30-220X		
Camera	Color CCD, 2M pixel		
Illumination	contour illumination: LED, brightness adjustment		
	surface illumination: LED(8 sections), brightness adjustment		
Max. glass stage loading	20kg	20kg	25kg
Glass stage size	358mm×258mm	458×358mm	558×458mm
Weight	320kg	400kg	500kg

* The Z axis travel are available upon request


INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
Software with USB dongle	1pc
Computer	1pc
Count card	1pc
Video card	1pc

OPTIONAL ACCESSORIES

0.5X auxiliary objective	VM-OB05X
2X auxiliary objective	VM-OB2X
Calibration scale	Series 552
MCP probe*	VM-MCP

* Should be bought with vision machine






- ◆ The stage is fixed, X/Y/Z Axis can move automatically by programming
- ◆ The light can be changed automatically by programming
- ◆ Automatic focus
- ◆ Granite stage and column with good stability
- ◆ With manufacturer inspection certificate



VM1000CNC





SERIES VM

AUTOMATIC VISION MACHINE

SPECIFICATION

Code	VM600CNC	VM800CNC	VM1000CNC	VM1200CNC	VM1500CNC
Measuring range(Y/X axis)	600×500mm	840×620mm	1000×800mm	1200×1000mm	1500×1200mm
Z axis travel with scale	200mm(automatic)				
Stage moving method	automatic				
Linear scale resolution (X/Y/Z axis)	0.5μm				
Accuracy (X/Y axis)	(2+L/200)μm			(2.5+L/200)μm	(3.5+L/200)μm
	L is the measuring length in mm				
Repeatability	2μm				
Focus	90mm				
Lens magnification	0.7X-4.5X				
Total magnification	23-190X				
Camera	Color CCD, 2M pixel				
Illumination	contour illumination: coaxial light, brightness adjustment				
	surface illumination: LED(8 sections), brightness adjustment				
Max. glass stage loading	45kg	50kg	50kg	60kg	60kg
Glass stage size	755×678mm	995×798mm	1155×978mm	1218×1395mm	1378×1655mm
Weight	1050kg	1400kg	1600kg	1800kg	2100kg

INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
Software with USB dongle	1pc
Computer	1pc
Count card	1pc
Video card	1pc

OPTIONAL ACCESSORIES

0.5X auxiliary objective	VM-OB05X
2X auxiliary objective	VM-OB2X
Calibration scale	Series 552
MCP probe*	VM-MCP

* Should be bought with vision machine

SERIES WE6800

DIGITAL READOUT

- ◆ Recalls the last position after power failure without power
- ◆ Can be connected with linear scale or encoder to carry out processing and measuring for various kinds of machines.



WE6800-3

SPECIFICATION

Code	WE6800-2	WE6800-3
Axis	2	3
RS232 output	Yes	No
Functions	set zero, numerical analysis, pre-sets value, absolute coordinate/relative coordinate, filters numerical value, metric units/imperial units conversion, diameter/semi-diameter conversion, shrinkage rate, find mechanical original point (RI), calculator, circular point hole, oblique line hole, arc processing, bevel processing, lathe	
Resolution	0.1, 0.2, 0.5, 1, 2, 5, 10μm	
Input signal	Orthogonality TTL square wave; frequency<2MHZ; electric current>1mA	
Input voltage	AC 90V~240V	
Dimension	296 x 184 x 45 mm	
Weight	1.5kg	


INCLUDED ACCESSORIES

Main unit	1pc
Mounting bracket	1pc
Ground cable	1pc



LSA1-250


◆ Code explanation:




Example:

Code	Type	Range
LSA1-50	A1	50mm
LSB5-1000	B5	1000mm

Type A1



Type B5



SPECIFICATION

Code	Series LSA1		Series LSB5	
Type	A1		B5	
Range	50-1000mm (step 50mm)		50-1000mm (step 50mm), 1000-3000mm(step 100mm)	
Max. travel length (L1)	L+30(L<950)	L+50(L≥950)	L+30(L<950)	L+50(L≥950)
Mounting hole pitch (L2)	L+132(L<950)	L+152(L≥950)	L+136(L<950)	L+156(L≥950)
Total length (L3)	L+149(L<950)	L+169(L≥950)	L+154(L<950)	L+174(L≥950)
Resolution	1μm		5μm	
Max. response speed	50m/min		60m/min	
Scale grating pitch	20μm			
Scale reference point pitch	50mm			
Accuracy	(5+5L/1000)μm L is the range in mm			
Cable length	3.5m (L: 50-950mm), 5m (L: 1000-1500mm), 10m (L: 1 600-3000mm)			

INCLUDED ACCESSORIES

Main unit	1pc
Shape support	1pc
Anti-dust cover	1pc
Plain base (for range >1500mm)	1pc
Mounting accessories	one package

**1300KPA****CAMERA**

- ◆ Easy to connect computer by USB
- ◆ Supplied with measuring software

**SPECIFICATION**

Camera sensor	1/3" CMOS
Pixel	1.3 Mega
Interface	USB
Dimension (L×W×H)	65 × 48 × 43(mm)
Weight	400g



Connect with Vickers hardness tester



Connect with microscope


OPTIONAL ACCESSORIES**INCLUDED ACCESSORIES**

Main unit	1pc
USB cable	1pc
Software	1pc

C-mount	1300KPA-CM
Calibration rule (graduation: 0.1mm)	RU01
Ø30mm eyepiece adaptor	AD30
Ø30.5mm eyepiece adaptor	AD305

SERIES 552**GLASS SCALE**

- ◆ For calibrating the accuracy of vision machine or profile projector
- ◆ Graduation: 1mm
- ◆ With manufacturer inspection certificate



Code	Range (mm)	Accuracy (μm)
552-008-11	200	1.5
552-012-11	300	2
552-016-11	400	2
552-024-11	600	2.5

- ◆ One key type graphic function for easy understanding.
- ◆ Edge detection is convenient and error-free.



TP340


(Optional)




Standard rod




Sleeve (BT50, 40, 30 /
HSK63, 50, 40)



Radius Inspection



Automatic Angle Inspection



Automatic Angle Inspection





TP340/560

IMAGE TYPE TOOL PRESETTER

SPECIFICATION

Code		TP340	TP560
Axis travel	X axis	D: 130mm	D: 230mm
	Z axis	L: 60-400mm	L: 60-600mm
	Snape	20mm	20mm
Drive mode	X/Z Axis move	manual	manual
	Fine adjustment	with	with
	C axis spindle auto drive	manual	
Accuracy		5μm	
Spindle		ISO50	
Spindle rotation concentricity		2μm	
Resolution		1μm	
Magnification		50X	
Camera		CMOS	
Light		surface light	
Computer		with	
Screen		24"	
Edge finder		with	
Power supply		110V or 220V	
Ampere		2A	
Weight		300 kg	320 kg
Dimension	Length	1 200 mm	1 200 mm
	Width	750 mm	750 mm
	Height	1 700 mm	1 900 mm

INCLUDED ACCESSORIES

Main unit	1pc
BT50 spindle	1pc
Computer with 24" monitor	1pc
Stand	1pc
Measuring software	1pc

OPTIONAL ACCESSORIES

BT50/BT40 sleeve	BT50-40
BT50/BT30 sleeve	BT50-30
BT50-HSK100 sleeve	BT50-HSK100
BT50-HSK63 sleeve	BT50-HSK63
BT50-HSK50 sleeve	BT50-HSK50
BT50-HSK40 sleeve	BT50-HSK40
40mm standard rod	BT40
30mm standard rod	BT30
Label printer	TP340-PR
Vacuum tool clamping	TP340-VTC



VIDEO



Certificate

- ◆ Manual loading control
- ◆ Economic type
- ◆ With manufacturer inspection certificate



Small flat anvil



Large flat anvil



V-type anvil



HARDNESS

SPECIFICATION

Load force	10kgf (98N)
Total load force	60kgf (588N), 100kgf (980N), 150kgf (1471N)
Stage elevation	manual
Loading control	manual
Graduation	0.5HR
Max. test height	155mm
Max. throat	130mm
Dimension	460×180×620mm
Weight	65kg

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter	1pc
Flat anvil	2pcs
V-type anvil	1pc
Rockwell test block	5pcs
Screw driver	2pcs

- ◆ Manual loading control
- ◆ With manufacturer inspection certificate



Small flat anvil



Large flat anvil



V-type anvil



SPECIFICATION

Load force	10kgf (98N)
Total load force	60kgf (588N), 100kgf (980N), 150kgf (1471N)
Stage elevation	manual
Loading control	manual
Graduation	1HR
Max. test height	170mm
Max. throat	160mm
Dimension	487×265×726mm
Weight	73kg

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter	1pc
Flat anvil	2pcs
V-type anvil	1pc
Rockwell test block	3pcs
Dustproof cover	1pc

HR150A**DIGITAL ROCKWELL HARDNESS TESTER**

ACCUD



HARDNESS

- ◆ Manual loading control
- ◆ The hardness scale can be converted to HV and HB
- ◆ With USB interface, for transferring data
- ◆ With manufacturer inspection certificate



Small flat anvil



Large flat anvil



V-type anvil



PR100 printer (optional)

SPECIFICATION

Load force	10kgf (98N)
Total load force	60kgf (588N), 100kgf (980N), 150kgf (1471N)
Stage elevation	manual
Loading control	manual
Resolution	0.1HR
Max. test height	170mm
Max. throat	160mm
Dimension	487×265×726mm
Weight	73kg

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter	1pc
Flat anvil	2pcs
V-type anvil	1pc
Rockwell test block	3pcs
Dustproof cover	1pc

OPTIONAL ACCESSORIES

Wireless printer	PR100
------------------	-------

HR150C

DIGITAL ROCKWELL HARDNESS TESTER



- ◆ Motorized loading control
- ◆ The hardness scale can be converted to HV and HB
- ◆ With USB interface, for transferring data
- ◆ With manufacturer inspection certificate



VIDEO



Small flat anvil



Large flat anvil



V-type anvil



PR100 printer (optional)

SPECIFICATION

Load force	10kgf (98N)
Total load force	60kgf (588N), 100kgf (980N), 150kgf (1471N)
Stage elevation	manual
Loading control	auto
Loading time	1-99s
Resolution	0.1HR
Max. test height	170mm
Max. throat	160mm
Dimension	487×265×726mm
Weight	73kg

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter	1pc
Flat anvil	2pcs
V-type anvil	1pc
Rockwell test block	3pcs
Dustproof cover	1pc

OPTIONAL ACCESSORIES

Wireless printer	PR100
------------------	-------



- ◆ Motorized loading control
- ◆ Economic type
- ◆ With manufacturer inspection certificate



Small flat anvil



Large flat anvil



V-type anvil


SPECIFICATION

Load force	10kgf (98N)
Total load force	60kgf (588N), 100kgf (980N), 150kgf (1471N)
Stage elevation	manual
Loading control	auto
Loading time	1-99s
Resolution	0.5HR
Max. test height	200mm
Max. throat	130mm
Dimension	470×230×680mm
Weight	75kg

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter	1pc
Flat anvil	2pcs
V-type anvil	1pc
Rockwell test block	5pcs

HR150CNC

AUTOMATIC ROCKWELL/SUPERFICIAL ROCKWELL HARDNESS TESTER



- ◆ The stage is fixed, and indenter moves up and down
- ◆ Motorized loading control
- ◆ High-precision closed loop force loading system
- ◆ The hardness scale can be converted to HV and HB
- ◆ With touch screen, easy to operate
- ◆ With wireless printer
- ◆ With manufacturer inspection certificate



SPECIFICATION

Type	Rockwell	Superficial Rockwell
Load force	10kgf (98N)	3kgf (29.4N)
Total load force	60kgf (588N), 100kgf (980N), 150kgf (1471N)	15kgf (147.1N), 30kgf (294.2N), 45kgf (441.3N)
Hardness scale	HRA, HRB, HRC, HRD, HRF, HRG	HR15N, HR30N, HR45N, HR15T, HR30T, HR45T,
Indenter elevation	auto	
Loading control	auto	
Loading time	1-60s	
Resolution	0.1HR	
Max. test height	280mm	
Max. throat	170mm	
Dimension	400×855×620mm	
Weight	80kg	

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter	1pc
Small flat anvil	1pc
V-type anvil	1pc
HRA test block	1pc
HRB test block	1pc

HRC test block	3pcs
HR15N test block	1pc
HR30N test block	2pcs
HR45N test block	1pc
Ø1.5875mm ball	5pcs
Wireless printer	1pc



- ◆ Motorized loading control
- ◆ High-precision closed loop force loading system
- ◆ The hardness scale can be converted to HV and HB
- ◆ With touch screen, easy to operate
- ◆ With printer
- ◆ With manufacturer inspection certificate


SPECIFICATION

Type	Rockwell	Superficial Rockwell
Load force	10kgf (98N)	3kgf (29.4N)
Total load force	60kgf (588N), 100kgf (980N), 150kgf (1471N)	15kgf (147.1N), 30kgf (294.2N), 45kgf (441.3N)
Hardness scale	HRA, HRB, HRC, HRD, HRF, HRG	HR15N, HR30N, HR45N, HR15T, HR30T, HR45T,
Stage elevation	manual	
Loading control	auto	
Loading time	1-60s	
Resolution	0.1HR	
Max. test height	200mm	
Max. throat	160mm	
Dimension	510×290×730mm	
Weight	95kg	

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter	1pc
Small flat anvil	1pc
Large flat anvil	1pc
V-type anvil	1pc

HRA test block	1pc
HRB test block	1pc
HRC test block	3pcs
HR15N test block	1pc
HR30N test block	2pcs
HR45N test block	1pc

HB3000

DIGITAL BRINELL HARDNESS TESTER



- ◆ Electronic close-loop load control system
- ◆ Can converted to HV, HK, HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRK, HR15N, HR30N, HR45N, HR15T, HR30T, HR45T, HS
- ◆ Touch screen
- ◆ With manufacturer inspection certificate



HARDNESS



Small flat anvil



Large flat anvil



V-type anvil



SPECIFICATION

Measuring range	8-650HBW
Loading force	62.5, 100, 125, 187.5, 250, 500, 750, 1000, 1500, 3000kgf
Measuring result	read from LCD
Stage elevation	manual
Load control	automatic
Load dwell time	5-60 seconds
Max. test height	225mm
Max. throat	135mm
Dimension	545×235×79mm
Weight	130kg

INCLUDED ACCESSORIES

Main unit	1pc
20X measuring microscope	1pc
Ø10mm carbide ball indenter	1pc
Ø5mm carbide ball indenter	1pc
Ø2.5mm carbide ball indenter	1pc
Small flat anvil	1pc

Large flat anvil	1pc
V-type anvil	1pc
Hardness test block 150-250HBW10/3000	1pc
Hardness test block 150-250HBW5/700	1pc
Anti-dust cover	1pc



- ◆ For measuring the hardness of the thin, small workpiece or coating
- ◆ Automatic turret
- ◆ The hardness scale can be changed to Rockwell and Brinell scales
- ◆ Touch screen
- ◆ With manufacturer inspection certificate



Measuring system (optional)



HARDNESS

SPECIFICATION

Measuring range	8-2900HV
Test load	0.01, 0.025, 0.05, 0.1, 0.2, 0.3, 0.5, 1kgf
Unit	HV0.01, HV0.025, HV0.05, HV0.1, HV0.2, HV0.3, HV0.5, HV1
Stage elevation	manual
Loading control	automatic (loading/dwell/unloading)
Loading time	1 ~ 99s
Objective	10X (observation), 40X (measurement)
Eyepiece	10X
Total magnification	100X (observation), 400X (measurement)
Max. test height	100mm
Max. throat	130mm
X-Y stage	size: 100×100mm
	travel range: 25×25mm
	graduation: 0.01mm
Dimension	540×260×650mm
Weight	50kg

INCLUDED ACCESSORIES

Main unit	1pc
10X eyepiece	1pc
X-Y stage	1pc
Test block	1pc
Touch screen pen	1pc
Level	1pc
Dustproof cover	1pc
Slice holder	1pc
Cylinder holder	1pc
Vice	1pc

OPTIONAL ACCESSORIES

Measuring system	HVS-MS
------------------	--------

- ◆ Basic type
- ◆ For measuring the hardness of the thin, small workpiece or coating
- ◆ Automatic turret
- ◆ The hardness scale can be changed to Rockwell and Brinell scales
- ◆ With manufacturer inspection certificate



Measuring system (optional)



SPECIFICATION

Measuring range	8-2900HV
Test load	0.01, 0.025, 0.05, 0.1, 0.2, 0.3, 0.5, 1kgf
Unit	HV0.01, HV0.025, HV0.05, HV0.1, HV0.2, HV0.3, HV0.5, HV1
Stage elevation	manual
Loading control	automatic (loading/dwell/unloading)
Loading time	1 ~ 60s
Objective	10X (observation), 40X (measurement)
Eyepiece	10X
Total magnification	100X (observation), 400X (measurement)
Max. test height	100mm
Max. throat	110mm
X-Y stage	size: 100×100mm
	travel range: 25×25mm
	graduation: 0.01mm
Dimension	530×290×490mm
Weight	40kg

INCLUDED ACCESSORIES

Main unit	1pc
10X eyepiece	1pc
X-Y stage	1pc
Test block	1pc
Level	1pc
Dustproof cover	1pc
Slice holder	1pc
Cylinder holder	1pc
Vice	1pc

OPTIONAL ACCESSORIES

Measuring system	HVS-MS
------------------	--------




- ◆ Automatic turret
- ◆ Touch screen
- ◆ The hardness scale can be changed to Rockwell and Brinell scales
- ◆ With manufacturer inspection certificate



HVS50M



X-Y Stage(Optional)



Measuring System(Optional)

SPECIFICATION

Code	HVS10M	HVS50M
Test load	0.3, 0.5, 1, 3, 5, 10kgf	1, 5, 10, 20, 30, 50kgf
Stage elevation	manual	
Loading control	automatic (loading/dwell/unloading)	
Loading time	1-99s (adjustable)	
Objective	10X (observation), 20X (measurement)	
Eyepiece	10X	
Total magnification	100X (observation), 200X (measurement)	
Max. test height	160mm	
Max. throat	135mm	
X-Y stage(optional)	size: 100×100mm	
	travel range: 25×25mm	
	graduation: 0.01mm	
Dimension	530×280×630mm	
Weight	35kg	

INCLUDED ACCESSORIES

Main unit	1pc
10X, 20X Objective	1pc. each
Indenter	1pc
Test block	2pcs
V-avail	1pc
Flat avail	2pcs
Level	1pc
Dustproof cover	1pc

OPTIONAL ACCESSORIES

Measuring system	HVS-MS
X-Y stage	HVS-STAGE

HVS1000MS/HVS1000MCNC

AUTOMATIC MICRO-VICKERS
HARDNESS TESTER

- ◆ Mainly used for various metal parts and parts after thermal treatment Vickers hardness measurement. It is also suitable for the determination of effective hardening depth, coating and heat affected parts of welding parts.
- ◆ It can also be used to observe the metallographic structure of various metal parts and collect, display and print the image
- ◆ Automatic turret
- ◆ The hardness scale can be changed to Rockwell and Brinell scales
- ◆ With manufacturer inspection certificate



HVS1000MCNC



SPECIFICATION

Code	HVS1000MS	HVS1000MCNC
Measuring range	8-2900HV	
Test load	0.01, 0.025, 0.05, 0.1, 0.2, 0.3, 0.5, 1kgf	
Unit	HV0.01, HV0.025, HV0.05, HV0.1, HV0.2, HV0.3, HV0.5, HV1	
Stage elevation	Manual	Automatic
Focus	Manual	Automatic
Repeatability	±1.0%	
Loading control	automatic (loading/dwell/unloading)	
Loading time	1~99s	
Objective	10X (observation), 40X (measurement)	
Eyepiece	10X	
Total magnification	10X (observation), 40X (measurement)	
Camera pixel	5M	
Max. test height	160mm	
Max. throat	160mm	
X-Y stage	size: 150×150mm	
	travel range: 50×50mm	
	movement graduation: 0.001mm	
	movement speed: 1-10mm/s, adjustable	
	movement position repeatability: 1-3μm	
	control: the software system can control the X-Y stage movement automatically by programming, click any point to set the random moving position	
Dimension	540×260×650mm	
Weight	50kg	

INCLUDED ACCESSORIES

Main unit	1pc
10X eyepiece	1pc
Camera	1pc
C-mount	1pc
Computer (with software)	1pc
USB dongle	1pc
Level	1pc
Test block	2pcs
X-Y stage	1pc
Controller	1pc
Vice	1pc
Slice holder	1pc
Cylinder holder	1pc
Touch screen pen	1pc
Dustproof cover	1pc



- ◆ For Rockwell, Brinell and Vickers testing
- ◆ Rockwell testing value gets from screen, and the Brinell and Vickers hardness gets from table in the operation manual
- ◆ With manufacturer inspection certificate


VIDEO


Small flat anvil



Large flat anvil



V-type anvil


SPECIFICATION

Load force for Rockwell	Preload force:98N, Total force: 588 , 980 , 1471 N
Rockwell resolution	0.1HR
Load force for Brinell	306, 613, 1839N
Load force for Vickers	294N
Stage elevation	manual
Loading control	motorized
Max. test height	175mm(Rockwell), 100mm(Brinell), 115mm(Vickers)
Max. throat	165mm
Dimension	520×240×700mm
Weight	105kg

INCLUDED ACCESSORIES

Main unit	1pc
Ø1.5875mm ball carbide indenter	1pc
Diamond indenter for Rockwell	1pc
Ø5mm ball indenter for Brinell	1pc
Ø2.5mm ball indenter for Brinell	1pc
Indenter for Vickers	1pc
Small flat anvil for Rockwell	1pc

Large flat anvil for Rockwell	1pc
V-type anvil	1pc
HRC hardness test block	2pcs
HRB hardness test block	1pc
Brinell hardness test block	1pc
Vickers hardness test block	1pc
Dustproof cover	1pc



HL100

PORTABLE HARDNESS TESTER



- ◆ Large LCD display with backlight
- ◆ Based on HL scale, converted to other hardness scales (HV, HB, HRC, HRB, HS) and tensile strength MPa
- ◆ With wireless printer
- ◆ Can set impact direction
- ◆ With average value calculation function
- ◆ Automatic power off
- ◆ Conforms to the standard ASTM A956-02
- ◆ With manufacturer inspection certificate



VIDEO



Wireless printer (included)



Support ring (12pcs/set, **optional**)

SPECIFICATION

Resolution	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa
Accuracy	$\pm 6\text{HLD}/0.6\text{HRC}$ (HLD=800)
Min. workpiece weight	5kg (directly)
	2kg (on solid support)
	0.1kg (coupled on large plate)
Min. workpiece thickness	5mm
Min. workpiece diameter	22mm
Max. workpiece surface roughness	1.6 μm (Ra)
Power	3 x AAA batteries
Dimension	150 × 80 × 24mm

INCLUDED ACCESSORIES

Main unit	1pc
Wireless printer	1pc
Test block	1pc
Small support ring	1pc
Brush	1pc
Charger for printer	1pc

OPTIONAL ACCESSORIES

Support ring (12pcs/set)	HL-SP
--------------------------	-------



- ◆ Touch screen, with backlight
- ◆ Based on HL scale, converted to other hardness scales (HV, HB, HRC, HRB, HS) and tensile strength Mpa
- ◆ With wireless printer
- ◆ Can set impact direction
- ◆ Memory : 500
- ◆ Low and high limits with judgement
- ◆ Automatic power off
- ◆ Conforms to the standard ASTM A956-02
- ◆ With manufacturer inspection certificate



VIDEO



HARDNESS



Wireless printer (included)



Support ring (12pcs/set, optional)



DC(optional)

C(optional)

D(included)

D+15(optional)

DL(optional)

G(optional)

SPECIFICATION

Resolution	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa
Accuracy	$\pm 6\text{HLD}/0.6\text{HRC}$ (HLD=800)
Min. workpiece weight	5kg (directly)
	2kg (on solid support)
	0.1kg (coupled on large plate)
Min. workpiece thickness	5mm
Min. workpiece diameter	22mm
Max. workpiece surface roughness	1.6 μm (Ra)
Power	Rechargeable battery
Dimension	135×83×24mm

INCLUDED ACCESSORIES

Main unit	1pc
Wireless printer	1pc
Test block	1pc
Small support ring and brush	1pc.each
USB cable and software	1pc
Charger	2pcs

OPTIONAL ACCESSORIES

Impact device DC	HL200-DC
Impact device C	HL200-C
Impact device D+15	HL200-D15
Impact device DL	HL200-DL
Impact device G	HL200-G
Support ring (12pcs/set)	HL-SP



HL350

PORTABLE HARDNESS TESTER



VIDEO



AAA

- ◆ Economic type
- ◆ Based on HL scale, converted to other hardness scales (HV, HB, HRC, HRB, HS) and tensile strength MPa
- ◆ Impact direction can be set
- ◆ With average value calculation function
- ◆ Conforms to the standard ASTM A956-02



Supporting ring (12pcs/set, **optional**)

SPECIFICATION

Resolution	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa
Accuracy	±8HLD/0.8HRC (HLD=800)
Min. workpiece weight	5kg (directly)
	2kg (on solid support)
	0.1kg (coupled on large plate)
Min. workpiece thickness	5mm
Min. workpiece diameter	22mm
Max. workpiece surface roughness	1.6μm (Ra)
Power	3xAAA batteries
Dimension	121×68×30mm

INCLUDED ACCESSORIES

Main unit	1pc
Test block	1pc
Small support ring	1pc
Brush	1pc
Batteries	3pcs

OPTIONAL ACCESSORIES

Support ring (12pcs/set)	HL-SP
--------------------------	-------

HL400

PORTABLE HARDNESS TESTER



Certificate



Data output



AAA

- ◆ Based on HL scale, converted to other hardness scales (HV, HB, HRC, HRB, HS) and tensile strength MPa
- ◆ Impact direction can be set
- ◆ With average value calculation function
- ◆ Automatic power off
- ◆ Conforms to the standard ASTM A956-02
- ◆ With manufacturer inspection certificate



VIDEO



SPECIFICATION

Resolution	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa
Accuracy	±6HLD/0.6HRC (HLD=800)
Min. workpiece weight	5kg (directly)
	2kg (on solid support)
	0.1kg (coupled on large plate)
Min. workpiece thickness	5mm
Min. workpiece diameter	22mm
Max. workpiece surface roughness	1.6μm (Ra)
Power	3xAAA batteries
Dimension	150×80×24mm

INCLUDED ACCESSORIES

Main unit	1pc
Test block	1pc
Small support ring	1pc
Brush	1pc
USB cable	1pc
Batteries	3pcs

HL450/HL450W

PORTABLE HARDNESS TESTER

- ◆ Pocket size, easy to carry
- ◆ Based on HL scale, converted to other hardness scales (HV, HB, HRC, HRB, HS) and tensile strength MPa
- ◆ Impact direction can be set
- ◆ With average value calculation function
- ◆ Conforms to the standard ASTM A956-02
- ◆ With manufacturer inspection certificate



Support ring (12pcs/set, optional)



VIDEO



Certificate



Charge



HL450

SPECIFICATION

Code	HL450	HL450W
Printer	with	without
Resolution	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa	
Accuracy	±6HLD/0.6HRC(HLD=800)	
Min. workpiece weight	5kg (directly)	
	2kg (on solid support)	
	0.1kg (coupled on large plate)	
Min. workpiece thickness	5mm	
Min. workpiece diameter	30mm	
Max. workpiece surface roughness	1.6μm(Ra)	
Output	USB and wireless	
Power supply	rechargeable battery	
Dimension	147×35×22mm	
Weight	65g	

INCLUDED ACCESSORIES

Main unit	1pc	Brush	1pc
Test block	1pc	Charger	1pc
Small support ring	1pc		

OPTIONAL ACCESSORIES

Support ring (12pcs/set)	HL-SP
--------------------------	-------

GY-2

FRUIT HARDNESS TESTER

- ◆ Used to measure the hardness of some fruit like apples, pears
- ◆ Hardness can judge ripeness of the fruit



SPECIFICATION

Range	0.5-4kg/cm ² (0.5-4×10 ⁵ pa)
Graduation	0.02kg/cm ² (0.02×10 ⁵ pa)
Accuracy	±2%
Probe diameter	Ø3.5mm
Probe depth	10mm
Dimension	151×55×30mm
Weight	220g

INCLUDED ACCESSORIES

Main unit	1pc
Probe	1pc





HARDNESS



- ◆ Put the workpiece under the indenter, and press one button, the measuring results will be shown soon
- ◆ Can measure plastic, rubber, sponge with different hardness
- ◆ Include three indenters (type A, D, OO)
- ◆ Touch screen
- ◆ With data output
- ◆ With manufacturer inspection certificate



HARDNESS



unit: mm

SPECIFICATION




Probe moving range	160mm
Stage moving range(X)	80mm
Loading control	Stepping motor
Loading force	Spring force
Max. workpiece height	120mm
Accuracy	±1
Resolution	0.1
Output	USB
Power supply	DC24V/5A

INCLUDED ACCESSORIES

Main unit	1pc
AD/DC adapter	1pc
Software and USB cable	1pc.each
A/D/OO indenter	1pc.each
Calibration block	2pcs



- ◆ Conforms to ISO868, ISO7619, ASTM D 2240
- ◆ Testing time is adjustable
- ◆ With average calculation function
- ◆ With manufacturer inspection certificate


VIDEO

HS5D indenter

HS1A indenter

HSOO indenter

HS1A

Standard block (included)

PR100 printer (optional)

Standard (optional)
SPECIFICATION

Code	HS1A	HS5D	HSOO
Scale	HA(Shore A)	HD(Shore D)	HOO(Shore OO)
For material	soft plastic, rubber, leather, etc.	hard plastic, hard rubber, etc.	soft sponge, soft rubber, etc.
Measuring range	20 ~ 90HA	20 ~ 90HD	20 ~ 90HOO
Resolution	0.1HA	0.1HD	0.1HOO
Accuracy	±1HA	±1HD	±1HOO
Indenter protrusion	2.5mm		
Power	rechargeable battery		
Weight	180g		

INCLUDED ACCESSORIES

Main unit	1pc
Standard block	1pc
Charger	1pc
Software	1pc

OPTIONAL ACCESSORIES

Printer	PR100
Stand for HS1A	HS-1A-STD
Stand for HS5D	HS-5D-STD
Stand for HSOO	HS-OO-STD

SERIES HSM

SHORE HARDNESS TESTER

- ◆ Conforms to ISO868, ISO7619, ASTM D 2240
- ◆ With peak value indicator




HARDNESS




HSM-1A-ST stand (optional)



HSM1A



HSM1A indenter



HSM5D indenter

SPECIFICATION

Code	HSM1A	HSM5D
Scale	HA(Shore A)	HD(Shore D)
For material	soft plastic, rubber, leather, etc.	hard plastic, hard rubber, etc.
Measuring range	20 ~ 90HA	20 ~ 90HD
Graduation	1HA	1HD
Accuracy	±1HA	±1HD
Indenter protrusion	2.5mm	
Weight	500g	

OPTIONAL ACCESSORIES

Stand for HSM1A	HSM-1A-ST
Stand for HSM5D	HSM-5D-ST



SERIES HS

TEST STAND FOR DIGITAL SHORE HARDNESS TESTER

- ◆ For digital shore hardness tester
- ◆ Perform repeatable hardness measurement due to fewer possibilities of human error or measurement variations
- ◆ Special structure for stable loading



HS-1A-STD

SPECIFICATION

Code	HS-1A-STD	HS-5D-STD	HS-OO-STD
For hardness tester	HS1A	HS5D	HSOO
Test force (weight block)	1kg	5kg	0kg
Stage diameter	Ø115mm		
Max. workpiece height	45mm		
Max. testing width	63mm (from test point to the column)		
Dimension	Ø195x370mm		
Weight	5.6kg	11kg	4.5kg

SERIES HSM

TEST STAND FOR SHORE HARDNESS TESTER

- ◆ For shore hardness tester
- ◆ Perform repeatable hardness measurement due to fewer possibilities of human error or measurement variations



HSM-1A-ST

SPECIFICATION

Code	HSM-1A-ST	HSM-5D-ST
For hardness tester	HSM1A	HSM5D
Test force (weight block)	1kg	5kg
Stage diameter	Ø100mm	
Max. workpiece height	75mm	
Max. testing width	65mm (from test point to the column)	
Weight	2kg	7kg



UHT200

ULTRASONIC HARDNESS TESTER



- ◆ Mainly used for small or thin-walled products as well as parts of complex shape or with areas that need to be tested in hard-to-reach places
- ◆ With a shockproof silicone case that prevents the device from malfunctioning
- ◆ Hardness scales: HV, HB, HRC and tensile strength Mpa
- ◆ Memory: 256
- ◆ Automatic power off
- ◆ With special software for data processing
- ◆ With manufacturer inspection certificate



Measure gear teeth



Measure small part



SPECIFICATION

Measuring range	HRC	20-70
	HB	90-650
	HV	230-940
	Mpa	370-1740
Accuracy	HRC	±1.5
	HB	±3%
	HV	±3%
Min. workpiece thickness		1mm
Min. workpiece diameter		5mm
Max. workpiece surface roughness		Ra:2.5μm
Min. thickness of surface hardening layer		0.1mm
Min. test area		Ø1mm
Power supply		Rechargeable battery
Dimension		122×65×24mm

INCLUDED ACCESSORIES

Main unit	1pc
Probe (50N)	1pc
Rechargeable battery	2pcs
USB cable and software	1pc.each
Charger	1pc

HB937-1**BARCOL HARDNESS TESTER**

Accud



HARDNESS

- ◆ To measure the hardness of thick workpieces made of pure aluminum, aluminum alloy, fiber reinforced plastic, hard plastic, etc.
- ◆ Comforms to ASTM B648-2000
- ◆ With manufacturer inspection certificate

**SPECIFICATION**

Hardness range	0 ~ 100HBa (25 ~ 150HBW)
Graduation	1HBa
Accuracy	±2HBa (42 ~ 52HBa) ±1HBa (84 ~ 88HBa)
Min. workpiece thickness	0.8mm
Dimension	142×65×90mm
Weight	500g

INCLUDED ACCESSORIES

Main unit	1pc
Spare indenter	2pcs
Hardness test block	2pcs
Wrench	1pc

SERIES DHB937**DIGITAL BARCOL HARDNESS TESTER**

- ◆ To measure the hardness of thick workpieces made of pure aluminum, aluminum alloy, fiber reinforced plastic, hard plastic, etc.
- ◆ Comforms to ASTM B648-2000
- ◆ The scale of DHB937-2 can converted to HW, HV, HBW and HRE

**DHB937-1****SPECIFICATION**

Code	DHB937-1	DHB937-2
Scale conversion	No	Yes
Hardness range	0 ~ 100HBa (25 ~ 150HBW)	
Graduation	0.1HBa	
Accuracy	±2HBa (42 ~ 48HBa) ±1HBa (84 ~ 88HBa)	
Min. workpiece thickness	0.8mm	
Power supply	3×AAA batteries	
Dimension	180×70×90mm	
Weight	800g	

INCLUDED ACCESSORIES

Main unit	1pc
Spare indenter	2pcs
Calibration block	1pc
Battery	3pcs
Hardness test block	2pcs
Wrench	1pc



SERIES HW

WEBSTER HARDNESS TESTER

- ◆ To measure the hardness of soft metal such as aluminum alloy, copper, brass, soft steel
- ◆ Conforms to the standard ASTM B647



HW-L20

SPECIFICATION

Code	HW-L20	HW-L20A	HW-L20B	HW-B75	HW-C75	HW-B92
Application	aluminum alloy			hard aluminum alloy and brass	soft brass and copper	soft steel and cold-rolled steel
Measuring hardness range	58-131HV			63-105HRF	18-100HRE	50-92HRB
Thickness range to be measured of flat workpiece	0.4 ~ 6mm	0.4 ~ 13mm	0.4 ~ 8mm	0.4 ~ 6mm	0.4 ~ 6mm	0.4 ~ 6mm
Min. Internal diameter of tube workpiece	Ø10mm	Ø10mm	Ø6mm	Ø10mm	Ø10mm	Ø10mm
Hardness range	0 ~ 20HW					
Min. reading	1HW					
Accuracy	±0.5HW (at 5 ~ 17HW)					
Dimension	205×30×85mm					
Weight	500g					

INCLUDED ACCESSORIES

Main unit	1pc	Hardness test block	1pc
Spare indenter	1pc	Wrench	1pc

STE70

DIGITAL REBOUND TESTER



- ◆ Measure the strength of general building components, bridges and various concrete components (slabs, beams, columns, bridges and so on.)
- ◆ Built in national unified curve (JGJ/T23-2011)
- ◆ Small size, modular design, easy to use
- ◆ Built in large capacity memory, can store 999 standard components, and a single component can set up 99 measuring areas and 159840 measuring point data




SPECIFICATION

Measuring range	10-60Mpa
Impact energy	2.207J
Accuracy	±1
Stiffness of spring	785±30N.m
Working length of spring	61.5±0.3mm
Tensile length of spring	75±0.3mm
Rated value of steel anvil	80±2
Operating temperature	-4°C-40°C
Display	2.08 inch OLED display
Power supply	rechargeable battery
Weight	1.1kg

INCLUDED ACCESSORIES

Main unit	1pc
Sander	1pc
Spare spring	1set
Screwdriver	3pcs
Software and cable	1set
AD/DC adapter	1pc



Rockwell/Vickers/Brinell



Shore A



Leeb

SPECIFICATION

Code	Type	Hardness
BLK-HRC1	Rockwell C	60-70HRC
BLK-HRC2		20-30HRC
BLK-HRC3		30-35HRC
BLK-HRC4		40-50HRC
BLK-HRC5		50-55HRC
BLK-HRB1	Rockwell B	85-95HRB
BLK-HRB2		60-70HRB
BLK-HV1	Vickers	700-800HV5
BLK-HV2		700-800HV10
BLK-HV3		400-600HV5
BLK-HV4		400-600HV10
BLK-HB1	Brinell	150-250HBW 10/3000
BLK-HB2		150-250HBW 5/750
BLK-HLD	Leeb	750-830HLD
BLK-HSA	Shore A	7pcs/set: 30-39HA, 40-49HA, 50-59HA, 60-69HA, 70-79HA, 80-89HA, 90-99HA

- ◆ For checking, identifying and specifying the roughness by symbol
- ◆ Accuracy: -17% ~ +12%



Machining method	Quantity	Roughness (Ra)
Flatlapping	2	0.1, 0.05μm
External grinding	4	0.2, 0.4, 0.8, 1.6μm
Plain grinding	6	0.05, 0.1, 0.2, 0.4, 0.8, 1.6μm
Horizontal milling	6	0.4, 0.8, 1.6, 3.2, 6.3, 12.5μm
Vertical milling	6	0.4, 0.8, 1.6, 3.2, 6.3, 12.5μm
Turning	6	0.4, 0.8, 1.6, 3.2, 6.3, 12.5μm





SERIES RP100XS

PROFILE AND ROUGHNESS MEASURING MACHINE




- ◆ Measure the surface profile and roughness with same probe at same time(for **RP100RS**)
- ◆ With high precision and good linearity digital probe(for **RP100RS** and **RP100TS**)
- ◆ Easy to install and replace without calibration
- ◆ Stylus can contact, lift and return automatically
- ◆ CAD file can be exported and imported(for **RP100RS** and **RP100JS**)
- ◆ With manufacturer inspection certificate



RP100RS



stage




vice



profile calibration block
(for **RP100RS** and **RP100JS**)



roughness calibration block
(for **RP100RS** and **RP100TS**)



Φ3*20mm point stylus



Φ3*21mm knife stylus


SPECIFICATION

Code		RP100RS	RP100TS	RP100JS
Measuring object		profile and roughness	roughness	profile
Roughness parameter		Ra, Rq, Rz(Ry), R3z, Rz(DIN), Rz(JIS), Rz(ISO), Rp, Rv, Rt, Rsk, Rsm, Rc, Rpm, Rku, Rdq, Roc, Mr1, Mr2, Rpk, Rvk, Rk, Rdc, A1, A2, R, Rx, AR, Rcp, Rmax		\
Wave parameter		wt, wa, wp, wv, wq, wc, wku, wsk, w, wx, wz, wsm, wdc, wte, wmr, Aw, c(wmr), wmr(c), wdq		\
Profile parameter		Pt, Pa, Pp, Pv, Pq, Pc, Pku, Psk, Pdq/p△q, Psm, Pdc, Pmr(c), Pz, pmr, C(pmr)		\
Profile	X axis range	100mm	\	100mm
	X axis straightness	0.8μm/100mm	\	0.8μm/100mm
	Z axis range	650mm	\	650mm
	Z1 axis range (probe)	40mm	\	40mm
	Accuracy	±(1+0.12H)μm, H is measuring height in mm	\	±(1+0.12H)μm, H is measuring height in mm
	Measuring arc accuracy	±(1.5+R/8)μm, R is measuring radius in mm	\	±(1.5+R/8)μm, R is measuring radius in mm
	Measuring angle accuracy	±2'	\	±2'
Roughness	Z1 axis range (probe)	40mm	20mm	\
	Accuracy	±5%		\
	Repeatability	±3%		\
	Resolution	0.0001μm		\
	Number of cut-offs	3-7		\
	Cut off	0.025, 0.08, 0.25, 0.8, 2.5, 8mm		\
Climbing ability		77°(up), 88°(down)		
Measuring speed		0.02mm- 4.0mm/s		
Measuring mode		probe movement		
Movement control		joystick		
Power supply		220V		
Size		985x710x1450mm		

INCLUDED ACCESSORIES

Main unit	1pc
Profile calibration block(for RP100RS and RP100JS)	1pc
Roughness calibration block(for RP100RS and RP100TS)	1pc
Stage	1pc
Vise	1pc
Φ3x21mm R0.025mm knife stylus	2pcs

Φ3x20mm R5μm point stylus	1pc
Φ8x150mm measuring rod	1pc
Computer	1pc
Printer	1pc
Anti-dust cover	1pc

Measuring profile

Measuring roughness


SR200

ROUGHNESS TESTER



VIDEO



Certificate



Data output



Charge

- ◆ 13 roughness parameters
- ◆ With probe position indicator
- ◆ Roughness values, profile, and curve can be shown on the display
- ◆ Memory of maximum 100 results
- ◆ With a mini SD card slot, can save the result into SD card
- ◆ Automatic power off
- ◆ With manufacturer inspection certificate




unit: mm



SR200-STD Stand(optional)



Measuring software



SPECIFICATION

Parameters		Ra, Rz, Ry, Rq, Rp, Rm, Rt, R3z, Rmax, Sk, S, Sm, tp
Range		160μm(±80μm)
Accuracy		±10%
Resolution (Ra)		0.001μm
Probe	type	inductive
	stylus radius/angle	5μm/90°
	stylus material	diamond
Measuring force		0.4mN
Measuring unit		μm/μin
Cut off		0.25/0.8/2.5mm
Number of cut-offs		1-5
Traverse speed		0.5mm/s, 1mm/s
Memory		100 measurement results
Output		USB
Power		built-in rechargeable battery
Dimension(L×W×H)		140×52×48mm
Weight		440g

INCLUDED ACCESSORIES

Main unit	1pc
Standard probe	1pc
Calibration block	1pc
Calibration support	1pc
Adjustable stand	1pc
Probe cover	1pc
USB cable and software	1pc
AC/DC adapter	1pc
Software	1pc

OPTIONAL ACCESSORIES



Extension rod	SR200-ER
Curved surface probe	SR200-02
Groove probe	SR200-03
Deep groove probe	SR200-04
Test stand	SR200-STD
Printer	SR200-PR



- ◆ Pocket size
- ◆ With a tablet, can set the parameter quickly
- ◆ Connected with tablet via bluetooth
- ◆ Roughness values, profile, and curve can be shown on the display
- ◆ With manufacturer inspection certificate



unit: mm



Measuring software



SR200-STD Stand(optional)

SPECIFICATION

Parameters		Ra, Rz, Ry, Rq, Rp, Rm, Rt R3z, Rmax, Sk, S, Sm, tp
Range(Ra)		0.025-12.5μm
Accuracy		±10%
Resolution (Ra)		0.001μm
Probe	type	inductive
	stylus radius/angle	5μm/90°
	stylus material	diamond
Measuring force		0.4mN
Measuring unit		μm/μin
Cut off		0.25/0.8/2.5mm
Number of cut-offs		1-5
Traverse speed		0.5mm/s, 1mm/s
Output file format		Word, Excel
Power		built-in rechargeable battery
Dimension(L×W×H)		130×40×44mm
Weight		340g

INCLUDED ACCESSORIES

Main unit	1pc
Standard probe	1pc
Tablet	1pc
Calibration block	1pc
Calibration support	1pc
USB cable	1pc
AC/DC adapter	1pc

OPTIONAL ACCESSORIES

Extension rod	SR200-ER
Curved surface probe	SR200-02
Groove probe	SR200-03
Deep groove probe	SR200-04
Test stand	SR200-STD
Printer	SR200-PR





SR400

ROUGHNESS TESTER



- ◆ The probe can be working with the main unit separately
- ◆ 22 roughness parameters
- ◆ With probe position indicator
- ◆ Roughness values, profile, and curve can be shown on the display
- ◆ Memory of maximum 100 results
- ◆ Automatic power off
- ◆ With manufacturer inspection certificate



unit: mm

Stand probe	
Curved surface probe 	
Groove probe (groove height < 10mm)	
Small hole probe (hole dia. > 2mm)	
Extension rod	

Working with height gauge



Work together



SR200-STD Stand(optional)

SPECIFICATION

Parameters		Ra, Rz, Rq, Rp, Ry, Rv, Rs, R3z, R3y, Rc, Rt, Rmax, Rk, Rku, Rsm, Rpc, Rpk, Rvk, Rsk, Mr1, Mr2, Rz(JIS)
Range		±160μm
Accuracy		±10%
Resolution(Ra)		0.001μm
Probe	type	inductive
	stylus radius/angle	5μm/90°
	stylus material	diamond
Measuring force		4mN
Measuring unit		μm/μin
Cut off		0.25/0.8/2.5mm
Number of cut-offs		1-5
Traverse speed		0.5mm/s, 1mm/s
Memory		100 measurement results
Output		USB
Power		built-in rechargeable battery
Dimension(L×W×H)		158×64×52mm
Weight		400g

INCLUDED ACCESSORIES

Main unit	1pc
Standard probe	1pc
Calibration block	1pc
Calibration support	1pc
Adjustable stand	1pc
Cable(long and short)	2pcs
USB cable and software	1pc
AC/DC adapter	1pc

OPTIONAL ACCESSORIES

50mm extension rod	SR400-ER
Curved surface probe	SR400-02
Deep groove probe	SR400-03
Small hole probe	SR400-04
Test stand	SR200-STD
Printer	SR400-PR
Connector for height gage	SR400-SP1

SR110

ROUGHNESS TESTER



- ◆ Pocket size
- ◆ Automatic power off
- ◆ With manufacturer inspection certificate

SPECIFICATION

Parameters		Ra, Rz, Rq, Rt
Range (Ra)		±10μm
Accuracy		±15%
Resolution (Ra)		0.001μm
Probe	type	piezoelectric
	stylus radius/angle	10μm/90°
	stylus material	diamond
Measuring force		0.5N
Measuring unit		μm/μin
Cut off		0.25/0.8/2.5mm
Evaluation length		1.25/4/5mm
Power		built-in rechargeble battery
Dimension(L×W×H)		114×82×33mm
Weight		160g



INCLUDED ACCESSORIES


Main unit	1pc
Calibration block	1pc
Calibration support	1pc
USB cable	1pc
AC/DC adapter	1pc

489

DIGITAL SURFACE PROFILE GAUGE



- ◆ Measure peak-to-valley height of blast cleaned surface.
If the profile is too low, the adhesion of the coating to the surface will be reduced.
If the profile is too high, it is dangerous that the profile peaks will remain non-coating, rust spots maybe occur.
- ◆ Meet ASTM D 4417-B
- ◆ Zero set block is included, set zero before measurement
- ◆ Buttons: tolerance Go and No-Go display, data preset, measuring direction change, max./min./TIR measurement, inch/metric conversion, ABS/INC measurement
- ◆ Automatically power off (time is adjustable)
- ◆ Data output (cable code:200-03 or 200-04)
- ◆ Stainless steel base



Code	Range	Digital indicator stroke	Digital indicator resolution	Accuracy
489-010-01	0-12.7mm/0-0.5"	12.7mm/0.5"	0.001mm/0.00005"	±0.005mm





489


DIGITAL SURFACE PROFILE GAUGE




- ◆ Measure peak-to-valley height of blast cleaned surface.
If the profile is too low, the adhesion of the coating to the surface will be reduced.

If the profile is too high, it is dangerous that the profile peaks will remain non-coating, rust spots maybe occur.

- ◆ Meet ASTM D 4417-B
- ◆ Zero set block is included, set zero before measurement
- ◆ Buttons: on/off, zero, mm/inch, ABS/INC measurement
- ◆ Automatically power off (time is adjustable)
- ◆ Data output (cable code: 200-03 or 200-04)
- ◆ Stainless steel base



measure peak-to-valley height
of blast cleaned surface



Code	Range	Digital indicator stroke	Digital indicator resolution	Accuracy
489-010-02	0-12.7mm/0-0.5"	12.7mm/0.5"	0.001mm/0.00005"	±0.005mm




489


SURFACE PROFILE GAUGE

- ◆ Measure peak-to-valley height of blast cleaned surface.
If the profile is too low, the adhesion of the coating to the surface will be reduced.
- If the profile is too high, it is dangerous that the profile peaks will remain non-coating, rust spots maybe occur.

- ◆ Meet ASTM D 4417-B
- ◆ Zero set block is included, set zero before measurement
- ◆ Stainless steel base



measure peak-to-valley height
of blast cleaned surface



Code	Range	Dial indicator stroke	Dial indicator graduation	Accuracy
489-001-01	0-1mm	1mm	0.001mm	±0.005mm



- ◆ High precision air-floating spindle, never wear, can keep high accuracy for long time
- ◆ High accuracy and good stability
- ◆ Large arc can be measured
- ◆ Automatic identification of contour discontinuities, can eliminate automatically or manually



SPECIFICATION

Measuring range	Max. dia.	Ø180mm
	Min. inner dia.	Ø5mm
	Max. height	420mm
Spindle accuracy	Radial error	$\pm(0.025+5H/10000)\mu\text{m}$
	Axial error	$\pm(0.02+6X/10000)\mu\text{m}$
Stage	Stage dia.	Ø180mm
	Rotation dia.	Ø300mm
	Max. load weight	25kg
	Adjustment range	adjust the eccentricity: $\pm 2\text{mm}$; adjust the level: $\pm 1^\circ$
	Rotation speed	0-12 rpm(adjustable)
Horizontal arm	Horizontal moving distance	150mm
	Probe moving speed	0.5-6mm/s (adjustable)
Sensor	Range	500 μm
	Resolution	0.005 μm
	Stylus	Ø2mm ruby ball
	Measuring force	1-12g
Air source		0.45-0.80Mpa
Air consumption		0.2m ³ /min
Power supply		110~220V
Dimension		920x530x1600mm

INCLUDED ACCESSORIES

Main unit	1pc
Stage	1pc
Precision chuck	1pc
Standard ball	1pc
Standard elliptical part	1pc
Probe	1pc

OPTIONAL ACCESSORIES

Computer	1pc
Printer	1pc
Anti-dust cover	1pc





- ◆ Measure the thickness of tank, pipe and big workpiece
- ◆ LCD with backlight
- ◆ With manufacturer inspection certificate



VIDEO



Transducer PT-06 (optional)



Transducer ZT-12 (optional)



Transducer GT-12 (optional)



SPECIFICATION

Graduation	0.01mm(<100mm)
	0.1mm(≥100mm)
Repeatability	0.03mm(<100mm)
	0.1mm(≥100mm)
Accuracy	±0.04mm (<10mm)
	±(0.04+H/1000)mm (10~100mm)
	±H/333mm (≥100mm)
	H is the thickness in mm
Velocity	1000-9999m/s
Power	3×AAA batteries
Dimension	69×150×29mm
Weight	220g

INCLUDED ACCESSORIES

Main unit	1pc
Transducer PT-08	1pc
AAA battery	3pcs
Couplant	1bottle
USB cable	1pc

OPTIONAL ACCESSORIES

Transducer	PT-06, ZT-12, GT-12
------------	---------------------

SPECIFICATION OF TRANSDUCERS

Code	Application	Range	Frequency	Min. pipe dimension diameter×thickness	Working temperature
PT-08	general use	0.8-300mm	5.0MHz	20×1.2mm	<60°C
PT-06	thin workpiece	0.75-40mm	7.5MHz	15×1.2mm	<60°C
ZT-12	casting steel	2-400mm	2.0MHz	30×4mm	<60°C
GT-12	high temperature	3-100mm	5.0MHz	25×3mm	<310°C



- ◆ Measure the thickness of tank, pipe and big workpiece
- ◆ Can measure thickness of workpiece with coating
- ◆ Wide measuring range with optional transducer
- ◆ LCD with backlight
- ◆ With manufacturer inspection certificate

Transducer **ST300-P6 (optional)**Transducer **ST300-ZT12 (optional)**Transducer **ST300-GT12 (optional)**

SPECIFICATION

Graduation	0.01mm(<100mm)
	0.1mm(≥100mm)
Repeatability	0.03mm(<100mm)
	0.1mm(≥100mm)
Accuracy	±0.05mm (<10mm)
	±(0.05+H/100)mm (≥100mm) H is the thickness in mm
Max. coating thickness	1000um
Velocity	1000-9999m/s
Power	2×AA batteries
Dimension	71×150×33mm
Weight	160g

INCLUDED ACCESSORIES

Main unit	1pc
Transducer PT-10	1pc
AA battery	2pcs
Couplant	1bottle

OPTIONAL ACCESSORIES

Transducer	ST300-P6
Transducer	ST300-ZT12
Transducer	ST300-GT12
Couplant (high temperature)	ST300-CP

SPECIFICATION OF TRANSDUCERS

Code	Application	Range	Frequency	Min. pipe dimension diameter×thickness	Working temperature
PT-10	general use	1-300mm	5.0MHz	20×1.2mm	<70°C
ST300-P6	thin workpiece	0.75-35mm	7.0MHz	15×1.2mm	<70°C
ST300-ZT12	casting steel	4-500mm	2.0MHz	30×5mm	<70°C
ST300-GT12	high temperature	4-80mm	5.0MHz	25×5mm	<480°C

ST100A

ULTRASONIC THICKNESS GAUGE



- ◆ Measure the thickness of tank, pipe and big workpiece
- ◆ LCD with backlight
- ◆ With manufacturer inspection certificate

SPECIFICATION

Measuring range	1.2-225mm(steel)
Graduation	0.01mm(<100mm)
	0.1mm(≥100mm)
Repeatability	0.05mm(<100mm)
	0.1mm(≥100mm)
Accuracy	±0.5%L+0.04mm L is the thickness in mm
Velocity	1000-9999m/s
Min.measured tube	Ø20×3mm
Power	rechargeable battery
Dimension	64×116×27mm
Weight	220g



INCLUDED ACCESSORIES

Main unit	1pc
Transducer	1pc
Battery	1 set
Couplant	1 bottle
Brush	1pc

CFN1500B

COATING THICKNESS GAUGE



- ◆ Integrated F and N type probe
- ◆ F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic substrates (iron, steel)
- ◆ N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive substrates (zinc, copper, aluminum)
- ◆ Large display screen
- ◆ V-type probe to make the cylinder measurement easier
- ◆ With um/mil unit conversion
- ◆ Automatic power on/ off
- ◆ With back light
- ◆ With manufacturer inspection certificate

SPECIFICATION

Range	0~1500μm
Accuracy	2μm(0~100μm)
	3%(100~1500μm)
Resolution	0.1μm (0~99.9μm)
	1μm (100~1500μm)
Min. measuring area	25×25mm
Min. curvature	convexity: 5mm; concave: 30mm
Min substrate thickness	magnetic material: 0.2mm; non magnetic material: 0.05mm
Memory	30 sets
Power supply	AAA batteries
Dimension(L×W×H)	120×52×26mm
Weight	170g



INCLUDED ACCESSORIES

Main unit	1pc
Calibration foil	1set
Calibration base	1set
AAA battery	2pcs



- ◆ F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic substrates (iron, steel)

N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive substrates (zinc, copper, aluminum)

- ◆ External interchangeable probe
- ◆ Single and continuous working mode
- ◆ Low and high limits setting with judgement
- ◆ With average calculation
- ◆ With comparison measurement function
- ◆ With temperature compensation
- ◆ Turn off automatically
- ◆ With manufacturer inspection certificate



VIDEO



CN1500

SPECIFICATION

Code	CF1500H	CF1500	CN1500	CFN1500
Probe type	F		N	F and N
Range	0 ~ 1500μm			
Accuracy	2μm (0 ~ 100μm)			
	2%(100 ~ 1500μm)			
Resolution	0.1μm (0 ~ 999μm)			
	1μm (1000 ~ 1500μm)			
Memory	500			
Working temperature	-10°C~150°C	-10°C~50°C		
Power	3×AAA batteries			
Dimension(L×W×H)	150×50×29mm			
Weight	170g			

INCLUDED ACCESSORIES

Main unit	1pc
Calibration foil	1set
Calibration base	1set
USB cable	1pc
AAA battery	3pcs

CN/CF/CFN1000S

COATING THICKNESS GAUGE (BASIC TYPE)



- ◆ F type probe is used to measure the thickness of non-magnetic coatings (zinc, copper, enamel, plastic and so on) on magnetic substrates (iron, steel)
- N type probe is used to measure the thickness of non-conductive coatings (varnish, enamel, plastic and so on) on conductive substrates (zinc, copper, aluminum)
- ◆ External interchangeable probe
- ◆ Low and high limits setting with judgement
- ◆ With average/Max/Min. calculation
- ◆ Turn off automatically
- ◆ With manufacturer inspection certificate



CF1000S



probe for bores and grooves
(Code:CF1000S-F90)



probe for large range
(Code:CF1000S-F10)

SPECIFICATION

Code	CF1000S	CN1000S	CFN1000S
Probe type	F	N	F and N
Range	0 ~ 1250μm		
Accuracy	3μm (0 ~ 50μm)		
	3%+1μm (50 ~ 1250μm)		
Resolution	0.1μm (0 ~ 999μm)		
	1μm (1000 ~ 1250μm)		
Memory	500		
Power	2xAA batteries		
Dimension(LxWxH)	128x68x32mm		
Weight	340g		

INCLUDED ACCESSORIES

Main unit	1pc
Calibration foil	1set
Calibration base	1set
USB cable	1pc
AA battery	2pcs

OPTIONAL ACCESSORIES

Magnetic induction probe for bores and grooves	CF1000S-F90
Magnetic induction probe for large range (500μm-10mm)	CF1000S-F10

SERIES 740

WET FILM GAUGE

- ◆ Made of stainless steel



package



740-300-01



740-800-11




Code	Range	Accuracy	Thickness
740-800-11	25-800μm	±5μm	1.8mm
740-300-01	25-3000μm	25μm-100μm:±5μm 100μm-3000μm:±5%	1mm

SERIES STB


STANDARD TEST BLOCK FOR ULTRASONIC THICKNESS GAUGE

- ◆ Material of step wedge blocks can be customized
- ◆ Accuracy: ±0.02mm
- ◆ Stainless steel material: 45#




STB-4B


unit:mm




STB-4A




STB-5A




STB-7A



STB-4B



STB-5B



STB-7B

THICKNESS

MTT3600

X-RAY FLUORESCENCE SPECTROMETER

- ◆ Fast and non-destructive test to identify alloy grade and composition
- ◆ For all kinds of high and low temperature alloy steel, stainless steel, tool steel, chromium/molybdenum steel, nickel alloy, cobalt alloy, nickel/cobalt heat resistant alloy, titanium alloy
- ◆ Can measure the coating thickness like PCB, range: 0.01-30μm
- ◆ IP54 dust/waterproof



Iron-based alloy	
957A C1	
304	
Stainless steel	
Element	%
Fe	71.51
Cr	18.45
Ni	8.43
Mn	1.18
Cu	0.23
V	0.09
Mo	0.05
Sn	0.02
Ti	0.02
Nb	0.00

SPECIFICATION

Excitation source	50KV/200μA; Ag target, integrated end window, micro X-ray tube and high voltage power supply, matching power ≥4W
Detector	Si-PIN, window area 25mm ²
Elemental analysis range	Ti, V, Cr, Mn, Fe, Co, Ni, Cu, Zn, Se, Zr, Nb, Mo, Rh, Pd, Ag, Cd, Sn, Sb, Hf, Ta, W, Re, Pb, Bi
Alloy analysis mode	automatically identify alloy grade/alloy material qualified test mode
Collimator filter	7 groups
Display	5-inch LCD touch screen
Analysis	3-60 sec (adjustable)
Memory	built-in 64G, storage data, >500000 groups
Data transmission	built-in WIFI, U disk, blue-tooth (support blue-tooth printer)
Data export format	EXCEL, BMP, PDF, CSV
Battery	6800mAh lithium battery, for 8 hours working time
Air pressure compensation	built-in pressure measurement module for system compensation and correction
System	Win-IOT operation system
Work environment	temperature: 0~40°C, relative humidity: 10%~90%
Dimension	250×320×80mm
Weight	1900g

INCLUDED ACCESSORIES

Main unit	1pc
Charger	1pc
Battery	2pcs
Test film	1pc
Sample with cup	1pc
Protection support (including calibration silver)	1pc
USB cable	1pc

HTC-1**TEMPERATURE METER**

Accud



VIDEO

**SPECIFICATION**

Temperature range	-20°C-60°C
Temperature accuracy	1%
Temperature resolution	0.1°C
Humidity range	10%RH-99%RH
Humidity accuracy	5%
Humidity resolution	1%
Power supply	AAA battery
Dimension	98×106×20 mm
Weight	50g

INCLUDED ACCESSORIES

Main unit	1pc
Battery	1pc

HTC-70**TEMPERATURE METER**

TEMPERATURE

- ◆ External probe
- ◆ Probe is IP67 protection level, can measure the water temperature in fish tank

**SPECIFICATION**

Temperature range	-5°C-70°C
Temperature accuracy	±1°C
Temperature resolution	0.1°C
Humidity range	10%RH-99%RH
Humidity accuracy	5%
Humidity resolution	1%
Power supply	AAA battery
Dimension	98×120×21 mm
Weight	60g

INCLUDED ACCESSORIES

Main unit	1pc
Battery	1pc

HTC-300

TEMPERATURE METER FOR FOOD




- ◆ Used to measure the temperature inside of food
- ◆ With magnet on the back
- ◆ Automatic power on/off
- ◆ With calibration function



Temperature range	-50°C-300°C(-58°F-572°F)
Temperature accuracy	0.8°C(0-150°C)
Temperature resolution	0.1°C/0.1°F
Max. protrusion depth	110mm
Power supply	CR2032
Dimension	164×42×20 mm
Weight	100g

With magnet on the back



INCLUDED ACCESSORIES

Main unit	1pc
CR2032 Battery	1pc

IT700/IT1650S

INFRARED THERMOMETER



- ◆ For quick measuring remote temperature
- ◆ Easy to operate



VIDEO



IT700

SPECIFICATION

Code	IT700	IT1650S
Measuring temperature range	-50°C-950°C	-50°C-1650°C
Accuracy	1.5°C(<75°C)/2%(75-500°C)/3%(>500°C)	
Repeatability	0.5°C or 1%	
Distance spot ratio	12:1	50:1
Response time	500ms	
Resolution	0.1°C	
Power supply	9V battery	
Emissivity	0.1-1.00 (adjustable)	
Dimension	186×119×50 mm	225×160×66 mm
Weight	185g	320g

INCLUDED ACCESSORIES

Main unit	1pc
Battery	1pc


ITC450

INFRARED THERMAL IMAGING CAMERA



Acceud

- ◆ Trigger button for taking pictures
- ◆ The IR image can be mixed with visible image
- ◆ Built-in 5000mA rechargeable battery
- ◆ With USB/WIFI data output interface
- ◆ With measuring software
- ◆ Menu in Chinese, English, Spanish, French, Japanese, Korean, Russian, Arabian



SPECIFICATION

IR image	Resolution	220x160
	Measuring range	-10°C - 450°C
	Accuracy	±2°C(<100°C), 2%(≥100°C)
	Detector	8-14um
	Frame rate	9Hz
	Field of view	Horizontal :56°, vertical:42°
	Lens	Ø4mm
	Measuring method	Max, Min, center spot and average
	Emissivity	0.1-1(adjustable)
	Color palettes	8 types
Visible camera	Resolution	640x480
	Frame rate	25Hz
	Illumination	LED
Screen size		3.5 inch
Image		outline fusion, overlay fusion, picture in picture, IR image, visible
Data output		USB/WIFI
Image storage		8G, can save 20,000 pictures
Image format		TIFF
Working temperature		-10°C-50°C
Protection level		IP54
Power supply		Rechargeable battery, for 5 hours working
Size		230×100×90mm
Weight		420g

INCLUDED ACCESSORIES

Main unit	1pc
USB cable and software	1pc

THICKNESS

DMT600

DIGITAL MULTIMETER

9V

- ◆ With protective case
- ◆ With backlight
- ◆ With low battery indicator
- ◆ Safety rating: CAT III 600V



test leads (included)

SPECIFICATION

Function	Range	Resolution(d)	Accuracy
DC Voltage	200mV/2V/20V/200V	0.1mV/1mV/10mV/100mV	$\pm(0.5\%+4d)$
	600V	1V	$\pm(1\%+5d)$
AC Voltage	200V/600V	100mV/1V	$\pm(1.2\%+10d)$
DC Current	2mA/20mA/200mA	1 μ A/10 μ A/100 μ A	$\pm(1.5\%+3d)$
	10A	100mA	$\pm(2\%+5d)$
Resistance	200 Ω	0.1 Ω	$\pm(1\%+5d)$
	2k Ω /20k Ω /200k Ω	1 Ω /10 Ω /100 Ω	$\pm(0.8\%+3d)$
	2Mk Ω	1k Ω	$\pm(1\%+15d)$
Diode test	open circuit voltage 2.8V DC		
Continuity check	<50 Ω		
Power supply	9V battery		
Dimension	150×75×50 mm		
Weight	325g		



INCLUDED ACCESSORIES

Main unit	1pc
9V battery	1pc
Test lead	2pcs

DCM600

DIGITAL AC/DC CLAMP METER

AAA

- ◆ 35mm open size
- ◆ With data hold function
- ◆ With low battery indicator
- ◆ Safety rating: CAT III 600V



test leads (included)

SPECIFICATION

Function	Range	Resolution(d)	Accuracy
AC Current	2A	1mA	$\pm(2.5\%+20d)$
	20A	10mA	$\pm(2.5\%+5d)$
	200A	100mA	$\pm(2.5\%+8d)$
	400A	1A	$\pm(2.5\%+8d)$
	600A	1A	for reference
DC Voltage	600V	1V	$\pm(1.5\%+5d)$
AC Voltage	600V	1V	$\pm(1.5\%+5d)$
Resistance	2000K Ω	10K Ω	$\pm(1.2\%+3d)$
Continuity check	<30 Ω		
Power supply	2×AAA batteries		
Dimension	195×48×30 mm		
Weight	380g		



INCLUDED ACCESSORIES

Main unit	1pc
AAA battery	2pcs
Test lead	2pcs

WMM700**WOOD MOISTURE METER**

- ◆ For quick measuring wood moisture
- ◆ Easy to operate



Extension probe (Optional)

SPECIFICATION

Moisture	Measuring range	2-40%/50%/60%/70%(for different wood)
	Accuracy	±1%+0.5
	Resolution	0.5%
Temperature	Measuring range	-10℃-60℃
	Accuracy	±1%
	Resolution	0.1℃
Humidity	Measuring range	20%RH-95%RH
	Accuracy	±5% RH
	Resolution	0.1% RH
Power supply		2×AAA
Dimension		136×55×60mm
Weight		107g

**INCLUDED ACCESSORIES**

Main unit	1pc
Battery	2pcs

OPTIONAL ACCESSORIES

Extension probe	WMM700-EP
-----------------	-----------

WMM900**CONCRETE MOISTURE METER**

- ◆ Use high frequency electromagnetic wave method to measure wall or concrete moisture
- ◆ Different density can be selected according to different building materials, increase the accuracy

Measure wall moisture



Measure concrete moisture

**SPECIFICATION**

Measuring range	0-40%
Accuracy	±2%
Resolution	0.5%
Working temperature	0℃-40℃
Power supply	3×AAA
Dimension	132×67×26mm95g
Weight	95g

**INCLUDED ACCESSORIES**

Main unit	1pc
Battery	3pcs

PORTABLE

LT900

LASER TACHOMETER

AAA

- ◆ With back light
- ◆ Real-time/ Max/Min/average measurement
- ◆ Can review the last measuring value



VIDEO



SPECIFICATION

Measuring range	2.5-99999rpm	
Resolution	< 1000rpm	0.1rpm
	≥ 1000rpm	1rpm
Accuracy	< 1000rpm	± (0.1%+5d)rpm, d is resolution
	≥ 1000rpm	± (1%+5d)rpm, d is resolution
Measuring distance	50-500mm	
Power supply	2x1.5V AAA batteries	
Dimension	56×30×127 mm	
Weight	106g	

CT900

CONTACT TYPE TACHOMETER

AAA

- ◆ Measure rotary speed, line speed
- ◆ With back light
- ◆ Real-time/ Max/Min/average measurement
- ◆ Can review the last measuring value



SPECIFICATION

Range	rotary speed	0.5-19999rpm
	line speed	0.05-1999.9m/min
Resolution(d)	rotary speed	0.1rpm (<1000rpm), 1rpm (≥1000rpm)
	line speed	0.01m/min (<100m/min), 0.1m/min (≥100m/min)
Accuracy	rotary speed	± (0.5%+d)rpm (<300rpm)
		± (0.05%+d)rpm (≥300rpm)
	line speed	± (0.1%+d)m/min
Sampling time	0.8s (above 60rpm)	
Power supply	2x1.5V AAA battery	
Dimension	55×33×158 mm	
Weight	106g	



OPTIONAL ACCESSORIES

Main unit	1pc
Accessories (5 types)	1pc.each
AAA battery	2pcs

DS40K

DIGITAL TACHOMETER/STROBPSCOPE



- ◆ Used to measure the rotation and vibration speed
- ◆ With back light
- ◆ With fine and coarse adjustment



SPECIFICATION

Measuring range	60 ~ 40000rpm	
Resolution	<400rpm	0.01rpm
	400-4000rpm	0.1rpm
Accuracy	≥4000rpm	1rpm
	≥1000rpm	±0.05%rpm
Memory	10	
Power supply	Lithium ion rechargeable batteries	
Dimension	195×73×38 mm	
Weight	220g	

VT63


PEN TYPE VIBRATION TESTER



- ◆ Measure the motor, fan, compressor and measuring tools vibration
- ◆ Power off automatically
- ◆ Pocket size



VIDEO



SPECIFICATION

Range	Speed	0.1-199.9m/s (frequency range:10-1KHz)
	Accelerated speed	0.1-199.9m/s ² (frequency range: 10-15KHz)
	Displacement	0.001-1.999mm (frequency range:10-500Hz)
Accuracy	±5%+2 digit	
Power supply	rechargeable battery	
Operation temperature	0-40℃	
Operation humidity	0-90%	
Dimension	152x23x12mm	
Weight	75g	

INCLUDED ACCESSORIES

Main unit	1pc
Charger	1pc

PORTABLE

TM100

LASER DISTANCE METER



- ◆ IP54 protection
- ◆ With a level in the body
- ◆ With distance, area, volume and height measurement function
- ◆ With Max, Min measuring function
- ◆ With back light
- ◆ Power off automatically



VIDEO



SPECIFICATION

Measuring range	0.1m-100m
Accuracy (at the prefect reflection surface)	1.5mm
Resolution	1mm
Unit	m/inch/ft
Light spot	Φ8mm@40m
Memory	20
Power supply	2x1.5VAAA batteries
Laser	635nm<1mW
Dimension	120×54×30 mm
Weight	110g

INCLUDED ACCESSORIES

Main unit	1pc
Battery	2pcs

TM40/100B

LASER DISTANCE METER



- ◆ Economic type
- ◆ With a level in the body
- ◆ With distance, area, volume and height measurement function
- ◆ With Max, Min measuring function
- ◆ With backlight
- ◆ Power off automatically



VIDEO



TM100B

SPECIFICATION

Code	TM40	TM100B
Measuring range	0.1m-40m	0.1m-100m
Accuracy (at the prefect reflection surface)	2mm	
Resolution	1mm	
Unit	m/inch/ft	
Light spot	Φ8mm@40m	
Memory	20	
Power supply	2x1.5VAAA batteries	
Laser	635nm<1mW	
Dimension	120×54×30 mm	
Weight	110g	

INCLUDED ACCESSORIES

Main unit	1pc
Battery	2pcs

TM1200


LASER DISTANCE METER




- ◆ IP54 protection
- ◆ Can measure distance, angle and speed
- ◆ Power off automatically



Distance, angle measurement



Speed measurement



SPECIFICATION

Measuring range	3m-1500m
Magnification	8X
View field	7°
Distance measuring accuracy	±1m
Speed measuring accuracy	±5km/h
Power supply	Rechargeable battery(for 30000 times)
Laser	635nm<1mW
Dimension	104×77×41 mm
Weight	197g

INCLUDED ACCESSORIES

Main unit	1pc
USB cable	1pc

LM100

LIGHT METER



- ◆ Unit: LUX/FC
- ◆ Max/Min/average measurement
- ◆ With data hold function
- ◆ Power off automatically

SPECIFICATION

Range	0.1-200000LUX/0.01-20000FC
Accuracy	±(6%+d) d is resolution
Resolution	0.1LUX (<1000), 1LUX (≥1000)
Temperature range	0-60°C
Temperature accuracy	2°C
Sampling time	8 times/s
Repeatability	±2%
Light wavelength range	400-700nm
Power supply	-10-50°C
Dimension	152×55×33 mm
Weight	136g



INCLUDED ACCESSORIES

Main unit	1pc
AAA battery	3pcs

PORTABLE

LL030

LASER LEVEL



- ◆ 2 lines (cross line)
- ◆ With auto-level mode



SPECIFICATION

Laser beam	green
Leveling range	4°±1°
Leveling accuracy	±3mm/10m
Horizontal/vertical accuracy	±3mm/10m
Laser class	Class II
Laser wavelength	510-530nm
Working distance(Line)	30m
Protection level	IP54
Power supply	2×AA
Operation temperature	-10°C- 50°C
Dimension	66x75x76mm
Weight	255g

STANDARD DELIVERY

Main unit	1pc
Stand	1pc
Battery	2pcs




Stand

LL025/325/525

LASER LEVEL



- ◆ With auto-level mode



SPECIFICATION

Code	LL025	LL325	LL525
Laser beam	cross line	3 lines	5 lines
Laser beam color	green		
Leveling range	<3°		
Leveling accuracy	±1mm/7m		
Horizontal/vertical accuracy	±1mm/7m		
Laser class	Class II		
Laser wavelength	635-650nm		
Max.working distance(Line)	30m		
Line width	3mm@10m		
Power supply	rechargeable battery		
Operation temperature	-10°C- 50°C		
Dimension	115x115x200mm		
Weight	1kg		



LL025

STANDARD DELIVERY

Main unit	1pc
Battery	2pcs
AC/DC adapter	1pc

OPTIONAL ACCESSORIES

Stainless steel stand	LL025-ST
-----------------------	----------

Stand(optional)



SLM130**DIGITAL SOUND LEVEL METER**

9V

- ◆ Fast(2 time/sec)/slow(1 time/sec) display
- ◆ With back light
- ◆ Real-time and Max/Min measurement
- ◆ High limits setting with judgement and alarm



VIDEO

**SPECIFICATION**

Measuring sound range	30-130db
Accuracy	1.5db
Resolution	0.1db
Power supply	9V battery
Dimension	143×56×35 mm
Weight	64g

AM30**DIGITAL ANEMOMETER**

9V

- ◆ With temperature display
- ◆ With back light
- ◆ Real-time/ Max/Average measurement
- ◆ Unit: m/s, km/h, ft/min, Knots, mph



VIDEO

**SPECIFICATION**

Measuring range	0.3-30m/s
Accuracy	±5%
Resolution	0.1m/s
Power supply	9Vbattery
Dimension	155×56×35 mm
Weight	154g

PORTABLE

PH12

PEN-TYPE PH METER



- ◆ Measure PH value and temperature
- ◆ Automatic temperature compensation
- ◆ Temperature unit conversion function
- ◆ Used for PH measurements like water or paper
- ◆ Waterproof button, more than 20,000 press times working life
- ◆ Calibration method can be selected for multi-point calibration or single-point calibration
- ◆ Electrode loss can be viewed for timely replacement of the electrode head
- ◆ ASTM and European standard are available
- ◆ Automatic power off

SPECIFICATION

PH range	-2.00~+16.00PH
PH accuracy	±0.01PH
Temperature measuring range	0-100.0°C/32-212°F
Type of electrode	Bubble electrodes
Display	LCD screen with backlight
Power supply	2×AAA batteries
Working temperature	0-60.0°C/32-140°F
Dimension	Ø39×180
Weight	108g



INCLUDED ACCESSORIES

Main unit	1pc
Battery	2pcs
PH buffer powder	3pcs

LSM25/LSM50

LASER SCAN MICROMETER

PORTABLE

- ◆ It can be used to measure the diameter of wires, cables and steel bars, as well as the width or thickness of steel strips and copper strips
- ◆ Can be accurately measured whether the product shakes or not
- ◆ Non contact and precision measurement

SPECIFICATION

Code	LSM25	LSM50
Range	0.1-20mm	0.4-50mm
Accuracy (d is diameter in mm)	±(0.2d+2)μm	±(0.3d+2)μm
Resolution	1μm	
Laser wavelength	650nm	
Sampling time	600 times/s	
Output	RS485/MODBUS	
Alarm output	DC24V/1A	
Working temperature	5-45°C	
Power supply	AC100-240V	
Dimension	298×72×167 mm	400×76×164 mm
Weight	8kg	10kg



LSM25


OPTIONAL ACCESSORIES

Main unit	1pc
Display	1pc
Power cable	1pc

- ◆ Used to test the adhesion of paint on metal, plastic and so on
- ◆ Conforms to ISO 2409, ASTM D3359, BS00E6
- ◆ Blade hardness: 58-62HRC



blade(1mm pitch)



blade(2mm pitch)



blade(3mm pitch)



3M tape



Magnifier



step 1: make grid cutting on surface



step 2: paste and remove the tape

0	5B	0	
1	4B	0-5%	
2	3B	5-15%	
3	2B	15-35%	
4	1B	35-65%	
5	0B	>65%	

step 3: according to the shedding status, judge the adhesion grade

SPECIFICATION

Blade pitch		1mm	2mm	3mm
Applied paint thickness	on hard substrate (like metal)	0-60μm	61-120μm	121-250μm
	on soft substrate (like wood, plaster)	—	0-120μm	121-250μm
Minimum substrate thickness	hard substrate (like metal)	0.25mm	0.25mm	0.25mm
	soft substrate (like wood, plaster)	—	10mm	10mm
Minimum size of test sample		150x100mm		
Dimension		130x25x30mm		
Weight		130g		

INCLUDED ACCESSORIES

Main unit	1pc
1mm pitch blade	1pc
2mm pitch blade	1pc
3mm pitch blade	1pc
Test tape	1pc
Magnifier	1pc
Small brush	1pc




DRM50

DIGITAL PORTABLE REFRACTOMETER



- ♦ Used to measure the concentration of coolant, honey water and salt water
- ♦ Power off automatically

Pipette (included)



SPECIFICATION

Measuring range	0-50%
Graduation	0.1%
Accuracy	±0.2%
Battery	rechargeable battery
Dimension	143x42x22mm
Weight	115g


INCLUDED ACCESSORIES

Main unit	1pc
Pipette	1pc
Cable for recharging	1pc

SERIES RM

PORTABLE REFRACTOMETER

- ♦ Used to measure the concentration of coolant, honey water and salt water




SPECIFICATION

Code	RM10	RM20	RM32
Measuring range	0-10%	0-20%	0-32%
Graduation	0.2%		
Accuracy	±0.1%	±0.1%	±0.2%
Dimension	160x27x40mm		
Weight	175g		

INCLUDED ACCESSORIES

Main unit	1pc
Pipette	1pc
Screwdriver	1pc


SPECIFICATION

Range (ethylene)	Glycol	0-50°C
	Propylene Glycol	0-50°C
	Battery fluid	1.10-1.40kg/L
	Cleaning liquid	0-40°C
	Adblue(Urea)	30-35%
Accuracy (ethylene)	Glycol	5°C
	Propylene Glycol	5°C
	Battery fluid	0.01kg/L
	Cleaning liquid	10°C
	Adblue(Urea)	0.2%

INCLUDED ACCESSORIES

Main unit	1pc
Pipette	1pc
Screwdriver	1pc

- ◆ To test the gloss of painting, printing ink, surfaces of future metal, granite, ceramic, plastic, paper, etc.
- ◆ Conforms to ISO 2813, ASTM D 2457, ASTM D 523
- ◆ Large display screen


THICKNESS
SPECIFICATION

Incidence angle	20°	60°	85°
Measuring range	0~2000GU	0~1000GU	0~160GU
Resolution	0.1GU (range<119.9GU)		
Accuracy	±1.5GU (range≤100GU)		
	±1.5% (range>100GU)		
Repeatability	±0.1GU (range<10GU)		
	±0.2GU (range: 10~100GU)		
	±0.2% (range>100GU)		
Measuring speed	1s		
Measuring area	10×10mm	15×9mm	36×5mm
Power supply	Rechargeable battery		
Dimension	160×75×90mm		
Weight	350g		

INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
USB cable and software	1pc

GM60

60° GLOSS METER



- ◆ Basic type
- ◆ To test the gloss of painting, printing ink, surfaces of future metal, granite, ceramic, plastic, paper, etc.
- ◆ Conforms to ISO 2813, ASTM D 2457, ASTM D 523
- ◆ With manufacturer inspection certificate



SPECIFICATION

Incidence angle	60°
Measuring range	0~200GU
Measuring area	9x15mm
Resolution	1GU
Repeatability	±1GU (0-100GU), ±1%GU (100-200GU)
Measuring speed	0.5S
Power supply	AA battery
Dimension	160x52x84mm
Weight	300g

INCLUDED ACCESSORIES

Main unit	1pc
Calibration block	1pc
AA battery	1pc

HM1000

HAZE METER



- ◆ Conform to the standards: ASTM D1003/1044, GB/T 2410, JJF 1303-2011, CIE 15.2, JIS K7105, JIS K7361, JIS K7136
- ◆ The instrument can easily achieve ASTM D1003 non-compensation method
- ◆ With quality control software

SPECIFICATION

Measuring range	0~100%
Accuracy	<0.4
Repeatability	0.1
Resolution	0.1
Integrating sphere size	Φ154mm
Light source	400nm to 700nm, combined LED light
Sensor	The PD array detector, satisfies CIE V(λ)2 degree visual response
Measuring aperture	Φ20mm
Sample size	Thickness<170mm
Observer angle	2°
Illumination	D65, A, C
Measuring time	about 1.5s
Data output	USB
Illumination life span	5 years, more than 3 million times measurements
Display	7-inch TFT color LCD, capacitive touch screen
Size	290×211×511mm
Weight	7.6kg



INCLUDED ACCESSORIES

Main unit	1pc
Calibration cover	1pc
USB cable and software	1pc
AC/DC adapter	1pc

CM100**COLOR METER**

- ◆ Pocket size, easy to carry
- ◆ Press one button to get the measure result in one second
- ◆ With software

SPECIFICATION

Illuminating/viewing geometry	8/d
Measuring aperture	Ø8mm
Measuring wave length	400~700nm
Wave length step	10nm
View angle	2°/10°
Light source device	LED light
Memory	10pcs standards
Measuring time	1s
Power supply	rechargeable lithium-ion battery
Lamp Life	5 years, more than 3 million measurements
Charging Time	12 thousand measurements(full electricity)
Output	USB/bluetooth
Dimension	Ø30×100 mm
Weight	88g

**INCLUDED ACCESSORIES**

Main unit	1pc
White calibration block	1pc
Charger	1pc
USB cable and software	1pc

CM200**COLOR METER**

- ◆ Convenient and fast locating
- ◆ Portable structure design which is more conducive to keep the instrument stable

**SPECIFICATION**

Illuminating/Viewing Geometry	8/d
Measuring Aperture	Φ8mm
Light Source	D65
Light Source Device	LED blue light excitation
Memory	5000pcs standards
Repeatability	<0.08ΔE*ab
Power supply	rechargeable lithium-ion battery
Lamp Life	3 years, more than 1 million measurements
Charging Time	2 hours (first time 8 hours--100% electricity)
Dimension	205×70×100 mm
Weight	500g

INCLUDED ACCESSORIES

Main unit	1pc
White calibration block	1pc
Charger	1pc
USB cable and software	1pc

PORTABLE

CM3010

SPECTROPHOTO METER



- ◆ Concave grating spectrophotometric
- ◆ 3.5-inch TFT color LCD
- ◆ D/8 geometrical optics, conforms with CIE No.15,ISO7724/1,ASTME1164, DIN5033
- ◆ Use long life and low power consumption combined LED light source
- ◆ Switchable 8mm/4mm aperture, support both SCI and SCE at the same time
- ◆ Large storage capacity, over 20,000 measurement data
- ◆ USB port and Bluetooth 4.0
- ◆ With software



SPECIFICATION

Optical geometry	reflect: di:8°, de:8°(diffused illumination, 8-degree viewing angle)
Integrating sphere size	Ø48mm
Light source	combined LED light
Spectrophotometric mode	concave grating
Sensor	256 image element double array CMOS image sensor
Wavelength range	400~700nm
Wavelength interval	10nm
Semiband width	10nm
Measured reflectance range	0~200%
Measuring aperture	dual aperture: MAV: Ø8mm; SAV: Ø4mm
Specular component	SCI&SCE
Color space	CIE LAB, XYZ, Yxy, LCh, CIE LUV, HunterLAB
Color difference formula	ΔE^*_{ab} , ΔE^*_{uv} , ΔE^*_{94} , $\Delta E^*_{cmc}(2:1)$, $\Delta E^*_{cmc}(1:1)$, ΔE^*_{00v} , ΔE (Hunter)
Other colorimetric index	WI(ASTM E313, CIE/ISO, AATCC, Hunter), YI(ASTM D1925, ASTM 313), Metamerism index MI, Staining fastness, Color fastness, Color strength, Opacity
Observer angle	2°/10°
Illuminant	A, C, D50, D55, D65, D75, F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, F11, F12, CWF, U30, T183, T184, U35
Displayed data	spectrogram/values, samples chromaticity values, color difference values/graph, PASS/FAIL result, color offset
Measuring time	2.6s
Repeatability	Spectral reflectance
	MAV/SCI, within 0.1% of standard deviation(400~700nm: 0.2%)
Repeatability	Colorimetric values
	MAV/SCI: $\Delta E^* \leq 0.04$
Inter-instrument error	MAV/SCI: $\Delta E^* \leq 0.2$
Measurement mode	single measurement, average measurement
Data port	USB, Bluetooth 4.0
Data storage	standard 1000 pcs, sample 20000 pcs
Illuminant life span	5 years, more than 3 million times measurements
Battery	Li-ion battery, 5000 measurements within 8 hours
Dimension	184×77×105mm
Weight	600g

INCLUDED ACCESSORIES

Main unit	1pc
White and black calibration cavity	1pc
USB cable and software	1pc
AC/DC adapter	1pc

OPTIONAL ACCESSORIES

Printer	CM3010-PT
Powder test box	CM3010-PB



- ◆ For pull and push measurement
- ◆ Adjusting the display direction automatically
- ◆ With overload protection
- ◆ Peak and real-time working mode
- ◆ Unit: mN, N, gf, kgf, ozf, lbf
- ◆ Memory: 1000
- ◆ Power off automatically
- ◆ Low and high limits setting with judgement
- ◆ With software, can show the force graph
- ◆ With manufacturer inspection certificate


VIDEO

DF200

 Stand(Code: **FS1000**, **Optional**)

PR100 printer (**Optional**)


flat



v-type



knife-edge



point



pull clamp



extension rod

SPECIFICATION

Code	DF10	DF20	DF50	DF100	DF200	DF500	DF1000
Range	10N	20N	50N	100N	200N	500N	1000N
Resolution	0.001N	0.005N	0.005N	0.005N	0.005N	0.01N	0.1N
Accuracy	$\pm 0.2\% \times \text{FS (full scale)}$						
Power	rechargeable battery						
Dimension	153x73x34mm						
Weight	700g						

INCLUDED ACCESSORIES

Main unit	1pc
Charger	1pc
Software	1pc
Push/pull clamps	6pcs(flat, V type, knife-edge, point, pull clamp, extension rod)

OPTIONAL ACCESSORIES

Wireless printer	PR100
Stand	FS1000

SERIES DF

DIGITAL FORCE GAUGE



- ◆ For pull and push measurement
- ◆ Adjusting the display direction automatically
- ◆ With overload protection
- ◆ Peak and real-time working mode
- ◆ Unit: mN, N, gf, kgf, ozf, lbf
- ◆ Memory: 1000
- ◆ Power off automatically
- ◆ Low and high limits setting with judgement
- ◆ With software, can show the force graph
- ◆ With manufacturer inspection certificate



VIDEO



DF5K



PR100 printer (Optional)



flat clamp (Optional)



extension (Optional)



pull clamp (Optional)

SPECIFICATION

Code	DF2K	DF5K	DF10K	DF20K
Range	2000N	5000N	10000N	20000N
Resolution	0.5N	1N	1N	1N
Accuracy	$\pm 0.2\% \times FS$ (full scale)			
Power	rechargeable battery			
Dimension	153x73x34mm			
Weight	700g			

INCLUDED ACCESSORIES

Main unit	1pc
Sensor	1pc
Charger	1pc
Software	1pc

OPTIONAL ACCESSORIES

M12 Flat clamp (for DF2K, DF5K and DF10K)	DF2K-FC
M12 Extension (for DF2K, DF5K and DF10K)	DF2K-ER
M12 Pull clamp (for DF2K, DF5K and DF10K)	DF2K-PC
M18 Flat clamp (for DF20K)	DF20K-FC
M18 Extension (for DF20K)	DF20K-ER
M18 Pull clamp (for DF20K)	DF20K-PC
Wireless printer	PR100



- ◆ For pull and push measurement
- ◆ Adjusting the display direction automatically
- ◆ With overload protection
- ◆ Peak and real-time mode
- ◆ Unit: N, gf, kgf, ozf, lbf
- ◆ Memory: 500
- ◆ Power off automatically
- ◆ With manufacturer inspection certificate


VIDEO

DF1000E

 Stand(Code: **FS1000**, **Optional**)

PR100 printer (**Optional**)


flat



v-type



knife-edge



point



pull clamp



extension rod

SPECIFICATION

Code	DF10E	DF50E	DF100E	DF500E	DF1000E
Range	10N	50N	100N	500N	1000N
Resolution	0.01N	0.01N	0.1N	0.1N	1N
Accuracy	$\pm 0.3\% \times \text{FS (full scale)}$				
Power	rechargeable battery				
Dimension	150x72x33mm				
Weight	450g				

INCLUDED ACCESSORIES

Main unit	1pc
Charger	1pc
Software	1pc
Push/pull clamps	6pcs(flat, V type, knife-edge, point, pull clamp, extension rod)

OPTIONAL ACCESSORIES

Wireless printer	PR100
Stand	FS1000

SERIES DFXXS

DIGITAL FORCE GAUGE



- ◆ Basic type
- ◆ For pull and push measurement
- ◆ Unit: N, kgf, ozf, lbf
- ◆ Low and high limits setting with judgement
- ◆ With backlight
- ◆ Power off automatically
- ◆ With manufacturer inspection certificate



DF500S



flat



v-type



knife-edge



point



pull clamp



extension rod

SPECIFICATION

Code	DF10S	DF20S	DF50S	DF100S	DF200S	DF500S
Range	10N	20N	50N	100N	200N	500N
Resolution	0.01N	0.01N	0.01N	0.1N	0.1N	0.1N
Accuracy	±1% x FS (full scale)					
Power	2xAAA batteries					
Dimension	124x60x31mm					
Weight	400g					

INCLUDED ACCESSORIES

Main unit	1pc
AAA batteries	2pcs
Push/pull clamps	6pcs(flat, V type, knife-edge, point, pull clamp, extension rod)



- ◆ Push and pull test
- ◆ Peak(max.) or tracking work mode
- ◆ With manufacturer inspection certificate



Stand(Code: **FS1000**, Optional)



NK-500



flat



v-type



point



knife-edge



pull clamp



extension rod

SPECIFICATION

Code	NK-20	NK-30	NK-50	NK-100	NK-200	NK-300	NK-500
Range(N)	20	30	50	100	200	300	500
Range(Kg)	2	3	5	10	20	30	50
Resolution(N)	0.1	0.2	0.25	0.5	1	2	2.5
Accuracy	±2% xFS (full scale)						

INCLUDED ACCESSORIES

Main unit	1pc
Push tip	4pcs (flat, V type, knife-edge, point)
Pull clamp	1pc
Extension rod	1pc

OPTIONAL ACCESSORIES

Stand	FS1000
-------	--------

SERIES FS

TEST STAND FOR FORCE GAUGE

- ◆ For force gauges
- ◆ To be used in vertical and horizontal orientation



Force gauge is
not included



FS1000

SPECIFICATION



Code	FS1000S	FS1000
Scale	with	without
Load capacity	1000N	
Travel	200mm (3mm vertical movement per revolution of handwheel)	
Dimension	96x250 x 446mm	
Weight	13kg	

SERIES DF



CLAMPS FOR FORCE GAUGE

unit:mm




FLAT CHUCK (Code: DF-FC1)






FLAT CHUCK (Code: DF-FC2)




CAM GRIP (Code: DF-CG1)





CAM GRIP (Code: DF-CG2)





LOCK THREAD ADAPTER (Code: DF-TA)





WIRE GRIP (Code: DF-WG1)



WIRE TERMINAL GRIP (Code: DF-TWG1)



WEDGE GRIP (Code: DF-WT1)



DFS500**MOTORIZED VERTICAL TEST STAND**

- ◆ Used to measure the force of pull or push with series DF force gauge
- ◆ Programmable, can do automatic testing cycle
- ◆ Can set three working modes: displacement cycle, force cycle, user-defined cycle
- ◆ With alarm: position, force and motor block

SPECIFICATION


Max. capacity	650N
Max. travel	220mm
Moving speed	30-720mm/min(adjustable)
Resolution of speed	1mm/min
Moving speed accuracy	2%
Displacement resolution	0.01mm
Displacement accuracy	±0.3mm
Output	USB, RS232
Working temperature	10-40°C
Power supply	AC100-240V
Dimension	340×180×630 mm
Weight	15kg

**INCLUDED ACCESSORIES**

Main unit	1pc
Software and USB cable	1pc
Power cable	1pc

DFS500H**MOTORIZED HORIZONTAL TEST STAND**

- ◆ Used to measure the force of pull or push with series DF force gauge
- ◆ Programmable, can do automatic testing cycle
- ◆ Can set three working modes: displacement cycle, force cycle, user-defined cycle
- ◆ With alarm: position, force and motor block

**SPECIFICATION**

Max. capacity	650N
Max. travel	220mm
Moving speed	30-720mm/min(adjustable)
Resolution of speed	1mm/min
Moving speed accuracy	2%
Displacement resolution	0.01mm
Displacement accuracy	±0.3mm
Output	USB, RS232
Working temperature	10-40°C
Power supply	AC100-240V
Dimension	671×120×278 mm
Weight	13kg

INCLUDED ACCESSORIES

Main unit	1pc
Software and USB cable	1set
Power cable	1pc

SERIES DST

DIGITAL SPRING TESTER

- ◆ For spring force testing
- ◆ Peak and real-time working mode
- ◆ Unit: N, kgf, lbf
- ◆ Power off automatically
- ◆ Low and high limits setting with judgement
- ◆ With digital scale, resolution:0.01mm



DST50

SPECIFICATION


Code	DST10	DST20	DST30	DST50	DST100	DST200	DST300	DST500
Capacity	10N	20N	30N	50N	100N	200N	300N	500N
Resolution	0.001N	0.002N	0.01N	0.01N	0.02N	0.05N	0.1N	0.1N
Test range	5%-100% capacity							
Accuracy	±1% x FS (full scale)							
Max. spring length(free status)	65mm			95mm				
Range of digital scale	65mm			95mm				
Disk diameter	Ø30mm			Ø49mm				
Power	220V/110V							
Dimension	300x235x600mm			300x235x620mm				
Weight	13.2kg	13.2kg	13.2kg	17.3kg	19.1kg	19.1kg	19.1kg	20.8kg

INCLUDED ACCESSORIES

Main unit	1pc
Power cable	1pc
Foot screw	4pcs

- ◆ For tensile, tear testing of different kinds of materials
- ◆ With testing analysis software
- ◆ Unit: N, kN, Kg, Lbf, Mpa, Lbf/in², Kg/mm²

Software



UTT100



UTT1000

SPECIFICATION

Code	UTT50	UTT100	UTT200	UTT500	UTT1000	UTT2000	UTT10000	UTT20000
Type	single column				double column			
Max.capacity	50kg	100kg	200kg	500kg	1000kg	2000kg	10000kg	20000kg
Accuracy	0.5%	0.5%	0.5%	0.5%	0.5%	0.5%	0.5%	0.5%
Resolution	1/1000000xFS (Max. capacity)				1/500000xFS(Max. capacity)			
Max. travel	600mm				800mm			
Width	180mm				450mm			
Test speed	0.1-500mm/min							
Moving speed accuracy	±0.3%							
Movement controller	servo motor							
Power supply	100-240AC							
Dimension	500×420×1250mm				750×500×1850mm		1100×760×2100mm	
Weight	50kg				260kg		750kg	

INCLUDED ACCESSORIES

Main unit	1pc
Computer	1pc
USB dongle	1pc
Fixture	1set



SERIES TWM


TORQUE WRENCH



- ◆ Easy to set the torque value
- ◆ Accuracy: $\pm 4\%$ *
- ◆ According to ISO6789, ASMEB107. 14
- ◆ With manufacturer inspection certificate



TWM25



SPECIFICATION

Code	TWM25	TWM50	TWM100	TWM200	TWM340
Range	5 ~ 25N.m	10 ~ 50N.m	20 ~ 100N.m	40 ~ 200N.m	70 ~ 340N.m
Size of square drive	3/8"	3/8"	3/8"	1/2"	1/2"
Length(L)	275mm	275mm	380mm	505mm	695mm
Weight	420g	420g	580g	1.3kg	1.9kg

* Accuracy is available upon request

SERIES TWM-B

TORQUE WRENCH



- ◆ Economic type
- ◆ Easy to set the torque value
- ◆ Accuracy: $\pm 4\%$ (clockwise)
- ◆ According to ISO6789, ASMEB107. 14
- ◆ With manufacturer inspection certificate



TWM25B

SPECIFICATION

Code	TWM25B	TWM60B	TWM60D	TWM110B	TWM110C	TWM210B	TWM330B
Range(N.m)	5 ~ 25	12 ~ 60	12 ~ 60	22 ~ 110	22 ~ 110	42 ~ 210	66 ~ 330
Size of square drive	1/4"	3/8"	1/2"	3/8"	1/2"	1/2"	1/2"
Length	250mm	415mm	425mm	460mm	470mm	490mm	565mm
Weight	350g	920g	980g	1.06kg	1.17kg	1.26kg	1.34kg

Code	TWM550B	TWM800B	TWM1000B	TWM1500B	TWM2000B	TWM3000B
Range(N.m)	110 ~ 550	160 ~ 800	200 ~ 1000	300 ~ 1500	400 ~ 2000	600 ~ 3000
Size of square drive	3/4"	3/4"	3/4"	1"	1"	1"
Length	900mm	1200mm	1200mm	1260mm	1260mm	1260mm
Weight	4.3kg	5.6kg	5.6kg	9.2kg	9.2kg	10.5kg

SERIES STWM

TORQUE WRENCH WITH BIT SET



ACEUD

- ◆ Accuracy: $\pm 4\%$ (clockwise)



STWM25



STWM110

SPECIFICATION

Code	STWM25	STWM110	STWM210
Torque wrench code	TWM25B	TWM110C	TWM210B
Range	5 ~ 25N.m	22 ~ 110N.m	42 ~ 210N.m
Size of square drive	1/4"	1/2"	1/2"
Bit size	Hexagon type: H2-H2.5-H3-H4-H5-H6-H8 Torx type: T10-T15-T20-T25-T27-T30 Extension rod: 100mm	Hexagon type: 17-19-21-22-23mm Extension rod: 125mm	
Main application	bicycle industry	automotive industry	
Torque wrench length	250mm	460mm	490mm
Weight	790g	2200g	2300g

SERIES TW

DIGITAL TORQUE WRENCH



- ◆ Clockwise or anti-clockwise operation
- ◆ Unit: N.m, in.lb, ft.lb, kg.cm
- ◆ Peak or real-time working mode
- ◆ Automatic power off
- ◆ With calibration certificate




VIDEO



TW200

unit: mm



SPECIFICATION

Code	TW12	TW20	TW30	TW135	TW200	TW340	TW550	TW850	TW1500	TW2000
Range(N.m)	2.4 ~ 12	4 ~ 20	6 ~ 30	27 ~ 135	40 ~ 200	68 ~ 340	110 ~ 550	170 ~ 850	300 ~ 1500	400 ~ 2000
Resolution	0.01N.m	0.01N.m	0.1N.m	0.1N.m	1N.m	1N.m	1N.m	1N.m	1N.m	1N.m
Accuracy	Clockwise	$\pm 3\%$	$\pm 3\%$	$\pm 2\%$	$\pm 2\%$	$\pm 2\%$	$\pm 2.5\%$	$\pm 2.5\%$	$\pm 2.5\%$	$\pm 2.5\%$
	Anti-clockwise	$\pm 4\%$	$\pm 4\%$	$\pm 3\%$	$\pm 3\%$	$\pm 3\%$	$\pm 3.5\%$	$\pm 3.5\%$	$\pm 3.5\%$	$\pm 3.5\%$
Size of square drive	1/4"	1/4"	1/4"	3/8"	1/2"	1/2"	3/4"	3/4"	1"	1"
Length(L)	390mm	390mm	390mm	415mm	530mm	650mm	950mm	1220mm	1800mm	1800mm
Weight	900g	900g	900g	950g	1400g	1800g	3400g	4400g	13kg	14kg
Power	2xAA batteries									

TORQUE

SERIES TWD

DIAL TORQUE WRENCH



- ◆ Clockwise and counter-clockwise operation
- ◆ Comforms to DIN ISO 6789, ASME B107.300
- ◆ With manufacturer inspection certificate



TWD70

SPECIFICATION


Code	TWD3	TWD9	TWD18	TWD35	TWD70	TWD140	TWD240	TWD350
Range	0.7~3.5N.m 6~30in.lb	1.8~9N.m 15~75in.lb	3.6~18N.m 30~150in.lb	7~35N.m 60~300in.lb	14~70N.m 120~600in.lb	28~140N.m 20~100ft.lb	48~240N.m 35~175ft.lb	70~350N.m 50~250ft.lb
Accuracy	±3%	±3%	±3%	±3%	±3%	±3%	±3%	±3%
Graduation	0.05N.m 0.5in.lb	0.1N.m 1in.lb	0.2N.m 2in.lb	0.5N.m 5in.lb	1N.m 10in.lb	2N.m 1ft.lb	3N.m 2.5ft.lb	2.5N.m 2.5ft.lb
Square drive	1/4"	1/4"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"
Length	254mm	254mm	254mm	254mm	378mm	546mm	546mm	546mm
Weight	480g	480g	480g	480g	820g	1300g	1300g	1300g

SERIES TWI/TWF

TORQUE WRENCH



- ◆ Easy to set the torque value
- ◆ According to ISO6789, ASME B107.300
- ◆ Metal construction
- ◆ With manufacturer inspection certificate



TWF150

SPECIFICATION

Code	TWI200	TWI250	TWF100	TWF150	TWF250	TWF600
Range	40~200lb.in	50~250lb.in	20~100lb.ft	30~150lb.ft	50~250lb.ft	100~600lb.ft
Graduation	1lb.in	1lb.in	0.5lb.ft	0.5lb.ft	1lb.ft	2.5lb.ft
Accuracy	±3%	±3%	±3%	±3%	±3%	±4%
Size of square drive	1/4"	3/8"	3/8"	1/2"	1/2"	3/4"
Length	11"	12.4"	16.7"	20"	26.7"	41.5"
Weight	1.5lb	1.8lb	2.3lb	2.6lb	2.9lb	13lb

SERIES TWS

WINDOWS TORQUE WRENCH



Accud

- ◆ Accuracy: $\pm 4\%$ (clockwise)
- ◆ According to ISO6789
- ◆ Unit: N.m; Lbf.ft
- ◆ With manufacturer inspection certificate



TWS60

SPECIFICATION


Code	Range (N.m)	Size of square drive	Length	Weight	Code	Range (N.m)	Size of square drive	Length	Weight
TWS12	2.4~12	1/4"	300mm	0.58kg	TWS330	66~330	1/2"	555mm	1.28kg
TWS20	4~20	1/4"	300mm	0.58kg	TWS400	80~400	1/2"	725mm	1.90kg
TWS20B	4~20	3/8"	300mm	0.60kg	TWS400B	80~400	3/4"	825mm	3.05kg
TWS30	6~30	3/8"	315mm	0.68kg	TWS550	110~550	3/4"	825mm	3.93kg
TWS60	12~60	3/8"	400mm	0.86kg	TWS1000	200~1000	3/4"	1115mm	5.28kg
TWS60B	12~60	1/2"	415mm	0.90kg	TWS1500	300~1500	1"	1250mm	8.20kg
TWS100B	20~100	1/2"	470mm	1.12kg	TWS2000	400~2000	1"	1250mm	8.20kg
TWS200	40~200	1/2"	495mm	1.18kg	TWS3000	600~3000	1"	1250mm	9.50kg

SERIES TQ

DIGITAL TORQUE SCREWDRIVER



- ◆ Clockwise or anti-clockwise operation
- ◆ Peak and track working mode
- ◆ With audible and visible alarm when the value is closed to setting target
- ◆ With manufacturer inspection certificate



TQ50CN

unit: mm

SPECIFICATION

Code	TQ50CN	TQ200CN	TQ400CN
Range	10 ~ 50cN.m	40 ~ 200cN.m	80 ~ 400cN.m
Clockwise operation accuracy	$\pm 3\%$	$\pm 2.5\%$	$\pm 2.5\%$
Anti-clockwise operation accuracy	$\pm 4\%$	$\pm 3.5\%$	$\pm 3.5\%$
Resolution	0.1cN.m	0.1cN.m	0.1cN.m
Size of shank	1/4"	1/4"	1/4"
Length (L)	258mm	268mm	268mm
Weight	200g	200g	200g
Power	1xAAA battery		

TORQUE

SERIES DT

DIGITAL TORQUE INDICATOR



- ◆ Peak, preset and real-time working mode
- ◆ Unit: N.m, N.cm, kgf.cm, lbf.ft, lbf.in
- ◆ Memory: 999
- ◆ Power off automatically
- ◆ With backlight
- ◆ With manufacturer inspection certificate

SPECIFICATION

Code	DT30	DT135	DT200
Range	5-30N.m	13.5-135N.m	20-200N.m
Drive size	1/2"	1/2"	1/2"
Resolution	0.01N.m	0.1N.m	0.1N.m
Accuracy	±2%(clockwise)/±2.5%(anti-clockwise)		
Memory	999		
Power	2xAAA batteries		
Weight	200g		

INCLUDED ACCESSORIES

Main unit	1pc
AAA battery	2pcs
Wrench	1pc



DT135

Application




SERIES TWQ


TORQUE MULTIPLIERS

- ◆ Accuracy: ±5%

Application



TWQ-5500



SPECIFICATION

Code	TWQ-1000	TWQ-2000	TWQ-3500	TWQ-5500	TWQ-7500	TWQ-10000
Capacity	1000N.m	2000N.m	3500N.m	5500N.m	7500N.m	10000N.m
Torque ratio	1:4.5	1:12	1:15	1:18.5	1:20	1:26.5
Square socket	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Square driver	1"	1"	1"	1 1/2"	1 1/2"	1 1/2"
For bolt	M20-30	M22-35	M30-45	M38-52	M42-60	M52-72
For nut	S30-46	S32-55	S46-70	S55-80	S65-90	S80-105
Dimension(AxHxDxH1)	82x98.5x97x122.4	82x120x105x147	98x131x120x163	115x163.5x137x199	127x173x146x215	141x170x164x238
Weight	2.1kg	3.15kg	4.9kg	8.1kg	10.6kg	14kg

SERIES TQM

TORQUE SCREWDRIVER

- ◆ Clockwise operation
- ◆ When achieving the setting target, there is "chatter"



TQM300

SPECIFICATION

Code	TQM60	TQM120	TQM300	TQM600
Range	0.12~0.6N.m	0.24~1.2N.m	0.6~3N.m	1.2~6N.m
Clockwise operation accuracy	±6%	±6%	±6%	±6%
Graduation	0.01N.m	0.02N.m	0.05N.m	0.1N.m
Size of shank	1/4"	1/4"	1/4"	1/4"
Length (L)	161mm	161mm	186mm	186mm
Weight	300g	300g	400g	400g

SERIES TTM

DIGITAL BOTTLE CAP TORQUE METER

- ◆ Test the open and tighten torque of bottle cap
- Peak, preset and real-time working mode
- ◆ Unit: N.m, N.cm, kgf.cm, lbf.cm, lbf.in
- ◆ Memory: 1000
- ◆ Power off automatically
- ◆ With software, can show the torque graph
- ◆ With manufacturer inspection certificate



TTM10



VIDEO




Certificate



Data output



Charge



SPECIFICATION

Code	TTM2	TTM5	TTM10	TTM20
Range	0.1-2N.m	0.25-5N.m	0.5-10N.m	1-20N.m
Accuracy	±0.5%			
Resolution	0.0002N.m	0.0005N.m	0.001N.m	0.002N.m
Open size	Ø19.5-190mm			
Output	USB and RS232			
Power	rechargeable battery			
Weight	2.5kg			

INCLUDED ACCESSORIES

Main unit	1pc
Charger	1pc
Software with cable	1pc

OPTIONAL ACCESSORIES

Wireless printer	PR100
------------------	-------

FORCE

SERIES TTB

DIGITAL TORQUE METER



- ◆ For torque wrench and torque screwdriver calibration
- ◆ Peak, preset and real-time working mode
- ◆ Unit: N.m, N.cm, kgf.cm, lbf.cm, lbf.in
- ◆ Memory: 1000
- ◆ Power off automatically
- ◆ With software, can show the torque graph
- ◆ With manufacturer inspection certificate




VIDEO



TTB10

run down adapter for torque meter (optional)



Stand (optional)



TTB500

SPECIFICATION

Code	TTB5	TTB10	TTB50	TTB100	TTB500	TTB1000
Range	0.25-5N.m	0.5-10N.m	2.5-50N.m	5-100N.m	25-500N.m	100-1000N.m
Accuracy	±0.3%					
Resolution	0.0005N.m	0.001N.m	0.005N.m	0.01N.m	0.05N.m	0.1N.m
Size of square drive	1/2"				3/4"	1"
Output	USB and RS232					
Power	rechargeable battery					
Weight	1.5kg				3kg	

INCLUDED ACCESSORIES

Main unit	1pc
Charger	1pc
Software with cable	1pc
Convertor (TTB500 and TTB1000 doesn't include)	1pc

OPTIONAL ACCESSORIES

Wireless printer	PR100	RUN DOWN ADAPTER FOR TORQUE METER (2N.m)	TTB-RDF2
Stand (Arm length: 150-600mm)	TTB-ST1	RUN DOWN ADAPTER FOR TORQUE METER (6N.m)	TTB-RDF6
Stand (Arm length: 150-1000mm)	TTB-ST2	RUN DOWN ADAPTER FOR TORQUE METER (40N.m)	TTB-RDF40
Stand (Arm length: 150-1500mm)	TTB-ST4	RUN DOWN ADAPTER FOR TORQUE METER (100N.m)	TTB-RDF100

TTB-ST1/ST2/ST4

STAND FOR TORQUE WRENCH TESTING


- ◆ For calibrating torque wrench with TTB series torque meter

(Torque meter is not included)



TTB-ST1

unit: mm



SPECIFICATION

Code	TTB-ST1	TTB-ST2	TTB-ST4
Arm length(L1)	150-600mm	150-1000mm	150-1500mm
Max. travel	200mm		
Max. force	1000N		2000N
Length(L2)	770mm	1270mm	1800mm
Weight	12kg	16kg	30kg

SERIES TTS

DIGITAL TORQUE METER

- ◆ Adjustable open size for fixing
- ◆ Peak, preset and real-time working mode
- ◆ Unit: N.m, N.cm, kgf.cm, lbf.cm, lbf.in
- ◆ Memory: 1000
- ◆ Power off automatically
- ◆ With software, can show the torque graph
- ◆ With manufacturer inspection certificate



VIDEO

SPECIFICATION

Code	TTS1	TTS5	TTS10
Range	0.05-1N.m	0.25-5N.m	0.5-10N.m
Open size	Ø10mm	Ø10mm	Ø13mm
Resolution	0.0001N.m	0.0005N.m	0.001N.m
Accuracy	±0.3%		
Memory	1000		
Output	USB and RS232		
Power	rechargeable battery		
Weight	0.7kg		

INCLUDED ACCESSORIES

Main unit	1pc
Charger	1pc
Software with cable	1pc
Wrench	1pc

OPTIONAL ACCESSORIES


Wireless printer	PR100
------------------	-------



TTS5



unit: mm



Code	L	D1
TTS1	156mm	Ø43
TTS5	156mm	Ø43
TTS10	178mm	Ø53

FORCE

SERIES TWT

TORQUE WRENCH TESTER

- ◆ Used to test or calibrate torque wrench
- ◆ Contains two torque sensors, with same touch screen LCD



TWT200

SPECIFICATION

Code		TWT200	TWT500
Range	Sensor 1	1-20N.m	2.5-50N.m
	Sensor 2	10-200N.m	25-500N.m
Resolution	Sensor 1	0.002N.m	0.005N.m
	Sensor 2	0.02N.m	0.05N.m
Accuracy		0.3%	
Max. wrench length		830mm	
Driver size		1/2", 3/8", 1/4"	3/4", 1/2", 3/8"
Memory		1000	
Data output		USB	
Dimension		780×688×433 mm	
Weight		45kg	

OPTIONAL ACCESSORIES

Main unit	1set
Charger	1pc
Driver adapter	2pcs
USB cable and software	1set

SERIES TWT

MOTORIZED TORQUE WRENCH TESTER

- ◆ Used to test or calibrate torque wrench
- ◆ Loading force: motorized
- ◆ Contains two torque sensors, with same touch screen LCD



TWT200M

SPECIFICATION

Code		TWT200M	TWT500M	TWT1000M
Range	Sensor 1	1-20N.m	2.5-50N.m	10-100N.m
	Sensor 2	10-200N.m	25-500N.m	100-1000N.m
Resolution	Sensor 1	0.002N.m	0.005N.m	0.01N.m
	Sensor 2	0.02N.m	0.05N.m	0.1N.m
Accuracy		0.3%		
Max. wrench length		830mm		
Driver size		1/2", 3/8", 1/4"	3/4", 1/2", 3/8"	1", 3/4", 1/2", 3/8"
Memory		1000		
Data output		USB		
Dimension		780×635×443 mm		
Weight		55kg		

OPTIONAL ACCESSORIES

Main unit	1set
Driver adapter	1set
Software and USB cable	1set
Power cable	1pc

PS075

PORTABLE SCALE



- ◆ Pocket size, easy to carry
- ◆ It can also measure the dimension
- ◆ With back light
- ◆ Power off automatically
- ◆ Can show temperature



SPECIFICATION

Range	0-75kg
Resolution	0.01kg
Accuracy	0.05kg (Weight≤50kg), 0.2kg (Weight>50kg)
Unit	kg, lb, JIN, oz
Power supply	2xAAA battery
Dimension	70x135x30mm
Weight	185g

STANDARD DELIVERY

Main unit	1pc
AAA battery	2pcs

WSC3000G

ELECTRONIC WEIGHING SCALE FOR KITCHEN



- ◆ LCD display, with backlight
- ◆ Automatic "Zero"
- ◆ Automatic power off



SPECIFICATION

Max. capacity	3kg
Min. capacity	0.5g
Division	0.1g
Verification interval	1g
Unit	g, ct, oz, tl, dwn, gn
Automatic "zero" range	0-60g
Power supply	9VAD/DC adapter or 6xAA battery
Dimension of pan	15x15cm
Dimension	23x15x4cm

SERIES WSJ

HIGH PRECISION ELECTRONIC BALANCE



- ◆ High accuracy, mainly used to measure weight of golden and jewellery
- ◆ LCD display, with backlight
- ◆ Overload and limits alarm
- ◆ RS232 output
- ◆ Automatic power off



WSJ2000G

SPECIFICATION

Code	WSJ100G	WSJ200G	WSJ300G	WSJ600G	WSJ1000G	WSJ2000G
Max. capacity	100g	200g	300g	600g	1000g	2000g
Min. capacity	0.005g	0.005g	0.005g	0.05g	0.05g	0.05g
Division	0.001g	0.001g	0.001g	0.01g	0.01g	0.01g
Verification interval	0.01g	0.01g	0.01g	0.1g	0.1g	0.1g
Unit	g, ct, lb, oz, dr, gn, ozt, dwt					
Power supply	re-chargeable battery					
Dimension of pan	Ø9CM			Ø14CM		
Dimension	32x21x31cm					

SERIES WS

ELECTRONIC WEIGHING SCALE

- ◆ LCD display, with backlight
- ◆ Overload and limits alarm
- ◆ RS232 output
- ◆ Automatic power off



WS15K

SPECIFICATION

Code	WS06K	WS15K	WS30K
Max. capacity	6kg	15kg	30kg
Min. capacity	1g	5g	10g
Division	0.1g	0.5g	1g
Verification interval	1g	5g	10g
Unit	kg, g, lb		
Power supply	9VAD/DC adapter		
Dimension of pan	32x23cm		
Dimension	32x36x11cm		

◆ With manufacturer inspection certificate

TOLERANCE

Weight	M1	F2	F1	E2
1mg	0.2mg	0.06mg	0.02mg	0.006mg
2mg	0.2mg	0.06mg	0.02mg	0.006mg
5mg	0.2mg	0.06mg	0.02mg	0.006mg
10mg	0.25mg	0.08mg	0.025mg	0.008mg
20mg	0.3mg	0.1mg	0.03mg	0.01mg
50mg	0.4mg	0.12mg	0.04mg	0.012mg
100mg	0.5mg	0.16mg	0.05mg	0.016mg
200mg	0.6mg	0.2mg	0.06mg	0.02mg
500mg	0.8mg	0.25mg	0.08mg	0.025mg
1g	1mg	0.3mg	0.1mg	0.03mg
2g	1.2mg	0.4mg	0.12mg	0.04mg
5g	1.6mg	0.5mg	0.16mg	0.05mg
10g	2mg	0.6mg	0.2mg	0.06mg
20g	2.5mg	0.8mg	0.25mg	0.08mg
50g	3mg	1mg	0.3mg	0.1mg
100g	5mg	1.6mg	0.5mg	0.16mg
200g	10mg	3mg	1mg	0.3mg
500g	25mg	8mg	2.5mg	0.8mg
1kg	50mg	16mg	5mg	1.6mg
2kg	100mg	30mg	10mg	3mg
5kg	250mg	80mg	25mg	8mg
10kg	500mg	160mg	50mg	16mg
20kg	1000mg	300mg	100mg	30mg



1kg



100g



100mg

GRADE SELECTION

Weighing instrument resolution	Grade selection
0.001mg	E1
0.01mg	E2
0.1mg	E2 or F1
1mg	F2
0.01g/0.1g	M1

INDIVIDUAL WEIGHT

Code Weight	Grade and stainless steel type					Sharp
	M1(304)	F2(304)	F1(304)	F1(non-magnetic)	E2(non-magnetic)	
1mg	WT-M001M1	WT-M001F2	WT-M001F1	WT-M001F1B	WT-M001E2	sheet
2mg	WT-M002M1	WT-M002F2	WT-M002F1	WT-M002F1B	WT-M002E2	
5mg	WT-M005M1	WT-M005F2	WT-M005F1	WT-M005F1B	WT-M005E2	
10mg	WT-M010M1	WT-M010F2	WT-M010F1	WT-M010F1B	WT-M010E2	
20mg	WT-M020M1	WT-M020F2	WT-M020F1	WT-M020F1B	WT-M020E2	
50mg	WT-M050M1	WT-M050F2	WT-M050F1	WT-M050F1B	WT-M050E2	
100mg	WT-M100M1	WT-M100F2	WT-M100F1	WT-M100F1B	WT-M100E2	
200mg	WT-M200M1	WT-M200F2	WT-M200F1	WT-M200F1B	WT-M200E2	
500mg	WT-M500M1	WT-M500F2	WT-M500F1	WT-M500F1B	WT-M500E2	
1g	WT-001M1	WT-001F2	WT-001F1	WT-001F1B	WT-001E2	cylinder
2g	WT-002M1	WT-002F2	WT-002F1	WT-002F1B	WT-002E2	
5g	WT-005M1	WT-005F2	WT-005F1	WT-005F1B	WT-005E2	
10g	WT-010M1	WT-010F2	WT-010F1	WT-010F1B	WT-010E2	
20g	WT-020M1	WT-020F2	WT-020F1	WT-020F1B	WT-020E2	
50g	WT-050M1	WT-050F2	WT-050F1	WT-050F1B	WT-050E2	
100g	WT-100M1	WT-100F2	WT-100F1	WT-100F1B	WT-100E2	
200g	WT-200M1	WT-200F2	WT-200F1	WT-200F1B	WT-200E2	
500g	WT-500M1	WT-500F2	WT-500F1	WT-500F1B	WT-500E2	
1kg	WT-1000M1	WT-1000F2	WT-1000F1	WT-1000F1B	WT-1000E2	
2kg	WT-2000M1	WT-2000F2	WT-2000F1	WT-2000F1B	WT-2000E2	
5kg	WT-5000M1	WT-5000F2	WT-5000F1	WT-5000F1B	WT-5000E2	
10kg	WT-10000M1	WT-10000F2	WT-10000F1	WT-10000F1B	WT-10000E2	
20kg	WT-20000M1	WT-20000F2	WT-20000F1	WT-20000F1B	WT-20000E2	

WEIGHT SET

Code Weight	Grade and stainless steel type					Quantity
	M1(304)	F2(304)	F1(304)	F1(non-magnetic)	E2(non-magnetic)	
1mg-200g	WTS-200M1	WTS-200F2	WTS-200F1	WTS-200F1B	WTS-200E2	23pcs
1mg-500g	WTS-500M1	WTS-500F2	WTS-500F1	WTS-500F1B	WTS-500E2	24pcs

Each set includes two pieces 2mg/20mg/200mg/2g/20g/200g and one piece each other sizes

CODE INDEX

CODE	NAME	PAGE	CODE	NAME	PAGE
100-197			152	DIGITAL OFFSET CALIPER	42
100	USB OUTPUT INTERFACE	2	153	DIGITAL BLADE CALIPER	41
101	DIAL CALIPER	13	154	DIGITAL HOOK CALIPER	43
103	DIAL CALIPER	14	155	DIGITAL SCRIBING CALIPER	319
106	DIGITAL CALIPER WITH LARGE SCREEN	9-10	156	DIGITAL GEAR TOOTH CALIPER	46
107	DIGITAL CALIPER WITH LONG UPPER JAWS	45	157	DIGITAL DISK BRAKE CALIPER	47
109	INSIDE GROOVE CALIPER	35	158	DIGITAL DRUM BRAKE CALIPER	48
111	WIRELESS DIGITAL CALIPER	4	159	DIGITAL INSIDE GROOVE CALIPER	35
111	DIGITAL CALIPER	5-7	160	CHAMFER GAUGE	279
112	IP67 DIGITAL CALIPER	8	161	OFFSET CENTERLINE VERNIER CALIPER	39
112	WATERPROOF CALIPER WITH ROUND DEPTH BAR	8	162	OFFSET VERNIER CALIPER	42
112	IP67 DIGITAL CALIPER	9	163	DIGITAL CHAMFER GAUGE	280
113	FRACTIONAL DIGITAL CALIPER	10	164	DIGITAL CHAMFER GAUGE	281
114	MINI DIGITAL CALIPER	11	165	DIGITAL DISK BRAKE AND PAD CALIPER	47
115	DIGITAL CALIPER	11	166	VERNIER GEAR TOOTH CALIPER	46
116	DIGITAL CALIPER WITH CARBIDE TIPPED JAWS	12	167	DIGITAL CALIPER WITH LARGE MEASURING FACES	45
117	PLASTIC DIGITAL CALIPER	12	168	DIGITAL SMALL POINT CALIPER	27
118	DIGITAL CALIPER	19	169	DIGITAL ARC RADIUS CALIPER	43
119	DIGITAL CALIPER	20	170	EXTENSION BASE FOR DEPTH CALIPER	58
120	VERNIER CALIPER	14-15	171	DIGITAL DEPTH CALIPER	51
120	VERNIER CALIPER(SOLID TYPE)	25	172	DIGITAL PIN DEPTH CALIPER	52
121	MINI VERNIER CALIPER	16-17	173	DIGITAL HOOK DEPTH CALIPER	52
122	VERNIER CALIPER	26	174	DIGITAL DOUBLE HOOK DEPTH CALIPER	53
123	VERNIER CALIPER(ANTI MAGNETIC)	18	175	VERNIER DEPTH CALIPER	56
124	VERNIER CALIPER	15	176	DIGITAL DEPTH CALIPER	58-59
125	VERNIER CALIPER	16	176	VERNIER DEPTH CALIPER	59
126	VERNIER CALIPER	22	177	VERNIER DEPTH CALIPER	56
127	VERNIER CALIPER	23	178	VERNIER DEPTH CALIPER	57
128	VERNIER CALIPER	24	179	ACCESSORY FOR CALIPER	49
129	VERNIER CALIPER	25	179	DIAL DEPTH CALIPER	55
130	DIGITAL CALIPER	21	180	SCRIBER FOR HEIGHT GAGE	75
131	DIGITAL CALIPER	21	181	DIGITAL HEIGHT GAGE	73
132	DIGITAL INSIDE GROOVE CALIPER	32-33	182	DIGITAL HEIGHT GAGE	73
133	DIGITAL OUTSIDE NECK CALIPER	28	183	MINI DIGITAL HEIGHT GAGE	76
134	DIGITAL OUTSIDE POINT CALIPER	29	184	DIGITAL HEIGHT GAGE WITH DRIVING WHEEL	74
135	DIGITAL INSIDE NECK CALIPER	30	185	DIAL HEIGHT GAGE	74
136	DIGITAL INSIDE POINT CALIPER	31-32	186	VERNIER HEIGHT GAGE	75
137	DIGITAL TUBE THICKNESS CALIPER	34	187	MINI VERNIER HEIGHT GAGE	77
138	DIGITAL POINT CALIPER	27	191	DIGITAL DEPTH CALIPER WITH HOLES	53
139	DIGITAL INSIDE KNIFE-EDGE CALIPER	34	192	VERNIER HOOK DEPTH CALIPER	57
140	VERNIER CALIPER WITH CARBIDE TIPPED JAWS	17	193	DIGITAL DEPTH CALIPER WITH ROUND DEPTH BAR	54
141	DIGITAL BACK-JAW CENTERLINE CALIPER	40	194	DIGITAL DEPTH CALIPER WITH ROUND DEPTH BAR	55
142	DIGITAL RTJ RING GROOVE CALIPER	44	195	DIGITAL KEYWAY GAUGE	282
143	OUTSIDE NECK VERNIER CALIPER	28	196	DIGITAL KEYWAY GAUGE	282
144	OUTSIDE POINT VERNIER CALIPER	29	197	IP67 WATERPROOF DIGITAL DEPTH CALIPER	50
145	INSIDE NECK VERNIER CALIPER	30	197	IP67 DIGITAL DEPTH CALIPER WITH HOLES	50
146	INSIDE POINT VERNIER CALIPER	31	200-299		
147	BACK-JAW DIGITAL EDGE TO CENTER CALIPER	40	200	USB OUTPUT INTERFACE	2
148	DIGITAL CENTERLINE/EDGE TO CENTER CALIPER	41	200	USB OUTPUT INTERFACE	3
149	CALIPER WITH INTERCHANGEABLE POINTS	36-38	201	LINEAR GAUGE	153
150	DIGITAL CALIPER	18	205	LINEAR GAUGES AND DISPLAY UNIT	156
151	DIGITAL OFFSET CENTERLINE CALIPER	39	206	DISPLAY UNIT FOR LINEAR GAUGE	154

CODE INDEX

CODE	NAME	PAGE	CODE	NAME	PAGE
208	COUNTER FOR LINEAR GAUGE	155	270	EXTENSION ROD FOR CONTACT POINTS	187-188
210	DIGITAL INDICATOR	157	271	SPINDLE LIFT KNOB	188
211	DIGITAL INDICATOR	157	272	LUG AND FLAT BACK	188
212	DIGITAL INDICATOR	158	273	SHAFT SLEEVE	182
213	WATERPROOF DIGITAL INDICATOR	160	277	HYDRAULIC UNIVERSAL MAGNETIC STAND	192
214	DIGITAL INDICATOR	161	278	UNIVERSAL MAGNETIC STAND	193
215	DIGITAL INDICATOR FOR BORE GAUGE	158	279	UNIVERSAL MAGNETIC STAND	192
216	DIGITAL INDICATOR	159	280	MEASURING TOOLS SET	346-351
217	HIGH PRECISION DIGITAL INDICATOR	162-163	281	MAGNETIC STAND	190
218	HIGH PRECISION DIGITAL INDICATOR	164-165	282	UNIVERSAL MAGNETIC STAND	191
221	DIAL INDICATOR	167	283	UNIVERSAL MAGNETIC STAND	191
222	DIAL INDICATOR	166	284	VACUUM STAND	195
222	DIAL INDICATOR	168	285	FLEX ARM MAGNETIC STAND	194
223	DIAL INDICATOR	168	286	MINI MAGNETIC STAND	194
224	DIAL INDICATOR	169	287	UNIVERSAL STAND	195
225	INCH DIAL INDICATOR	175	288	MINI MAGNETIC STAND	193
226	SHOCKPROOF DIAL INDICATOR	169	289	INDICATOR STAND WITH GRANITE BASE	196
227	DIGITAL INDICATOR WITH LIFTING LEVER	166	290	INDICATOR STAND WITH CERAMIC BASE	196
228	DIAL INDICATOR	167	291	DIAL DEPTH INDICATOR	66
228	DIAL INDICATOR	170	291	REVERSE DIAL INDICATOR	174
229	DIAL INDICATOR	170-171	292	DIAL DEPTH INDICATOR	65
230	DIAL INDICATOR	174	292	REVERSE DIAL INDICATOR	175
231	WATERPROOF DIAL INDICATOR	172	293	DIGITAL DEPTH INDICATOR	62-64
232	ONE REVOLUTION DIAL INDICATOR	173	294	INDICATOR STAND	197
233	DOUBLE FACE DIAL INDICATOR	173	295	DIAL DEPTH INDICATOR	66
240	SPLIT TYPE DIAL BORE GAUGE SET	145	296	DIGITAL RADIUS GAUGE	151
240	SPLIT TYPE DIAL BORE GAUGE SET	146-147	297	CENTERING INDICATOR	338
241	DIGITAL BORE GAUGE	141-142	298	CRANKSHAFT TESTER	220
243	BORE GAUGE	144	299	DIGITAL DEPTH INDICATOR	67
244	BORE GAUGE	144	300-399		
245	LARGE DIAMETER DIAL BORE GAUGES	143	300	USB OUTPUT INTERFACE	2
250	ANVIL FOR BORE GAUGES/LONG HANDLE	149	301	UNIVERSAL MICROMETER TIPS	108
251	DIAL BORE GAUGE SET	138	301	NON ROTATING SPINDLE MICROMETER	107
251	DIAL BORE GAUGE	139-140	302	DIGITAL UNIVERSAL MICROMETER	106
252	INCH DIAL BORE GAUGE	148	304	DIGITAL GEAR TOOTH MICROMETER	110
253	BORE GAUGE	144	305	NON MAGNETIC MICROMETER	116
254	BORE GAUGE	144	306	DISK BRAKE MICROMETER	117
255	BORE GAUGE CHECKER	149	307	DIGITAL DISK BRAKE MICROMETER	116
256	BORE GAUGE SETTER	150	308	LARGE ANVIL MICROMETER	105
260	STYL I FOR DIAL TEST INDICATOR	181	310	OUTSIDE MICROMETER FOR LEFT OR RIGHT HAND	108
261	PRECISION DIAL TEST INDICATOR	178	312	DIGITAL OUTSIDE MICROMETER	80
261	DIAL TEST INDICATOR	176-178	313	DIGITAL OUTSIDE MICROMETER	78-79
263	LONG STYL I DIAL TEST INDICATOR	179	314	DIGITAL SNAP MICROMETER	81
264	BACK PLUNGER TYPE DIAL TEST INDICATOR	179	315	MICROMETER WITH INTERCHANGEABLE ANVILS	85
265	DIAL TEST INDICATOR	180	316	DIGITAL BLADE MICROMETER	90
266	LARGE RANGE DIAL TEST INDICATOR	180	317	DIGITAL POINT MICROMETER	91
267	HOLDER FOR INDICATOR	181	318	DIGITAL SPLINE MICROMETER	92
268	UNIVERSAL HOLD FOR INDICATOR	182	319	DIGITAL CRIMP HEIGHT MICROMETER	93
269	DIAL TEST INDICATOR CENTERING HOLDER	182	319	DIGITAL POINT MICROMETER	94
270	CONTACT POINTS	183-186	320	MINI OUTSIDE MICROMETER	84
270	ROLLER POINT	186	321	OUTSIDE MICROMETER	82
270	POINT SET	187	321	MICROMETER SETTING STANDARD	121

CODE INDEX

CODE	NAME	PAGE	CODE	NAME	PAGE
322	MICRO GRADUATION OUTSIDE MICROMETER	83	365	PISTOL GRIP THREE POINTS BORE GAUGE	131
323	OUTSIDE MICROMETER	83	370	WIRE MICROMETER	115
324	OUTSIDE MICROMETER	84	371	MICROMETER HEAD	119
324	INCH MICROMETER SETTING STANDARD	122	373	MICROMETER HEAD	120
325	MICROMETER WITH INTERCHANGEABLE ANVILS	86-87	376	DIGITAL MICROMETER HEAD	118
326	BLADE MICROMETER	90	377	INTERCHANGEABLE ANVIL MICROMETER	109
327	POINT MICROMETER	91	378	CALIPER TYPE MICROMETER	104
328	SPLINE MICROMETER	92	379	LONG SPINDLE OUTSIDE MICROMETER	117
329	OUTSIDE MICROMETER WITH EXTENSION ANVIL	88	380	DIGITAL CYLINDRICAL ANVIL TUBE MICROMETER	95
330	JAW TYPE MICROMETER	103	381	MICROMETER STAND	125
331	DIGITAL SPHERICAL ANVIL TUBE MICROMETER	94	383	MICROMETER STAND	125
332	NON ROTATING SPINDLE DISK MICROMETER	96	387	MICROMETER MEASURING FORCE DETECTOR	123
333	DIGITAL SCREW THREAD MICROMETER	101	389	ELECTRONIC INDICATING MICROMETER	114
334	DIGITAL V-ANVIL MICROMETER	98	390	OUTSIDE MICROMETER WITH COUNTER	81
334	V-ANVIL MICROMETER	99	391	DEPTH MICROMETER	61
335	LIMIT MICROMETER	101	392	DEPTH MICROMETER	61
336	SHEET METAL MICROMETER	102	395	DIGITAL DEPTH MICROMETER	60
337	HUB MICROMETER	105	397	DIGITAL INTERCHANGEABLE ANVIL MICROMETER	109
338	DIGITAL CALIPER TYPE MICROMETER	104	399	DEPTH MICROMETER CHECKERS	67
339	DIGITAL JAW TYPE MICROMETER	103	400-499		
340	SPHERICAL ANVIL TUBE MICROMETER	95	400	USB OUTPUT INTERFACE	2
341	TUBE MICROMETER	96	401	UNIVERSAL GAUGE	150
342	DISK MICROMETER	97	406	LARGE RANGE DIGITAL RADIUS GAUGE	151
343	SCREW THREAD MICROMETER	100	410	DIGITAL INTERNAL CALIPER GAUGE	199
343	MEASURING TIPS FOR MICROMETER	100	411	INTERNAL DIAL CALIPER GAUGE	199
343	MICROMETER SETTING STANDARD	122	412	DIGITAL INTERNAL CALIPER GAUGE	201
344	GROOVE MICROMETER	111	413	INTERNAL DIAL CALIPER GAUGE	201
345	GEAR TOOTH MICROMETER	110	419	DIGITAL INTERNAL CALIPER GAUGE	204
345	BALL TIPS FOR GEAR TOOTH MICROMETER	111	420	DIGITAL EXTERNAL CALIPER GAUGE	200
346	CRIMP HEIGHT MICROMETER	93	421	EXTERNAL DIAL CALIPER GAUGE	200
347	SHEET METAL MICROMETER	115	422	DIGITAL EXTERNAL CALIPER GAUGE	202
348	CAN SEAM MICROMETER	112	423	EXTERNAL DIAL CALIPER GAUGE	202
349	INDICATING MICROMETER	113	425	EXTERNAL DIAL CALIPER GAUGE	203
349	DIAL SNAP GAUGE	113	428	EXTERNAL DIAL CALIPER GAUGE	203
350	DIGITAL SHEET METAL MICROMETER	102	429	DIGITAL EXTERNAL CALIPER GAUGE	204
351	INSIDE MICROMETER	132	430	MICROMETER WITH DIAL INDICATOR	89
352	TUBULAR INSIDE MICROMETER	133-134	431	DIAL SNAP GAUGE	207
353	TUBULAR INSIDE MICROMETER	135	432	DIGITAL SNAP GAUGE	219
354	TUBULAR INSIDE MICROMETER	135	433	DIGITAL SNAP GAUGE	218
355	TUBULAR INSIDE MICROMETER	136	434	DIGITAL SNAP GAUGE	219
356	DIGITAL INSIDE MICROMETER	133	435	DIGITAL SNAP GAUGE	219
357	TUBULAR INSIDE MICROMETER	136	436	DIGITAL 3-PURPOSE SNAP GAUGE	220
358	SCREW THREAD MICROMETER/MEASURING TIPS	137	437	STEP AND GAP GAUGE	284
359	DIGITAL TUBULAR INSIDE MICROMETERS	134	441	THICKNESS GAUGE	209
361	DIGITAL THREE POINTS INSIDE MICROMETER	126	442	HIGHT PRECISION DIGITAL THICKNESS GAUGE	208
361	DIGITAL TWO POINTS INSIDE MICROMETER	127	443	THICKNESS GAUGE	210
361	DIGITAL POINTS INSIDE MICROMETER SET	127	444	THICKNESS GAUGE	212
362	THREE POINTS INSIDE MICROMETER	128	445	THICKNESS GAUGE WITH ROLLING WHEEL	216
362	TWO POINTS INSIDE MICROMETER	129	446	THICKNESS GAUGE	217
362	POINTS INSIDE MICROMETER SET	129	447	THICKNESS GAUGE	217
363	THREE POINTS INTERNAL MICROMETER	130	448	THICKNESS GAUGE	213
364	THREE POINTS INTERNAL MICROMETER	130	449	THICKNESS GAUGE	215

CODE	NAME	PAGE	CODE	NAME	PAGE
450	PET BOTTLE WALL THICKNESS GAUGE	218	544	NPT THREAD GAUGE	248
451	THICKNESS GAUGE	205	545	WITHWORTH PIPE THREAD GAUGE(G SERIES)	249
452	THICKNESS GAUGE	206	547	AMERICAN STANDARD THREAD PLUG GAUGE	247
453	THICKNESS GAUGE WITH POINTED TIPS	206	551	OPTICAL PARALLEL	123-124
457	DIGITAL THICKNESS GAUGE	205	552	GLASS SCALE	382
460	DIGITAL THICKNESS GAUGE	211	553	OPTICAL FLAT	124
461	DIGITAL TUBE THICKNESS GAUGE	213	559	THREAD DEPTH GAUGE	251
462	DIGITAL TUBE THICKNESS GAUGE	214	560	CALIPER/HEIGHT GAUGE CHECKERS	233
463	DIGITAL TUBE THICKNESS GAUGE	215	561	CHECK MASTER	232
464	POINT THICKNESS GAUGE	214	570	ANGLE GAUGE BLOCK SET	234
465	DIGITAL THICKNESS GAUGE	216	571	ANGLE GAUGE BLOCK SET	234
489	DIGITAL SURFACE PROFILE GAUGE	415-416	571	ANGLE GAUGE BLOCK SET	334
489	SURFACE PROFILE GAUGE	416	585	KEY SLOT LIMIT GAUGE	244
499	DIAL INDICATOR TESTER	189	589	LIMIT SNAP GAUGE	244
500-595			594	AIR GAUGE	249
500	USB OUTPUT INTERFACE	2	595	AIR GAUGE DISPLAY	250
508	GAUGE BLOCK FOR MICROMETER INSPECTION	229	611-697		
510	GAUGE BLOCK HOLDER	232	611	GRANITE SURFACE PLATE	326
511	CERAMIC GAUGE BLOCKS SET	221	615	MAGNETIC INDUCTION PARALLEL SET	334
512	STEEL GAUGE BLOCKS SET	222-224	621	STAND FOR GRANITE SURFACE PLATE	326
513	STEEL INDIVIDUAL GAUGE BLOCK	225	625	JACK SET FOR GRANITE SURFACE PLATE	327
514	STEEL INDIVIDUAL GAUGE BLOCK	226	630	V-BLOCK SET	333
515	CERAMIC INDIVIDUAL GAUGE BLOCK	224	631	GRANITE V-BLOCK SET	329
516	CERAMIC INDIVIDUAL GAUGE BLOCK	225	632	V-BLOCK SET	330
517	GAUGE BLOCK SET FOR CALIPER INSPECTION	227	633	MAGNETIC V-BLOCK	327
518	GAUGE BLOCK SET FOR MICROMETER	228-229	634	MAGNETIC V-BLOCK	328
519	GAUGE BLOCK ACCESSORIES	230	635	MAGNETIC V-BLOCK SET	329
520	GAUGE BLOCK ACCESSORIES	231	636	V-BLOCK SET	330
521	PIN GAUGE HANDLE	236	637	V-BLOCK SET	331
522	INDIVIDUAL PIN GAUGE	235	638	V-BLOCK SET	331
522	INDIVIDUAL CARBIDE PIN GAUGE	235	639	V-BLOCK	332
523	PIN GAUGE SET	237	640	V-BLOCK SET	332
523	CARBIDE PIN GAUGE SET	238	641	PARALLEL SET	333
524	BOX FOR PIN GAUGE SET	239	642	GRANITE STRAIGHT EDGE	270
525	MASTER SETTING DISC	240	643	GRANITE SQUARE	268
526	STEEL BALL SET	239	644	GRANITE SQUARE	268
528	INDIVIDUAL CERAMIC PIN GAUGE	236	645	GRANITE SQUARE AND V-BLOCK	269
528	CARBIDE PIN GAUGE SET	238	646	UNIVERSAL ANGLE PLATE SET	335
529	THREE WIRE MEASURING UNITS	240	647	MAGNALIUM STRAIGHT EDGES	271
531	SETTING RING	241	648	GRANITE PARALLEL SET	270
532	THREAD RING GAUGE	245	649	MAGNETIC SQUARE AND V-BLOCK	269
533	THREAD RING GAUGE	245	651	SINE BAR	335
534	THREAD RING GAUGE	245	652	PRECISION VISE	336
535	THREAD RING GAUGE	245	653	PRECISION VISE	336
535	WITHWORTH PIPE THREAD GAUGE(G SERIES)	249	656	PRECISION UNIVERSAL VISE	337
536	WITHWORTH PIPE THREAD GAUGE(G SERIES)	249	657	PRECISION SINE VISE	337
537	AMERICAN STANDARD THREAD RING GAUGE	247	660	CONCENTRICITY GAUGE	197
538	AMERICAN STANDARD THREAD RING GAUGE	247	661	QUICK POSITIONING CONCENTRICITY GAUGE	198
541	PLAIN PLUG GAUGE	242	662	CONCENTRICITY GAUGE	198
541	CARBIDE PLAIN PLUG GAUGE	243	685	DIAL TEST INDICATOR CENTERING HOLDER	338
542	THREAD PLUG GAUGE	246	686	INDICATOR CENTERING HOLDER	339
543	FINE THREAD PLUG GAUGE	246	688	EDGE FINDER(WITH ROTARY HEAD)	344

CODE INDEX

CODE	NAME	PAGE	CODE	NAME	PAGE
689	NON-MAGNETIC EDGE FINDER	343	845	MACHINIST SQUARE WITH WIDE BASE	262
690	NON-MAGNETIC EDGE FINDER(DOUBLE HEAD)	344	846	45° SQUARE	265
691	CERAMIC EDGE FINDER	340-341	847	60° SQUARE	266
692	ELECTRONIC EDGE FINDER	339	848	120° SQUARE	267
693	NON-MAGNETIC EDGE FINDER	340	849	135° SQUARE WITH WIDE BASE	267
694	EDGE FINDER	341-343	850	MACHINIST SQUARE	261
695	ZERO SET	345	851	MACHINIST SQUARE WITH SCALE	262
696	ZERO SET	346	855	MACHINIST SQUARE WITH WIDE BASE AND SCALE	263
697	DIGITAL ZERO SETTER	345	856	45° SQUARE WITH WIDE BASE	265
711-749			857	60° SQUARE WITH WIDE BASE	266
711	FRAME LEVEL	274	880	CALIPER END GRINDING MACHINE	48
712	DIGITAL LEVEL	275	881	CALIPER/MICROMETER LAPPING MACHINE	49
713	BLOCK LEVEL	273	900-999		
714	OPTICAL IMAGE LEVEL	275	900	SCRIBING CALIPER	320
715	BLOCK LEVEL	274	902	T-SHAPE MARKING GAUGE	320
720	DIGITAL ENGINEERS LEVEL	276	903	HEIGHT SCRIBER	321
721	DIGITAL LEVEL	277	906	PRECISION STRAIGHT EDGE	273
722	DIGITAL LEVEL	277	907	PRECISION STRAIGHT EDGE WITH BEVELED EDGE	272
723	DIGITAL LEVEL	278	909	POCKET RULE WITH SLIDING CLIP	318
725	DIGITAL LEVEL	278	911	FEELER	285
726	DIGITAL PROTRACTOR	253	912	FEELER	285
740	WET FILM GAUGE	423	913	FEELER	286
741	U.S. STANDARD SHEET METAL GAUGE	312	914	FEELER	286
741	U.S. STANDARD SHEET WIRE GAUGE	312	915	FEELER	286
742	THICKNESS GAUGE	313	916	FEELER TAPE	286
745	FILLET WELDING GAUGE	307	917	INCH FEELER GAUGE	287
746	WELDING GAUGE	310	919	OFFSET DUAL SCALE FEELER GAUGE	287
747	WELDING GAUGE	310	921	PITCH GAUGE	288
748	PIPE PIT GAUGE	311	922	PITCH GAUGE	288
749	WELDING GAUGE	307	923	PITCH GAUGE	288
800-881			924	PITCH GAUGE	288
800	WIRELESS DATA TRANSFER SYSTEM	1	925	PITCH GAUGE	288
809	MOVABLE WORKBENCH	3	926	CENTER GAUGE	289
811	PROTRACTOR	257	927	THREAD GAUGE	289
812	PROTRACTOR	258	930	ANGLE GAUGE	290
813	PROTRACTOR	258	931	ANGLE GAUGE	291
814	UNIVERSAL PROTRACTOR	252	932	ANGLE GAUGE SET	292
815	UNIVERSAL PROTRACTOR	252	933	ANGLE GAUGE	290
816	UNIVERSAL PROTRACTOR	253	934	ANGLE GAUGE	291
817	COMBINATION SQUARE SET	256	940	GAP/DIAMETER GAUGE	313
821	DIGITAL PROTRACTOR	255	941	RADIUS GAUGE	292
822	DIGITAL PROTRACTOR	251	942	RADIUS GAUGE	293
823	DIGITAL PROTRACTOR	254	951	TELESCOPING GAUGE SET	293
824	DIGITAL PROTRACTOR	254	952	SMALL HOLE GAUGE SET	294
831	ADJUSTABLE SQUARE	264	953	LONG HANDLE TELESCOPING GAUGE	295
832	90° BEVELED EDGE SQUARE	259	955	CIRCUMFERENCE TAPE	152
833	90° TOOL MAKER SQUARE	263	956	CIRCUMFERENCE TAPE	152
839	SQUARE SET	264	960	PIP WELDING GAUGE	306
840	90° BEVELED EDGE SQUARE WITH WIDE BASE	259	961	TAPER GAUGE	296
841	90° FLAT EDGE SQUARE	260	962	TAPER GAUGE	296
842	90° FLAT EDGE SQUARE WITH WIDE BASE	260	962	TAPER GAUGE SET	297
843	90° FLAT EDGE SQUARE WITH WIDE BASE	261	963	DIGITAL TAPER GAUGE	295

CODE	NAME	PAGE	CODE	NAME	PAGE
964	TAPER BORE GAUGE	298	BLK-HRC4	STANDARD HARDNESS BLOCK	409
965	DRILL POINT GAUGE	311	BLK-HRC5	STANDARD HARDNESS BLOCK	409
966	WELDING GAUGE	308	BLK-HSA	STANDARD HARDNESS BLOCK	409
967	CHAMFER GAUGE	281	BLK-HV1	STANDARD HARDNESS BLOCK	409
968	DRILL ANGLE GAUGE	311	BLK-HV2	STANDARD HARDNESS BLOCK	409
969	FILLET WELDING GAUGE	309	BLK-HV3	STANDARD HARDNESS BLOCK	409
970	DIGITAL WELDING GAUGE	298	BLK-HV4	STANDARD HARDNESS BLOCK	409
971	WELDING GAUGE	299	C		
972	WELDING GAUGE	299	CAT12	CROSS CUT ADHESION TESTER	437
973	WELDING GAUGE	300	CF1000S	COATING THICKNESS GAUGE (BASIC TYPE)	422
974	WELDING GAUGE	301	CFN1000S	COATING THICKNESS GAUGE (BASIC TYPE)	422
975	WELDING GAUGE	302-304	CN1000S	COATING THICKNESS GAUGE (BASIC TYPE)	422
976	PIPE WELDING GAUGE	305	CF1500	COATING THICKNESS GAUGE	421
977	FILLET WELD GAUGE	306	CF1500H	COATING THICKNESS GAUGE	421
978	WELDING GAUGE	308	CFN1500	COATING THICKNESS GAUGE	421
979	WELDING GAUGE	309	CN1500	COATING THICKNESS GAUGE	421
981	INSIDE CALIPER	314	CFN1500B	COATING THICKNESS GAUGE	420
982	INSIDE SPRING CALIPER	314	CM100	COLOR METER	441
983	OUTSIDE CALIPER	315	CM200	COLOR METER	441
984	OUTSIDE SPRING CALIPER	315	CM3010	SPECTROPHOTOMETER	442
985	SPRING DIVIDER	316	CT900	CONTACT TYPE TACHOMETER	430
986	DIVIDER	316	D		
988	MEASURING WHEEL	319	DCM600	DIGITAL AC/DC CLAMP METER	428
989	MEASURING TAPE	318	DF10	DIGITAL FORCE GAUGE	443
990	STEEL RULE	317	DF100	DIGITAL FORCE GAUGE	443
991	STRAIGHT EDGE RULE	272	DF1000	DIGITAL FORCE GAUGE	443
992	MARKING GAUGE	321	DF20	DIGITAL FORCE GAUGE	443
993	CENTER MARKING GAUGE	322	DF200	DIGITAL FORCE GAUGE	443
994	STRAIGHT EDGE	271	DF50	DIGITAL FORCE GAUGE	443
995	SCRIBER	322-323	DF500	DIGITAL FORCE GAUGE	443
996	DIGITAL HORIZONTAL SCALE	324	DF1000E	DIGITAL FORCE GAUGE	445
997	DIGITAL VERTICAL SCALE	325	DF100E	DIGITAL FORCE GAUGE	445
998	VERNIER STEP GAUGE	283	DF10E	DIGITAL FORCE GAUGE	445
999	DIGITAL STEP GAUGE	283	DF500E	DIGITAL FORCE GAUGE	445
999	MINI DIGITAL HEIGHT GAUGE	284	DF50E	DIGITAL FORCE GAUGE	445
1300			DF100S	DIGITAL FORCE GAUGE	446
1300KPA	CAMERA	382	DF10S	DIGITAL FORCE GAUGE	446
A			DF200S	DIGITAL FORCE GAUGE	446
AccuGage700	2D HEIGHT GAGE	68-69	DF20S	DIGITAL FORCE GAUGE	446
AccuGage1000	2D HEIGHT GAGE	68-69	DF500S	DIGITAL FORCE GAUGE	446
AccuHite700	1D HEIGHT GAGE	70-71	DF50S	DIGITAL FORCE GAUGE	446
AccuHite1000	1D HEIGHT GAGE	70-71	DF10K	DIGITAL FORCE GAUGE	444
AM30	DIGITAL ANEMOMETER	435	DF20K	DIGITAL FORCE GAUGE	444
B			DF2K	DIGITAL FORCE GAUGE	444
BLK-HB1	STANDARD HARDNESS BLOCK	409	DF5K	DIGITAL FORCE GAUGE	444
BLK-HB2	STANDARD HARDNESS BLOCK	409	DF-CG1	CLAMPS FOR FORCE GAUGE	448
BLK-HLD	STANDARD HARDNESS BLOCK	409	DF-CG2	CLAMPS FOR FORCE GAUGE	448
BLK-HRB1	STANDARD HARDNESS BLOCK	409	DF-FC1	CLAMPS FOR FORCE GAUGE	448
BLK-HRB2	STANDARD HARDNESS BLOCK	409	DF-FC2	CLAMPS FOR FORCE GAUGE	448
BLK-HRC1	STANDARD HARDNESS BLOCK	409	DF-TA	CLAMPS FOR FORCE GAUGE	448
BLK-HRC2	STANDARD HARDNESS BLOCK	409	DF-TWG1	CLAMPS FOR FORCE GAUGE	448
BLK-HRC3	STANDARD HARDNESS BLOCK	409	DF-WG1	CLAMPS FOR FORCE GAUGE	448

CODE INDEX

CODE	NAME	PAGE	CODE	NAME	PAGE
DF-WT1	CLAMPS FOR FORCE GAUGE	448	HL200	PORTABLE HARDNESS TESTER	399
DFS500	MOTORIZED VERTICAL TEST STAND	449	HL350	PORTABLE HARDNESS TESTER	400
DFS500H	MOTORIZED HORIZONTAL TEST STAND	449	HL400	PORTABLE HARDNESS TESTER	400
DHB937-1	DIGITAL BARCOL HARDNESS TESTER	407	HL450	PORTABLE HARDNESS TESTER	401
DHB937-2	DIGITAL BARCOL HARDNESS TESTER	407	HL450W	PORTABLE HARDNESS TESTER	401
DM200	DIGITAL MICROSCOPE	357	HM1000	HAZE METER	440
DMT600	DIGITAL MULTIMETER	428	HR150	MANUAL ROCKWELL HARDNESS TESTER	385
DRM50	DIGITAL PORTABLE REFRACTOMETER	438	HR150A	DIGITAL ROCKWELL HARDNESS TESTER	387
DS40K	DIGITAL TACHOMETER/STROBPSCOPE	431	HR150B	MANUAL ROCKWELL HARDNESS TESTER	386
DST10	DIGITAL SPRING TESTER	450	HR150C	DIGITAL ROCKWELL HARDNESS TESTER	388
DST100	DIGITAL SPRING TESTER	450	HR150CNC	AUTOMATIC ROCKWELL HARDNESS TESTER	390
DST20	DIGITAL SPRING TESTER	450	HR150D	MOTORIZED ROCKWELL HARDNESS TESTER	389
DST200	DIGITAL SPRING TESTER	450	HRSS150C	DIGITAL ROCKWELL HARDNESS TESTER	391
DST30	DIGITAL SPRING TESTER	450	HS1A	DIGITAL SHORE HARDNESS TESTER	403
DST300	DIGITAL SPRING TESTER	450	HS5D	DIGITAL SHORE HARDNESS TESTER	403
DST50	DIGITAL SPRING TESTER	450	HOO	DIGITAL SHORE HARDNESS TESTER	403
DST500	DIGITAL SPRING TESTER	450	HS-1A-STD	STAND FOR SHORE HARDNESS TESTER	405
DT135	DIGITAL TORQUE INDICATOR	456	HS-5D-STD	STAND FOR SHORE HARDNESS TESTER	405
DT200	DIGITAL TORQUE INDICATOR	456	HS-OO-STD	STAND FOR SHORE HARDNESS TESTER	405
DT30	DIGITAL TORQUE INDICATOR	456	HSC	AUTOMATIC SHORE HARDNESS TESTER	402
DVM1000	VIDEO MICROSCOPE	359	HSM1A	SHORE HARDNESS TESTER	404
DVM2000	HD VIDEO MICROSCOPE	360	HSM5D	SHORE HARDNESS TESTER	404
DVM3000	VIDEO MICROSCOPE	361	HSM-1A-ST	STAND FOR SHORE HARDNESS TESTER	405
DVM3D	3D MOTORIZED ROTATION MICROSCOPE	363	HSM-5D-ST	STAND FOR SHORE HARDNESS TESTER	405
DVM3DS	3D MOTORIZED ROTATION MICROSCOPE	363	HTC-1	TEMPERATURE METER	425
DVM4000	AUTO FOCUS VIDEO MICROSCOPE	362	HTC-300	TEMPERATURE METER FOR FOOD	426
DVM4000S	AUTO FOCUS VIDEO MICROSCOPE	362	HTC-70	TEMPERATURE METER	425
E			HVS1000M	MICRO-VICKERS HARDNESS TESTER	393
ES2320	ENDOSCOPE FOR PIPE	353	HVS1000MCNC	MICRO-VICKERS HARDNESS TESTER	396
ES4015	ENDOSCOPE	354	HVS1000MS	MICRO-VICKERS HARDNESS TESTER	396
ES5515	ENDOSCOPE	354	HVS1000S	MICRO-VICKERS HARDNESS TESTER	394
ES5530	ENDOSCOPE	354	HVS10M	VICKERS HARDNESS TESTER	395
ESE40	ENDOSCOPE	355	HVS50M	VICKERS HARDNESS TESTER	395
ESE60	ENDOSCOPE	355	HW-B75	WEBSTER HARDNESS TESTER	408
ESE80	ENDOSCOPE	355	HW-B92	WEBSTER HARDNESS TESTER	408
ESS0615	MANUAL 360° SWIVEL ENDOSCOPE	352	HW-C75	WEBSTER HARDNESS TESTER	408
EST0810	WIFI ENDOSCOPE	356	HW-L20	WEBSTER HARDNESS TESTER	408
F			HW-L20A	WEBSTER HARDNESS TESTER	408
FS1000	TEST STAND FOR FORCE GAUGE	448	HW-L20B	WEBSTER HARDNESS TESTER	408
FS1000S	TEST STAND FOR FORCE GAUGE	448	I		
G			IT1650S	INFRARED THERMOMETER	426
GM268	20°/60°/85° GLOSS METER	439	IT700	INFRARED THERMOMETER	426
GM60	60° GLOSS METER	440	ITC450	INFRARED THERMAL IMAGING CAMERA	427
GY-2	FRUIT HARDNESS TESTER	401	L		
H			LL030	LASER LEVEL	434
HB3000	DIGITAL BRINELL HARDNESS TESTER	392	LL025	LASER LEVEL	434
HB937-1	BARCOL HARDNESS TESTER	407	LL325	LASER LEVEL	434
HG100E	DIGITAL HEIGHT GAGE WITH STAND	72	LL525	LASER LEVEL	434
HG100S	DIGITAL HEIGHT GAGE WITH STAND	72	LM100	LIGHT METER	433
HG50E	DIGITAL HEIGHT GAGE WITH STAND	72	LSA1	LINEAR SCALE	381
HG50S	DIGITAL HEIGHT GAGE WITH STAND	72	LSB5	LINEAR SCALE	381
HL100	PORTABLE HARDNESS TESTER	398	LSM25	LASER SCAN MICROMETER	436

CODE	NAME	PAGE	CODE	NAME	PAGE
LSM50	LASER SCAN MICROMETER	436	STB-4B	STANDARD THICKNESS TEST BLOCK	423
LT900	LASER TACHOMETER	430	STB-5A	STANDARD THICKNESS TEST BLOCK	423
M			STB-5B	STANDARD THICKNESS TEST BLOCK	423
MG10	FOLDING MAGNIFIER	357	STB-7A	STANDARD THICKNESS TEST BLOCK	423
MG305	MAGNIFICATION GLASSES	356	STB-7B	STANDARD THICKNESS TEST BLOCK	423
MG30X	MEASURING MAGNIFIER	357	STE70	DIGITAL REBOUND TESTER	408
MM1000A	METALLURGICAL MICROSCOPE	365	STWM110	TORQUE WRENCH WITH BIT SET	453
MTM200	TOOLMAKER VISION MACHINE	374	STWM210	TORQUE WRENCH WITH BIT SET	453
MTM300	TOOLMAKER VISION MACHINE	374	STWM25	TORQUE WRENCH WITH BIT SET	453
MTM400	TOOLMAKER VISION MACHINE	374	T		
MTT3600	X-RAY FLUORESCENCE SPECTROMETER	424	TM100	LASER DISTANCE METER	432
N			TM40	LASER DISTANCE METER	432
NK-100	FORCE GAUGE	447	TM100B	LASER DISTANCE METER	432
NK-20	FORCE GAUGE	447	TM1200	LASER DISTANCE METER	433
NK-200	FORCE GAUGE	447	TP340	IMAGE TYPE TOOL PRESETTER	383-384
NK-30	FORCE GAUGE	447	TP560	IMAGE TYPE TOOL PRESETTER	383-384
NK-300	FORCE GAUGE	447	TQ200CN	DIGITAL TORQUE SCREWDRIVER	455
NK-50	FORCE GAUGE	447	TQ400CN	DIGITAL TORQUE SCREWDRIVER	455
NK-500	FORCE GAUGE	447	TQ50CN	DIGITAL TORQUE SCREWDRIVER	455
P			TQM120	TORQUE SCREWDRIVER	457
PH12	PEN-TYPE PH METER	436	TQM300	TORQUE SCREWDRIVER	457
PM100	PORTABLE MEASURING MICROSCOPE	358	TQM60	TORQUE SCREWDRIVER	457
PP3015	PROFILE PROJECTOR	366-367	TQM600	TORQUE SCREWDRIVER	457
PP3020	PROFILE PROJECTOR	366-367	TTB10	DIGITAL TORQUE METER	458
PP3020W	HORIZONTAL PROFILE PROJECTOR	368-369	TTB100	DIGITAL TORQUE METER	458
PP6020	PROFILE PROJECTOR	370-371	TTB1000	DIGITAL TORQUE METER	458
PS075	PORTABLE SCALE	461	TTB5	DIGITAL TORQUE METER	458
Q			TTB50	DIGITAL TORQUE METER	458
QVM100	QUICK MEASUREMENT VISION MACHINE	373	TTB500	DIGITAL TORQUE METER	458
QVM120	QUICK MEASUREMENT VISION MACHINE	372	TTB-ST1	STAND FOR TORQUE WRENCH TESTING	459
QVM80B	QUICK MEASUREMENT VISION MACHINE	372	TTB-ST2	STAND FOR TORQUE WRENCH TESTING	459
R			TTB-ST4	STAND FOR TORQUE WRENCH TESTING	459
RBV150C	HARDNESS TESTER	397	TTM10	DIGITAL BOTTLE CAP TORQUE METER	457
RC30	SURFACE ROUGHNESS SPECIMEN	409	TTM2	DIGITAL BOTTLE CAP TORQUE METER	457
RM10	PORTABLE REFRACTOMETER	438	TTM20	DIGITAL BOTTLE CAP TORQUE METER	457
RM20	PORTABLE REFRACTOMETER	438	TTM5	DIGITAL BOTTLE CAP TORQUE METER	457
RM32	PORTABLE REFRACTOMETER	438	TTS1	DIGITAL TORQUE METER	459
RM50S	AUTOMOTIVE REFRACTOMETER	439	TTS10	DIGITAL TORQUE METER	459
RN1000	ROUNDNESS TESTER	417	TTS5	DIGITAL TORQUE METER	459
RP100JS	PROFILE AND ROUGHNESS MACHINE	410-411	TW12	DIGITAL TORQUE WRENCH	453
RP100RS	PROFILE AND ROUGHNESS MACHINE	410-411	TW135	DIGITAL TORQUE WRENCH	453
RP100TS	PROFILE AND ROUGHNESS MACHINE	410-411	TW1500	DIGITAL TORQUE WRENCH	453
S			TW20	DIGITAL TORQUE WRENCH	453
SLM130	DIGITAL SOUND LEVEL METER	435	TW200	DIGITAL TORQUE WRENCH	453
SR110	ROUGHNESS TESTER	415	TW2000	DIGITAL TORQUE WRENCH	453
SR200	ROUGHNESS TESTER	412	TW30	DIGITAL TORQUE WRENCH	453
SR300	ROUGHNESS TESTER	413	TW340	DIGITAL TORQUE WRENCH	453
SR400	ROUGHNESS TESTER	414	TW550	DIGITAL TORQUE WRENCH	453
ST100A	ULTRASONIC THICKNESS GAUGE	420	TW850	DIGITAL TORQUE WRENCH	453
ST200	ULTRASONIC THICKNESS GAUGE	418	TWD140	DIAL TORQUE WRENCH	454
ST300	ULTRASONIC THICKNESS GAUGE	419	TWD18	DIAL TORQUE WRENCH	454
STB-4A	STANDARD THICKNESS TEST BLOCK	423	TWD240	DIAL TORQUE WRENCH	454

CODE INDEX

CODE	NAME	PAGE	CODE	NAME	PAGE
TWD3	DIAL TORQUE WRENCH	454	TWT200M	MOTORIZED TORQUE WRENCH TESTER	460
TWD35	DIAL TORQUE WRENCH	454	TWT500M	MOTORIZED TORQUE WRENCH TESTER	460
TWD350	DIAL TORQUE WRENCH	454	TWT200	TORQUE WRENCH TESTER	460
TWD70	DIAL TORQUE WRENCH	454	TWT500	TORQUE WRENCH TESTER	460
TWD9	DIAL TORQUE WRENCH	454	U		
TWF100	TORQUE WRENCH	454	UHT200	ULTRASONIC HARDNESS TESTER	406
TWF150	TORQUE WRENCH	454	UTT100	UNIVERSAL TENSILE TESTING MACHINE	451
TWF250	TORQUE WRENCH	454	UTT1000	UNIVERSAL TENSILE TESTING MACHINE	451
TWF600	TORQUE WRENCH	454	UTT10000	UNIVERSAL TENSILE TESTING MACHINE	451
TWI200	TORQUE WRENCH	454	UTT200	UNIVERSAL TENSILE TESTING MACHINE	451
TWI250	TORQUE WRENCH	454	UTT2000	UNIVERSAL TENSILE TESTING MACHINE	451
TWM100	TORQUE WRENCH	452	UTT20000	UNIVERSAL TENSILE TESTING MACHINE	451
TWM200	TORQUE WRENCH	452	UTT50	UNIVERSAL TENSILE TESTING MACHINE	451
TWM25	TORQUE WRENCH	452	UTT500	UNIVERSAL TENSILE TESTING MACHINE	451
TWM340	TORQUE WRENCH	452	V		
TWM50	TORQUE WRENCH	452	VM300CNC	AUTOMATIC VISION MACHINE	377-378
TWM1000B	TORQUE WRENCH	452	VM400CNC	AUTOMATIC VISION MACHINE	377-378
TWM110B	TORQUE WRENCH	452	VM500CNC	AUTOMATIC VISION MACHINE	377-378
TWM110C	TORQUE WRENCH	452	VM600CNC	AUTOMATIC VISION MACHINE	379-380
TWM1500B	TORQUE WRENCH	452	VM800CNC	AUTOMATIC VISION MACHINE	379-380
TWM2000B	TORQUE WRENCH	452	VM1000CNC	AUTOMATIC VISION MACHINE	379-380
TWM210B	TORQUE WRENCH	452	VM1200CNC	AUTOMATIC VISION MACHINE	379-380
TWM25B	TORQUE WRENCH	452	VM1500CNC	AUTOMATIC VISION MACHINE	379-380
TWM3000B	TORQUE WRENCH	452	VM2010	VISION MACHINE	375-376
TWM330B	TORQUE WRENCH	452	VM3020	VISION MACHINE	375-376
TWM550B	TORQUE WRENCH	452	VM4030	VISION MACHINE	375-376
TWM60B	TORQUE WRENCH	452	VM5040	VISION MACHINE	375-376
TWM60D	TORQUE WRENCH	452	VT63	PEN TYPE VIBRATION TESTER	431
TWM800B	TORQUE WRENCH	452	W		
TWQ-1000	TORQUE MULTIPLIERS	456	WE6800-2	DIGITAL READOUT	380
TWQ-10000	TORQUE MULTIPLIERS	456	WE6800-3	DIGITAL READOUT	380
TWQ-2000	TORQUE MULTIPLIERS	456	WIFI200	DIGITAL WIFI MICROSCOPE	358
TWQ-3500	TORQUE MULTIPLIERS	456	WMM700	WOOD MOISTURE METER	429
TWQ-5500	TORQUE MULTIPLIERS	456	WMM900	CONCRETE MOISTURE METER	429
TWQ-7500	TORQUE MULTIPLIERS	456	WS06K	ELECTRONIC WEIGHING SCALE	462
TWS1000	WINDOWS TORQUE WRENCH	455	WS15K	ELECTRONIC WEIGHING SCALE	462
TWS100B	WINDOWS TORQUE WRENCH	455	WS30K	ELECTRONIC WEIGHING SCALE	462
TWS12	WINDOWS TORQUE WRENCH	455	WSC3000G	WEIGHING SCALE FOR KITCHEN	461
TWS1500	WINDOWS TORQUE WRENCH	455	WSJ1000G	HIGH PRECISION ELECTRONIC BALANCE	462
TWS20	WINDOWS TORQUE WRENCH	455	WSJ100G	HIGH PRECISION ELECTRONIC BALANCE	462
TWS200	WINDOWS TORQUE WRENCH	455	WSJ2000G	HIGH PRECISION ELECTRONIC BALANCE	462
TWS2000	WINDOWS TORQUE WRENCH	455	WSJ200G	HIGH PRECISION ELECTRONIC BALANCE	462
TWS20B	WINDOWS TORQUE WRENCH	455	WSJ300G	HIGH PRECISION ELECTRONIC BALANCE	462
TWS30	WINDOWS TORQUE WRENCH	455	WSJ600G	HIGH PRECISION ELECTRONIC BALANCE	462
TWS3000	WINDOWS TORQUE WRENCH	455	WT	WEIGHT	463
TWS330	WINDOWS TORQUE WRENCH	455	WTS	WEIGHT SET	463
TWS400	WINDOWS TORQUE WRENCH	455	Z		
TWS400B	WINDOWS TORQUE WRENCH	455	ZS1045	ZOOM STEREO MICROSCOPE	364
TWS550	WINDOWS TORQUE WRENCH	455	ZS1045T	ZOOM STEREO MICROSCOPE	364
TWS60	WINDOWS TORQUE WRENCH	455			
TWS60B	WINDOWS TORQUE WRENCH	455			
TWT1000M	MOTORIZED TORQUE WRENCH TESTER	460			